

## SLN-Series

Slimline  
Corded VoIP  
Telephone

SLN-1103



SLN-1203



### Features

- One or Two-Line
- Full Duplex Handset
- 3 Guest Service Keys
- Flash and Redial Keys
- Desk or Wall Mountable
- Hearing Aid Compatible
- Handset Volume Control
- Hold key (Two line version)
- Line 1 and Line 2 LED Indicators
- Room Number Displayed on Faceplate
- Message Waiting & Ring Indicator on Base
- Customizable Hotel Logo and Dialing Instructions on Faceplate

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## PRODUCT OPTIONS



**SLN-1100**  
Single-Line Slimline  
IP Telephone  
No Guest Service  
Keys.



**SLN-1200**  
Two-Line Slimline  
IP Telephone  
No Guest Service  
Keys.

## SPECIFICATIONS

Power	<ul style="list-style-type: none"> <li>• Adapter 100-240 VAC Output 6V/1A (Optional)</li> <li>• PoE IEEE802.3af</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>• 10/100 RJ45 WAN</li> <li>• RJ9 Handset</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 225mm(L)x110mm(W)x50mm(H) (8.86"x4.33"x1.97")</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 660g</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>• GUI</li> <li>• Web Based speed-dial key setting for m1-m6</li> <li>• Firmware Upgrade via Web</li> <li>• Auto Provisioning</li> <li>• IP Address auto announcement from Handset</li> </ul>
Codec	<ul style="list-style-type: none"> <li>• G.711a/u-law/G.723/G.729</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>• Telnet / http Server / DNS Client</li> <li>• PPPoE / Static / DHCP Client IP assignment.</li> <li>• ToS field / VLAN IEEE 802.1 p/q</li> </ul>
SIP	<ul style="list-style-type: none"> <li>• SIP V1 (RFC2543) SIP V2 (RFC3261)</li> </ul>
Security	<ul style="list-style-type: none"> <li>• Web Login authentication for web setup</li> <li>• MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
Voice Quality	<ul style="list-style-type: none"> <li>• CNG Comfortable Noise Generator</li> <li>• LEC Line Echo Canceller</li> <li>• Jitter Buffer</li> <li>• VAD Voice Activity Detection</li> <li>• Packet Loss Compression</li> </ul>
EMI	USA: FCC Part 15B,D ICES-003 EU: EN 55022
EMC	EU: EN 55024, EN 61000-4-4, EN 61000-3-2, IEC 61000-4-5 EN 61000-3-3, IEC 61000-4-6, EN 61000-4-2, IEC 61000-4-11
RoHS	• Comply with directive 2002/95/EC RoHS (2005/613/EC)
Temperature	<ul style="list-style-type: none"> <li>• Storage -10C to +60C</li> <li>• Operating 0C to +40C</li> </ul>

