

## SMT-2110-S

Single-Line  
Corded VoIP  
Speakerphone



### Features

- 1-line Speakerphone
- Hearing Aid Compatible
- Unique Customizable Faceplate
- Message Waiting & Ring Indicator
- 10 Programmable Guest Service keys
- Adjustable Handset & Speakerphone Volume Control

**AEi** brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



## PRODUCT OPTIONS



### SMT-2105-S

One-Line Telephone  
5 Guest Service Keys  
with Speakerphone



### SMT-2100-S

One-Line Telephone  
No Guest Service Keys  
with Speakerphone

Custom Guest Service Key configuration available

## SPECIFICATIONS

Power	<ul style="list-style-type: none"> <li>• Adapter 100-240 VAC Output 6V/1A (Optional)</li> <li>• PoE module Class 0</li> </ul>
Jacks	<ul style="list-style-type: none"> <li>• 10/100 RJ45 WAN</li> <li>• RJ9 Handset</li> <li>• DC Jack</li> </ul>
Color	<ul style="list-style-type: none"> <li>• Black, Textured</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 8.7" x 6.2" x 4.3"</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 804g</li> </ul>
Cords	<ul style="list-style-type: none"> <li>• 10' Line Cord (15' Upon Request) &amp; 10' Coiled Cord</li> </ul>
Handset	<ul style="list-style-type: none"> <li>• Hearing Aid Compatible</li> </ul>
Easy Administration	<ul style="list-style-type: none"> <li>• GUI</li> <li>• Firmware Upgrade via TFTP/HTTP</li> <li>• Auto Provisioning</li> </ul>
Codec	<ul style="list-style-type: none"> <li>• G.711/G.729</li> </ul>
Network Protocol	<ul style="list-style-type: none"> <li>• HTTP/DHCP Server</li> <li>• Static / DHCP IP assignment.</li> <li>• ToS field / VLAN IEEE 802.1 p/q</li> <li>• SIP V2 (RFC3261)</li> </ul>
SIP Security	<ul style="list-style-type: none"> <li>• Web Login authentication for web setup</li> <li>• MD5 for SIP authentication (RFC2069/ RFC2617)</li> </ul>
DTMF	<ul style="list-style-type: none"> <li>• In Band / Out of Band DTMF (RFC2833) / SIP Info (RFC2976)</li> </ul>
Voice Quality	<ul style="list-style-type: none"> <li>• CNG Comfortable Noise Generator</li> <li>• LEC/AEC Line Echo Cancellor</li> <li>• Jitter Buffer/PLC</li> </ul>
EMI	USA: FCC Part 15B,D
EMC	EN 55022, EN 600950-1, EN 55024
RoHS	EN 61000-3-2,3-3, IEC 61000-4-2,4-3, IEC 61000-4-4,4-5,4-6,4-11
	• Comply with directive 2002/95/EC RoHS (2005/613/EC)