



www.koontech.com

香港昆仑科技(深圳)有限公司

Regular Customer

THALES SIEMENS



Alcatel-Lucent



HUAWEI

ERICSSON
TAKING YOU FORWARD

AVAYA
The Power of 800




Clean Phone KNZD-63



The most professional manufacture in Asia The exclusive supplier for all Metro project in China

The emergency call telephone will be designed to work on railway, metro, tunnel, etc. Housed in stainless steel box with one CALL/ ANSWER button, it will offer protection against the outdoor environment and vandals. The unit will meet all the latest European/UK standards telephony, waterproofing IP65, and lightening protection together with offering the level of performance and reliability demanded in such an environment.



70-80CM



Main Product features

1. High waterproof, dustproof performance, ABS industrail standard material, protection grade reaches to IP65.
2. High durability, oil, acid, alkali resistance, conform to the standards of GJB - 773 and UL1332 requirements.
3. Without handset, communication via loudspeaker.
4. Highly integrated mainboard, using the most advanced industry-specific microcontroller made in ATMEL company.
5. The box with earthing device is completely isolated with internal electric circuit, and has certain electromagnetic shielding effect.
6. Conversation with clear loud voice, no feedback screaming.
7. Support hotline of exchange system.
8. Support the function of exterior line automatic lift.
9. Support conversation time limited.
10. Strong, thick and beautiful body with embed wall design.
11. talking distance: 80cm-100cm.

- Standard and SMART Analogue and VoIP-SIP options available
- DTMF(Dual Tone Multi Frequency)
- Matching with most PABX,PBX and PAX systems.

Main PCB

1. Well treated PCB used inside the phone.
2. Robust screw terminals used for the connection of ringer, handset, line in, hookswitch.
3. Selectable 7 minute time out, to release the line if the handset is left off hook.
4. All connectors be greased in production.

VOIC OVER IP- SIP (Version)

Connection type: RJ45 Socket inside sealed enclosure
Power supply: External 24V dc
Call set-up Protocol: Session Initiation Protocol(SIP)
Configuration: DHCP or STATIC IP address provisioning



HONGKONG KOON TECHNOLOGY LTD


Tel: 0086755 29790158 / 27448753 Fax: 0086755 29790278 Email: koon03@vip.163.com www.koontech.com



1 2 3

The most professional manufacture in Asia
The exclusive supplier for all Metro project in China


Telephone layout



TECHNICAL SPECIFICATION

1. It is suitable for automatic instruction amplification telephone system when feed voltage reaches to 33- 60V.
2. Environmental temperature: -30'C ~ 60'C
3. Relative humidity: 10% ~ 95%
4. Atmospheric pressure: 86 ~ 106Kpa
5. Environmental noise: $\leq 80\text{dB}$
6. Double audio dialing
7. Standard frequency: 697, 770, 852, 941Hz
8. Low frequency group: 697, 770, 852, 941Hz
9. High frequency group: 1209, 1336, 1477Hz
10. Frequency offset: $\leq \pm 1.5\%$
11. The signal level when the length of user's line is 3km:
12. Standard frequency: Low frequency group: -9dB
13. High frequency group: -7dB $\pm 3\text{dB}$
14. Level difference between high and low frequency of combined signal: $2 \pm 1\text{dB}$
15. The total intermodulation distortion caused by harmonic is 20dB lower than wave level.
16. Call transmission index: (5Km) SLR ≤ 12 , RLR ≤ -1 , and STMR ≥ 10 , Input impedance: 600 Ω
17. Handsfree operation built-in loud speaker 0.5W.

Mounting bracket



Connection cable

Stainless steel connection cable to exchange.
 Well treated keep waterproof.

Packing detail:



Kntech standard export packing carton
 Unit size: 105*205*32mm,
 N.W.: 0.37KG.
 10pcs in each inner CTN BOX,
 SIZE: 320*300*240mm,
 G.W.: 4.50KG.

Certification:



EMC: EN50121 (Railway application-
 Electromagnetic Compatibility)
 EN55022: emissions
 EN55024: immunity

FCC
 ITU-T Recommendations K21



HONGKONG KOON TECHNOLOGY LTD

Tel: 0086755 29790158 / 27448753 Fax: 0086755 29790278 Email: koon03@vip.163.com www.koontech.com