
AGENT SUBSTRATE DAY

Pleading the Agent: proof of agent identity



Greg Castle • Taahir Ahmed, Google

/in/greg-castle • in/taahir-ahmed-9545b5175/

ATECon • Monday, November 9, 2026 • Sky SLC

“It wasn’t me, it was my agent”

- Andrew asks his OpenClaw agent, running on Claude, to get him into a full morning class at his gym
- The agent finds the gym’s cancel API has no authorization check
- Andrew is now in!
- “Bad news, I can’t add them back.”

Source: ABC News, 10 Aug 2026

Attribution: who acted, and why?

- **Agent or human?**
- **For whom?** The user it was acting for
- **Which agent?** The instance, not “one of Andrew’s agents”
- **Was it told to?** Its trajectory and prompts

New challenges for agent identity

Least privilege	Policy is task-specific, and can change during the task
Delegate	Run for hours, spawn sub-agents; go back to the human only for risky steps
Govern	Know which agents act for which users; revoke permissions for one agent without revoking the user
Automate	Agent-sized quotas; no security keys or phone codes

Substrate's goal is to give you identities to solve these problems with your cloud and your application.


Terminology

Actor	Agent-like software. Doesn't *have* to be an agent. Single tenant: no meaningful security boundary inside an actor.
Atespace	A group of actors, like a Kubernetes namespace.

Substrate identity use cases

Flow	Credential	Issued by
User → Agent	User's SSO token	Human IdP: Entra ID, Cloud Identity, Auth0
SRE / dev → Substrate	Short-lived OIDC token	Same human IdP
Agent → Agent	Actor JWT, injected at egress	Substrate
Agent → Cloud	Actor JWT, federated via OIDC	Substrate, trusted by the cloud's STS
Agent → SaaS	OAuth access token, injected at egress	The SaaS OAuth server (e.g. Gmail)


User → Agent



1 Alice signs in to your app via SSO; the frontend picks her actor


2 Frontend → ingress over mTLS; only trusted frontends **3** Ingress routes to Actor A

SRE / developer debugging




1 Engineer gets a short-lived token from SSO **2** Substrate API trusts your SSO issuer; roles per atespace
3 Inspect, suspend, delete actors. No standing credentials

Agent → Agent




1 Actor A calls B through the egress gateway **2** Gateway injects A's JWT
3 Frontend verifies the JWT: may A call B? **4** Ingress routes to Actor B

Agent → Cloud



1 Actor A sends a request with a placeholder header **2** Gateway asks the credential provider (soon: native RFC8693 support)
3 Provider exchanges the actor JWT at the cloud STS (OIDC federation) **4** Token injected; the log names the actor


Deep Dive: Agent → SaaS with OAuth




1 Actor A sends a request with a placeholder header **2** Gateway matches the egress rule
3 Swaps in a secret from the provider, or a fresh actor JWT. The sandbox never sees it

Inbox agent: OAuth


- “Don’t act until I confirm.” Context compaction drops the instruction
- Basic setup: app password that the agent holds
- Better: an OAuth app with gmail.readonly; a broker holds the token and the egress gateway injects it





Source: Summer Yue on X, Feb 2026


OAuth: consent at sign-up



Auth Manager stores the app's OAuth client ID and secret, and each user's refresh token, encrypted.

One atespace per user: email-app puts Alice's actors in atespace u-alice and uses u-alice as her Auth Manager user ID.

OAuth: fetching the token



Credential provider asks auth manager for an access token for the user that matches the atespace name
Auth Manager returns a short-lived gmail.readonly access token


The demo agent’s egress policy


on actor u-alice/mail-agent

```
$ kubectl ate create egress-policy mail-agent -a u-alice -f policy.yaml
                                  ^ actor name  ^ its atespace
# the actor is the policy's parent; each actor has exactly one
metadata:
  atespace: u-alice     # must match the actor's atespace
  name: default        # the singleton policy for that actor
rules:
- https:
    hostnames: ["gmail.googleapis.com"]
    effects:
      replaceHeaders:
      - header: Authorization
        prefix: "Bearer "
        credentialUri: ate-secret://authmanager.demo/gmail-oauth/gmail.readonly
```

Demo: a mail agent with no credentials

Demo code:
https://github.com/destijl/atecon-identity-2026





Looking Forward

On-Behalf-Of (OBO): which agent, for who

Today: pick one identity

The user's identity

The log says Alice. Which agent?

The infrastructure's identity

The log says actor u-alice/mail-agent. For whom?

Goal: both, so policy can combine them

```
allow actor   mail-agent
  to   read Alice's mail
  when trust domain == mycompany.prod
```



user token + agent token → token with sub = user, agent as actor. **Substrate: not yet.**

ID-JAG: Improving on OAuth

The problem


One click per app, per user. 20 sites = 20 screens

Pre-consent (most IdPs today)

An admin approves each app up front, so no screen. Still point-wise: each app on its own

ID-JAG adds app-to-app

App 1 forwards the user to app 2 with no consent screen. The IdP decides which hops are allowed




Substrate: not yet. 1 RFC 8693 token exchange in Substrate (first building block) 2 work with IdPs so this functionality works with Substrate

Roadmap

01	**Token exchange**	RFC 8693 in Substrate: cloud federation, OBO, ID-JAG	#1661
02	**On-Behalf-Of**	One credential naming the actor and the user	#3715
03	**ID-JAG**	Enterprise IdP policy instead of consent screens	#3714
04	**Grouping**	A way to group actors beyond the atespace	#3713
05	**Ingress policy**	Per-actor and per-atespace ingress policy	#3589

AGENT SUBSTRATE DAY

Thank you



Greg Castle • Taahir Ahmed

/in/greg-castle • in/taahir-ahmed-9545b5175/

Demo code: https://github.com/destijl/atecon-identity-2026