

Package ‘oec’

July 26, 2016

Type Package

Title The Observatory of Economic Complexity

Version 1.0.1

Date 2016-07-26

Author Mauricio Vargas S. <mauriciovargas@ug.uchile.cl>

Maintainer Mauricio Vargas S. <mauriciovargas@ug.uchile.cl>

URL <http://atlas.media.mit.edu/en/>, <https://github.com/pachamaltese/oec/>

Description Use The Observatory of Economic Complexity's API from R console to obtain international trade data to create spreadsheets (csv format) and D3Plus visualizations.

License MIT + file LICENSE

LazyData TRUE

Depends curl,
data.table,
jsonlite,
plyr,
servr

RoxygenNote 5.0.1

R topics documented:

oec-package	2
countries_list	2
d3plus	3
demos	3
getdata	4
hs92_2char	4
hs92_6char	5
hs92_8char	5
hs_colors	6
network	6
network.compare	7
sitc_colors	8
sitc_rev2_2char	8
sitc_rev2_4char	9
treemap	9

Index	11
--------------	-----------

 oec-package

oec: The Observatory of Economic Complexity

Description

Use The Observatory of Economic Complexity's API from R console to obtain international trade data to create spreadsheets (csv format) and D3Plus visualizations.

Details

The functions provided within this package are:

[d3plus](#) Install D3 and D3plus in your working directory.

[demos](#) Copies demo file with examples.

[getdata](#) Download trade data from OEC's API.

[network](#) Create an animated network with nodes and edges.

[network.compare](#) Creates a network that compares the exporting opportunities of a country in two different years.

[treemap](#) Creates an animated treemap.

The datasets provided within this package are:

[countries_list](#) Contains a list of all the countries in the world and its respective country code.

[hs92_2char](#) This file contains the HS92 groups. This file is used to create spreadsheets and visualizations with trade data.

[hs92_6char](#) This file contains the HS92 products (6 characters codes). This file is used to create spreadsheets and visualizations with trade data.

[hs92_8char](#) This file contains the HS92 products (8 characters codes). This file is used to create spreadsheets and visualizations with trade data.

[hs_colors](#) This file contains the HS92 colors. This file is used to create spreadsheets and visualizations based on trade data.

[sitc_rev2_2char](#) This file contains the SITC (rev. 2) groups. This file is used to create spreadsheets and visualizations with trade data.

[sitc_rev2_4char](#) This file contains the SITC (rev. 2) products (4 characters codes). This file is used to create spreadsheets and visualizations with trade data.

[sitc_colors](#) This file contains the SITC (rev. 2) colors. This file is used to create spreadsheets and visualizations with trade data.

 countries_list

A list of all the countries

Description

A list of all the countries in the world and its country code. You need the country code (e.g. chl) to obtain data of a country (e.g Chile)

Usage

```
countries_list
```

Format

A data frame with 305 observations on the following 2 variables.

country the full names of the countries

country_code the ids of the countries

Examples

```
countries_list
```

d3plus	<i>Installs D3Plus</i>
--------	------------------------

Description

Installs D3Plus

Usage

```
d3plus()
```

Value

Copies a folder named d3plus to the working directory and it contains the js files and icons to make the visualizations

Examples

```
d3plus()
```

demos	<i>Copies the demo file</i>
-------	-----------------------------

Description

Copies the demo file

Usage

```
demos()
```

Value

Copies a file named demo_examples.R to the working directory.

Examples

```
demos()
```

getdata

Downloads and processes the data from the API

Description

Downloads and processes the data from the API

Usage

```
getdata(ORIGIN, DESTINATION, CLASSIFICATION, YEAR)
```

Arguments

ORIGIN	is the country code of origin (e.g. "chl" for Chile)
DESTINATION	is the country code of origin (e.g. "chn" for China)
CLASSIFICATION	refers to the trade classification that can be "6" (HS92 6 characters) or "8" (HS92 8 characters) for the year 1995 and going or "4" (SITC rev.2 4 characters) for the year 1962 and ongoing
YEAR	is the year and the OEC's API ranges from 1962 to 2014

Value

Downloads the data from the OEC's API and creates the data files in json and csv formats that are needed to create the visualizations.

Examples

```
# Run countries_list() to display the full list of countries
# Chile is "chl" and China is "chn"

# Download Chile (chl) and China (chn) trade data (imports, export and trade balance)
getdata("chl", "chn", 6, 2010)

# Download trade data from OEC's API (HS92 6 characters product lists)
getdata("chl", "chn", 6, 2010)

# Download trade data from OEC's API (SITC rev.2 4 characters product lists)
getdata("chl", "chn", 4, 2010)
```

hs92_2char

HS92 groups

Description

HS92 groups. This file is used to create the visualizations.

Usage

```
hs92_2char
```

Format

A data frame with 22 observations on the following 2 variables.

group Contains the H292 groups (e.g. animal products, vegetable products, etc)

group_id Contains the associated codes of every group (e.g. animal products is 01)

Examples

hs92_2char

hs92_6char	<i>HS92 products (6 characters)</i>
------------	-------------------------------------

Description

HS92 products (6 characters). This file is used to create the visualizations.

Usage

hs92_6char

Format

A data frame with 1242 observations on the following 4 variables.

product Contains the H292 products' names (e.g. horses, bovine, pigs, etc)

group Contains the H292 groups (e.g. animal products, vegetable products, etc)

product_id Contains the associated codes of every product (e.g. horses is 010101)

group_id Contains the associated codes of every group (e.g. animal products is 01)

Examples

hs92_6char

hs92_8char	<i>HS92 products (8 characters)</i>
------------	-------------------------------------

Description

HS92 products (8 characters). This file is used to create the visualizations.

Usage

hs92_8char

Format

A data frame with 5040 observations on the following 4 variables.

product Contains the H292 products' names (e.g. horses, bovine, pigs, etc)

group Contains the H292 groups (e.g. animal products, vegetable products, etc)

product_id Contains the associated codes of every product (e.g. horses is 010101)

group_id Contains the associated codes of every group (e.g. animal products is 01)

Examples

```
hs92_8char
```

hs_colors	<i>HS92 colors</i>
-----------	--------------------

Description

HS92 colors. This file is used to create the visualizations.

Usage

```
hs_colors
```

Format

A data frame with 21 observations on the following 2 variables.

group Contains the H292 groups (e.g. animal products, vegetable products, etc)

color Contains the associated colors of every group (e.g. mineral products is #330000)

Examples

```
hs_colors
```

network	<i>Creates a network for a given year</i>
---------	---

Description

Creates a network for a given year

Usage

```
network(ORIGIN, DESTINATION, CLASSIFICATION, YEAR)
```

Arguments

ORIGIN	is the country code of origin (e.g. "chl" for Chile)
DESTINATION	is the country code of origin (e.g. "chn" for China)
CLASSIFICATION	refers to the trade classification that can be "6" (HS92 6 characters) or "8" (HS92 8 characters) for the year 1995 and going or "4" (SITC rev.2 4 characters) for the year 1962 and ongoing
YEAR	is the year and the OEC's API ranges from 1962 to 2014

Value

Creates an HTML file with a network visualization for a given year.

Examples

```
network("chl", "chn", 6, 2004)
```

network.compare	<i>Creates a network to compare two years</i>
-----------------	---

Description

Creates a network to compare two years

Usage

```
network.compare(ORIGIN, DESTINATION, CLASSIFICATION, YEAR1, YEAR2)
```

Arguments

ORIGIN	is the country code of origin (e.g. "chl" for Chile)
DESTINATION	is the country code of origin (e.g. "chn" for China)
CLASSIFICATION	refers to the trade classification that can be "6" (HS92 6 characters) or "8" (HS92 8 characters) for the year 1995 and going or "4" (SITC rev.2 4 characters) for the year 1962 and ongoing
YEAR1	is the initial year and the OEC's API ranges from 1962 to 2014
YEAR2	is the final year and the OEC's API ranges from 1962 to 2014

Value

Creates an HTML file with a network visualization that compares two given years.

Examples

```
network.compare("chl", "chn", 6, 2000, 2010)
```

`sitc_colors`*SITC (rev. 2) colors*

Description

SITC (rev. 2) colors. This file is used to create the visualizations.

Usage`hs_colors`**Format**

A data frame with 36 observations on the following 2 variables.

`group` Contains the SITC (rev. 2) groups (e.g. machinery, electronics, etc)

`color` Contains the associated colors of every group (e.g. machinery is #17bcef)

Examples`sitc_colors`

`sitc_rev2_2char`*SITC (rev. 2) groups*

Description

SITC (rev. 2) groups. This file is used to create the visualizations.

Usage`hs92_2char`**Format**

A data frame with 36 observations on the following 2 variables.

`group` Contains the SITC (rev. 2) groups (e.g. machinery, electronics, etc)

`group_id` Contains the associated codes of every group (e.g. machinery is 10)

Examples`sitc_rev2_2char`

sitc_rev2_4char	<i>SITC (rev. 2) products (4 characters)</i>
-----------------	--

Description

SITC (rev. 2) products (4 characters). This file is used to create the visualizations.

Usage

sitc_rev2_4char

Format

A data frame with 1242 observations on the following 5 variables.

product Contains the H292 products' names (e.g. initiating devices, polymerization ion exchangers, etc)

group Contains the H292 groups (e.g. machinery, electronics products, etc)

product_id Contains the associated codes of every product (e.g. initiating devices is 5722)

group_id Contains the associated codes of every group (e.g. machinery is 10)

id Contains the associated extended codes of every group (e.g. machinery is 105722 that is group code + product code)

Examples

sitc_rev2_4char

treemap	<i>Creates a treemap for a given year</i>
---------	---

Description

Creates a treemap for a given year

Usage

```
treemap(ORIGIN, DESTINATION, VARIABLE, CLASSIFICATION, YEAR)
```

Arguments

ORIGIN is the country code of origin (e.g. "chl" for Chile)

DESTINATION is the country code of origin (e.g. "chn" for China)

VARIABLE is the variable to visualize and it can be "imports", "exports" or "exchange" (trade exchange)

CLASSIFICATION refers to the trade classification that can be "6" (HS92 6 characters) or "8" (HS92 8 characters) for the year 1995 and going or "4" (SITC rev.2 4 characters) for the year 1962 and ongoing

YEAR is the year and the OEC's API ranges from 1962 to 2014

Value

Creates an HTML file with a treemap visualization for a given year.

Examples

```
treemap("chl", "chn", "exports", 6, 2004)
```

Index

*Topic **datasets**

- [countries_list](#), [2](#)
- [hs92_2char](#), [4](#)
- [hs92_6char](#), [5](#)
- [hs92_8char](#), [5](#)
- [hs_colors](#), [6](#)
- [sitc_colors](#), [8](#)
- [sitc_rev2_2char](#), [8](#)
- [sitc_rev2_4char](#), [9](#)

*Topic **functions**

- [d3plus](#), [3](#)
- [demos](#), [3](#)
- [getdata](#), [4](#)
- [network](#), [6](#)
- [network.compare](#), [7](#)
- [treemap](#), [9](#)

[countries_list](#), [2](#), [2](#)

[d3plus](#), [2](#), [3](#)

[demos](#), [2](#), [3](#)

[getdata](#), [2](#), [4](#)

[hs92_2char](#), [2](#), [4](#)

[hs92_6char](#), [2](#), [5](#)

[hs92_8char](#), [2](#), [5](#)

[hs_colors](#), [2](#), [6](#)

[network](#), [2](#), [6](#)

[network.compare](#), [2](#), [7](#)

[oec-package](#), [2](#)

[sitc_colors](#), [2](#), [8](#)

[sitc_rev2_2char](#), [2](#), [8](#)

[sitc_rev2_4char](#), [2](#), [9](#)

[treemap](#), [2](#), [9](#)