

Regression Conformal Prediction Under Neutral Claim Boundaries

Emre Tasar, Data Scientist

2026

Evidence scope: This output summarizes the public Research Atlas evidence scope.

Contact: detasar@gmail.com

1 Abstract

This report summarizes a regression conformal prediction study assembled from 145,839 publication-scoped completed rows, 67 datasets, 95 dataset-alpha cells, and 28 conformal-method labels. The largest coverage-gated selected-cell pattern is CQR, with 56 coverage-gated selected cells, followed by Mondrian absolute-residual calibration with 15 and CV+ with 13. These results are interpreted as diagnostic evidence only. The current evidence does not establish broad deployment guidance, bounded-support validity, population-level group inference, or a validated Venn-Abers regression interval.

2 Introduction

Regression conformal prediction provides a way to wrap predictive models with prediction intervals calibrated for marginal coverage under exchangeability [3]. This study asks how a broad set of regression conformal methods behaves across audited tabular datasets while preserving source traceability, resumability, leakage checks, duplicate-split caveats, and explicit claim boundaries.

The article deliberately separates empirical diagnostics from final claims. A method can appear frequently on the descriptive frontier without becoming a universal deployment rule. A group coverage table can be useful without becoming a population-level group inference claim. A Venn-Abers bridge can be scientifically important even when the observed evidence is negative.

2.1 Reader Orientation

A prediction interval is a range-valued prediction. Instead of saying that the model predicts one number, the procedure returns a lower and an upper endpoint. The target `1 - alpha` is the nominal coverage level: when `alpha = 0.10`, the interval procedure aims at 90% coverage under the assumptions required by the conformal method. Coverage and interval width must be read together, because a very wide interval can cover often without being informative.

This article therefore treats the empirical output as a controlled measurement exercise. The central question is not 'Which method can we promote?' but 'Which patterns are supported by the completed evidence, and which stronger claims remain outside the current evidence?' That framing is important for readers who are new to conformal prediction: the coverage target explains what the interval is trying to guarantee, while the interpretation boundaries explain what this particular experiment does not prove.

2.2 Guarantee And Claim Boundary Snapshot

The snapshot below is the main article version of the Research Document’s guarantee boundary ledger. It separates conformal prediction’s theorem-level language from the empirical audit language used in this study, and it marks readings that remain outside the current evidence in the article.

Topic	Article statement	Outside current evidence reading
Marginal conformal coverage	The conformal guarantee is a marginal coverage statement under exchangeability and the stated calibration protocol.	It is not conditional, subgroup, endpoint, or deployment coverage.
Empirical coverage	Coverage values in this article summarize observed held-out behavior inside the audited dataset-alpha-method scope.	They are not theorem claims and not general product guidance.
Group diagnostics	Group and Mondrian rows are heterogeneity diagnostics that help read the supplement.	They do not establish population-level group inference while the group-inference-ready bundle count is zero.
Frontier evidence	Frontier counts describe observed coverage-width trade-offs among audited methods.	They are not final method selection or universal superiority claims.
Venn-Abers bridge	The negative evidence concerns the evaluated interval bridge.	It is not a rejection of predictive-distribution or generalized Venn-Abers research.

2.3 Contributions And Boundaries

- The study consolidates a large audited regression conformal-prediction evidence base under resumable, source-traceable execution records.
- It reports CQR/CV+ as strong practical candidates observed in these experiments, without converting that observation into a universal deployment rule.
- It reports the evaluated Venn-Abers regression bridge as negative/failure-mode evidence, without rejecting the broader Venn-Abers literature.
- It keeps population-level group inference, bounded-support validity, final method selection, public release, and citable web-artifact claims outside current evidence unless their explicit evidence gates are opened later.

2.4 Paper Architecture And Review Contract

The paper is organized as a small article, a broad supplement, and working navigation artifacts. This structure follows the source-backed publication exemplar review: the article carries the central claim-evidence narrative, while the supplement and KG carry the detailed audit trail. The contract below tells a reader where to look and what each surface must not claim.

Surface	Reader job	Boundary	Source basis
---------	------------	----------	--------------

Minimal main article	Use the article for the study question, non-specialist primer, claim-evidence map, headline diagnostics, and interpretation-boundary summary.	Read the article as the compact scientific summary of the audited experiment.	Use a minimal main article and a broad supplementary document.
Broad supplementary document	Use the supplement for method detail, robustness diagnostics, post-selection checks, bounded-support policy, group diagnostics, duplicate caveats, and Venn-Abers negative evidence.	Supplementary diagnostics do not open final selection, group inference, or validity claims.	Use a minimal main article and a broad supplementary document.
README review router	Use the README to choose the review path, locate artifacts, and check status before interpreting results.	README navigation does not establish stronger scientific claims or citable status.	Make the README a review router, not a dense methods dump.
Research Atlas site and KG browser	Use the site and KG browser to trace claims to source artifacts, citation gates, quality checks, nodes, edges, and provenance.	The KG and GitHub Pages site are public Research Atlas navigation artifacts.	Use the site as a reader review portal with explicit lanes.
Claim-evidence contract	Use the claim matrix to keep each reader-facing sentence tied to evidence, citation requirements, and an explicit outside current evidence overclaim.	No prose may convert a outside current evidence claim into a positive conclusion.	<code>claim_boundary_for_every_surface</code>

3 Research Questions

The article is organized around five research questions. The answers below are intentionally scoped: each answer states what the audited evidence supports and the stronger reading that remains outside the current evidence.

Research question	Article answer	Evidence anchor	Outside current evidence reading
What empirical object is being audited?	A publication-scoped regression conformal prediction evidence base with 145,839 completed rows, 67 datasets, 95 dataset-alpha cells, and 28 method labels.	Completed-row accounting and individual experiment report facts.	Do not read the scope as exhaustive internet coverage or deployment generality.

Which practical method pattern is supported descriptively?	CQR/CV+ were observed as strong practical candidates in these experiments, with CQR carrying the largest coverage-gated selected-cell count (56) and CV+ contributing 13 coverage-gated selected cells.	Frontier counts, coverage-width diagnostics, and claim/evidence matrix.	Do not turn the pattern into a selected method, best-method statement, or deployment rule.
Was the CQR signal only a fixed-GBM backend artifact?	A completed model-matched CQR rerun produced 4,564 model-matched rows and 224 paired comparison cells. Fixed-GBM CQR was selected in 116 coverage-eligible interval-score cells, model-matched CQR in 71, and neither variant in 37.	Fixed-GBM CQR vs model-matched CQR synthesis.	Do not treat the sensitivity check as a universal CQR deployment rule.
What did the evaluated Venn-Abers regression bridge show?	The evaluated bridge is negative/failure-mode evidence in this study, including 14 undercoverage runs.	Bridge diagnostics and Venn-Abers claim-boundary rows.	Do not reject the broader Venn-Abers predictive-distribution or generalized-calibration literature.
Which stronger positive claims remain outside the current evidence?	Bounded-support validity and population-level group inference remain outside the current evidence: 0 bounded-support-validity-ready bundles and 0 population-group-inference-ready bundles.	Paper gate map, bounded-support audit, group-diagnostic audit, and claim matrix.	Keep diagnostic end-point and group evidence separate from validity or group-inference conclusions.
How can the evidence be audited without opening release?	The KG and Research Atlas package provide traceability infrastructure with 3,643 KG nodes and 21,019 KG edges.	Knowledge-graph quality audit and sterile package metadata.	Use the KG and site to inspect how claims connect to evidence.

4 Concept Bridge For Non-Specialist Readers

This bridge links the main technical concepts to the sources and claim boundaries used in the article. It is intentionally compact: the supplement carries the longer method discussion, while this article keeps only the definitions needed to avoid over-reading the results.

Concept	Source or evidence anchor	Article use	Safe sentence	Outside current evidence sentence
---------	---------------------------	-------------	---------------	-----------------------------------

Conformal prediction target	Distribution-free regression conformal prediction [3]	$1 - \alpha$ is the nominal marginal coverage target under the stated calibration assumptions.	The article may report target and observed coverage separately.	Do not write that the nominal target proves subgroup, endpoint, or future-deployment coverage.
Conformalized Quantile Regression	CQR lower/upper quantile calibration [7]	CQR starts with lower and upper quantile models, then applies conformal calibration to the interval.	CQR can be described as a strong practical candidate observed in these experiments.	Do not write that CQR is the selected, best, or recommended regression conformal method.
CV+ and jackknife-style intervals	Jackknife+/CV+ resampling evidence [1, 2]	CV+ uses out-of-fold prediction evidence so interval construction reflects fitted-model variability.	CV+ can be described as another strong practical candidate observed in these experiments.	Do not write that cross-validation evidence removes all model, split, or dataset caveats.
Venn-Abers regression bridge	Venn-Abers predictive-distribution and generalized-calibration literature [5, 4, 8, 6]	The study evaluates a bridge from Venn-Abers-style calibration evidence into regression interval diagnostics.	The evaluated bridge produced bridge-specific negative evidence in these experiments.	Do not write that the result rejects the broader Venn-Abers literature.
Claim-gated empirical wording	Publication claim-evidence matrix and section-boundary audit	Every empirical sentence is paired with evidence, an allowed reading, and a outside current evidence stronger reading.	Outside current evidence gates are part of the scientific result and should remain visible.	Keep diagnostic patterns separate from deployment, group-inference, endpoint-validity, and release-scope conclusions.

5 Claim-Evidence Map

The table below is the draft’s control surface: every reader-facing claim is paired with source-backed evidence and an explicit boundary. This keeps useful empirical signals separate from unsupported deployment rules, group-inference claims, endpoint-validity claims, and release claims.

Claim surface	Evidence	Supported reading	Boundary
Audited empirical scope	145,839 publication-scoped rows, 67 datasets, 95 dataset-alpha cells, and 28 method labels.	The study has a broad audited regression-CP accounting base.	Scope does not by itself authorize external validity or a general deployment guidance.

CQR/CV+ descriptive performance	CQR appears in 56 coverage-gated selected cells; CV+ appears in 13 coverage-gated selected cells.	CQR/CV+ were observed in these experiments as strong practical candidates.	This is not a claim that either method is universally best for regression conformal prediction.
CQR backend sensitivity check	4,564 model-matched CQR rows paired against 4,564 fixed-GBM CQR rows across 224 dataset-alpha-model-family cells; selected-cell counts are fixed-GBM CQR=116, model-matched CQR=71, neither=37.	The CQR signal was stress-tested against model-matched quantile backends and remains experiment-scoped.	The backend check does not establish a CQR method-selection or deployment guidance claim.
Venn-Abers regression bridge	The evaluated bridge has 14 undercoverage runs in the current evidence base.	The expected strong Venn-Abers regression solution did not emerge in these experiments.	This is not a rejection of the Venn-Abers literature or of future bridge designs.
Bounded-support validity	0 validity-ready bounded-support bundles.	Endpoint/bounded-support diagnostics remain useful audit signals.	No bounded-support validity claim is established.
Population-level group inference	0 population-group-inference-ready bundles.	Group diagnostics can guide supplementary inspection.	No population-level group inference claim is established.
Knowledge-graph traceability	3,643 KG nodes and 21,019 KG edges.	The KG is evidence infrastructure linking artifacts, sections, citations, claims, and quality checks.	The KG becomes a citable web artifact only after sterile-repository review and release.

6 Study Design Summary

The empirical system was designed to survive long execution, partial completion, and later review. Completed rows are counted only after they pass the publication-scoped accounting layer. Dataset-alpha cells preserve the calibration target being evaluated. Method labels preserve the conformal wrapper or calibration family being compared. Interpretation boundaries then decide which interpretations are allowed in the article.

This separation is deliberate. Model training, interval construction, diagnostic aggregation, literature-aware method description, and release scope are treated as different objects. As a result, a useful empirical pattern can be reported without becoming a deployment deployment rule, and a negative result can be retained without being softened into a positive story.

7 Evidence-To-Claim Ladder

The table below shows how a raw experimental object becomes a reader-facing statement in this article. Each step has an allowed claim and a outside current evidence upgrade. The purpose is to make the scientific method visible: evidence can support a scoped statement only after the relevant accounting, diagnostic, claim-boundary, and release checks are kept attached.

Stage	Reader question	Evidence object	Allowed claim	Outside current evidence upgrade
Completed row	What was counted?	145,839 publication-scoped completed rows.	The empirical accounting base is broad and auditable.	A completed row is not, by itself, external validity.
Dataset-alpha cell	What comparison unit was preserved?	95 dataset-alpha cells across 67 datasets.	Coverage behavior is read inside recorded calibration targets.	A dataset-alpha cell is not a population claim.
Method diagnostic	What pattern was observed?	CQR=56, CV+=13, Mondrian=15 coverage-gated selected cells.	CQR/CV+ can be described as strong practical candidates observed here.	Frontier counts do not select a final or universal best method.
Failure-mode diagnostic	What did not work as expected?	14 Venn-Abers bridge undercoverage runs.	The evaluated bridge is reportable as negative evidence.	The result does not reject the broader Venn-Abers literature.
Outside current evidence positive gate	Which stronger claims stay absent?	0 bounded-support-validity-ready bundles and 0 population-group-inference-ready bundles.	Outside current evidence gates are reported as scientific results.	Zero-ready gates cannot be converted into validity or group-inference claims.
Release and citation gate	When can artifacts be cited or published?	Reader review package and KG navigation artifacts.	The artifacts support reader review and traceability.	The public release includes the KG and site as navigation and traceability artifacts.

8 Background And Methods

The core coverage target is $1 - \alpha$; α is the target miscoverage rate. Split conformal regression estimates a residual calibration quantile on held-out calibration data. CQR replaces the single residual score with a lower/upper quantile-regression score and then conformalizes that interval [7]. CV+ and jackknife+ use out-of-fold or leave-one-out predictions to account for fitted-model variability [1, 2].

Venn-Abers-related regression work is handled separately because the literature includes predictive-distribution and calibration objects, not only ordinary interval wrappers [5, 4, 8, 6]. This distinction matters: the present experiment evaluates a current bridge into interval-style diagnostics and therefore reports the observed failure modes without converting them into a validation claim.

8.1 Method Primer For Non-Specialist Readers

A conformal method should be read as a calibration wrapper, not as proof that the base prediction model is correct. The wrapper turns model outputs and calibration evidence into a set-valued prediction; under the method’s assumptions, the target coverage statement is about future exchangeable observations, not about every subgroup, endpoint range, or deployment setting.

CQR means Conformalized Quantile Regression. It starts from lower and upper quantile models, then uses calibration data to correct the interval so the final set can be judged against the nominal coverage target [7]. CV+ belongs to the cross-validation-plus family: it uses out-of-fold prediction evidence rather than one fixed calibration split [1, 2]. In this article, both families are reported only as observed practical candidates in the completed experiment.

The evaluated Venn-Abers regression bridge has a different status. Venn-Abers regression work is closer to predictive distributions and generalized calibration than to a single ordinary interval recipe [5, 4, 8, 6]. The experiment therefore tests a bridge from that calibration evidence into interval diagnostics. The observed undercoverage is evidence against this bridge in this study, not evidence against the whole Venn-Abers research program.

8.2 Reader Safety Checklist

The checklist below is intentionally conservative. It translates the method primer into claim boundaries so a reader can tell which parts are conformal-method background, which parts are empirical findings from this study, and which stronger readings remain outside the current evidence.

Concept	Reader-safe meaning	Outside scope reading
1 - α target	A nominal design target for marginal coverage under the stated calibration protocol.	It is not proof that every subgroup, endpoint region, or future deployment slice is covered at that rate.
CQR	Lower and upper quantile models are conformalized with calibration evidence so intervals can adapt to heterogeneous noise.	It is not a final selected method, universal best method, or deployment guidance.
CV+	Out-of-fold prediction evidence is used to build intervals that reflect fitted-model variability.	It is not caveat-free evidence and does not open final method selection.
Mondrian/group calibration	Calibration can be stratified by groups when the comparison is intended to expose heterogeneity.	It is not a population-level group inference claim while the group-inference-ready bundle count is zero.
Venn-Abers bridge	The experiment evaluates a bridge from Venn-Abers-style calibration evidence into interval diagnostics.	The observed undercoverage is not a rejection of predictive distribution or generalized Venn-Abers research.

Reader question	Short answer	Boundary
What is 1 - α ?	The nominal target coverage level used to design or calibrate the interval.	It is not the realized empirical coverage of every subgroup or future dataset.
What is CQR?	Conformalized Quantile Regression: quantile models plus conformal calibration.	It is an observed strong practical candidate here, not a universal deployment rule.

What is CV+?	A cross-validation-plus interval family using out-of-fold prediction evidence.	Its frontier signal remains diagnostic and experiment-scoped.
What is the Venn-Abers bridge result?	The evaluated bridge did not behave as the expected strong regression solution.	This is bridge-specific negative evidence, not a literature-wide rejection.

8.3 Notation And Evaluation Protocol

For an observation with features $\mathbf{X}_i$ and outcome Y_i , a method m returns an interval $\mathbf{C}_m(\mathbf{X}_i) = [L_m(\mathbf{X}_i), U_m(\mathbf{X}_i)]$. The basic coverage indicator is $1\{Y_i \text{ in } \mathbf{C}_m(\mathbf{X}_i)\}$. Empirical coverage is the average of this indicator over the evaluated rows, and empirical width is the average of $U_m(\mathbf{X}_i) - L_m(\mathbf{X}_i)$. The nominal target $1 - \alpha$ is therefore a target for coverage, not a guarantee that every subgroup, endpoint region, or future dataset will satisfy the same rate.

The article uses these quantities descriptively. A coverage-gated selected cell marks an observed coverage/width trade-off within a dataset- α comparison. Row-weighted coverage summarizes completed result rows. Undercoverage runs identify places where the empirical coverage fell below the target enough to be treated as failure-mode evidence. None of these summaries alone opens a final method-selection, group inference, or bounded-support claim.

Quantity	Definition	Article use
Interval $\mathbf{C}_m(\mathbf{X}_i)$	Lower and upper endpoint returned by method m	Basic object being evaluated
Empirical coverage	Mean of $1\{Y_i \text{ in } \mathbf{C}_m(\mathbf{X}_i)\}$ over evaluated rows	Descriptive calibration evidence
Empirical width	Mean of $U_m(\mathbf{X}_i) - L_m(\mathbf{X}_i)$	Informativeness evidence paired with coverage
Coverage-gated selected cell	Observed coverage/width trade-off cell	Diagnostic pattern, not final selection
Undercoverage run	Completed run below its target boundary	Failure-mode evidence

8.4 Method Mechanics Snapshot

For a non-specialist reader, the methods differ mainly in how they choose or adjust interval endpoints. Split conformal uses a held-out residual quantile. CQR starts with lower and upper quantile models before conformal calibration. CV+ and jackknife+ use out-of-fold or leave-one-out predictions. Mondrian variants calibrate within groups or strata. The evaluated Venn-Abers regression bridge maps a distinct calibration object into interval-style diagnostics.

Method family	Interval mechanism	Boundary in this article
Split conformal	Residual-score quantile on a calibration set	Baseline mechanism; not a complete endpoint or heterogeneity solution
CQR	Lower/upper quantile models plus conformal calibration	Strong practical candidate observed here; not a universal deployment rule
CV+ / jackknife+	Out-of-fold or leave-one-out conformity evidence	Strong practical candidate observed here; no final method selection

Mondrian calibration	Group- or stratum-specific calibration	Diagnostic comparator; not a population-level group inference claim
Venn-Abers bridge	Bridge from Venn-Abers-style calibration evidence to interval diagnostics	Negative evidence for the evaluated bridge only

9 Results

9.1 How To Read The Results Table

The results table mixes scope counts, descriptive method signals, and outside current evidence interpretation boundaries. Coverage-gated selected cells summarize observed coverage/width trade-offs; row-weighted coverage summarizes empirical coverage across completed result blocks; undercoverage runs flag failure modes; and zero-ready gates record claims the article must not make. These quantities support interpretation, not final method selection.

Evidence area	Result	Interpretation
Publication-scoped completed rows	145,839	Empirical accounting scope
Datasets	67	Method synthesis scope
Dataset-alpha cells	95	Calibration/coverage comparison scope
CQR coverage-gated selected cells	56	Largest coverage-gated selected-cell pattern
Mondrian coverage-gated selected cells	15	Secondary descriptive pattern
CV+ coverage-gated selected cells	13	Secondary descriptive pattern
Model-matched CQR completed rows	4,564	Backend sensitivity check completed
CQR fixed-vs-matched paired cells	224	Direct fixed-GBM versus model-matched CQR comparison
Venn-Abers bridge under-coverage runs	14	Negative/failure-mode evidence
Bounded-support validity-ready bundles	0	No bounded-support validity claim
Population-group-inference-ready bundles	0	No population-level group inference claim

The descriptive method result is internally consistent with the individual experiment report: CQR has the largest current frontier share, but the final selection claim remains outside current evidence. The correct claim is not that CQR is the best regression conformal method in general; the supported claim is that CQR is the largest current diagnostic coverage-gated selected pattern in this audited study.

9.2 CQR Backend Sensitivity Check

A completed model-matched CQR rerun tests whether the historical fixed-GBM CQR pipeline alone explains the CQR signal. The rerun completed 4,564 model-matched CQR rows and pairs them with 4,564 fixed-GBM CQR rows across 224 dataset-alpha-model-family cells.

CQR variant outcome	Coverage-eligible interval-score selected cells
Fixed-GBM CQR	116
Model-matched CQR	71
Neither coverage-eligible variant	37

This check keeps the interpretation conservative. It supports a pipeline-level backend sensitivity statement and does not convert CQR into a universal method-selection, best-method claim, or deployment guidance.

10 Discussion

The study’s main scientific value is the combination of broad empirical accounting and explicit negative evidence. Venn-Abers is not forced into a positive result: the current bridge shows 14 undercoverage runs and is therefore reported as a failure mode. This is compatible with the broader Venn-Abers literature because the bridge design is part of the empirical object being tested.

The outside current evidence claims are also results. Zero bounded-support validity-ready bundles and zero population-group-inference-ready bundles mean the article should not claim endpoint validity or group inference. Those boundaries prevent useful diagnostics from becoming stronger claims than the evidence supports.

11 Reproducibility And Traceability

The knowledge graph snapshot used by this draft has 3,643 nodes and 21,019 edges. The graph links report sections, source artifacts, citation keys, claim boundaries, and quality checks. It is evidence infrastructure for the article and will become citable only after the sterile repository and release review are complete.

12 Limitations

- The method evidence is descriptive and diagnostic; it is not a general deployment rule.
- Venn-Abers evidence is negative for the current bridge; it is not a rejection of the entire literature.
- Group metrics are diagnostic and do not establish population-level group inference.
- Endpoint audits currently block bounded-support validity claims.

13 Conclusion

This report closes with a descriptive, not prescriptive, interpretation of the completed regression conformal-prediction evidence. The audited evidence base supports reporting CQR/CV+ as strong practical candidates observed in these experiments and the evaluated Venn-Abers regression bridge as bridge-specific negative evidence. It does not support final method selection, broad deployment guidance, bounded-support validity, or population-level group inference.

The scientific contribution is therefore the audited measurement and boundary record itself: useful empirical patterns are retained, negative evidence is not rewritten as success, and outside current evidence claims remain visible until later evidence explicitly opens them.

14 References

- @barber2020jackknife_plus: <https://arxiv.org/abs/1905.02928>
- @kim2020jackknife_after_bootstrap: <https://arxiv.org/abs/2002.09025>
- @lei2017distribution_free_regression: <https://arxiv.org/abs/1604.04173>
- @nouretdinov2018ivapd: <https://proceedings.mlr.press/v91/nouretdinov18a.html>
- @nouretdinov2024ivapd_applications: <https://proceedings.mlr.press/v230/nouretdinov24a.html>
- @petej2026inductive_venn_abers_regressors: <https://arxiv.org/html/2605.06646v1>
- @romano2019conformalized_quantile_regression: <https://arxiv.org/abs/1905.03222>
- @vanderlaan2025generalized_venn_abers: <https://proceedings.mlr.press/v267/van-der-laan25a.html>

15 Source Artifacts

- individual_experiment_report_draft: experiments/regression/Research Document/
individual_experiment_report_draft.json
- article_supplement_blueprint_alignment: experiments/regression/Research
Document/article_supplement_blueprint_alignment.json
- Research_Document_section_evidence_packet: experiments/regression/Research
Document/Research_Document_section_evidence_packet.json
- section_claim_boundary_audit: experiments/regression/Research Document/
section_claim_boundary_audit.json
- publication_claim_evidence_verification_matrix: experiments/regression/
Research_Document/publication_claim_evidence_verification_matrix.json
- publication_citation_registry: experiments/regression/Research Document/
publication_citation_registry.json
- publication_exemplar_review: experiments/regression/Research Document/
publication_exemplar_review.json

- `knowledge_graph_quality_summary:` `experiments/regression/reports/knowledge_graph_quality/quality_summary.json`
- `cqr_fixed_vs_model_matched_synthesis:` `experiments/regression/reports/model_matched_cqr_rerun_plan/cqr_fixed_vs_model_matched_synthesis.json`

References

- [1] Rina Foygel Barber, Emmanuel J. Candes, Aaditya Ramdas, and Ryan J. Tibshirani. Predictive inference with the jackknife+, 2020.
- [2] Byol Kim, Chen Xu, and Rina Foygel Barber. Predictive inference is free with the jackknife+-after-bootstrap, 2020.
- [3] Jing Lei, Max G’Sell, Alessandro Rinaldo, Ryan J. Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression, 2017.
- [4] Ilia Nourtdinov and James Gammerman. Inductive venn-abers predictive distributions: New applications & evaluation. In *Proceedings of the Thirteenth Symposium on Conformal and Probabilistic Prediction with Applications*, volume 230 of *Proceedings of Machine Learning Research*, pages 490–507. PMLR, 2024.
- [5] Ilia Nourtdinov, Denis Volkhonskiy, Pitt Lim, Paolo Toccaceli, and Alexander Gammerman. Inductive venn-abers predictive distribution. In *Proceedings of the Seventh Workshop on Conformal and Probabilistic Prediction and Applications*, volume 91 of *Proceedings of Machine Learning Research*, pages 15–36. PMLR, 2018.
- [6] Ivan Petej and Vladimir Vovk. Inductive venn-abers and related regressors, 2026.
- [7] Yaniv Romano, Evan Patterson, and Emmanuel J. Candes. Conformalized quantile regression, 2019.
- [8] Lars Van Der Laan and Ahmed Alaa. Generalized venn and venn-abers calibration with applications in conformal prediction. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 60748–60763. PMLR, 2025.