inner_text(), text_content(), all_inner_texts(), all_text_contents(), and all()

1️⃣ inner_text() vs text_content()

Both methods retrieve text from a **single element** – but there are key differences:

Method	What It Does	Key Points	When to Use
inner_text()	Returns the **visible text** of the element	✅ Ignores hidden elements ✅ Removes extra whitespaces ✅ Removes line breaks	When you want **clean, user-visible text** for validation
text_content()	Returns the **raw text content** of the element.	❌ Includes hidden text ❌ Keeps extra spaces, tabs, and line breaks 🔄 Returns None if element has no text	When you want **exact text** including hidden/whitespace.

Example:

```
product = page.locator(".product-title").nth(1)

print(product.inner_text())     # Clean visible text: '14.1-inch Laptop'

print(product.text_content())   # Raw text with spaces: '\n   14.1-inch Laptop  \n'
```

2️⃣ all_inner_texts() vs all_text_contents()

Both methods return **text from multiple elements at once**, as a **list of strings**.

Method	What It Does	Key Points
all_inner_texts()	Returns **visible text** of each matched element (cleaned)	✅ Removes whitespace/line breaks ✅ Ignores hidden text
all_text_contents()	Returns **raw text content** of each matched element	❌ Keeps whitespaces and line breaks ❌ Includes hidden text

Example:

```
products = page.locator(".product-title")
print(products.all_inner_texts())
```

Output: ['14.1-inch Laptop', 'Build your own cheap computer', 'Digital Storm ...']

```
print(products.all_text_contents())
```

Output: ['\n 14.1-inch Laptop \n', '\n Build your own cheap computer \n', ...]

You can clean the result manually:

```
product_names = [text.strip() for text in products.all_text_contents()]
print(product_names)
```

3 all() – Converting Locator to List of Locators

The all() method **converts a Locator into a list of individual locators**.
This allows you to iterate over them and perform actions one by one.

Method	What It Does
locator.all()	Returns a **list of Locator objects** (one per element)

Example:

```
products = page.locator(".product-title")
product_locators = products.all()  # Now we have a Python list of Locators
print(product_locators)  # [<Locator ...>, <Locator ...>, <Locator ...>]
```

```
# Loop through each locator
for product in product_locators:
    print(product.inner_text())
```

This is useful when:

- You need to **click each element** one by one.
- You want to **perform different actions** per element (not just read all text at once).
- You want to **combine with index-based logic** (e.g., click the 2nd, 4th, and 5th element only).

Summary Table

Concept	Returns	Cleans Whitespace?	Includes Hidden Text?	Best Use Case
inner_text()	Single string	✅ Yes	❌ No	Get visible text of one element
text_content()	Single string (or None)	❌ No	✅ Yes	Get raw/unprocessed text
all_inner_texts()	List of strings	✅ Yes	❌ No	Get visible text of multiple elements
all_text_contents()	List of strings	❌ No	✅ Yes	Get raw text of multiple elements
all()	List of Locators	N/A	N/A	Iterate and act on elements individually