

# Boolean Indexing with NumPy:

## Takeaways



by Dataquest Labs, Inc. - All rights reserved © 2024

## Syntax

### READING CSV FILES WITH NUMPY

- Reading in a CSV file with a single header row:

```
import numpy as np
taxi = np.genfromtxt('nyc_taxis.csv', delimiter=',', skip_header=1)
```

### BOOLEAN ARRAYS

- Creating a Boolean array using a comparison operator:

```
np.array([2,4,6,8]) < 5
```

- Boolean filtering for 1D ndarray:

```
a = np.array([2, 4, 6, 8])
filter = a < 5
a[filter]
```

- Boolean filtering for 2D ndarray:

```
tip_amount = taxi[:, 12]
tip_bool = tip_amount > 50
top_tips = taxi[tip_bool, 5:14]
```

### ASSIGNING VALUES

- Assigning values in a 2D ndarray using indices:

```
taxi[1066, 5] = 1
taxi[:, 0] = 16
taxi[550:552, 7] = taxi[:, 7].mean()
```

- Assigning values using Boolean arrays:

```
taxi[taxi[:, 5] == 2, 15] = 1
```

## Concepts

- Selecting values from a ndarray using Boolean arrays is very powerful. Using Boolean arrays helps us think in terms of filters on the data, instead of specific index values.

## Resources

- [Reading a CSV file into NumPy](#)
- [ndarray.shape attribute](#)

- [ndarray.dtype attribute](#)
- [None constant](#)
- [Comparison operators](#)
- [ndarray.copy method](#)
- [numpy.zeros function](#)
- [ndarray.mean\(\) method](#)

Takeaways by Dataquest Labs, Inc. - All rights reserved © 2024