C2B QUERY API

API Specification Document

©NCBA Bank PLC 2024 | C2B Query API

Contents

BACKGROUND 3

i. Token Generation 3

Request 3

Authorization 3

Request Body 3

Response 3

ii. Transaction Query 4

Request 4

Authorization 4

Request Body 4

Request Body 4

Response 4

Sample Response Request 4

Example Response 5

BACKGROUND

The C2B Query API allows customer who have integrated to query and fetch a paybill or Buygoods transaction using M-Pesa reference as the query parameter.

To enjoy this service, interested business merchants (customers) are required to;

a) Hold an Account at NCBA where mobile funds shall be credited
b) Has an active Paybill, Buygoods and/or an NCBA Till short code
c) Develop and integrate to the query API or as per below specifications
d) Submit a signed instruction/letter to the bank for completion of the integration;
   Share a user name (first and last name), user name and a secret key on the letter.

BASE_URL = https://c2bapis.ncbagroup.com

i. Token Generation

This endpoint sends an HTTP GET request to generate a token for authentication

Request

Method	URL
GET	BASE_URL/api/auth/generate-token

Authorization

Type	Params	Values
HEAD	Authorization	Basic {base64-encoded(username:password)}

Request Body

This request does not require a request body.

Response

- message (string): A message related to the response.
- responseCode (string): The response code indicating the status of the request.
- token (string): The generated authentication token.

Status	Response

200	{
	"message": "success",
	"responseCode": "000",
	"token":
	"eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiJJQlBTliwiaWF0IjoxNzE3Mzk4NzE0LCJleHAiOjE3MTc0MDIzMTR9.yQtAmQab-oWlHVrgdc1TvYIAW4kuymMeWA0VwiDPM6U"
	}

200	{
	"message": "Invalid API credentials",
	"responseCode": "001""
	}

ii. Transaction Query

This endpoint is used to check the availability of IBPS (Immediate Payment Service) based on the provided parameters.

Request

Method	URL
POST	BASE_URL/api/payments/query

Authorization

Type	Params	Values
HEAD	Authorization	Bearer token

Request Body

- SHORTCODE (string): The shortcode for the payment query.
- TYPE (string): The type of payment being queried.
- MPESA_REFERENCE (string): The M-Pesa reference for the payment.

Request Body

```
{
 "SHORTCODE":"878787",
 "TYPE": "CORPORATE",
 "MPESA_REFERENCE": "SG84XUBHT4"
}
```

Response

The response will be in the form of a JSON schema:
JSON

Sample Response Request

- message (string): A message related to the query.
- transactions (array): An array of transaction details.
    - ✓ mobile (string): The mobile number associated with the transaction.
    - ✓ transAmount (number): The amount of the transaction.
    - ✓ transID (string): The transaction ID.
    - ✓ businessShortCode (string): The organization short code.
    - ✓ name (string): The name associated with the shortcode.
    - ✓ transType (string): The type of the transaction.
    - ✓ billRefNumber (string): The bill reference number.
    - ✓ transTime (string): The time of the transaction.
- status (number): The status of the query

Example Response

JSON


```
{
"message": "",
"transactions": [
        {
        "mobile": "",
        "transAmount": 0,
        "transID": "",
        "businessShortCode": "",
        "name": "",
        "transType": "",
        "billRefNumber": "",
        "transTime": ""
        }
],
"status": 0
}
```