

Estimated TDS Values by Area — Faisalabad, Punjab, Pakistan

Important: These are screening estimates for untreated local groundwater/tube-well water, not certified or current readings for individual homes. TDS can change substantially by water source, well depth, season, pipe condition, filtration, and location within the same locality.

Area	Estimated TDS (mg/L / ppm)	Interpretation
Ghulam Muhammad Abad	900–2,000	Often high; verify before drinking
Rasool Nagar	800–1,800	Variable urban groundwater
Jinnah Colony	700–1,600	Moderate to high possible
Gulberg	700–1,600	Moderate to high possible
People's Colony No. 1	600–1,400	Variable; supply source matters strongly
People's Colony No. 2	700–1,600	Variable; bore water may be higher
Madina Town	600–1,400	Moderate range, but highly source-dependent
Susan Road	700–1,700	Urban/roadside bore water can be elevated
Samanabad	800–1,800	Moderate to high possible
D-Type Colony	800–1,800	Moderate to high possible
Nisar Colony	900–2,000	Higher risk of saline groundwater
Sir Syed Town	800–1,800	Moderate to high possible
Allama Iqbal Colony	900–2,000	Higher-priority area for testing
Batala Colony	1,000–2,300	High-risk range; industrial/urban influence possible
Warispura	1,000–2,500	High-risk range; test bore water
Ayub Colony	800–1,800	Moderate to high possible
Nishatabad	1,200–3,000	Higher risk; industrial influence may affect groundwater
Millat Town	900–2,000	High variation between wells
Mansoorabad	900–2,000	Moderate to high possible
Nigehban Pura	1,000–2,500	Higher-risk groundwater estimate
Sargodha Road	1,000–2,500	High variability; roadside/industrial influence
Canal Road	500–1,300	Often comparatively better where canal recharge influences groundwater, but not guaranteed
Factory Area	1,500–3,500+	Very high risk; do not assume bore water is drinkable
Jaranwala Road	900–2,200	Variable; outer industrial stretches can be worse
Chak 224 RB	700–1,800	Agricultural-area variation; test local source
Lathianwala / Chak 194–200 RB	700–1,800	Variable rural groundwater
Chak 7 JB	800–2,000	Variable, often moderately saline
Sadhar	800–2,000	Rural/peri-urban groundwater can be high

Area	Estimated TDS (mg/L / ppm)	Interpretation
Dijkot	900–2,200	Moderate to high likely
Chak Jhumra	2,500–7,500+	Very high risk; strongly brackish conditions reported
Jaranwala City	900–2,200	Moderate to high likely; local water source matters
Samundri City	1,000–2,500	Higher risk; salts and TDS can be elevated
Tandlianwala City	1,000–2,500	Higher risk; test before relying on groundwater
Mamukanjan	900–2,200	Moderate to high likely

How to interpret a TDS reading

TDS reading	Meaning
Below 300 ppm	Low mineral content; generally acceptable from a TDS perspective
300–500 ppm	Generally acceptable TDS range
500–1,000 ppm	Noticeable dissolved salts; test full chemistry and microbiology
1,000–2,000 ppm	High; avoid untreated regular drinking and arrange further testing
2,000–3,000 ppm	Very high/brackish; appropriate treatment is needed
Above 3,000 ppm	Strongly brackish; generally unsuitable for ordinary drinking without appropriate treatment

Key notes

- Published Faisalabad groundwater studies have reported TDS values ranging approximately from 138 to 3,926 mg/L, with substantial variation across the city and district.
- Areas near industrial activity, drains, and wastewater-affected corridors can have higher dissolved salts and other contaminants. Factory Area, Nishatabad, Batala Colony, Warispura, the Sargodha Road corridor, and Chak Jhumra should be treated as priorities for actual testing.
- Canal Road and canal-recharged zones may have comparatively lower TDS in some wells, but this cannot confirm safety for every house or bore.
- TDS alone does not prove water is safe. For drinking water, test E. coli/coliform bacteria, arsenic, fluoride, nitrate, hardness, chloride, sulphate, iron, and heavy metals as appropriate.
- For a household measurement, run the source for 2–3 minutes, collect a clean sample, and measure with a calibrated handheld TDS meter. Record the date, location, source type, and reading.

Source basis: public Faisalabad groundwater studies, regional planning documents, and water-quality reports consulted on 26 September 2026. The locality-level figures are estimated ranges synthesized from this broader evidence and are not laboratory results.