Legend:
↯ Electrified Opening

Door#	HwSet#
D1-001	001
D1-002↯	002
D1-003A↯	003
D1-003B↯	004
D1-004	005
D1-005.1	006
D1-005.2↯	007
D1-005.3	001
D1-005.4	008
D1-005.5	009
D1-005A	010
D1-006↯	011
D1-007↯	012
D1-010	013
D1-011↯	014
D1-011.1	015
D1-012	016
D1-013	006
D1-014↯	017
D1-015	018
D1-015.2	013
D1-016A	018
D1-016B	018
D1-017A	019
D1-017B	020
D1-018	021
D1-019	022
D1-020↯	012
D1-021.1	013
D1-021.2	023
D1-021.3	023
D1-021.4	006
D1-021.A↯	024
D1-021.B↯	025
D1-021.C↯	026
D1-022.1A↯	027
D1-022.1B↯	028
D1-022A↯	029
D1-022B	030
D1-022C↯	031
D1-022D	030
D1-023A↯	032
D1-023B↯	032
D1-024A↯	029

Door#	HwSet#
D1-024B	033
D1-025↯	012
D1-026↯	034
D1-027	035
D1-028	001
D1-033	036
D1-033.1	037
D1-034.1	037
D1-034A	036
D1-034B	038
D1-035↯	039
D1-036	040
D1-037	036
D1-037.1	037
D1-038	036
D1-038.1	037
D1-039↯	041
D1-040	036
D1-040.1	037
D1-041	042
D1-042	036
D1-042.1	037
D1-043	036
D1-043.1	037
D1-044	036
D1-044.1	037
D1-045	036
D1-045.1	037
D1-046	043
D1-047↯	044
D1-048	036
D1-048.1	037
D1-049	036
D1-049.1	037
D1-050	045
D1-052	036
D1-052.1	037
D1-053	036
D1-053.1	037
D1-054	046
D1-055	040
D1-056	036
D1-056.1	037
D1-057↯	047

Door#	HwSet#
D1-058	036
D1-058.1	037
D1-059	048
D1-060	036
D1-060.1	037
D1-061	041
D1-062	036
D1-062.1	037
D1-063	049
D1-063.1	037
D1-064	050
D1-065A	051
D1-065B	047
D1-066A	052
D1-066B	053
D1-067	040
D1-068	054
D1-069	001
D1-070	007
D1-071	002
D1-072	035
D1-073	055
D1-COMM.1	056
D1-COMM.2	057
D1-COMM.3	058
D1-CORR.4	059
D1-CORR.5	060
D1-CORR.10	061
D1-ELEC.1	062
D1-ELEC.2	063
D1-ELEC.3A	050
D1-ELEC.3B	064
D1-ELEC.4	065
D1-ELEC.5	066
D1-MECH.1	067
D1-MECH.2	068
D1-MECH.3	069
D1-PRAC	070
D1-SHED.1	067
D1-ST.1A	071
D1-ST.1B	072
D1-ST.2	071
D1-ST.4A	073
D1-ST.4B	074
D1-ST.5A	073
D1-ST.5B	071

Door#	HwSet#
D1-STOR.1	035
D1-VEST.1A	075
D1-VEST.1B	076
D1-VEST.2A	077
D1-VEST.2B	078
D1-VEST.3A	079
D1-VEST.3B	079
D1-VEST.5	080
D1-VEST.6A	079
D1-VEST.6B	079
D2-001A	047
D2-001B	081
D2-002	036
D2-002.1	037
D2-003	036
D2-003.1	037
D2-004	046
D2-005	036
D2-005.1	037
D2-006	001
D2-007	041
D2-009	045
D2-012	036
D2-012.1	037
D2-013	082
D2-014	036
D2-014.1	037
D2-015	036
D2-015.1	037
D2-016	016
D2-017	040
D2-018	036
D2-018.1	037
D2-019	049
D2-019.1	037
D2-020	043
D2-021	036
D2-021.1	037
D2-022	036
D2-022.1	037
D2-023.1	037
D2-023A	036
D2-023B	038
D2-024	036
D2-024.1	037
D2-025	036

Door#	HwSet#
D2-025.1	037
D2-026	036
D2-026.1	037
D2-027 ✓	044
D2-028	036
D2-028.1	037
D2-030	036
D2-030.1	037
D2-031 ✓	047
D2-032A ✓	053
D2-032B ✓	053
D2-033	036
D2-033.1	037
D2-034	040
D2-035	036
D2-035.1	037
D2-036	040
D2-037.1	083
D2-037.2	083
D2-037.3	083
D2-037.4	083
D2-037A	084
D2-037B	085
D2-038	015
D2-038.1	086
D2-040 ✓	087
D2-040.1	088
D2-041.1A ✓	089
D2-041.1B ✓	090
D2-041.1C ✓	090
D2-041B	091
D2-042	049
D2-042.1	092
D2-043	006
D2-047	001
D2-048	036
D2-050.1	037
D2-051	036
D2-051.1	037
D2-052 ✓	039
D2-053	036
D2-053.1	037
D2-054 ✓	044
D2-055	036
D2-055.1	037
D2-056	021

Door#	HwSet#
D2-057	036
D2-057.1	037
D2-058	036
D2-058.1	037
D2-059	036
D2-059.1	037
D2-060	040
D2-061	036
D2-061.1	037
D2-062	042
D2-062.1	037
D2-063	036
D2-063.1	037
D2-064	036
D2-065 ✓	041
D2-066	036
D2-066.1	037
D2-067	049
D2-067.1	037
D2-068A	051
D2-068B ✓	047
D2-069A ✓	093
D2-069B ✓	053
D2-070 ✓	047
D2-071 ✓	054
D2-072 ✓	002
D2-073 ✓	007
D2-074 ✓	094
D2-075 ✓	095
D2-076.1	096
D2-076.1.1	037
D2-076.2	097
D2-076A ✓	098
D2-076B	045
D2-077.1	097
D2-077.2 ✓	099
D2-077A ✓	100
D2-077B ✓	099
D2-129	035
D2-COMM.1 ✓	058
D2-COMM.2 ✓	057
D2-COMM.3 ✓	058
D2-CORR.3 ✓	101
D2-CORR.5 ✓	101
D2-CORR.6 ✓	059
D2-CORR.10 ✓	061

Door#	HwSet#
D2-ELEC.1	062
D2-ELEC.2	102
D2-ELEC.3	068
D2-ELEC.4	062
D2-ELEC.5	062
D2-MECH.2	069
D2-ST.1	080
D2-ST.2A	071
D2-ST.2B	073
D2-ST.3B	103
D2-ST.4	080
D2-ST.5	071
D2-STOR.1	035
D2-STOR.2	104
D2-STOR.3	035
D2-VEST.1A	105
D2-VEST.1B	100
D2-VEST.1C	100
D2-VEST.1D	106
D2-VEST.3A	033
D2-VEST.3B	107
D2-VEST.4	080
D3-001A	047
D3-001B	081
D3-002	036
D3-002.1	037
D3-003	036
D3-003.1	037
D3-004	046
D3-005	036
D3-005.1	037
D3-006	001
D3-007	041
D3-009	045
D3-012	036
D3-012.1	037
D3-013A	082
D3-014	036
D3-014.1	037
D3-015	036
D3-015.1	037
D3-016	016
D3-017	040
D3-018	036
D3-018.1	037
D3-019	036

Door#	HwSet#
D3-019.1	037
D3-020	043
D3-021	036
D3-021.1	037
D3-022	036
D3-022.1	037
D3-023.1	037
D3-023A	036
D3-023B	038
D3-024	036
D3-024.1	037
D3-025	036
D3-025.1	037
D3-026	036
D3-026.1	037
D3-027	044
D3-028	036
D3-028.1	037
D3-030	036
D3-030.1	037
D3-031	047
D3-032	036
D3-032.1	037
D3-033A	053
D3-033B	053
D3-034	040
D3-035	036
D3-035.1	037
D3-036	040
D3-037	043
D3-038	036
D3-038.1	037
D3-039	036
D3-039.1	037
D3-040	036
D3-040.1	037
D3-041	036
D3-041.1	037
D3-042	049
D3-042.1	037
D3-043	040
D3-044	016
D3-045	036
D3-045.1	037
D3-046A	053
D3-046B	053

Door#	HwSet#
D3-047.1	037
D3-047A	036
D3-047B	038
D3-048A ✓	047
D3-048B	005
D3-049	046
D3-050 ✓	047
D3-051A	108
D3-051B	108
D3-052	109
D3-055	036
D3-055.1	037
D3-056	036
D3-056.1	037
D3-057 ✓	044
D3-058	036
D3-058.1	037
D3-059 ✓	110
D3-060	036
D3-060.1	037
D3-061	036
D3-061.1	037
D3-062	036
D3-062.1	037
D3-063	040
D3-064	036
D3-064.1	037
D3-065 ✓	041
D3-066	036
D3-066.1	037
D3-067	036
D3-067.1	037
D3-068	043
D3-069 ✓	082
D3-070	036
D3-070.1	037
D3-072	036
D3-072.1	037
D3-074	001
D3-075	040
D3-077	049
D3-077.1	111
D3-079 ✓	112
D3-COMM.1 ✓	058
D3-COMM.2 ✓	057
D3-CORR.2 ✓	101

Door#	HwSet#
D3-CORR.5 ✓	101
D3-CORR.7 ✓	059
D3-CORR.10 ✓	101
D3-ELEC.1	062
D3-ELEC.2	102
D3-ELEC.3	062
D3-MECH.1	113
D3-ST.1A ✓	080
D3-ST.2	071
D3-ST.3 ✓	114
D3-ST.4 ✓	080
D3-STOR.1	035
D3-STOR.2	046
D3-STOR.3	035
D3-STOR.4 ✓	115
D3-VEST.1A ✓	105
D3-VEST.1B ✓	100
D3-VEST.1C ✓	100
D3-VEST.1D ✓	116
D3-VEST.4A ✓	105
D3-VEST.4B ✓	116
D3-VEST.4C ✓	100
D3-VEST.4D ✓	117
D4-001A ✓	047
D4-001B ✓	081
D4-002	036
D4-002.1	037
D4-003	036
D4-003.1	037
D4-004	046
D4-005	036
D4-005.1	037
D4-006	001
D4-007 ✓	041
D4-009	045
D4-012	036
D4-012.1	037
D4-013 ✓	082
D4-014	036
D4-014.1	037
D4-015	036
D4-015.1	037
D4-016	016
D4-017	040
D4-018	036
D4-018.1	037

Door#	HwSet#
D4-019	036
D4-019.1	037
D4-020	043
D4-021	036
D4-021.1	037
D4-022	036
D4-022.1	037
D4-023.1	037
D4-023A	036
D4-023B	038
D4-024	036
D4-024.1	037
D4-025	036
D4-025.1	037
D4-026	036
D4-026.1	037
D4-027 ✓	044
D4-028	036
D4-028.1	037
D4-030	036
D4-030.1	037
D4-031 ✓	047
D4-032	036
D4-032.1	037
D4-033A ✓	053
D4-033B ✓	053
D4-034	040
D4-035	036
D4-035.1	037
D4-036	040
D4-037	043
D4-038	036
D4-038.1	037
D4-039	036
D4-039.1	037
D4-040	036
D4-040.1	037
D4-041	036
D4-041.1	037
D4-042	049
D4-042.1	037
D4-043	040
D4-044	016
D4-045	036
D4-045.1	037
D4-046A ✓	053

Door#	HwSet#
D4-046B ✓	053
D4-047.1	037
D4-047A	036
D4-047B	038
D4-048A ✓	047
D4-048B ✓	047
D4-049	006
D4-050 ✓	047
D4-052	109
D4-055	036
D4-055.1	037
D4-056	036
D4-056.1	037
D4-057 ✓	044
D4-058	036
D4-058.1	037
D4-059	036
D4-059.1	037
D4-060	036
D4-060.1	037
D4-061	040
D4-062	036
D4-062.1	037
D4-063	036
D4-063.1	037
D4-064 ✓	041
D4-065	036
D4-065.1	037
D4-066	036
D4-066.1	037
D4-067	043
D4-068 ✓	082
D4-069	036
D4-069.1	037
D4-071	036
D4-071.1	037
D4-073	001
D4-074	040
D4-075	049
D4-075.1	118
D4-076 ✓	119
D4-076.1	111
D4-COMM.1 ✓	058
D4-COMM.2 ✓	057
D4-CORR.3 ✓	101
D4-CORR.5 ✓	101

Door#	HwSet#
D4-CORR.6 ✓	101
D4-CORR.7 ✓	059
D4-ELEC.1	062
D4-ELEC.2	102
D4-ELEC.3	062
D4-MECH.1	113
D4-ST.1 ✓	080
D4-ST.2	071
D4-ST.4 ✓	080
D4-STOR.1	035
D4-STOR.2	120
D4-STOR.3	121
D4-STOR.4 ✓	115
D4-VEST.1A ✓	105
D4-VEST.1B ✓	100
D4-VEST.1C ✓	100
D4-VEST.1D ✓	116
D4-VEST.4A ✓	105
D4-VEST.4B ✓	116
D4-VEST.4C ✓	100
D4-VEST.4D ✓	117
D5-001A ✓	047
D5-001B ✓	081
D5-002	036
D5-002.1	037
D5-003	036
D5-003.1	037
D5-004	046
D5-005	036
D5-005.1	037
D5-006	001
D5-007 ✓	041
D5-008A	108
D5-008B	108
D5-009	045
D5-012 ✓	082
D5-013 ✓	110
D5-014	016
D5-015	040
D5-016	043
D5-017	049
D5-017.1	037
D5-018	036
D5-018.1	037
D5-019	036
D5-019.1	037

Door#	HwSet#
D5-020	036
D5-020.1	037
D5-021	036
D5-021.1	037
D5-022 ✓	044
D5-023	036
D5-023.1	037
D5-024	122
D5-026	036
D5-026.1	037
D5-027 ✓	047
D5-028	036
D5-028.1	037
D5-029A ✓	053
D5-029B ✓	053
D5-030	040
D5-031	036
D5-031.1	037
D5-032	040
D5-033	123
D5-034	043
D5-035	036
D5-035.1	037
D5-036	036
D5-036.1	037
D5-037	036
D5-037.1	037
D5-038	036
D5-038.1	037
D5-039	049
D5-039.1	037
D5-040	040
D5-041	016
D5-042	036
D5-042.1	037
D5-043A ✓	053
D5-043B ✓	053
D5-044.1	037
D5-044A	036
D5-044B	038
D5-045A ✓	047
D5-045B ✓	047
D5-046	046
D5-047 ✓	047
D5-049	109
D5-052	036

Door#	HwSet#
D5-052.1	037
D5-053	036
D5-053.1	037
D5-054	044
D5-055	036
D5-055.1	037
D5-056	036
D5-056.1	037
D5-057	036
D5-057.1	037
D5-058	040
D5-059	036
D5-059.1	037
D5-060	036
D5-060.1	037
D5-061	041
D5-062	036
D5-062.1	037
D5-063	036
D5-063.1	037
D5-064	043
D5-065	082
D5-066	036
D5-066.1	037
D5-068	036
D5-068.1	037
D5-070	001
D5-071	040
D5-073	119
D5-073.1	111
D5-COMM.1	058
D5-COMM.2	057
D5-CORR.3	124
D5-CORR.5	124
D5-CORR.7	059
D5-CORR.10	101
D5-ELEC.1	062
D5-ELEC.2	102
D5-ELEC.3	020
D5-MECH.1	113
D5-ST.1	080
D5-ST.2	071
D5-ST.4	080
D5-STOR.1	120
D5-STOR.2	121
D5-STOR.3	115

Door#	HwSet#
D5-VEST.1A	105
D5-VEST.1B	100
D5-VEST.1C	100
D5-VEST.1D	116
D5-VEST.4A	105
D5-VEST.4B	116
D5-VEST.4C	100
D5-VEST.4D	125
D6-001	126
D6-002	065
D6-002.1	065
D6-002A	127
D6-003.1	065
D6-004	065
D6-005A	065
D6-005B	126
D6-ST.1	128
MISC. ITEMS	129
TD1-002	130
TD1-003	130
TD1-005	131
TD1-005.1	131
TD1-005.2A	131
TD1-005.2B	131
TD1-005.3A	131
TD1-005.3B	131
TD1-CORRS.5A	132
TD1-CORRS.5B	133
TD1-CORRS.5C	134
TD1-ST.4B	135
TD3-001	071

Legend:
Link to catalog cut sheet
Electrified Opening

Hardware Group No. 001

For use on Door #(s):

D1-001	D1-005.3	D1-028	D1-069	D2-006	D2-047
D3-006	D3-074	D4-006	D4-073	D5-006	D5-070

Provide each DA door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7255 SET		626	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR W/ INSIDE INDICATOR	L9040 17B L583-363 OS-OCC IS-LOC		626	SCH
1	EA	EMER. STOP ASSEMBLY	299-AB/AS X JAMB DEPTH		US32D	IVE
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	GASKETING	8150SBK PSA X 2/JAMBS		BK	ZER

NOTE:
-ADJUST OVERHEAD STOP DEGREE OF OPENING PER SITE CONDITIONS.
-CONFIRM JAMB DEPTH SCHEDULED FOR DOUBLE-LIPPED STRIKE.
-CONFIRM DOOR LOCATION WITHIN FRAME (CENTER / OFFSET).

Hardware Group No. 002

For use on Door #(s):
D1-002 D1-071 D2-072

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 003

For use on Door #(s):
D1-003A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
2	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
2	EA	MANUAL FLUSH BOLT	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	DEADBOLT	TD1850		628	TAH
1	EA	THUMBTURN	TT1025		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
2	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
2	EA	OH STOP & HOLDER	100H		630	GLY
2	EA	SURFACE CLOSER	4040XP TOP JAMB		689	LCN
2	EA	FLUSH CEILNG MTG PLATE	4040XP-18G SRT		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	FULL LENGTH INTERCONNECTED ASTRAGAL	BY ALUMINUM DOOR/FRAME SUPPLIER			
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
2	EA	CONCEALED DOOR CONTACT	7764		628	SCE

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

Hardware Group No. 004

For use on Door #(s):
D1-003B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9095P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP EDA ST-3068		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-4RL-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED BOTH SIDES.
-PRESENTING VALID CREDENTIAL ON EITHER SIDE, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS CROSSING.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED BOTH SIDES.
-KEY OVERRIDE ON BOTH SIDES ALLOWS CROSSING.
-DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 005

For use on Door #(s):
D1-004 D3-048B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 006

For use on Door #(s):
D1-005.1 D1-013 D1-021.4 D2-043 D4-049

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 007

For use on Door #(s):
D1-005.2 D1-070 D2-073

Provide each DA door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	PIVOT SET	7255 SET		626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	INTERFACE BOX	JB7			VON
1	EA	KEYSWITCH CYLINDER	COORDINATE WITH DIV. 26 PER REQUIREMENTS. (CAM X LENGTH X COLLAR)		626	
1	EA	ELECTRIC STRIKE	6211 FS CON 12/16/24/28 VAC/VDC		630	VON
1	EA	EMER STOP LATCH ASSY	299AL		US32D	IVE
1	EA	SURF. AUTO OPERATOR	9531 SPEC ST-3642 AS REQ (120/240 VAC)		ANCL R	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH			LCN
1	EA	MOUNTING PLATE	9530-18 X HEADER WIDTH + 89MM		ANCL R	LCN
1	EA	OCCUPANCY INDICATOR	CM-AF500		630	CAM
1	EA	PUSH TO LOCK/ANNUNCIATOR	CM-AF500R		630	CAM
1	EA	EMERGENCY CALL KIT	CX-WEC10K2			CAM
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	GASKETING	8150SBK PSA X 2/JAMBS		BK	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	120V KEYSWITCH TO CUT POWER TO ADO	SUPPLIED BY DIV. 26 (ELECTRICAL)			
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
-120V KEYSWITCH TO CUT POWER TO DOOR OPERATOR, SUPPLIED BY DIV.26 (ELECTRICAL)
-DOOR LOCATION MUST BE HUNG ON INSIDE (PULL SIDE) FACE OF THE FRAME.
-ELECTRIC STRIKE POWERED BY DOOR OPERATOR.

OPERATIONAL DESCRIPTION:
-DOOR NORMALLY CLOSED AND UNLOCKED.
-OUTSIDE ACTUATOR CYCLES DOOR OPERATOR ALLOWING ASSISTED ACCESS, PUSHING THE DOOR ALLOWS MANUAL ACCESS.
-INSIDE PUSH-TO-LOCK BUTTON SECURES ELECTRIC STRIKE, AND CHANGES STATE OF OUTSIDE LED OCCUPANCY-INDICATOR/ANNUNCIATOR.
-MANUAL EGRESS BY INSIDE LEVER, OR ASSISTED EGRESS VIA INSIDE ACTUATOR.
-EXITING SPACE CHANGES OUTSIDE OCCUPANCY INDICATOR STATUS AND UNLOCKS ELECTRIC STRIKE FOR THE NEXT USER (VIA DOOR POSITION SWITCH).
-INSIDE EMERGENCY CALL KIT TO CALL FOR ASSISTANCE.
-OUTSIDE 120V KEYSWITCH, TO CUT POWER TO DOOR OPERATOR ENABLING DOOR TO SWING OUT FOR EMERGENCY ACCESS.

Hardware Group No. 008

For use on Door #(s):
D1-005.4

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

NOTES:
- CONFIRM SITE CONDITIONS TO ALLOW 180 SWING. ADJUST TO WIDE THROUGH HINGES AS NEEDED.

Hardware Group No. 009

For use on Door #(s):
D1-005.5

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 010

For use on Door #(s):
D1-005A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	PUSH PLATE	8200 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	PULL PLATE	8303 205MM 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE

Hardware Group No. 011

For use on Door #(s):
D1-006

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP REG			689	LCN
1	EA	OCCUPANCY INDICATOR	CM-AF500		✓	630	CAM
1	EA	PUSH TO LOCK/ANNUNCIATOR	CM-AF500R			630	CAM
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- COORDINATE LOCATION OF CREDENTIAL READER, PUSH TO LOCK BUTTON AND INDICATOR WITH ARCHITECT PRIOR INSTALLATION.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED.
- PRESENTING VALID CREDENTIAL ALLOWS ACCESS.
- PRESSING "PUSH TO LOCK" BUTTON SETS PRIVACY MODE (VIA ACCESS CONTROL SYSTEM) WHICH DISABLES READER, PREVENTING ACCESS WHILE OCCUPIED. SIMULTANEOUSLY, THE "LOCKED" INDICATOR NEXT TO "PUSH TO LOCK" BUTTON AND EXTERIOR "OCCUPIED" INDICATOR WILL TURN ON.
- FREE EGRESS AT ALL TIMES. THE "LOCKED" AND "OCCUPIED" INDICATORS WILL TURN OFF UPON EXITING AND RESET THE CREDENTIAL READER TO ACTIVE.
- EMERGENCY ACCESS INTO WASHROOM BY USING OVERRIDE KEY IN OUTSIDE LEVER.
- DURNIG POWER LOSS DOOR REMAINS CLOSED AND LOCKED.

Hardware Group No. 012

For use on Door #(s):
D1-007 D1-020 D1-025

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 013

For use on Door #(s):
D1-010 D1-015.2 D1-021.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 014

For use on Door #(s):
D1-011

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 015

For use on Door #(s):
D1-011.1 D2-038

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	OH STOP & HOLDER	100H		630	GLY
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 016

For use on Door #(s):

D1-012	D2-016	D3-016	D3-044	D4-016	D4-044
D5-014	D5-041				

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR W/ INSIDE INDICATOR	L9040 17B L583-363 OS-OCC IS-LOC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 017

For use on Door #(s):
D1-014

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC	✓	630	VON
1	EA	SURF. AUTO OPERATOR	9531IQ RSA	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)	✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28	✓		
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	REQUEST TO EXIT SENSOR	SCANII 12/24 VDC	✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 FA900 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- ELECTRIC STRIKE AND AUTO DOOR OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED. OUTSIDE ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR REMOTE/SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF OUTSIDE ACTUATOR.
-INSIDE ACTUATOR(S) ALWAYS FUNCTIONAL
-PRESSING ACTUATORS MOMENTARILY UNLOCKS AND CYCLES DOOR OPERATOR.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS OR ACTIVATION OF FIRE ALARM DOOR REMAINS CLOSED AND LOCKED. AUTO OPERATOR WILL NOT BE FUNCTIONAL.

Hardware Group No. 018

For use on Door #(s):
D1-015 D1-016A D1-016B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER

Hardware Group No. 019

For use on Door #(s):
D1-017A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP DEL REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER

Hardware Group No. 020

For use on Door #(s):
D1-017B D5-ELEC.3

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 021

For use on Door #(s):
D1-018 D2-056

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER

Hardware Group No. 022

For use on Door #(s):
D1-019

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 023

For use on Door #(s):
D1-021.2 D1-021.3

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	OH STOP & HOLDER	100H		630	GLY
1	EA	ARMOR PLATE	8400 B-NH-A 610MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE

Hardware Group No. 024

For use on Door #(s):
D1-021.A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-9847-EO-LBR 24 VDC		626	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-9847-L-NL-LBR-17 24 VDC		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9553IQ REG2 LESS TRACK COV2 SW (PUSH SIDE)		628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH (INTERIOR)			LCN
2	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
2	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
2	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
2	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
2	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS904 900-4RL 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED. EXTERIOR ACTUATOR NORMALLY INNACTIVE
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR.
- INTERIOR ACTUATOR ALWAYS ACTIVE. PRESSING IT MOMENTARILY UNLOCKS (IF LOCKED) AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE BOTH LEAFS.
- OUTSIDE KEY OVERRIDE AS REQUIRED.
- FREE EGRESS AT ALL TIMES.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 025

For use on Door #(s):
D1-021.B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC	✓	630	VON
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9531IQ RSA	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)	✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28	✓		
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	REQUEST TO EXIT SENSOR	SCANII 12/24 VDC	✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED. OUTSIDE ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR REMOTE/SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF OUTSIDE ACTUATOR.
-INSIDE ACTUATOR(S) ALWAYS FUNCTIONAL
-PRESSING ACTUATORS MOMENTARILY UNLOCKS AND CYCLES DOOR OPERATOR.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED. AUTO OPERATOR WILL NOT BE FUNCTIONAL.

Hardware Group No. 026

For use on Door #(s):
D1-021.C

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	AUTO FLUSH BOLT	FB31T		630	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	ELECTRIC STRIKE	6223 FSE CON 12/16/24/28 VAC/VDC		630	VON
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ STD2 STD2 RSA		628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INTERIOR)			LCN
2	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
2	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT		STST	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
2	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-4RL 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED. ACCESS ACTUATOR NORMALLY INNACTIVE
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR.
- EGRESS ACTUATOR ALWAYS ACTIVE. PRESSING IT MOMENTARILY UNLOCKS (IF LOCKED) AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING).
- OUTSIDE KEY OVERRIDE AS REQUIRED.
- FREE EGRESS AT ALL TIMES.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 027

For use on Door #(s):
D1-022.1A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	AUTO FLUSH BOLT	FB31P			630	IVE
1	EA	DUST PROOF STRIKE	DP1			626	IVE
1	EA	PASSAGE SET	L9010 17B			626	SCH
1	EA	ELECTRIC STRIKE	6223 FSE CON 12/16/24/28 VAC/VDC		✓	630	VON
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)			630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ STD2 STD2 RSA		✓	628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
2	EA	MEETING STILE	8193AA X DOOR HEIGHT			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- ELECTRIC STRIKE AND AUTO OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED, UNLOCKED, AND LATCHED.
- INSIDE AND OUTSIDE ACTUATORS ALWAYS ACTIVE. PRESSING THEM MOMENTARILY UNLATCH AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING). CLOSING SEQUENCE TO ALLOW INACTIVE LEAF TO CLOSE FIRST (TO ENSURE LATCHING OF ACTIVE LEAF AFTER AUTO FLUSHBOLT IS ENGAGED).
- ROCKER SWITH ON AUTO OPERATOR TURNS DEVICE ON/OFF/HOLD OPEN.
- FREE EGRESS AT ALL TIMES.
- DURING ACTIVATION OF FIRE ALARM OR POWER LOSS DOOR REMAINS CLOSED AND LATCHED.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 028

For use on Door #(s):
D1-022.1B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			630	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-98-L-NL-17-CON 24 VDC		✓	626	VON
1	EA	RIM CYLINDER	20-021			626	SCH
1	EA	OH STOP	100S			630	GLY
1	EA	SURFACE CLOSER	4040XP EDA ST-1944 ST-3068			689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH			630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER			AA	ZER
1	EA	ASTRAGAL	W-7 X DOOR HEIGHT				KNC
1	EA	DOOR SWEEP	39A X DOOR WIDTH			A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH			A	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.
- INSTALL EXIT DEVICE STRIKE ON THE #429 AT THE JAMB, SHIFT EXIT DEVICE BACKSET BY 6MM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED.

Hardware Group No. 029

For use on Door #(s):
D1-022A D1-024A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	PUSH PLATE	8200 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	PULL PLATE	8303 205MM 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9553IQ REG2 LESS TRACK COV2 SW (PUSH SIDE)	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
2	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE

Hardware Group No. 030

For use on Door #(s):
D1-022B D1-022D

Provide each RU door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	HARDWARE	BY ROLL-UP DOOR SUPPLIER		

Hardware Group No. 031

For use on Door #(s):
D1-022C

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-98-L-NL-17-CON 24 VDC		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP EDA ST-1944 ST-3068		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
1	EA	ASTRAGAL	W-7 X DOOR HEIGHT			KNC
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	VIEWER	698		626	IVE
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.
- INSTALL EXIT DEVICE STRIKE ON THE #429 AT THE JAMB, SHIFT EXIT DEVICE BACKSET BY 6MM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED.

Hardware Group No. 032

For use on Door #(s):
D1-023A D1-023B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	AUTO FLUSH BOLT	FB31P			630	IVE
1	EA	DUST PROOF STRIKE	DP1			626	IVE
1	EA	PASSAGE SET	L9010 17B			626	SCH
1	EA	ELECTRIC STRIKE	6223 FSE CON 12/16/24/28 VAC/VDC		✓	630	VON
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)			630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ STD2 STD2 RSA		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
2	EA	MEETING STILE	8193AA X DOOR HEIGHT			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- ELECTRIC STRIKE AND AUTO OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED, UNLOCKED, AND LATCHED.
- INSIDE AND OUTSIDE ACTUATORS ALWAYS ACTIVE. PRESSING THEM MOMENTARILY UNLATCH AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING). CLOSING SEQUENCE TO ALLOW INACTIVE LEAF TO CLOSE FIRST (TO ENSURE LATCHING OF ACTIVE LEAF AFTER AUTO FLUSHBOLT IS ENGAGED).
- ROCKER SWITH ON AUTO OPERATOR TURNS DEVICE ON/OFF/HOLD OPEN.
- FREE EGRESS AT ALL TIMES.
- DURING ACTIVATION OF FIRE ALARM OR POWER LOSS DOOR REMAINS CLOSED AND LATCHED.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 033

For use on Door #(s):
D1-024B D2-VEST.3A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	PUSH PLATE	8200 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	PULL PLATE	8303 205MM 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
2	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 034

For use on Door #(s):
D1-026

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 035

For use on Door #(s):

D1-027	D1-072	D1-STOR.1	D2-129	D2-STOR.1	D2-STOR.3
D3-STOR.3	D3-STOR.1	D4-STOR.1			

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 036

For use on Door #(s):

D1-033	D1-034A	D1-037	D1-038	D1-040	D1-042
D1-043	D1-044	D1-045	D1-048	D1-049	D1-052
D1-053	D1-056	D1-058	D1-060	D1-062	D2-002
D2-003	D2-005	D2-012	D2-014	D2-015	D2-018
D2-021	D2-022	D2-023A	D2-024	D2-025	D2-026
D2-028	D2-030	D2-033	D2-035	D2-048	D2-051
D2-053	D2-055	D2-057	D2-058	D2-059	D2-061
D2-063	D2-064	D2-066	D3-002	D3-003	D3-005
D3-012	D3-014	D3-015	D3-018	D3-019	D3-021
D3-022	D3-023A	D3-024	D3-025	D3-026	D3-028
D3-030	D3-032	D3-035	D3-038	D3-039	D3-040
D3-041	D3-045	D3-047A	D3-055	D3-056	D3-058
D3-060	D3-061	D3-062	D3-064	D3-066	D3-067
D3-070	D3-072	D4-002	D4-003	D4-005	D4-012
D4-014	D4-015	D4-018	D4-019	D4-021	D4-022
D4-023A	D4-024	D4-025	D4-026	D4-028	D4-030
D4-032	D4-035	D4-038	D4-039	D4-040	D4-041
D4-045	D4-047A	D4-055	D4-056	D4-058	D4-059
D4-060	D4-062	D4-063	D4-065	D4-066	D4-069
D4-071	D5-002	D5-003	D5-005	D5-018	D5-019
D5-020	D5-021	D5-023	D5-026	D5-028	D5-031
D5-035	D5-036	D5-037	D5-038	D5-042	D5-044A
D5-052	D5-053	D5-055	D5-056	D5-057	D5-059
D5-060	D5-062	D5-063	D5-066	D5-068	

Provide each UEP door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	MANUAL FLUSH BOLT	FB458		626	IVE
1	EA	ENTRANCE/OFFICE LOCK	ND50P6D SPA LLL		626	SCH
1	EA	SERVICE PART - FLAT LIP STRIKE	XQ07-351-078 626		626	SCH
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	EDGEGUARD	730X___TO SUIT UL X DOOR HEIGHT (ON INACTIVE LEAF)		630	IVE
1	EA	HINGE PIN//SPRING DOOR STOP	75/74___TO SUIT (ON INACTIVE LEAF)		F26	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
2	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER

Hardware Group No. 037

For use on Door #(s):

D1-060.1	D1-063.1	D2-002.1	D2-050.1	D2-051.1	D2-053.1
D2-055.1	D2-057.1	D2-058.1	D2-059.1	D2-061.1	D2-063.1
D2-062.1	D2-066.1	D2-067.1	D2-076.1.1	D3-019.1	D3-038.1
D3-039.1	D3-040.1	D3-041.1	D3-042.1	D3-045.1	D3-047.1
D3-055.1	D3-058.1	D3-060.1	D3-061.1	D3-062.1	D3-064.1
D3-066.1	D3-067.1	D3-070.1	D3-072.1	D4-002.1	D4-003.1
D4-042.1	D4-055.1	D4-056.1	D4-059.1	D4-005.1	D5-002.1
D5-003.1	D5-005.1	D5-017.1	D5-018.1	D5-019.1	D5-020.1
D5-021.1	D5-023.1	D5-026.1	D5-028.1	D5-031.1	D5-039.1
D5-052.1	D5-053.1	D3-056.1	D5-056.1	D4-063.1	D5-060.1
D5-055.1	D2-014.1	D2-012.1	D2-003.1	D4-058.1	D4-065.1
D5-062.1	D4-071.1	D4-069.1	D4-066.1	D5-068.1	D5-066.1
D5-063.1	D4-062.1	D4-060.1	D5-059.1	D5-057.1	D1-058.1
D1-056.1	D1-053.1	D1-052.1	D1-044.1	D1-045.1	D1-048.1
D1-049.1	D1-038.1	D1-037.1	D1-034.1	D1-033.1	D1-043.1
D1-042.1	D1-040.1	D1-062.1	D4-030.1	D3-022.1	D4-021.1
D2-021.1	D3-021.1	D2-028.1	D2-026.1	D2-035.1	D2-024.1
D2-033.1	D2-030.1	D2-023.1	D2-025.1	D2-022.1	D2-018.1
D2-015.1	D2-005.1	D3-028.1	D3-026.1	D3-035.1	D3-024.1
D3-032.1	D3-030.1	D3-023.1	D3-025.1	D3-018.1	D3-015.1
D3-014.1	D3-012.1	D3-002.1	D3-003.1	D3-005.1	D4-028.1
D4-026.1	D4-035.1	D4-024.1	D4-032.1	D4-023.1	D4-025.1
D4-022.1	D4-018.1	D4-015.1	D4-014.1	D4-012.1	D4-047.1
D4-045.1	D4-040.1	D4-041.1	D5-044.1	D5-042.1	D5-037.1
D5-038.1	D4-039.1	D4-038.1	D5-036.1	D5-035.1	D2-019.1
D4-019.1					

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK	ND40S SPA		626	SCH
1	EA	MOP PLATE	8400 305MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	HINGE PIN//SPRING DOOR STOP	75/74___TO SUIT		F26	IVE

Hardware Group No. 038

For use on Door #(s):
D1-034B D2-023B D3-023B D3-047B D4-023B D4-047B
D5-044B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	DBL CYL STORE W/DB	L9466P6 17B		626	SCH
2	EA	DOOR BOLT	B680		626	SCH
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

NOTES:
- INSTALL ONE DEADBOLT THUMBTURN PER DOOR SIDE.

OPERATIONAL DESCRIPTION:
TO OPEN DOOR, MORTISE LOCK DEADBOLT HAS TO BE KEY UNLOCKED (BY STAFF), AND BOTH RESIDENTS NEED TO RETRACT THEIR RESPECTIVE DEADBOLTS.

Hardware Group No. 039

For use on Door #(s):
D1-035 D2-052

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	VIEWER	698		626	IVE
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 040

For use on Door #(s):

D1-036	D1-055	D1-067	D2-017	D2-034	D2-036
D2-060	D3-017	D3-034	D3-036	D3-043	D3-063
D3-075	D4-017	D4-034	D4-036	D4-043	D4-061
D4-074	D5-015	D5-030	D5-032	D5-040	D5-058
D5-071					

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	MAGNETIC CATCH	327		A92	IVE
2	EA	SINGLE DUMMY TRIM	ND170 SPA		626	SCH
2	EA	OH STOP & HOLDER	100H		630	GLY
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE

Hardware Group No. 041

For use on Door #(s):

D1-039	D1-061	D2-007	D2-065	D3-007	D3-065
D4-007	D4-064	D5-007	D5-061		

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
1	EA	DEADBOLT	TD1850		628	TAH
1	EA	THUMBTURN	TT1025		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
1	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9542IQ LESS TRACK RSA		628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INSIDE)			LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T (ON OUTSIDE)		630	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	CONCEALED DOOR CONTACT	7764		628	SCE

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
- DOOR NORMALLY CLOSED AND LOCKED/UNLOCKED.
- WHILE UNLOCKED, INSIDE & OUTSIDE ACTUATORS CYCLE AUTO DOOR OPERATOR.
- ROCKER SWITCH ON AUTO DOOR OPERATOR TURN ON/OFF DEVICE OR HOLD OPEN. (KEEP TURNED OFF WHEN LOCK LATCH IS PROJECTED).
- FREE EGRESS FROM BALCONY AT ALL TIMES (BY TURNING THUMBTURN IF LOCKED).

Hardware Group No. 042

For use on Door #(s):

D1-041 D2-062

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR W/ INSIDE INDICATOR	L9040 17B L583-363 OS-OCC IS-LOC		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP DEL REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 043

For use on Door #(s):

D1-046 D2-020 D3-020 D3-037 D3-068 D4-020
D4-037 D4-067 D5-016 D5-034 D5-064

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 044

For use on Door #(s):

D1-047	D2-027	D2-054	D3-027	D3-057	D4-027
D4-057	D5-022	D5-054			

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC	✓	630	VON
1	EA	SURF. AUTO OPERATOR	9531IQ RSA	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)	✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28	✓		
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	REQUEST TO EXIT SENSOR	SCANII 12/24 VDC	✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED. OUTSIDE ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR REMOTE/SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF OUTSIDE ACTUATOR.
-INSIDE ACTUATOR(S) ALWAYS FUNCTIONAL
-PRESSING ACTUATORS MOMENTARILY UNLOCKS AND CYCLES DOOR OPERATOR.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED. AUTO OPERATOR WILL NOT BE FUNCTIONAL.

Hardware Group No. 045

For use on Door #(s):

D1-050	D2-009	D2-076B	D3-009	D4-009	D5-009

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	MOUNTING BRACKET	870SPB			ZER

Hardware Group No. 046

For use on Door #(s):

D1-054	D2-004	D3-004	D3-STOR.2	D3-049	D4-004
D5-004	D5-046				

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 047

For use on Door #(s):

D1-057	D1-065B	D2-001A	D2-031	D2-068B	D2-070
D3-001A	D3-031	D3-048A	D3-050	D4-001A	D4-031
D4-048A	D4-048B	D4-050	D5-001A	D5-027	D5-045A
D5-045B	D5-047				

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG			689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 048

For use on Door #(s):
D1-059

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 049

For use on Door #(s):

D1-063	D2-019	D2-042	D2-067	D3-042	D3-077
D4-042	D4-075	D5-017	D5-039		

Provide each UEP door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	MANUAL FLUSH BOLT	FB458		626	IVE
1	EA	OFFICE W/SIM RETRACT	L9056P6 17B 10-072 7/8" LIP L583-363		626	SCH
1	EA	OH STOP & HOLDER	100H		630	GLY
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	EDGEGUARD	730X___TO SUIT UL X DOOR HEIGHT (ON INACTIVE LEAF)		630	IVE
1	EA	HINGE PIN//SPRING DOOR STOP	75/74___TO SUIT (ON INACTIVE LEAF)		F26	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
2	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER

Hardware Group No. 050

For use on Door #(s):
D1-064 D1-ELEC.3A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 051

For use on Door #(s):
D1-065A D2-068A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 052

For use on Door #(s):
D1-066A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	PASSAGE SET	L9010 17B			626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC		✓	630	VON
1	EA	SURF. AUTO OPERATOR	9531IQ RSA		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- ELECTRIC STRIKE AND AUTO DOOR OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.
- DOOR IS ALWAYS CLOSED AND UNLOCKED.
- DOOR CAN BE MANUALLY OR AUTOMATICALLY OPENED VIA ACTUATOR.
- EXTERIOR AND INTERIOR ACTUATORS TEMPORARILY RELEASE ELECTRIC STRIKE AND CYCLES AUTO DOOR OPERATOR.
- FREE EGRESS AT ALL TIMES BY INSIDE ACTUATOR OR BY OPENING DOOR MANUALLY.
- DURING ACTIVATION OF FIRE ALARM OR POWER LOSS DOOR REMAINS CLOSED, UNLOCKED AND LATCHED.

Hardware Group No. 053

For use on Door #(s):

D1-066B	D2-032A	D2-032B	D2-069B	D3-033A	D3-033B
D3-046A	D3-046B	D4-033A	D4-033B	D4-046A	D4-046B
D5-029A	D5-029B	D5-043A	D5-043B		

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC	✓	630	VON
1	EA	SURF. AUTO OPERATOR	9531IQ RSA	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)	✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28	✓		
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	REQUEST TO EXIT SENSOR	SCANII 12/24 VDC	✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 FA900 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- ELECTRIC STRIKE AND AUTO DOOR OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED. OUTSIDE ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR REMOTE/SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF OUTSIDE ACTUATOR.
-INSIDE ACTUATOR(S) ALWAYS FUNCTIONAL
-PRESSING ACTUATORS MOMENTARILY UNLOCKS AND CYCLES DOOR OPERATOR.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS OR ACTIVATION OF FIRE ALARM DOOR REMAINS CLOSED AND LOCKED. AUTO OPERATOR WILL NOT BE FUNCTIONAL.

Hardware Group No. 054

For use on Door #(s):
D1-068 D2-071

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 055

For use on Door #(s):
D1-073

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 056

For use on Door #(s):
D1-COMM.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	OH STOP	100S			630	GLY
1	EA	SURFACE CLOSER	4040XP REG ST-1630			689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT			689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 057

For use on Door #(s):
D1-COMM.2 D2-COMM.2 D3-COMM.2 D4-COMM.2 D5-COMM.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	FLOOR STOP	FS436		626	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 058

For use on Door #(s):
D1-COMM.3 D2-COMM.1 D2-COMM.3 D3-COMM.1 D4-COMM.1 D5-COMM.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL EDA ST-3068		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	MOUNTING BRACKET	870SPB			ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 059

For use on Door #(s):
D1-CORR.4 D2-CORR.6 D3-CORR.7 D4-CORR.7 D5-CORR.7

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP REG			689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 060

For use on Door #(s):
D1-CORR.5

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
2	EA	AUTO FLUSH BOLT	FB31P			630	IVE
1	EA	DUST PROOF STRIKE	DP1			626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B			626	SCH
1	EA	ELECTRIC STRIKE	6223 FSE CON 12/16/24/28 VAC/VDC		✓	630	VON
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)			630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ REG2 LESS TRACK RSA		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INTERIOR)		✓		LCN
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT			STST	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33				CAM
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
2	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-4RL-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
-ELECTRIC STRIKE AND AUTO OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED. ACCESS ACTUATOR NORMALLY INNACTIVE
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR.
- EGRESS ACTUATOR ALWAYS ACTIVE. PRESSING IT MOMENTARILY UNLOCKS (IF LOCKED) AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING).
- OUTSIDE KEY OVERRIDE AS REQUIRED.
- FREE EGRESS AT ALL TIMES.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 061

For use on Door #(s):
D1-CORR.10 D2-CORR.10

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	ELEC FIRE EXIT HARDWARE	QEL-98-L-BE-F-17-CON 24 VDC		✓	626	VON
1	EA	MAGNETIC LOCK	M420P 12/24 VDC		✓	628	SCE
1	EA	SURF. AUTO OPERATOR	9531IQ RSA		✓	628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)				
1	EA	ADVANCED LOGIC RELAY	CX-33				CAM
2	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL		✓		
1	EA	POWER SUPPLY	PS902 900-4RL-FA 120/240 VAC		✓	LGR	SCE
1	EA	WANDERGUARD	IN CONTRACT, SUPPLIED BY OTHERS				
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTE:
-MAGNETIC LOCK, AUTO OPERATOR AND QEL DEVICE TO BE CONNECTED TO FIRE ALARM SYSTEM.
-MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED/UNLOCKED (CONTROLLED ACCESS AND EGRESS WITH MAGNETIC LOCK ON PUSH SIDE).
-PRESENTING VALID CREDENTIAL ON EITHER SIDE, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR(S).
-WANDERGUARD CAN LOCK/UNLOCK MAGNETIC LOCK (BY WANDERGUARD/ACCESS CONTROL SYSTEM SUPPLIER).
-PRESSING ACTUATORS MOMENTARELY RETRACTS LATCH AND CYCLES DOOR OPERATOR (ONLY ACTIVE TEMPORARILY AFTER PRESENTING VALID CREDENTIAL OR ON SCHEDULE BY ACCESS CONTROL SYSTEM AND WHEN NOT CONFLICTING WITH WANDERGUARD FUCNTIONALITY).
-FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
-DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 062

For use on Door #(s):

D1-ELEC.1	D2-ELEC.1	D2-ELEC.4	D2-ELEC.5	D3-ELEC.1	D4-ELEC.1
D3-ELEC.3	D4-ELEC.3	D5-ELEC.1			

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 063

For use on Door #(s):
D1-ELEC.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 064

For use on Door #(s):
D1-ELEC.3B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR OUTSWING KEYED DOORS)		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	CONST LATCHING BOLT	FB51P		630	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	EU MORTISE LOCK	L9092P6EU 17B 10-072 7/8" LIP RX CON 12/24 VDC		626	SCH
1	EA	COORDINATOR	COR X FL		628	IVE
2	EA	MOUNTING BRACKET	MB1(F)//MB2(F)___TO SUIT		689	IVE
2	EA	OH STOP	100S		630	GLY
2	EA	SURFACE CLOSER	4040XP DEL EDA ST-3068		689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT		STST	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
2	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED. THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

Hardware Group No. 065

For use on Door #(s):

D1-ELEC.4 D6-002.1 D6-002 D6-003.1 D6-004 D6-005A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR OUTSWING KEYED DOORS)		630	IVE
1	EA	CONST LATCHING BOLT	FB51P		630	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B 10-072 7/8" LIP		626	SCH
1	EA	COORDINATOR	COR X FL		628	IVE
2	EA	MOUNTING BRACKET	MB1(F)//MB2(F)___TO SUIT		689	IVE
2	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT		STST	ZER

Hardware Group No. 066

For use on Door #(s):
D1-ELEC.5

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	FLOOR STOP	FS436		626	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 067

For use on Door #(s):
D1-MECH.1 D1-SHED.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	HARDWARE	TO LATER DETAIL		

Hardware Group No. 068

For use on Door #(s):
D1-MECH.2 D2-ELEC.3

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR OUTSWING KEYED DOORS)		630	IVE
1	EA	CONST LATCHING BOLT	FB51P		630	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	COORDINATOR	COR X FL		628	IVE
2	EA	MOUNTING BRACKET	MB1(F)//MB2(F)___TO SUIT		689	IVE
2	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT		STST	ZER

NOTES:
- INSTALL ASTRAGAL ON PUSH SIDE OF INACTIVE LEAF.

Hardware Group No. 069

For use on Door #(s):
D1-MECH.3 D2-MECH.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 070

For use on Door #(s):
D1-PRAC

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR OUTSWING KEYED DOORS)		630	IVE
2	EA	MANUAL FLUSH BOLT	FB458		626	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B 10-072 7/8" LIP		626	SCH
2	EA	OH STOP & HOLDER	100H		630	GLY
1	EA	ASTRAGAL	47A X DOOR HEIGHT		A	ZER

NOTES:
-INSTALL ASTRAGAL ON PUSH SIDE OF INACTIVE LEAF.

Hardware Group No. 071

For use on Door #(s):

D1-ST.1A	D1-ST.2	D1-ST.5B	D2-ST.2A	D2-ST.5	D3-ST.2
D4-ST.2	D5-ST.2	TD3-001			

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-BE-F-17		626	VON
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 072

For use on Door #(s):
D1-ST.1B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		630	IVE
1	EA	PANIC HARDWARE	98-EO		626	VON
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP EDA ST-1944 ST-3068		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
1	EA	ASTRAGAL	W-7 X DOOR HEIGHT			KNC
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE

NOTES:
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.
- INSTALL EXIT DEVICE STRIKE ON THE #429 AT THE JAMB, SHIFT EXIT DEVICE BACKSET BY 6MM.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS

Hardware Group No. 073

For use on Door #(s):
D1-ST.4A D1-ST.5A D2-ST.2B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		630	IVE
1	EA	PANIC HARDWARE	98-EO		626	VON
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP EDA ST-1944 ST-3068		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
1	EA	ASTRAGAL	W-7 X DOOR HEIGHT			KNC
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE

NOTES:
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.
- INSTALL EXIT DEVICE STRIKE ON THE #429 AT THE JAMB, SHIFT EXIT DEVICE BACKSET BY 6MM.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS

Hardware Group No. 074

For use on Door #(s):
D1-ST.4B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	ELEC FIRE EXIT HARDWARE	RX-QEL-98-L-NL-F-17 24 VDC		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
-QEL DEVICE TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
- DURING POWER LOSS OR ACTIVATION OF FIRE ALARM DOOR REMAINS CLOSED AND LOCKED.

Hardware Group No. 075

For use on Door #(s):
D1-VEST.1A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	PASSAGE SET	L9010 17B			626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE CON		✓	630	VON
1	EA	SURF. AUTO OPERATOR	9542IQ LESS TRACK RSA		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
-AUTO OPERATOR AND ELECTRIC STRIKE TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-INSIDE & OUTSIDE ACTUATORS MOMENTARELY UNLATCH AND CYCLE DOOR OPERATOR.
-FREE ACCESS & EGRESS AT ALL TIMES.
-ROCKER SIWTH TUNRS AUTO OPERATOR ON/OFF OR HOLD OPEN.
-DURING POWER LOSS OR ACTIVATION OF FIRE ALARM DOOR REMAINS CLOSED, LATCHED, AND UNLOCKED.

Hardware Group No. 076

For use on Door #(s):
D1-VEST.1B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EL MORTISE LOCK	L9092P6EL 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP REG			689	LCN
1	EA	MOP PLATE	8400 305MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
-ELECTRIC LOCK TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-DURING POWER LOSS OR ACTIVATION OF FIRE ALARM SYSTEM, DOOR REMAINS CLOSED, LATCHED AND UNLOCKED ALLOWING ACCESS TO SECOND PATH OF EGRESS.
-RX IN COMBINATION TO DOOR POSITION SWITCH INDICATES VALID EXIT TO ACCESS CONTROL SYSTEM.

Hardware Group No. 077

For use on Door #(s):
D1-VEST.2A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
2	EA	CONT. HINGE	112XY EPT X DOOR HEIGHT			628	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-3549A-EO-CON 24 VDC		✓	626	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-3549A-T-360T-CON 24 VDC		✓	626	VON
1	EA	MORTISE CYLINDER	20-001 114			626	SCH
2	EA	LONG DOOR PULL, FLAT TIP	9264F 36 O			630-316	IVE
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)			630	GLY
1	EA	SURF. AUTO OPERATOR	9553IQ REG2 LESS TRACK COV2 SW (PUSH SIDE)		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INTERIOR)		✓		LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T (ON EXTERIOR)		✓	630	LCN
1	EA	BOLLARD	8310-866FLA			689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER				
2	EA	DOOR SWEEP	39A X DOOR WIDTH			A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH			A	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33				CAM
2	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
2	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
2	EA	CONCEALED DOOR CONTACT	7764		✓	628	SCE
1	EA	POWER SUPPLY	PS904 900-4RL 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.
- T-360T TRIM TO BE INSTALLED WITH NL CYLINDER PLATE.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED. EXTERIOR ACTUATOR NORMALLY INNACTIVE
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR.
- EGRESS ACTUATOR ALWAYS ACTIVE. PRESSING IT MOMENTARILY UNLOCKS (IF LOCKED) AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE BOTH LEAFS.
- OUTSIDE KEY OVERRIDE AS REQUIRED.
- FREE EGRESS AT ALL TIMES.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 078

For use on Door #(s):
D1-VEST.2B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	LONG DOOR PULL	PR 9264F 36 N		630-316	IVE
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9553IQ REG2 LESS TRACK COV2 SW (PUSH SIDE)	✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T	✓	630	LCN
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-INSIDE & OUTSIDE ACTUATORS CYCLE DOOR OPERATOR.
-FREE ACCESS & EGRESS AT ALL TIMES.

Hardware Group No. 079

For use on Door #(s):
D1-VEST.3A D1-VEST.3B D1-VEST.6A D1-VEST.6B

Provide each BP door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	SLIDING AUTOMATIC ENTRANCE	DURA-GLIDE (SEE SECTION 08 42 29.23)	✓		SAT

Hardware Group No. 080

For use on Door #(s):

D1-VEST.5	D2-ST.1	D2-ST.4	D2-VEST.4	D3-ST.1A	D3-ST.4
D4-ST.1	D4-ST.4	D5-ST.1	D5-ST.4		

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	FIRE EXIT HARDWARE	9875-L-BE-F-RX996-17-CON		626	VON
1	EA	MAGNETIC LOCK	M420P 12/24 VDC		628	SCE
1	EA	SURFACE CLOSER	4040XP DEL EDA ST-3068		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)			
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL			
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	WANDERGUARD	IN CONTRACT, SUPPLIED BY OTHERS			
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
- MAGNETIC LOCKS TO BE CONNECTED TO FIRE ALARM SYSTEM.
- MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED (CONTROLLED EGRESS).
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL EGRESS.
- RX SWITCH MOMENTARELY RELEASES MAGNETIC LOCK, GRANTING ACCESS.
- FREE FOR IMMEDIATE EGRESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
- DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 081

For use on Door #(s):
D2-001B D3-001B D4-001B D5-001B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP DEL REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 082

For use on Door #(s):

D2-013	D3-013A	D3-069	D4-013	D4-068	D5-012
D5-065					

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9494P6EU 17B RX DM CON 12/24 VDC		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	VIEWER	698		626	IVE
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-RX SWITCH ON DEADBOLT ACTIVATES (WHILE RETRACTED) / DEACTIVATES (WHILE PROJECTED) CARD READER.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS (WHILE DEADBOLT IS RETRACTED).
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 083

For use on Door #(s):
D2-037.1 D2-037.2 D2-037.3 D2-037.4

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR	ND40S SPA OS-OCC		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 084

For use on Door #(s):
D2-037A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 085

For use on Door #(s):
D2-037B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 086

For use on Door #(s):
D2-038.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	MOUNTING BRACKET	870SPB			ZER

Hardware Group No. 087

For use on Door #(s):
D2-040

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 088

For use on Door #(s):
D2-040.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

NOTES:
- CONFIRM SITE CONDITIONS TO ALLOW 180 SWING. ADJUST TO WIDE THROUGH HINGES AS NEEDED.

Hardware Group No. 089

For use on Door #(s):
D2-041.1A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
1	EA	DEADLATCH	TL4510		628	TAH
1	EA	LEVER	TP4560		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
1	EA	ELECTRIC STRIKE	6211AL FSE DS CON		630	VON
1	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9542IQ LESS TRACK RSA		628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INSIDE)			LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T (OUTSIDE)		630	LCN
1	EA	BOLLARD	8310-866FLA		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	CONCEALED DOOR CONTACT	7764		628	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED. OUTSIDE ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR REMOTE/SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF OUTSIDE ACTUATOR.
-INSIDE ACTUATOR(S) ALWAYS FUNCTIONAL
-PRESSING ACTUATORS MOMENTARILY UNLOCKS AND CYCLES DOOR OPERATOR.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED. AUTO OPERATOR WILL NOT BE FUNCTIONAL.
-DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 090

For use on Door #(s):
D2-041.1B D2-041.1C

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
1	EA	CONT. HINGE	112XY EPT X DOOR HEIGHT		628	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
2	EA	AUTOMATIC FLUSH BOLT	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	DEADLATCH	TL4510		628	TAH
1	EA	LEVER	TP4560		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
1	EA	ELECTRIC STRIKE	6224AL FSE DS CON 12/16/24/28 VAC/VDC (USE DA FOR REX)		630	VON
2	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ REG2 LESS TRACK RSA		628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INTERIOR)			LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T (ON EXTERIOR)		630	LCN
1	EA	BOLLARD	8310-866FLA		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	ADVANCED LOGIC RELAY	CX-33			CAM
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
2	EA	CONCEALED DOOR CONTACT	7764		628	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED AND LOCKED. ACCESS ACTUATOR NORMALLY INNACTIVE
- PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR.
- EGRESS ACTUATOR ALWAYS ACTIVE. PRESSING IT MOMENTARILY UNLOCKS (IF LOCKED) AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING).
- OUTSIDE KEY OVERRIDE AS REQUIRED.
- FREE EGRESS AT ALL TIMES.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 091

For use on Door #(s):
D2-041B

Provide each SL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
1	EA	SLIDING DOOR HARDWARE	BY GATE MANUFACTURER		

Hardware Group No. 092

For use on Door #(s):
D2-042.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)	652	IVE
1	EA	PRIVACY LOCK	ND40S SPA	626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)	630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)	630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT	630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER	BK	ZER

Hardware Group No. 093

For use on Door #(s):
D2-069A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	PASSAGE SET	L9010 17B			626	SCH
1	EA	ELECTRIC STRIKE	6211 FSE DS CON 12/16/24/28 VAC/VDC		✓	630	VON
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)			630	GLY
1	EA	SURF. AUTO OPERATOR	9531IQ RSA		✓	628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH		✓		LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- ELECTRIC STRIKE AND AUTO DOOR OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.
- DOOR IS ALWAYS CLOSED AND UNLOCKED.
- DOOR CAN BE MANUALLY OR AUTOMATICALLY OPENED VIA ACTUATOR.
- EXTERIOR AND INTERIOR ACTUATORS TEMPORARILY RELEASE ELECTRIC STRIKE AND CYCLES AUTO DOOR OPERATOR.
- FREE EGRESS AT ALL TIMES BY INSIDE ACTUATOR OR BY OPENING DOOR MANUALLY.
- ROCKER SWITCH ON AUTO OPERATOR TURNS DEVICE ON/OFF/HOLD OPEN.
- DURING ACTIVATION OF FIRE ALARM OR POWER LOSS DOOR REMAINS CLOSED, UNLOCKED AND LATCHED.

Hardware Group No. 094

For use on Door #(s):
D2-074

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP REG ST-1630		689	LCN
1	EA	TOP JAMB MTG PLATE	4040XP-18TJ SRT		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 095

For use on Door #(s):
D2-075

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 096

For use on Door #(s):
D2-076.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

NOTES:
- CONFIRM SITE CONDITIONS TO ALLOW 180 SWING. ADJUST TO WIDE THROUGH HINGES AS NEEDED.

Hardware Group No. 097

For use on Door #(s):
D2-076.2 D2-077.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR	ND40S SPA OS-OCC		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER

Hardware Group No. 098

For use on Door #(s):
D2-076A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EL MORTISE LOCK	L9092P6EL 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP REG			689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
1	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
-MAGNETIC LOCK TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-DURING POWER LOSS OR ACTIVATION OF FIRE ALARM SYSTEM, DOOR REMAINS CLOSED, LATCHED AND UNLOCKED ALLOWING ACCESS TO SECOND PATH OF EGRESS.
-RX IN COMBINATION TO DOOR POSITION SWITCH INDICATES VALID EXIT TO ACCESS CONTROL SYSTEM.

Hardware Group No. 099

For use on Door #(s):
D2-077.2 D2-077B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
2	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
2	EA	MANUAL FLUSH BOLT	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	DEADBOLT	TD1850		628	TAH
1	EA	THUMBTURN	TT1025		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
2	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
2	EA	OH STOP & HOLDER	100H		630	GLY
2	EA	SURFACE CLOSER	4040XP TOP JAMB		689	LCN
2	EA	FLUSH CEILNG MTG PLATE	4040XP-18G SRT		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
2	EA	CONCEALED DOOR CONTACT	7764	✓	628	SCE

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

Hardware Group No. 100

For use on Door #(s):

D2-077A	D2-VEST.1B	D2-VEST.1C	D3-VEST.1B	D3-VEST.1C	D3-VEST.4C
D4-VEST.1B	D4-VEST.1C	D4-VEST.4C	D5-VEST.1B	D5-VEST.1C	D5-VEST.4C

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	MAGNETIC LOCK	M420P 12/24 VDC		628	SCE
2	EA	PUSH PLATE	8200 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	PULL PLATE	8303 205MM 100X405MM (CFT/CFC TO SUIT)		630	IVE
2	EA	SURFACE CLOSER	4040XP SHCUSH		689	LCN
2	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
2	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)			
2	EA	FOB/CARD READER	BY DIV. 28			
2	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL			
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
- MAGNETIC LOCKS TO BE CONNECTED TO FIRE ALARM SYSTEM.
- MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY HELD OPEN AND UNLOCKED.

- DURING BREACKOUT LOCKDOWN, DOORS CAN BE MANUALLY CLOSED AND LOCKED (CONTROLLED ACCESS AND EGRESS WITH MAGNETIC LOCK ON PUSH SIDE).
- DUIRNG LOCKDOWN, PRESENTING VALID CREDENTIAL ON EITHER SIDE MOMENTARILY UNLOCKS ALLOWING CROSSING.
- FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
- DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 101

For use on Door #(s):

D2-CORR.3	D2-CORR.5	D3-CORR.2	D3-CORR.5	D3-CORR.10	D4-CORR.3
D4-CORR.5	D4-CORR.6	D5-CORR.10			

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR-499F		626	VON
1	EA	FIRE EXIT HARDWARE	9827-EO-F-LBRAFL-499F		626	VON
2	EA	SURFACE CLOSER	4040XP REG		689	LCN
4	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
2	EA	WALL HOLD OPEN MAGNET	SEM7830 12V/24V/120V	✓	689	LCN
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
2	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
- MAGNETIC HOLD OPEN TO BE CONNECTED TO FIRE ALARM SYSTEM.

Hardware Group No. 102

For use on Door #(s):
D2-ELEC.2 D3-ELEC.2 D4-ELEC.2 D5-ELEC.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	FLOOR STOP	FS436		626	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 103

For use on Door #(s):
D2-ST.3B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-BE-F-17		626	VON
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 104

For use on Door #(s):
D2-STOR.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 105

For use on Door #(s):
D2-VEST.1A D3-VEST.1A D3-VEST.4A D4-VEST.1A D4-VEST.4A D5-VEST.1A D5-VEST.4A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON			689	VON
1	EA	ELEC FIRE EXIT HARDWARE	QEL-98-L-BE-F-17-CON 24 VDC			626	VON
1	EA	MAGNETIC LOCK	M420P 12/24 VDC			628	SCE
1	EA	SURF. AUTO OPERATOR	9531IQ RSA			628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH				LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)				
1	EA	ADVANCED LOGIC RELAY	CX-33				CAM
2	EA	FOB/CARD READER	BY DIV. 28				
1	EA	DOOR CONTACT	679-05_TO SUIT			BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL				
1	EA	POWER SUPPLY	PS902 900-4RL-FA 120/240 VAC			LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTE:
-MAGNETIC LOCK, AUTO OPERATOR AND QEL DEVICE TO BE CONNECTED TO FIRE ALARM SYSTEM.
-MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED (CONTROLLED ACCESS AND EGRESS WITH MAGNETIC LOCK ON PUSH SIDE).
-PRESENTING VALID CREDENTIAL ON EITHER SIDE, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS OR USE OF ACTUATOR(S).
-PRESSING ACTUATORS MOMENTARELY RETRACTS LATCH AND CYCLES DOOR OPERATOR (ONLY ACTIVE TEMPORARILY AFTER PRESENTING VALID CREDENTIAL OR ON SCHEDULE BY ACCESS CONTROL SYSTEM).
-FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
-DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 106

For use on Door #(s):
D2-VEST.1D

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON			689	VON
1	EA	ELEC FIRE EXIT HARDWARE	QEL-98-L-BE-F-RX996-17-CON 24 VDC			626	VON
1	EA	MAGNETIC LOCK	M420P 12/24 VDC			628	SCE
1	EA	SURF. AUTO OPERATOR	9531IQ RSA			628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH				LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)				
1	EA	ADVANCED LOGIC RELAY	CX-33				CAM
1	EA	FOB/CARD READER	BY DIV. 28				
1	EA	DOOR CONTACT	679-05_TO SUIT			BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL				
1	EA	POWER SUPPLY	PS902 900-4RL-FA 120/240 VAC			LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTE:
-MAGNETIC LOCK, AUTO OPERATOR AND QEL DEVICE TO BE CONNECTED TO FIRE ALARM SYSTEM.
-MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED (CONTROLLED EGRESS). EGRESS ACTUATOR NORMALLY INACTIVE.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL EGRESS OR USE OF EGRESS ACTUATORS.
-SERVICE SIDE ACTUATORS ALWAYS ACTIVE.
-PRESSING ACTUATORS MOMENTARELY RETRACTS LATCH, REALEASE MAGLOCK IF ENGAGED, AND CYCLES DOOR OPERATOR (EGRESS ACTUATORS ONLY ACTIVE TEMPORARILY AFTER PRESENTING VALID CREDENTIAL OR ON SCHEDULE BY ACCESS CONTROL SYSTEM).
-FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
-RX SWITCH ON LEVER MOMENTARELY RELEASES MAGNETIC LOCK, GRANTING ACCESS FROM SERVICE CORRIDOR SIDE.
-FREE FOR IMMEDIATE EGRESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
-DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 107

For use on Door #(s):
D2-VEST.3B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
2	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
2	EA	MANUAL FLUSH BOLT	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	DEADBOLT	TD1850		628	TAH
1	EA	THUMBTURN	TT1025		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
2	EA	MAGNETIC LOCK	M420P 12/24 VDC	✓	628	SCE
2	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
2	EA	OH STOP & HOLDER	100H		630	GLY
2	EA	SURFACE CLOSER	4040XP TOP JAMB		689	LCN
2	EA	FLUSH CEILNG MTG PLATE	4040XP-18G SRT		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
2	EA	FOB/CARD READER	BY DIV. 28	✓		
2	EA	CONCEALED DOOR CONTACT	7764	✓	628	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

Hardware Group No. 108

For use on Door #(s):
D3-051A D3-051B D5-008A D5-008B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	OH STOP & HOLDER	100H		630	GLY
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE

Hardware Group No. 109

For use on Door #(s):
D3-052 D4-052 D5-049

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE

Hardware Group No. 110

For use on Door #(s):
D3-059 D5-013

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
1	EA	DEADLATCH	TL4510		628	TAH
1	EA	LEVER	TP4560		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
1	EA	ELECTRIC STRIKE	6211AL FSE DS CON		630	VON
1	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
1	EA	OH STOP	100S		630	GLY
1	EA	SURFACE CLOSER	4040XP TOP JAMB		689	LCN
1	EA	FLUSH CEILNG MTG PLATE	4040XP-18G SRT		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	CONCEALED DOOR CONTACT	7764		628	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.
-DURING POWER LOSS DOOR REMAINS CLOSED AND LOCKED.

Hardware Group No. 111

For use on Door #(s):
D3-077.1 D4-076.1 D5-073.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK	ND40S SPA		626	SCH
1	EA	MOP PLATE	8400 305MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	HINGE PIN//SPRING DOOR STOP	75/74___TO SUIT		F26	IVE

Hardware Group No. 112

For use on Door #(s):
D3-079

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
1	EA	CONT. HINGE	112XY X DOOR HEIGHT		628	IVE
1	EA	DEADBOLT	TD1850		628	TAH
1	EA	THUMBTURN	TT1025		628	TAH
1	EA	MORTISE CYLINDER	20-013		626	SCH
1	EA	PUSH/PULL BAR	9145EZHD-205MM-NO		630-316	IVE
1	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9542IQ LESS TRACK RSA		628	LCN
2	EA	ACTUATOR, TOUCHLESS	8310-813WH (INSIDE)			LCN
1	EA	FULL LENGTH TOUCH ACTUATOR	8310-836T (ON OUTSIDE)		630	LCN
1	EA	BOLLARD	8310-866FLA		689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER			
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	CONCEALED DOOR CONTACT	7764		628	SCE

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
- DOOR NORMALLY CLOSED AND LOCKED/UNLOCKED.
- WHILE UNLOCKED, INSIDE & OUTSIDE ACTUATORS CYCLE AUTO DOOR OPERATOR.
- ROCKER SWITCH ON AUTO DOOR OPERATOR TURN ON/OFF DEVICE OR HOLD OPEN. (KEEP TURNED OFF WHEN LOCK LATCH IS PROJECTED).
- FREE EGRESS FROM BALCONY AT ALL TIMES (BY TURNING THUMBTURN IF LOCKED).

Hardware Group No. 113

For use on Door #(s):
D3-MECH.1 D4-MECH.1 D5-MECH.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER

Hardware Group No. 114

For use on Door #(s):
D3-ST.3

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
1	EA	CONT. HINGE	112XY EPT X DOOR HEIGHT			628	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	ELEC PANIC HARDWARE	RX-QEL-98-L-NL-17-CON 24 VDC		✓	626	VON
1	EA	OH STOP	100S			630	GLY
1	EA	SURFACE CLOSER	4040XP TOP JAMB			689	LCN
1	EA	FLUSH CEILNG MTG PLATE	4040XP-18G SRT			689	LCN
1	EA	GASKETING/WEATHER STRIPPING	BY ALUMINUM DOOR MFR/SUPPLIER				
1	EA	FULL LENGTH INTERCONNECTED ASTRAGAL	BY ALUMINUM DOOR/FRAME SUPPLIER				
1	EA	DOOR SWEEP	39A X DOOR WIDTH			A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH			A	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	CONCEALED DOOR CONTACT	7764		✓	628	SCE
1	EA	POWER SUPPLY	PS902 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- CONFIRM COMPATIBILITY BETWEEN ALUMINUM DOOR/FRAME SYSTEM SELECTED AND SPECIFIED HARDWARE PRIOR ORDERING.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 115

For use on Door #(s):
D3-STOR.4 D4-STOR.4 D5-STOR.3

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 116

For use on Door #(s):
D3-VEST.1D D3-VEST.4B D4-VEST.1D D4-VEST.4B D5-VEST.1D D5-VEST.4B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	FIRE EXIT HARDWARE	9875-L-BE-F-RX996-17-CON			626	VON
1	EA	MAGNETIC LOCK	M420P 12/24 VDC		✓	628	SCE
1	EA	SURFACE CLOSER	4040XP DEL EDA ST-3068			689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER			BK	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)				
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL		✓		
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTE:
- MAGNETIC LOCKS TO BE CONNECTED TO FIRE ALARM SYSTEM.
- MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED (CONTROLLED EGRESS).
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL EGRESS.
-RX SWITCH ON LEVER MOMENTARELY RELEASES MAGNETIC LOCK, GRANTING ACCESS FROM SERVICE CORRIDOR SIDE.
- FREE FOR IMMEDIATE EGRESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
- DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 117

For use on Door #(s):
D3-VEST.4D D4-VEST.4D

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	9827-L-BE-F-4'-LBR-17-499F		626	VON
1	EA	FIRE EXIT HARDWARE	9827-L-BE-F-4'-LBRAFL-17-499F		626	VON
2	EA	MAGNETIC LOCK	M420P 12/24 VDC	✓	628	SCE
2	EA	SURFACE CLOSER	4040XP EDA ST-3068		689	LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
2	EA	WALL HOLD OPEN MAGNET	SEM7830 12V/24V/120V	✓	689	LCN
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH		AA	ZER
2	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)			
2	EA	FOB/CARD READER	BY DIV. 28	✓		
2	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL	✓		
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
- MAGNETIC LOCKS AND MAGNETIC HOLD OPEN TO BE CONNECTED TO FIRE ALARM SYSTEM.
- MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY HELD OPEN AND UNLOCKED.
- DURING BREACKOUT LOCKDOWN, DOORS CAN BE MANUALLY CLOSED AND LOCKED (CONTROLLED ACCESS AND EGRESS WITH MAGNETIC LOCK ON PUSH SIDE).
- DUIRNG LOCKDOWN, PRESENTING VALID CREDENTIAL ON EITHER SIDE MOMENTARILY UNLOCKS ALLOWING CROSSING.
- ACTIVATION OF FIRE ALARM RELEASES MAGNETIC HOLD OPEN DEVICES, KEEPING DOORS CLOSED AND LATCHED.
- DURING LOCKDOWN, FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
- DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 118

For use on Door #(s):
D4-075.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	PRIVACY LOCK W/ OUTSIDE INDICATOR	ND40S SPA OS-OCC		626	SCH
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 119

For use on Door #(s):
D4-076 D5-073

Provide each UEP door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
6	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	MANUAL FLUSH BOLT	FB458			626	IVE
1	EA	EU STOREROOM LOCK	ND80P6DEU SPA CON 12V/24V DC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG			689	LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	EDGEGUARD	730X___TO SUIT UL X DOOR HEIGHT (ON INACTIVE LEAF)			630	IVE
1	EA	HINGE PIN//SPRING DOOR STOP	75/74___TO SUIT (ON INACTIVE LEAF)			F26	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER			AA	ZER
2	EA	AUTO DOOR BOTTOM	369AA X DOOR WIDTH			AA	ZER
1	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT			AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 120

For use on Door #(s):
D4-STOR.2 D5-STOR.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	ARMOR PLATE	8400 B-NH-A 915MM X REQ WIDTH		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 121

For use on Door #(s):
D4-STOR.3 D5-STOR.2

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 122

For use on Door #(s):
D5-024

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	SET	SOUND SEALS	870AA-S X FRAME PERIMETER		AA	ZER
1	EA	MOUNTING BRACKET	870SPB			ZER

Hardware Group No. 123

For use on Door #(s):
D5-033

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 124

For use on Door #(s):
D5-CORR.3 D5-CORR.5

Provide each DE door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBR-499F		626	VON
2	EA	FIRE EXIT HARDWARE	9827-EO-F-LBRAFL-499F		626	VON
2	EA	MAGNETIC LOCK	M420P 12/24 VDC	✓	628	SCE
2	EA	SURFACE CLOSER	4040XP REG		689	LCN
4	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
2	EA	WALL HOLD OPEN MAGNET	SEM7830 12V/24V/120V	✓	689	LCN
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	DOOR BOTTOM	355AA X DOOR WIDTH		AA	ZER
2	EA	OVERLAPING ASTRAGAL	383AA X DOOR HEIGHT		AA	ZER
1	EA	VISUAL AND TACTILE SIGNAGE	COMPLIANT WITH CODE REQUIREMENT 3.4.6.16.6 (D & E)			
2	EA	FOB/CARD READER	BY DIV. 28	✓		
2	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE
1	EA	MANUALLY OPERATED SWITCH & PULL STATION	PER CODE REQUIREMENTS 3.4.6.16.6) B) III) AND 3.4.6.16.6) B) IV) SUPPLIED BY ELECTRICAL	✓		
1	EA	POWER SUPPLY	PS902 900-2RS-FA 120/240 VAC	✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTE:
- MAGNETIC LOCKS AND MAGNETIC HOLD OPEN TO BE CONNECTED TO FIRE ALARM SYSTEM.
- MANUALLY OPERATED SWITCH AND MANUAL PULL STATION (PER REQUIREMENTS 3.4.6.16.6.B) III) AND 3.4.6.16.B) IV)) IN CONTRACT, SUPPLIED BY GC.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY HELD OPEN AND UNLOCKED.

- DURING BREACKOUT LOCKDOWN, DOORS CAN BE MANUALLY CLOSED AND LOCKED (CONTROLLED ACCESS AND EGRESS WITH MAGNETIC LOCK ON PUSH SIDE).
- DUIRNG LOCKDOWN, PRESENTING VALID CREDENTIAL ON EITHER SIDE MOMENTARILY UNLOCKS ALLOWING CROSSING.
- ACTIVATION OF FIRE ALARM RELEASES MAGNETIC HOLD OPEN DEVICES, KEEPING DOORS CLOSED AND LATCHED.
- FREE FOR IMMEDIATE EGRESS/ACCESS UPON ACTIVATION OF FIRE ALARM, PULL SWITCH RELEASE AT NURSING STATION, LOCAL PULL STATION, OR POWER OUTAGE.
- DOOR CONTACT MONITORS DOOR OPEN/CLOSED STATE.

Hardware Group No. 125

For use on Door #(s):
D5-VEST.4D

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	CONST LATCHING BOLT	FB51P		630	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	CLASSROOM LOCK	L9070P6 17B		626	SCH
1	EA	COORDINATOR	COR X FL		628	IVE
2	EA	MOUNTING BRACKET	MB1(F)//MB2(F)___TO SUIT		689	IVE
2	EA	SURFACE CLOSER	4041 DEL SCUSH		689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
1	EA	ASTRAGAL	44STST X DOOR HEIGHT		STST	ZER

Hardware Group No. 126

For use on Door #(s):
D6-001 D6-005B

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1 114X102MM (NRP FOR OUTSWING KEYED DOORS)		630	IVE
1	EA	MANUAL FLUSH BOLT	FB458		626	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	STOREROOM LOCK	L9080P6 17B 10-072 7/8" LIP		626	SCH
2	EA	OH STOP & HOLDER	100H		630	GLY
1	EA	SURFACE CLOSER	4040XP DEL EDA ST-3068		689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
2	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	ASTRAGAL	47A X DOOR HEIGHT		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
2	EA	DOOR CONTACT	679-05_TO SUIT	✓	BLK	SCE

NOTES:
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.

Hardware Group No. 127

For use on Door #(s):
D6-002A

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	STOREROOM LOCK	L9080P6 17B		626	SCH
1	EA	SURFACE CLOSER	4040XP DEL REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 128

For use on Door #(s):
D6-ST.1

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		630	IVE
1	EA	POWER TRANSFER	EPT10 CON		689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER		AA	ZER
1	EA	DOOR SWEEP	39A X DOOR WIDTH		A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH		A	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)			SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)			SCH
1	EA	FOB/CARD READER	BY DIV. 28			
1	EA	DOOR CONTACT	679-05_TO SUIT		BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS.

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 129

For use on Door #(s):
MISC. ITEMS

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
20	EA	EXTRACTOR TOOL	35-057			SCH
1	EA	KEY CABINET	LD1200___TO SUIT			LUN
500	EA	KEY BLANKS	35-270 EV S145			SCH
20	EA	CUT CONSTRUCTION KEY	48-097 EV S145			SCH
25	EA	MASTER KEY	49-270 EV S145			SCH

NOTES:
- CONFIRM KEYING REQUIREMENTS AND QUANTITIES WITH OWNER PRIOR ORDERING.

Hardware Group No. 130

For use on Door #(s):
TD1-002 TD1-003

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
3	EA	HINGE	5BB1 114X102MM (NRP FOR KEYED OUTSWING DOORS)			652	IVE
1	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	EU MORTISE LOCK	L9092P6EU 17B RX CON 12/24 VDC		✓	626	SCH
1	EA	SURFACE CLOSER	4040XP REG			689	LCN
1	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT			630	IVE
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
1	EA	FOB/CARD READER	BY DIV. 28		✓		
1	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	POWER SUPPLY	PS902 900-2RS 120/240 VAC		✓	LGR	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

OPERATIONAL DESCRIPTION:
-DOOR IS NORMALLY CLOSED AND LOCKED.
-PRESENTING VALID CREDENTIAL, OR SCHEDULED UNLOCK (VIA ACCESS CONTROL SYSTEM), ALLOWS MANUAL ACCESS.
-OUTSIDE KEY OVERRIDE AS REQUIRED.
-FREE EGRESS AT ALL TIMES.

Hardware Group No. 131

For use on Door #(s):
TD1-005.2A TD1-005.2B TD1-005.3A TD1-005.3B TD1-005 TD1-005.1

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	POWER TRANSFER	EPT10 CON	✓	689	VON
1	EA	AUTO FLUSH BOLT	FB31P		630	IVE
1	EA	DUST PROOF STRIKE	DP1		626	IVE
1	EA	PASSAGE SET	L9010 17B		626	SCH
1	EA	ELECTRIC STRIKE	6223 FSE CON 12/16/24/28 VAC/VDC	✓	630	VON
2	EA	OH STOP	100S ADJ (W/ AUTO OPERATOR)		630	GLY
1	EA	SURF. AUTO OPERATOR	9563IQ STD2 STD2 RSA	✓	628	LCN
4	EA	ACTUATOR, TOUCHLESS	8310-813WH	✓		LCN
2	EA	MOP PLATE	8400 150MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
2	EA	ARMOR PLATE	8402 915MM X REQ. WIDTH		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER
2	EA	MEETING STILE	8193AA X DOOR HEIGHT		AA	ZER
1	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)	✓		SCH
1	EA	WIRE HARNESS	CON___6W (IN FRAME)	✓		SCH
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM			
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM			

NOTES:
- ELECTRIC STRIKE AND AUTO OPERATOR TO BE CONNECTED TO FIRE ALARM SYSTEM.

OPERATIONAL DESCRIPTION:
- DOOR IS NORMALLY CLOSED, UNLOCKED, AND LATCHED.
- INSIDE AND OUTSIDE ACTUATORS ALWAYS ACTIVE. PRESSING THEM MOMENTARILY UNLATCH AND CYCLES AUTO OPERATOR.
- AUTO OPERATOR TO CYCLE IN SEQUENCE, ALLOWING ACTIVE LEAF TO OPEN FIRST, FOLLOWED BY INACTIVE LEAF (ALLOWING AUTO FLUSH BOLTS TO DISENGAGE BEFORE OPENING). CLOSING SEQUENCE TO ALLOW INACTIVE LEAF TO CLOSE FIRST (TO ENSURE LATCHING OF ACTIVE LEAF AFTER AUTO FLUSHBOLT IS ENGAGED).
- ROCKER SWITH ON AUTO OPERATOR TURNS DEVICE ON/OFF/HOLD OPEN.
- FREE EGRESS AT ALL TIMES.
- DURING ACTIVATION OF FIRE ALARM OR POWER LOSS DOOR REMAINS CLOSED AND LATCHED.
- DOOR POSITION SWITCH INDICATES OPEN/CLOSED DOOR STATUS.

Hardware Group No. 132

For use on Door #(s):
TD1-
CORRS.5A

Provide each PR door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER			FINISH	MFR
6	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)			630	IVE
2	EA	POWER TRANSFER	EPT10 CON		✓	689	VON
1	EA	REMOVABLE MULLION	KR4954			689	VON
1	EA	ELEC PANIC HARDWARE	RX-98-EO-CON		✓	626	VON
1	EA	ELEC PANIC HARDWARE	RX-98-L-NL-17-CON		✓	626	VON
1	EA	MORTISE CYLINDER	20-001 114			626	SCH
1	EA	RIM CYLINDER	20-021			626	SCH
2	EA	OH STOP	100S			630	GLY
2	EA	SURFACE CLOSER	4040XP EDA ST-1944 ST-3068			689	LCN
2	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)			630	IVE
1	SET	GASKETING	429AA X FRAME PERIMETER			AA	ZER
1	EA	MULLION SEAL	8780NBK PSA X MULLION HEIGHT			BK	ZER
2	EA	DOOR SWEEP	39A X DOOR WIDTH			A	ZER
1	EA	THRESHOLD	626A X FRAME WIDTH			A	ZER
2	EA	WIRE HARNESS	CON___TO SUIT (IN DOOR)		✓		SCH
2	EA	WIRE HARNESS	CON___6W (IN FRAME)		✓		SCH
2	EA	DOOR CONTACT	679-05_TO SUIT		✓	BLK	SCE
1	EA	ELECTRICAL DRAWING	ELEVATION DIAGRAM				
1	EA	ELECTRICAL DRAWING	POINT TO POINT DIAGRAM				

NOTES:
- INSTALL DOOR CLOSER SHOE ON #429 AT THE HEAD, LOWER CLOSER INSTALLATION BY 6MM.
- CONFIRM THRESHOLD DEPTH REQUIRED PER DETAILS & SITE CONDITIONS

Hardware Group No. 133

For use on Door #(s):
TD1-
CORRS.5B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 114X102MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-F-17		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 134

For use on Door #(s):
TD1-
CORRS.5C

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-F-17		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER

Hardware Group No. 135

For use on Door #(s):
TD1-ST.4B

Provide each SGL door(s) with the following:

QTY		DESCRIPTION	CATALOG NUMBER		FINISH	MFR
3	EA	HINGE	5BB1HW 127X114MM (NRP FOR KEYED OUTSWING DOORS)		652	IVE
1	EA	FIRE EXIT HARDWARE	98-L-NL-F-17		626	VON
1	EA	RIM CYLINDER	20-021		626	SCH
1	EA	SURFACE CLOSER	4040XP REG		689	LCN
1	EA	KICK PLATE	8400 205MM X REQ. WIDTH (B-NH-A FOR DOORS WITH BOTTOM HARDWARE)		630	IVE
1	EA	WALL STOP	WS406/407 CCV//CVX___TO SUIT		630	IVE
1	EA	SMOKE/SOUND SEAL	188SBK PSA X FRAME PERIMETER		BK	ZER