

Set Index

Total Sets (46) Total Openings (151) Total Areas (1)

Door	Set	Door	Set	Door	Set	Door	Set	Door	Set
101-1	10	120a-1	34	219-1	25	ST-C-3	16		
101-2	41	121-1	25	220-1	25	ST-C-4	16		
102-1	24	121-2	4	221-1	25				
102-2	46	121a-1	34	222-1	32				
102a-1	30	122-1	25	223-1	32				
102b-1	30	122-2	4	224-1	32				
102c-1	30	122a-1	34	225-1	14				
103-1	22	123-1	25	226-1	24				
103-2	5	123-2	4	227-1	6				
104-1	24	123a-1	34	301-1	24				
104-2	3	124-1	24	302-1	25				
104-4	4	124-2	4	303-1	25				
104a-1	19	124-3	20	304-1	24				
104b-1	29	124a-1	34	305-1	25				
104c-1	26	125-1	43	306-1	25				
104c-2	27	125a-1	7	307-1	25				
105-1	33	125b-1	7	308-1	25				
106-1	33	126-1	38	309-1	25				
107-1	14	127-1	25	310-1	25				
108-1	18	127-2	5	311-1	24				
108-2	3	127a-1	21	312-1	14				
108-3	45	127a-2	21	313-1	32				
109-1	12	127b-1	37	314-1	32				
109-2	3	128-1	33	315-1	32				
109-3	3	129-1	33	316-1	39				
109-4	10	130-1	13	317-1	38				
109-5	45	131-1	25	318-1	25				
110-1	40	131-2	5	319-1	25				
110-2	2	131a-1	37	320-1	25				
111-1	35	201-1	24	321-1	25				
112-1	14	202-1	25	322-1	32				
113-1	33	203-1	25	323-1	32				
114-1	33	204-1	24	324-1	32				
115-1	14	204a-1	29	325-1	14				
116-1	24	205-1	25	326-1	24				
116-2	24	206-1	25	C100-1	10				
116-3	3	207-1	25	C100-2	9				
116-4	36	208-1	25	C100-3	15				
116-5	46	209-1	25	C100-4	46				
116a-1	28	210-1	25	C101-1	31				
116b-1	28	211-1	24	C101-2	11				
116c-2	23	212-1	14	ST-A-1	42				
117-1	24	213-1	32	ST-A-2	10				
117-2	4	214-1	32	ST-A-3	42				
118-1	13	215-1	32	ST-A-4	1				
119-1	25	216-1	44	ST-A-5	42				
119-2	4	216a-1	43	ST-A-6	8				
119a-1	34	217-1	38	ST-B-1	17				
120-1	25	218-1	25	ST-C-1	16				
120-2	4	219-1	25	ST-C-2	3				

Hardware Set: 1

Opening(s):

(ST-A-4) CORRIDOR/STAIR - A

1828 x 2134 x 45mm ALF() ALD(A1)

Base Function: Lever (Storeroom)

2	Continuous Hinge	112XY x (Door Height - 1")	Aluminum (US28)	Ives	✓
1	Flush Bolt (Self Latching, Top + Bottom Set)	F7845 (Metal)	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Push Side, Built in Stop, Blade Spacer)	4040XP SCUSH 61	Aluminum (689)	LCN	✓
1	Astragal (Inswing - Mount on InActive)	DS185_T x (Door Height)	Aluminum (C)	Draftseal	✓

Free Egress from Roof
Note: Weatherstrip, Sweep, and Threshold to be Supplied by Door Supplier
Note: Aluminum Door requires min 5" stiles

Hardware Set: 2

Opening(s):

(110-2) GYM STOR. 1828 x 2134 x 45mm PSF() HMD(S2)

Base Function: Deadbolt (Classroom) / Push Pull

6	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
2	Flush Bolt (Manual)	F65	Satin Chrome (US26D)	Standard Metal	✓
1	Deadbolt (Classroom)	B663__	Satin Chrome (US26D)	Schlage K	✓
1	Push Pull (Deadbolt)	H411 / K11A-3	Stainless Steel (US32D)	Standard Metal	✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal	DS185_T x (Door Height)	Aluminum (C)	Draftseal	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 3**Opening(s):**

(104-2) INDIGENOUS HUB	1828 x 2134 x 45mm PSF() HMD(S4)
(108-2) MULTI-PURPOSE ROOM	1828 x 2134 x 45mm PSF() HMD(S4)
(109-2) GYM	1828 x 2134 x 45mm PSF() HMD(S6)
(109-3) GYM	1828 x 2134 x 45mm PSF() HMD(S6)
(116-3) LEARNING COMMONS	1828 x 2134 x 45mm PSF() HMD(S6)
(ST-C-2) STAIR - C	1828 x 2134 x 45mm PSF() HMD(S6)

Base Function: Exit Device (Exit Only)

6	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Mullion (Keyed Removable)	KR4954 x (Opening Height) x 154 w/ Cyl to Suit	Aluminum (689)	Von Duprin K	✓
2	Exit Device - Rim (Exit Only)	98 EO	Satin Chrome (626)	Von Duprin	✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Note: Include Smoke seal for mullion

Hardware Set: 4

Opening(s):

(104-4) INDIGENOUS HUB	914 x 2134 x 45mm PSF() HMD(S5)
(117-2) INCLUSIVE EDUCATION	914 x 2134 x 45mm PSF() HMD(S5)
(119-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)
(120-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)
(121-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)
(122-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)
(123-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)
(124-2) KINDERGARTEN	914 x 2134 x 45mm PSF() HMD(S5)

Base Function: Lever (Exit Only)

3	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Lever (Exit Lock)	ND25D RHO	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_x (Opening Width)	Aluminum (A)	Draftseal	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 5**Opening(s):**

(103-2) STAFF ROOM	914 x 2134 x 45mm PSF() HMD(S3)
(127-2) BEFORE & AFTER SCHOOL	914 x 2134 x 45mm PSF() HMD(S5)
(131-2) BEFORE & AFTER SCHOOL	914 x 2134 x 45mm PSF() HMD(S5)

Base Function: Lever (Exit Only) / Electric Strike / AutoOperator (1 Actuator)

3	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Lever (Exit Lock)	ND25D RHO	Satin Chrome (US26D)	Schlage	✓
1	Electric Strike (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✗ ✓
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689),Stainless Steel (630)	LCN	✗ ✓
1	Actuator (36")	CM-7536/4 (One Side Only)	-	Camden	✗ ✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

(103-2) 2025.12.11 - During meeting this opening was noted to be changed to single

Electronic Elevation: E1

Mode of Operations:

Entry: No Entry

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains unlocked

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 6**Opening(s):****(227-1) MECH. MEZZANINE****1828 x 2134 x 45mm PSF() HMD(S2) 45 MIN****Base Function: Lever (Storeroom)**

6	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Flush Bolt (Self Latching, Top + Bottom Set)	F7845 (Metal) or F7945 (Wood)	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Storeroom - 3/4" Latch)	ND80__ RHO 14-042 (3/4" Latch)	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Coordinator	1700	Aluminum (US28)	Rockwood	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal	DS185_T x (Door Height)	Aluminum (C)	Draftseal	✓

Note: Provide Flat Lip Strike for lockset

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 7**Opening(s):**

(125a-1) ELECTRICAL

914 x 2134 x 45mm PSF() HMD(S1)

(125b-1) MECH

914 x 2134 x 45mm PSF() HMD(S1)

Base Function: Lever (Storeroom)

3	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Hardware Set: 8

Opening(s):

(ST-A-6) STAIR - A/ROOF DECK 914 x 2134 x 45mm PSF() HMD(S1) 45 MIN

Base Function: Lever (Storeroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 9

Opening(s):

(C100-2) CORRIDOR

1828 x 2134 x 45mm PSF() HMD(S6) 45 MIN

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull) / AutoOperator

4	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (5 Knuckle, Heavy Weight, EL 8 Wire)	5BB1HW TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, Heavy Weight, EL 4 Wire)	5BB1HW TW4 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✓
1	Mullion (Keyed Removable)	KR9954 x (Opening Height) x 154 w/ Cyl to Suit	Aluminum (689)	Von Duprin	✓
1	Exit Device - N Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL35A-NL-OP-F CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	✓
1	Exit Device - N Rim (Exit Only) (REX)	RX 35A-EO-F CON	Satin Chrome (626)	Von Duprin	✓
1	Pull for Exit Device (33 or 35 Series)	386 (NL or DT to Suit)	Stainless Steel (US32D)	Von Duprin	
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side, Built-in Stop)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer 4040XP Top Jamb x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer Plate 4040XP-18G 2ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689), Stainless Steel (630)	LCN	✓
1	Actuator Set (36")	1ea - CM-7536/4-WT (Exterior) 1ea - CM-7536/4	-	Camden	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Note: Include Smoke seal for mullion

Electronic Elevation: E2

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 10

Opening(s):

(101-1) VEST	1828 x 2134 x 45mm PSF() HMD(S7)
(109-4) GYM	1828 x 2134 x 45mm PSF() HMD(S6)
(C100-1) CORRIDOR	1828 x 2134 x 45mm PSF() HMD(S6)
(ST-A-2) STAIR - A	1828 x 2134 x 45mm PSF() HMD(S6)

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull) / AutoOperator

4	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (5 Knuckle, Heavy Weight, EL 8 Wire)	5BB1HW TW8 CON 4-1/2" x 4" x CON-6P x CON-___ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, Heavy Weight, EL 4 Wire)	5BB1HW TW4 CON 4-1/2" x 4" x CON-6P x CON-___ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✓
1	Mullion (Keyed Removable)	KR4954 x (Opening Height) x 154 w/ Cyl to Suit	Aluminum (689)	Von Duprin	✓
1	Exit Device - N Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL35A-NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	✓
1	Exit Device - N Rim (Exit Only) (REX)	RX 35A-EO CON	Satin Chrome (626)	Von Duprin	✓
1	Pull for Exit Device (33 or 35 Series)	386 (NL or DT to Suit)	Stainless Steel (US32D)	Von Duprin	
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side, Built-in Stop)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer 4040XP Top Jamb x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer Plate 4040XP-18G 2ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689), Stainless Steel (630)	LCN	✓
1	Actuator Set (36")	1ea - CM-7536/4-WT (Exterior) 1ea - CM-7536/4	-	Camden	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Note: Include Smoke seal for mullion

Electronic Elevation: E3

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 11**Opening(s):****(C101-2) CORRIDOR****914 x 2134 x 45mm PSF() HMD(S3)****Base Function: Credential Reader / Exit Device (Storeroom w/ Pull) / AutoOperator**

2	Hinge (5 Knuckle, Heavy Weight, Stainless, NRP)	5BB1HW NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (5 Knuckle, Stainless, Heavy Weight, EL 8 Wire)	5BB1HW TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	⚡ ✓
1	Exit Device - N Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL35A-NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ⚡ ✓
1	Pull for Exit Device (33 or 35 Series)	386 (NL or DT to Suit)	Stainless Steel (US32D)	Von Duprin	
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689),Stainless Steel (630)	LCN	⚡ ✓
1	Actuator Set (36")	1ea - CM-7536/4-WT (Exterior) 1ea - CM-7536/4	-	Camden	⚡ ✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/2" Rise)	DS800_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Advance Logic Relay	CX-33	-	Camden	⚡ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	⚡
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	⚡

Electronic Elevation: E4**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set: 12**Opening(s):****(109-1) CORRIDOR/GYM****1828 x 2134 x 45mm PSF() WD(W5)****Base Function: Entry [Free] Egress [Credential Reader / Key Switch / Emergency Pull Station] - Exit Device (Passage) / Magnetic Lock**

6	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Exit Device - VRT (Classroom Trim, Trim Rex)	9827L LBR RX996-06 CON	Satin Chrome (626)	Von Duprin	K ⚡ ✓
1	Exit Device - VR (Exit Only, Less Bottom Rod)	9827EO LBR	Satin Chrome (626)	Von Duprin	✓
2	Magnetic Lock (DPS, Bond Sensor)	M62BD	Aluminum	Securitron	⚡ ✓
1	Keyswitch (Reset / Override)	960RO-MO/MO w/ Cylinder	-	RCI	K ⚡ ✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
2	Meeting Stile	B606 _BB x (Opening Height)	Aluminum (A)	NGP	✓
1	Emergency Pull Station	904PB (Blue)	-	RCI	⚡ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	⚡
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	⚡
1	Pull Station Cover (Blue, Alarmed)	STI-13030NB	-	STI	⚡ ✓

Requires Alternate Solution Approval

Electronic Elevation: E5

Mode of Operations:

Normal State: Locked on Egress

Entry: Unlocked or Locked by Key.

Egress: User presents credential to Reader which releases door.

Emergency Egress: In case of emergency use emergency pull station which will immediately open door

During loss of power: Door unlocked on Egress (Fail Safe)

Fire Alarm Connection: Required

Hardware Set: 13

Opening(s):

(118-1) CORRIDOR/TOILETING	914 x 2134 x 45mm PSF() WD(W1)
(130-1) CORRIDOR/ACC. WR	914 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Storeroom, Push to Lock Button, LED Indicators) / Electric Strike / AutoOperator

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✓
1	Automatic Operator (Pull Side, Built-in Stop)	4632 (Arm to Suit)	Aluminum (689)	LCN	✓
1	Actuator Set (36") w/ Integrated Indicator	1ea - Push to Open CM-7436/4-LED (Exterior) 1ea - Push to Open CM-7436/4 (Interior) 1ea - Push to Lock CM-7436/4-LED (Interior)	-	Camden	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Door Position Switch (DPDT)	MSS100-4Y (To match frame color)	Black	Flair Electronics	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Electronic Elevation: E6

Mode of Operation:

Normal state: Unlocked on entry

Entry: Free Entry. User has option to push the actuator marked "push to open" which automatically opens the door. User pushes button inside the room to lock door. Lock status shown on inside and outside indicators.

Egress: Free Egress and user can push the "push to open" button which automatically opens the door

During loss of power: Door remains locked (Fail Secure)

Connected to fire alarm: Not Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 14**Opening(s):**

(107-1) WR/CORRIDOR	914 x 2134 x 45mm PSF() WD(W1)
(112-1) CORRIDOR/ACC.WR	914 x 2134 x 45mm PSF() WD(W1)
(115-1) ACC.WR/CORRIDOR	914 x 2134 x 45mm PSF() WD(W1)
(212-1) CORRIDOR/ACC. WR	914 x 2134 x 45mm PSF() WD(W1)
(225-1) ACC. WR/CORRIDOR	914 x 2134 x 45mm PSF() WD(W1)
(312-1) CORRIDOR/ACC. WR	914 x 2134 x 45mm PSF() WD(W1)
(325-1) ACC. WR/CORRIDOR	914 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Storeroom, Push to Lock Button, LED Indicators) / Electric Strike / AutoOperator

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✓
1	Automatic Operator (Pull Side)	4632 (Arm to Suit)	Aluminum (689)	LCN	✓
1	Actuator Set (36") w/ Integrated Indicator	1ea - Push to Open CM-7436/4-LED (Exterior) 1ea - Push to Open CM-7436/4 (Interior) 1ea - Push to Lock CM-7436/4-LED (Interior)	-	Camden	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	Door Position Switch (DPDT)	MSS100-4Y (To match frame color)	Black	Flair Electronics	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Electronic Elevation: E7**Mode of Operation:**

Normal state: Unlocked on entry

Entry: Free Entry. User has option to push the actuator marked "push to open" which automatically opens the door. User pushes button inside the room to lock door. Lock status shown on inside and outside indicators.

Egress: Free Egress and user can push the "push to open" button which automatically opens the door

During loss of power: Door remains locked (Fail Secure)

Connected to fire alarm: Not Required

Hardware Set: 15

Opening(s):

(C100-3) CORRIDOR 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Exit Device (Exit Only)

3	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Exit Device - Rim (Exit Only)	98 EO	Satin Chrome (626)	Von Duprin	✓
1	Surface Closer (Push Side Mount)	4040XP EDA	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 16**Opening(s):**

(ST-C-1) CORRIDOR/STAIR - C	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN
(ST-C-3) CORRIDOR/STAIR - C	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN
(ST-C-4) CORRIDOR/STAIR - C	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN

Base Function: Exit Device (Passage) / Electric Hold Open

6	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Exit Device (F) VRT (Passage, Less Bottom Rod)	9827L-BE-F 06 LBR	Satin Chrome (626)	Von Duprin	✓
1	Exit Device (F) VRT (Exit Only, Less Bottom Rod)	9827EO-F LBR	Satin Chrome (626)	Von Duprin	✓
2	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
2	Hold Open (Electromagnetic)	SEM7850 or equal (By Div 26)	Aluminum (689)	By Others	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
2	Meeting Stile	B606_-BB x (Opening Height)	Aluminum (A)	NGP	✓

Frame and Door to be installed to allow for 180deg swing.

Electronic Elevation: E8**Mode of Operations:**

Normal State: Held Open.

Entry: Free Entry.

Egress: Free egress.

During loss of power: Door automatically closes and latches. Door remains unlocked

Connected to fire alarm: Required

Hardware Set: 17

Opening(s):

(ST-B-1) CORRIDOR/STAIR-B

914 x 2134 x 45mm PSF() HMD(ST4) 45 MIN

Base Function: Exit Device (Passage) / Electric Strike / AutoOperator

3	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Exit Device - Rim (Passage Trim)	98L-BE-F 06	Satin Chrome (626)	Von Duprin	✓
1	Electric Strike Rim (Rated) (1500lbs Static)	9500 w/QC-C006P	Stainless Steel (US32D)	Hes	✗ ✓
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689),Stainless Steel (630)	LCN	✗ ✓
1	Actuator Set (36")	2ea - CM-7536/4	-	Camden	✗ ✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Electronic Elevation: E9

Mode of Operations:

Normal State: Unlocked

Entry: Free Entry. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains unlocked

Connection to fire alarm: Required

Hardware Set: 18

Opening(s):

(108-1) CORRIDOR/MULTI-PURPOSE ROOM 1828 x 2134 x 45mm PSF() WD(W5)

Base Function: Lever (Classroom)

6	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Flush Bolt (Self Latching, Top Only)	F7805 (Metal) or F7905 (Wood)	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Security Classroom)	ND78__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Pull Side, DA, Built-in Holder)	4040XP-DEL-H	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
2	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Note: Provide Flat Lip Strike for lockset

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 19**Opening(s):****(104a-1) SMUDGE ROOM/INDIGENOUS HUB****1828 x 2134 x 45mm PSF() WD(W3)****Base Function: Lever (Classroom)**

6	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Flush Bolt (Manual, Top Mount Only)	F65	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
2	Auto Door Bottom (Surface)	STC4131_PK x (Door Width)	Aluminum (C)	Pemko	✓
1	Astragal	DS185_T x (Door Height)	Aluminum (C)	Draftseal	✓

Hardware Set: 20

Opening(s):

(124-3) CLOSET 1828 x 2134 x 45mm PSF() HMD(ST2)

Base Function: Lever (Classroom)

6	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Flush Bolt (Manual, Top Mount Only)	F65	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 21

Opening(s):

(127a-1) BEFORE & AFTER SCHOOL/SERVERY	914 x 2134 x 45mm PSF() WD(W2)
(127a-2) BEFORE & AFTER SCHOOL/SERVERY	914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 22

Opening(s):		914 x 2134 x 45mm PSF() WD(W2)			
(103-1) STAFF ROOM/CORRIDOR					
Base Function: Lever (Classroom)					
3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Security Classroom)	ND78__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side, DA)	4040XP-DEL-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 23

Opening(s):

(116c-2) CORRIDOR/OFFICE 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Security Classroom)	ND78__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 24

Opening(s):

(102-1) RECEPTION/CORRIDOR	914 x 2134 x 45mm PSF() HMD(ST4)
(104-1) INDIGENOUS HUB/CORRIDOR	914 x 2134 x 45mm PSF() HMD(ST4)
(116-1) CORRIDOR/LEARNING COMMONS	914 x 2134 x 45mm PSF() WD(W2)
(116-2) CORRIDOR/LEARNING COMMONS	914 x 2134 x 45mm PSF() WD(W2)
(117-1) CORRIDOR/INCLUSIVE EDUCATION	914 x 2134 x 45mm PSF() WD(W2)
(124-1) CORRIDOR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W2)
(201-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(204-1) INCLUSIVE EDUCATION/CORRIDOR	914 x 2134 x 45mm PSF() WD(W4)
(211-1) CORRIDOR/BREAKOUT ROOM	914 x 2134 x 45mm PSF() WD(W4)
(226-1) CORRIDOR/BREAKOUT ROOM	914 x 2134 x 45mm PSF() WD(W4)
(301-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(304-1) INCLUSIVE ED./CORRIDOR	914 x 2134 x 45mm PSF() WD(W4)
(311-1) CORRIDOR/BREAKOUT ROOM	914 x 2134 x 45mm PSF() WD(W4)
(326-1) CORRIDOR/BREAKOUT ROOM	914 x 2134 x 45mm PSF() WD(W4)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Security Classroom)	ND78__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 25

Opening(s):

(119-1) CORRIDOR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W2)
(120-1) KINDERGARTEN/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(121-1) CORRIDOR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W2)
(122-1) CORRIDOR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W2)
(123-1) KINDERGARTEN/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(127-1) CORRIDOR/BEFORE & AFTER SCHOOL	914 x 2134 x 45mm PSF() WD(W2)
(131-1) BEFORE & AFTER SCHOOL/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(202-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(203-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(205-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(206-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(207-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(208-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(209-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(210-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(218-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(219-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(220-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(221-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(302-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(303-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(305-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(306-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(307-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(308-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(309-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(310-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(318-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(319-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)
(320-1) CLASSROOM/CORRIDOR	914 x 2134 x 45mm PSF() WD(W2)
(321-1) CORRIDOR/CLASSROOM	914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3 Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1 Lever (Security Classroom)	ND78__ RHO	Satin Chrome (US26D)	Schlage K	✓
1 Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1 Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 26

Opening(s):

(104c-1) MULTI-PURPOSE ROOM/SERVERY 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side, Mount Plate for Concealed Stop)	4040XP DEL REG 18TJ ST-1630	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Overhead Stop (Concealed Heavy Duty)	10_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 27

Opening(s):

(104c-2) INDIGENOUS HUB/SERVERY 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side, DA)	4040XP-DEL-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 28

Opening(s):

(116a-1) MEETING/LEARNING COMMONS	914 x 2134 x 45mm PSF() WD(W2)
(116b-1) OFFICE/LEARNING COMMONS	914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 29

Opening(s):

(104b-1) OFFICE/INDIGENOUS HUB	914 x 2134 x 45mm PSF() WD(W4)
(204a-1) OFFICE/INCLUSIVE EDUCATION	914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom)	ND70__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 30**Opening(s):**

(102a-1) RECEPTION/VP OFFICE	914 x 2134 x 45mm PSF() WD(W2)
(102b-1) RECEPTION/PRINCIPAL OFFICE	914 x 2134 x 45mm PSF() WD(W2)
(102c-1) VP OFFICE/RECEPTION	914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Office)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Office)	ND53__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 31

Opening(s):

(C101-1) GYM/CORRIDOR 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Lever (Passage) / Electric Strike / AutoOperator

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Passage)	ND10S RHO	Satin Chrome (US26D)	Schlage	✓
1	Electric Strike (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✗✓
1	Automatic Operator (Pull Side)	4632 (Arm to Suit)	Aluminum (689)	LCN	✗✓
1	Actuator Set (36")	2ea - CM-7536/4	-	Camden	✗✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Note: Electric strike powered by automatic operator

Electronic Elevation: E10
Mode of Operations:

Normal State: Unlocked

Entry: Free Entry. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains unlocked

Connection to fire alarm: Not Required

Hardware Set: 32

Opening(s):

(213-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(214-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(215-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(222-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(223-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(224-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(313-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(314-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(315-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(322-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(323-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(324-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Privacy w/ Indicator)

3	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Privacy Lock w/ indicator on Rosette)	ND40S RHO OS-OCC	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Push Side Mount Built in Holder)	4040XP DEL HCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓

Closer to be adjusted to not latch opening. This is a visual indicator that no one is in the washroom. Also openings can be pushed into the 90deg hold open position

Hardware Set: 33

Opening(s):

(105-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(106-1) ACC. WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(113-1) CORRIDOR/WR	813 x 2134 x 45mm PSF() WD(W1)
(114-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(128-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)
(129-1) WR/CORRIDOR	813 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Privacy w/ Indicator)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Privacy Lock w/ indicator on Rosette)	ND40S RHO OS-OCC	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Pull Side, DA)	4040XP-DEL-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Closer to be adjusted to not latch opening. This is a visual indicator that no one is in the washroom.

Hardware Set: 34

Opening(s):

(119a-1) WR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W1)
(120a-1) WR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W1)
(121a-1) KINDERGARTEN/WR	914 x 2134 x 45mm PSF() WD(W1)
(122a-1) KINDERGARTEN/WR	914 x 2134 x 45mm PSF() WD(W1)
(123a-1) KINDERGARTEN/WR	914 x 2134 x 45mm PSF() WD(W1)
(124a-1) WR/KINDERGARTEN	914 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Privacy w/ Indicator)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Privacy Lock w/ indicator on Rosette)	ND40S RHO OS-OCC	Satin Chrome (US26D)	Schlage	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 35

Opening(s):

(111-1) GYM STOR./GYM 1828 x 2134 x 45mm PSF() HMD(ST2)

Base Function: Lever (Storeroom)

6	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Flush Bolt (Manual, Top Mount Only)	F65	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Pull Side Mount, Built-in Holder)	4040XP-H	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
2	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 36

Opening(s):

(116-4) LEARNING COMMONS 813 x 2134 x 45mm PSF() WD(W1)

Base Function: Lever (Storeroom)

3	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 37**Opening(s):****(127b-1) BEFORE & AFTER SCHOOL/STOR.****914 x 2134 x 45mm PSF() WD(W1)****(131a-1) STOR./BEFORE & AFTER SCHOOL****914 x 2134 x 45mm PSF() WD(W1)**[Base Function: Lever \(Storeroom\)](#)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side, DA, Built-in Holder)	4040XP-DEL-H	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 38

Opening(s):

(126-1) CORRIDOR/CUST.	914 x 2134 x 45mm PSF() WD(W1) 0 MIN
(217-1) CORRIDOR/CUST.	914 x 2134 x 45mm PSF() WD(W1) 0 MIN
(317-1) CORRIDOR/CUST.	914 x 2134 x 45mm PSF() WD(W1) 0 MIN

Base Function: Lever (Storeroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side, DA)	4040XP-DEL-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓

Hardware Set: 39

Opening(s):

(316-1) STOR./CORRIDOR 914 x 2134 x 45mm PSF() WD(W1) 45 MIN

Base Function: Lever (Storeroom)

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
1	Sweep (Brush)	DS148__NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Hardware Set: 40

Opening(s):

(110-1) GYM STOR./GYM STOR. 1828 x 2134 x 45mm PSF() HMD(ST2)

Base Function: Lever (Storeroom Both Sides)

6	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Flush Bolt (Manual, Top Mount Only)	F65	Satin Chrome (US26D)	Standard Metal	✓
1	Lever (Keyed Both Sides Storeroom)	ND82__ RHO	Satin Chrome (US26D)	Schlage K	✓
2	Surface Closer (Push Side Mount Built in Holder)	4040XP SHCUSH	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓

Hardware Set: 41

Opening(s):

(101-2) VEST/CORRIDOR 1828 x 2134 x 45mm PSF() HMD(ST5)

Base Function: Push Bar Pull / AutoOperator

6	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
2	Push Bar & Pull Offset	9190EZHD-12" (13" OA x 12" CTC) x (To Suit Door Width)	Stainless Steel (US32D)	Ives	✓
1	Automatic Operator Set (Closer, Overhead Stop) (Push Side, Built-in Stop)	1ea - Operator 4642 x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer 4040XP Top Jamb x Long Arm (Arm TBC to Suit Jamb Depth) 1ea - Closer Plate 4040XP-18G 2ea - Overhead Stops 100S (Series) x ADJ	Aluminum (689),Stainless Steel (630)	LCN	✗ ✓
1	Actuator Set (36")	2ea - CM-7536/4	-	Camden	✗ ✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓

Electronic Elevation: E11

Mode of Operations:

Normal State: Unlocked

Entry: Free Entry. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains unlocked

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 42**Opening(s):**

(ST-A-1) CORRIDOR/STAIR - A	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN
(ST-A-3) CORRIDOR/STAIR - A	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN
(ST-A-5) CORRIDOR/STAIR - A	1828 x 2134 x 45mm PSF() HMD(ST3) 45 MIN

Base Function: Credential Reader / Exit Device (Storeroom EL Latch Retraction) / Electric Hold Open

5	Hinge (5 knuckle, Heavy Weight, NRP)	5BB1HW NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, Heavy Weight, EL 8 Wire)	5BB1HW TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✗ ✓
1	Exit Device (F) VRT (Storeroom, Less Bottom Rod, EL Latch Retraction)	QEL9827L-NL-F 06 LBR CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Exit Device (F) VRT (Exit Only, Less Bottom Rod)	9827EO-F LBR	Satin Chrome (626)	Von Duprin	✓
2	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
2	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
2	Hold Open (Electromagnetic)	SEM7850 or equal (By Div 26)	Aluminum (689)	By Others	✗ ✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
2	Sweep (Brush)	DS148_ NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
2	Meeting Stile	B606_ -BB x (Opening Height)	Aluminum (A)	NGP	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

(ST-A-1) Frame and Door to be installed to allow for 180deg swing.

Electronic Elevation: E12**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

Additional Function: User has the option to hold door open (Option to schedule hold open time with access control system)

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 43

Opening(s):

(125-1) MECH/CORRIDOR	914 x 2134 x 45mm PSF() HMD(ST1) 45 MIN
(216a-1) STOR./MECH	914 x 2134 x 45mm PSF() HMD(ST1) 45 MIN

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✗ ✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E13

Mode of Operations:

Normal State: Locked on entry
Entry: User presents credential to Reader which releases door.
Egress: Free egress.
During loss of power: Door remains locked (Fail Secure)
Fire Alarm Connection: Required

Hardware Set: 44

Opening(s):

(216-1) STOR./CORRIDOR 914 x 2134 x 45mm PSF() WD(W2)

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike / AutoOperator

3	Hinge (5 Knuckle, Heavy Weight)	5BB1HW 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom Vandlgard)	ND96__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C w/QC-C006P	Stainless Steel (US32D)	Hes	✓
1	Automatic Operator (Pull Side)	4632 (Arm to Suit)	Aluminum (689)	LCN	✓
1	Actuator Set (36")	2ea - CM-7536/4	-	Camden	✓
1	Kick Plate	K10A- 10" [254] x (Dr Width - 1-1/2" [38])	Stainless Steel (US32D)	Standard Metal	✓
1	Stop (Wall)	S122	Satin Chrome (US26D)	Standard Metal	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Electronic Elevation: E14

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 45

Opening(s):

(108-3) INDIGENOUS HUB/MULTI-PURPOSE

4600 x 2500 OPW() OPW(OW1)

(109-5) MULTIPURPOSE/GYM

OPW() OPW(OW2)

Base Function: Hardware by Opening Supplier

Operable Wall

Note: All other hardware by supplier

Hardware Set Specifications

Project: Cameron Elementary School

Section 08 71 00.1

Submittal Date: 2026.02.06 (IFT)

Hardware Set: 46

Opening(s):

(102-2) RECEPTION	Grille() Grille(SL1)
(C100-4) CORRIDOR	Grille() Grille(SL3)
(116-5) LEARNING COMMONS	Grille() Grille(SL2)

Base Function: Cylinder Only

1	Cylinder	To Suit	Satin Chrome (US26D)	Schlage	K	✓
---	----------	---------	-------------------------	---------	---	---

(102-2, C100-4) Accordion Grille
Note: All other hardware by supplier