

Set Index

Total Sets (51) Total Openings (88) Total Areas (1)

Door	Set	Door	Set	Door	Set	Door	Set	Door	Set
101.1	1	202.1	23						
101.2	5	203.1	39						
102.1	41	204.1	7						
102.2	40	205.1	52						
103.1	36	205.2	54						
104.1	22	206.1	51						
104.2	2	206.2	25						
105.1	3	206.3	32						
106.1	19	208.1	28						
107.1	35	209.1	53						
109.1	12	210.1	53						
110.1	21	212.1	23						
111.1	24	213.1	23						
112.1	20	214.1	30						
113.1	18	G100.1	49						
114.1	38	G100.10	45						
114.2	28	G100.11	49						
119.1	28	G100.12	43						
119.2	12	G100.13	43						
120.1	26	G100.14	42						
130.1	29	G100.15	46						
131.1	37	G100.16	46						
132.1	33	G100.17	46						
133.1	9	G100.18	46						
134.1	34	G100.19	46						
135.1	28	G100.2	46						
135.2	28	G100.20	49						
141.1	12	G100.21	46						
142.1	28	G100.22	46						
142.2	10	G100.23	49						
148.1	15	G100.24	49						
149.1	15	G100.3	46						
150.1	11	G100.4	49						
151.1	31	G100.5	48						
152.1	31	G100.6	47						
153.1	31	G100.7	50						
154.2	14	G100.8	48						
155.1	11	G100.9	44						
156.1	13								
157.1	13								
158.1	15								
159.1	15								
160.1	17								
162.1	12								
163.1	28								
163.2	28								
164.1	27								
168.1	38								
168.2	10								
201.1	4								

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 1**Opening(s):****(101.1) Glen Drive/Vestibule****1850 x 2134 x 57 ALF() ALD(D1) -****Base Function: Credential Reader / Intercom / Exit Device (Storeroom w/ Pull) / AutoOperator**

1	Continuous Hinge	112XY x (Door Height - 1")	Aluminum (US28)	Ives	✓
1	Continuous Hinge (EL)	112XY TWP8 CON x (Door Height - 1") x CON-6P x CON-__ (Length to Suit, Thru Door)	Aluminum (US28)	Ives	✗ ✓
1	Flush Bolt (Face Mount, Manual)	1870 w/ Cylinder	Satin Chrome (US26D)	Adams Rite	K ✓
1	Flush Bolt (Manual)	By Aluminum Door Supplier	-	By Others	
1	Exit Device - N Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL35A-NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Automatic Operator (Push Side, Built-in Stop)	8100 Full Length Header (Manual Closer on inactive) w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✗ ✓
1	Actuator Set (Top + Bottom)	2ea - CM-35N/4-WT (Exterior) 2ea - CM-35N/4	-	Camden	✗ ✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
2	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Intercom System	Supplied by Div 28	-	By Others	✗
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: Weatherstrip, Sweep, and Threshold to be Supplied by Door Supplier

Note: Keyed flushbolt operated by facility only.

Note: Include overlapping double door strike

Electronic Elevation: E1

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader or use intercom system. Intercom System can remotely unlock door. After access is granted from card reader or intercom, user has the option to push actuator to automatically open door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 2**Opening(s):****(104.2) Meet and Greet/Meet and Greet Courtyard****819 x 2132 x 38 ALF() ALD(D2) -****Base Function: Credential Reader / Lever (Storeroom Electrically Unlocked)**

1	Continuous Hinge (EL)	112XY TWP8 CON x (Door Height - 1") x CON-6P x CON-__ (Length to Suit, Thru Door)	Aluminum (US28)	Ives	✓
1	Knob Mortise (Electrified Fail Secure, REX)	L9092__EU 42B RX CON (12V/24VDC)	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓

Note: Aluminum Door requires min 5" stiles

Note: Weatherstrip, Sweep, and Threshold to be Supplied by Door Supplier

Electronic Elevation: E2**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 3

Opening(s):

(105.1) Entrance Lobby/Stair 1

915 x 2132 x 38 ALF() ALD(A7) 45 min

Base Function: Exit Device (Passage)

1	Pivot Set	By Door Supplier	-	By Manufacturer
1	Exit Device - N Rim (Passage Trim)	35A-L-BE-F 06	Satin Chrome (626)	Von Duprin
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN
1	Auto Door Bottom (Mortise Metal)	420_PKL x (Door Width)	-	Pemko

Note: Aluminum style system from allegion used as basis of design for fire rating on aluminum.

Note: All other hardware by supplier

Hardware Set: 4

Opening(s):

(201.1) Waiting Lounge/Stair 1

915 x 2134 x 38 ALF() ALD(A7) 45 min

Base Function: Exit Device (Passage)

1	Pivot Set	By Door Supplier	-	By Manufacturer	
1	Exit Device - N Rim (Passage Trim)	35A-L-BE-F 06	Satin Chrome (626)	Von Duprin	
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Auto Door Bottom (Mortise Metal)	420_PKL x (Door Width)	-	Pemko	✓

Note: Aluminum style system from allegion used as basis of design for fire rating on aluminum.
Note: All other hardware by supplier

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 5**Opening(s):****(101.2) Vestibule/Entrance Lobby****1850 x 2134 x 57 ALF() ALD(D1) -****Base Function: Credential Reader / Intercom / Exit Device (Storeroom w/ Pull) / AutoOperator**

1	Continuous Hinge	112XY x (Door Height - 1")	Aluminum (US28)	Ives	✓
1	Continuous Hinge (EL)	112XY TWP8 CON x (Door Height - 1") x CON-6P x CON-___ (Length to Suit, Thru Door)	Aluminum (US28)	Ives	✗ ✓
1	Flush Bolt (Face Mount, Manual)	1870 w/ Cylinder	Satin Chrome (US26D)	Adams Rite	K ✓
1	Flush Bolt (Manual)	By Aluminum Door Supplier	-	By Others	
1	Exit Device - N Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL35A-NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Automatic Operator (Push Side, Built-in Stop)	8100 Full Length Header (Manual Closer on inactive) w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✗ ✓
1	Actuator Set (Top + Bottom)	2ea - CM-35N/4-WT (Exterior) 2ea - CM-35N/4	-	Camden	✗ ✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
2	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Intercom System	Supplied by Div 28	-	By Others	✗
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: All other hardware by supplier

Note: Keyed flushbolt operated by facility only.

Note: Include overlapping double door strike

Electronic Elevation: E1

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader or use intercom system. Intercom System can remotely unlock door. After access is granted from card reader or intercom, user has the option to push actuator to automatically open door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 7**Opening(s):****(204.1) Waiting Lounge/Volunteer****915 x 2134 x 38 ALF() ALD(D2) -****Base Function: Credential Reader / Lever (Storeroom) / Electric Strike**

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side, Mount Plate for Concealed Stop)	4040XP REG 18TJ ST-1630		LCN	✓
1	Overhead Stop (Concealed Heavy Duty)	10_S	Stainless Steel (US32D)	Glynn Johnson	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: Aluminum Door requires min 5" stiles

Electronic Elevation: E3

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 9

Opening(s):

(133.1) Centre Corr. 3/Parking Yard

1473 x 2134 x 44 PSF(F1) HMD(C1) 1 h

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull) / AutoOperator

5	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✗ ✓
2	Flush Bolt (Self Latching, Top + Bottom Set)	2845 (Metal) or 2945 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Exit Device - Mortise (Storeroom, Less Pull)	9875NL-L/Trim-F w/Cyl to Suit	Satin Chrome (626)	Von Duprin K	✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Automatic Operator (Push Side, Built-in Stop)	8100 Full Length Header (Manual Closer on inactive) w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✗ ✓
1	Actuator Set (Top + Bottom)	2ea - CM-35N/4-WT (Exterior) 2ea - CM-35N/4	-	Camden	✗ ✓
1	Coordinator	1700	Aluminum (US28)	Rockwood	✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
2	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: Provide Flat Lip Strike for lockset

Electronic Elevation: E4

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door Unlocked (Fail Secure)

Connection to fire alarm: Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 10

Opening(s):

(142.2) West Corr. 3/Parking Yard	915 x 2134 x 44 PSF(F5) HMD(A6) 1 h
(168.2) East Corr. 3/Receiving Yard	915 x 2134 x 44 PSF(F4) HMD(A5) 1 h

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull)

2	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Exit Device - Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL 98NL-OP-F CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E5

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 11

Opening(s):

(150.1) Isolation/Parking Yard	915 x 2134 x 44 PSF(F4) HMD(A5) -
(155.1) Stair B/Parking Yard	915 x 2134 x 44 PSF(F2) HMD(A3) -

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull)

2	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Exit Device - Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL 98NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
1	Sweep (Brush, with Rain Drip)	DS161_NB x (Door Width)	Aluminum (A)	Draftseal	✓

Electronic Elevation: E6

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 12**Opening(s):**

(109.1) Centre Corr. 1/South Courtyard	915 x 2134 x 44 PSF(F5) HMD(A6) -
(119.2) South Corr. 2/Ext. Walkway	915 x 2134 x 44 PSF(F5) HMD(A6) -
(141.1) West Corr. 2/West Courtyard	915 x 2134 x 44 PSF(F5) HMD(A6) -
(162.1) East Corr. 1/Ext. Walkway	915 x 2134 x 44 PSF(F5) HMD(A6) -

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull)

2	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Exit Device - Rim (Storeroom, Less Pull) (Electric Latch Retraction, REX)	RX QEL 98NL-OP CON (24VDC) w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K ✗ ✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives	✓
1	Surface Closer (Push Side Mount)	4040XP EDA	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline	✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E6**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 13**Opening(s):**

(156.1) Electrical/Receiving Yard	1676 x 2134 x 44 PSF(F2) HMD(C2) 1 h
(157.1) Mechanical/Receiving Yard	1676 x 2134 x 44 PSF(F2) HMD(C2) 1 h

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

5	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-___ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Flush Bolt (Self Latching, Top + Bottom Set)	2845 (Metal) or 2945 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Lever (Storeroom - 3/4" Latch)	ND80___ RHO 14-042 (3/4" Latch)	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400	Stainless Steel (US32D)	Von Duprin	✗ ✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Coordinator	1700	Aluminum (US28)	Rockwood	✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (For Electric Strikes, Interlocking, Dbl)	SP2300 Series x (Door Height) (To Match Frame Color) 1-3/4" Throat	-	Frontline	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E7**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 14

Opening(s):

(154.2) Water Entry/West Courtyard

1219 x 2134 x 44 PSF(F2) HMD(B1) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

5	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Flush Bolt (Self Latching, Top + Bottom Set)	2845 (Metal) or 2945 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400	Stainless Steel (US32D)	Von Duprin	✗ ✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (For Electric Strikes, Interlocking, Dbl)	SP2300 Series x (Door Height) (To Match Frame Color) 1-3/4" Throat	-	Frontline	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E8

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 15**Opening(s):**

(148.1) Parking Yard/Drop-Off Kennel 148	610 x 2134 x 44 PSF(F2) HMD(E1) -
(149.1) Parking Yard/Drop-Off Kennel 149	610 x 2134 x 44 PSF(F2) HMD(E1) -
(158.1) Receiving Yard/Drop-Off Kennel 158	610 x 2134 x 44 PSF(F2) HMD(E1) -
(159.1) Receiving Yard/Drop-Off Kennel 159	610 x 2134 x 44 PSF(F2) HMD(E1) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Push Side Mount Built in Holder)	4040XP SHCUSH	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130__R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148__NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000__x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (For Electric Strikes, Interlocking, Sgl)	SP2300 Series x (Door Height) (To Match Frame Color) 1-3/4" Throat	-	Frontline	✓
1	Credential Reader with Integrated Keypad / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: CR requested to be keypad for animal drop off.

Electronic Elevation: E9**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 17

Opening(s):

(160.1) Dead Animal Room/Receiving Yard

1676 x 2134 x 44 PSF(F2) HMD(C3) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike / AutoOperator

5	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Hinge (Stainless, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-___ (Length to Suit, Thru Door)	Stainless Steel (US32D)	Ives	✗ ✓
1	Flush Bolt (Self Latching, Top + Bottom Set)	2845 (Metal) or 2945 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Lever (Storeroom)	ND80___ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Automatic Operator (Push Side, Built-in Stop)	8100 Full Length Header (Manual Closer on inactive) w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✗ ✓
1	Actuator Set (Top + Bottom)	2ea - CM-35N/4-WT (Exterior) 2ea - CM-35N/4	-	Camden	✗ ✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Weather-Strip	DS130_R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
2	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000_ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (For Electric Strikes, Interlocking, Dbl)	SP2300 Series x (Door Height) (To Match Frame Color) 1-3/4" Throat	-	Frontline	✓
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
2	Kick Down Door Holder	FS452-4	Satin Chrome (US26D)	Ives	✓

Electronic Elevation: E10

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 18**Opening(s):****(113.1) Entrance Lobby/South Courtyard****915 x 2134 x 44 PSF(F5) HMD(A6) -****Base Function: Credential Reader / Lever (Storeroom) / Electric Strike**

3	Hinge (5 Knuckle, Stainless, NRP)	5BB1 NRP 4-1/2" x 4"	Stainless Steel (US32D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Weather-Strip	DS130__R x (Door Perimeter)	Aluminum (C)	Draftseal	✓
1	Sweep (Brush)	DS148__NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (8" x 1/4" Rise)	DS8000__ x (Opening Width)	Aluminum (A)	Draftseal	✓
1	Astragal (For Electric Strikes, Interlocking, Sgl)	SP2300 Series x (Door Height) (To Match Frame Color) 1-3/4" Throat	-	Frontline	✓
1	Door Position Switch (SPST)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E11**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

- Door Position Switch, for intrusion system only not access control.

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 19

Opening(s):

(106.1) Elevator

915 x 2134 x 44 PSF(F1) HMD(A1) 45 min

Base Function: Deadbolt / Lever (Passage)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Deadbolt	B660__	Satin Chrome (US26D)	Schlage K	✓
1	Lever (Passage)	ND10S RHO	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Pull Side, Mount Plate for Concealed Stop)	4040XP REG 18TJ ST-1630	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Overhead Stop (Concealed Heavy Duty)	10_S	Stainless Steel (US32D)	Glynn Johnson	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Note: Elevator shaft door.

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 20

Opening(s):

(112.1) Centre Corr. 1/Behaviour Room

915 x 2134 x 44 PSF(F6) HMD(A4) -

Base Function: 0

4	Hinge (5 Knuckle)	58B1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Deadbolt (Double Sided)	B662__	Satin Chrome (US26D)	Schlage	K ✓
1	Knob Mortise (Classroom)	L9070__ 42B	Satin Chrome (US26D)	Schlage	K ✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Door Holder	WS40	Satin Chrome (US26D)	Ives	✓
1	Astragal	357 Series x (Door Width) (To Match Frame Color)	Aluminum (C)	Pemko	
1	Gasketing	S88_ x (Door Width)	D	Pemko	✓
	Package/Kit:	1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)	-	Pemko	✓
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			

Note: Additional Gasketing and Astragal for width of door between dutch door leafs.
Note: Dutch Door. Deadbolt Latches from Top Leaf to Bottom Leaf. Lever on bottom leaf

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 21**Opening(s):****(110.1) Centre Corr. 1/Kennel Supervisor****915 x 2134 x 44 PSF(F6) HMD(A4) -****Base Function: Lever (Storeroom) / Electric Strike / Electrically Unlocked / Credential Reader**

4	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Deadbolt	B660__	Satin Chrome (US26D)	Schlage K	✓
1	Knob Mortise (Storeroom)	L9080__ 42B	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Floor) 1-1/2" Height	FS439	Satin Chrome (US26D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			
			-	Pemko	✓

Note: Dutch Door. Deadbolt Latches from Top Leaf to Bottom Leaf. Lever on bottom leaf

Electronic Elevation: E12**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 22**Opening(s):****(104.1) Entrance Lobby/Meet and Greet Room****915 x 2134 x 44 PSF(F3) HMD(A4) -****Base Function: Lever (Storeroom) / Electric Strike / Electrically Unlocked / Credential Reader**

4	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Deadbolt	B660__	Satin Chrome (US26D)	Schlage K	✓
1	Knob Mortise (Storeroom)	L9080__ 42B	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin ⚡	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Floor) 1-1/2" Height	FS439	Satin Chrome (US26D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others ⚡	
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others ⚡	

Note: Dutch Door. Deadbolt Latches from Top Leaf to Bottom Leaf. Lever on bottom leaf

Electronic Elevation: E12**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 23**Opening(s):**

(202.1) Waiting Lounge/Universal WC	915 x 2134 x 44 PSF(F7) HMD(A1) -
(212.1) Locker Room/Staff WC	915 x 2134 x 44 PSF(F7) HMD(A1) -
(213.1) Locker Room/Staff Shower	915 x 2134 x 44 PSF(F7) HMD(A1) -

Base Function: Lever (Storeroom, Push to Lock Button, LED Indicators) / Electric Strike / AutoOperator / Emergency Call System

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✓
1	Automatic Operator (Pull Side)	8100 w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✓
1	Actuator Set (Top + Bottom), Stainless Steel Faceplate	2ea - Push to Open CM-35N/4 (Exterior) 2ea - Push to Open CM-35N/4 (Interior) 2ea - Push to Lock CM-35N/8B (Interior)	-	Camden	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
2	Emergency Call System (Push Button)	SS2471EM-EN (Blue)	-	STI	✓
1	Emergency Call System (Sounder)	CX-DA100	-	Camden	✓
2	LED Indicator (Red: Occupied, Green: UnOccupied, Blue: Assistance Required)	CM-AF142SO	-	Camden	✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓
1	Sweep (Brush)	DS148__NB x (Door Width)	Aluminum (C)	Draftseal	✓
	Package/Kit:	1ea - Auto Door Bottom STC4131__PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter) 1ea - Gasketing S773__ x (Door Perimeter) 1ea - Corner Pad ACP122	-	Pemko	✓

Electronic Elevation: E13**Mode of Operation:**

Normal state: Unlocked on entry

Entry: Free Entry. User has option to push the actuator marked push to open which automatically opens the door. User pushes button inside the room to lock door. Lock status shown on inside and outside indicators.

Egress: Free Egress and user can push the "push to open" button which automatically opens the door.

Emergency: User can push the Push for Emergency Assistance button which will unlock the opening and alert personal.

During loss of power: Door remains locked (Fail Secure)

Connected to fire alarm: Not Required

Connection to Security / Annunciator panel by Access Control

Hardware Set: 24**Opening(s):**

(111.1) Centre Corr. 1/Universal WC

915 x 2134 x 44 PSF(F7) HMD(A1) -

Base Function: Lever (Storeroom, Push to Lock Button, LED Indicators) / Electric Strike / AutoOperator / Emergency Call System

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Automatic Operator (Pull Side)	8100 w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✗ ✓
1	Actuator Set (Top + Bottom), Stainless Steel Faceplate	2ea - Push to Open CM-35N/4 (Exterior) 2ea - Push to Open CM-35N/4 (Interior) 2ea - Push to Lock CM-35N/8B (Interior)	-	Camden	✗ ✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
2	Emergency Call System (Push Button)	SS2471EM-EN (Blue)	-	STI	✗ ✓
1	Emergency Call System (Sounder)	CX-DA100	-	Camden	✗ ✓
2	LED Indicator (Red: Occupied, Green: UnOccupied, Blue: Assistance Required)	CM-AF142SO	-	Camden	✗ ✓
1	Door Position Switch (DPDT)	Supplied by Div 28 (To Match Frame Color)	-	By Others	✗
1	Advance Logic Relay	CX-33	-	Camden	✗ ✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E13**Mode of Operation:**

Normal state: Unlocked on entry

Entry: Free Entry. User has option to push the actuator marked push to open which automatically opens the door. User pushes button inside the room to lock door. Lock status shown on inside and outside indicators.

Egress: Free Egress and user can push the "push to open" button which automatically opens the door.

Emergency: User can push the Push for Emergency Assistance button which will unlock the opening and alert personal.

During loss of power: Door remains locked (Fail Secure)

Connected to fire alarm: Not Required

Connection to Security / Annunciator panel by Access Control

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 25**Opening(s):****(206.2) Circulation/Stair B****915 x 2134 x 44 PASF(F6) HMD(A7) 45 min****Base Function: Exit Device (Passage)**

3	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Exit Device - Rim (Passage Trim)	98L-BE-F 06	Satin Chrome (626)	Von Duprin	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	SmokeSeal	DSS66_ x (Door Perimeter) (Confirm Color)	Dark Bronze (D)	Draftseal	✓
1	Sweep (Brush)	DS148_NB x (Door Width)	Aluminum (C)	Draftseal	✓
1	Threshold (5" x 1/4" Rise)	DS5000_ x (Opening Width)	Aluminum (A)	Draftseal	✓

Hardware Set: 26

Opening(s):

(120.1) South Corr. 2/Grooming Room

915 x 2134 x 44 PSF(F1) HMD(A2) -

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Knob Mortise (Classroom)	L9070__ 42B	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 27**Opening(s):****(164.1) East Corr. 2/Kennel Janitor****915 x 2134 x 44 PSF(F1) HMD(A2) -**[Base Function: Lever \(Classroom\)](#)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom w/ push button)	ND73__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Floor) 1-1/2" Height	FS439	Satin Chrome (US26D)	Ives	✓

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 28

Opening(s):

(114.2) Centre Corr. 1/South Corr. 1	915 x 2134 x 44 PSF(F3) HMD(A5) -
(119.1) Centre Corr. 1/South Corr. 2	915 x 2134 x 44 PSF(F3) HMD(A5) -
(135.1) Centre Corr. 2/West Corr. 1	915 x 2134 x 44 PSF(F3) HMD(A5) -
(135.2) West Corr. 2/West Corr. 1	915 x 2134 x 44 PSF(F3) HMD(A5) -
(142.1) West Corr. 2/West Corr. 3	915 x 2134 x 44 PSF(F3) HMD(A5) -
(163.1) East Corr. 1/East Corr. 2	915 x 2134 x 44 PSF(F3) HMD(A5) -
(163.2) South Corr. 2/East Corr. 2	915 x 2134 x 44 PSF(F3) HMD(A5) -
(208.1) Clerical Area/File Storage Print	915 x 2109 x 38 ALF() WD(D5) -

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom w/ push button)	ND73__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			
			-	Pemko	✓

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 29**Opening(s):****(130.1) Food Prep/Laundry****915 x 2134 x 44 PSF(F8) HMD(A6) -**[Base Function: Lever \(Classroom\)](#)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom w/ push button)	ND73__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)	-	Pemko	✓
		1ea - Corner Pad ACP122			

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 30**Opening(s):****(214.1) Locker Room/Janitor****915 x 2134 x 44 PSF(F6) HMD(A1) -****Base Function: Lever (Passage)**

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Passage)	ND10S RHO	Satin Chrome (US26D)	Schlage	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓

Hardware Set: 31

Opening(s):				
(151.1)	Isolation/Iso Kennel 151	610	x 2134 x 44 PSF(F1) HMD(E1) -	
(152.1)	Isolation/Iso Kennel 152	610	x 2134 x 44 PSF(F1) HMD(E1) -	
(153.1)	Isolation/Iso Kennel 153	610	x 2134 x 44 PSF(F1) HMD(E1) -	

Base Function: Lever (Storeroom)

3	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set: 32

Opening(s):

(206.3) Circulation/Store

915 x 2134 x 44 PSF(F6) HMD(A1) -

Base Function: Lever (Storeroom)

3	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Overhead Stop (Surface Heavy Duty)	90_S	Stainless Steel (US32D)	Glynn Johnson	✓

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 33

Opening(s):

(132.1) Food Storage/Comms

1524 x 2134 x 44 PSF(F1) HMD(B1) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

5	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✗ ✓
1	Flush Bolt (Self Latching, Top Only)	2805 (Metal) or 2905 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400	Stainless Steel (US32D)	Von Duprin	✗ ✓
2	Surface Closer (Push Side Mount Built in Stop)	4040XP SCUSH	Aluminum (689)	LCN	✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E14

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 34

Opening(s):

(134.1) Centre Corr. 3/Storage

1676 x 2134 x 44 PSF(F1) HMD(C2) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

5	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Hinge (5 Knuckle, EL 8 Wire)	5BB1 TW8 CON 4-1/2" x 4" x CON-6P x CON-__ (Length to Suit, Thru Door)	Satin Chrome (US26D)	Ives	✗ ✓
1	Flush Bolt (Self Latching, Top Only)	2805 (Metal) or 2905 (Wood)	Satin Chrome (US26D)	Rockwood	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate (Double - Set)	2ea - 8400- 5" [127] x (Dr Width - 1" [25.4]) B-CS	Stainless Steel (US32D)	Ives	✓
2	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: Closer on Active Leaf Only

Electronic Elevation: E14

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 35**Opening(s):****(107.1) Centre Corr. 2/Exam****915 x 2134 x 44 PSF(F3) HMD(A5) -****Base Function: Credential Reader / Lever (Storeroom) / Electric Strike**

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Knob Mortise (Storeroom)	L9080__ 42B	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E15**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 36

Opening(s):

(103.1) Entrance Lobby/Small Animal Room

915 x 2134 x 44 PSF(F3) HMD(A7) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side, Mount Plate for Concealed Stop)	4040XP REG 18TJ ST-1630	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Overhead Stop (Concealed Heavy Duty)	10_S	Stainless Steel (US32D)	Glynn Johnson	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
		1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)	-	Pemko	✓
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Corner Pad ACP122			

Electronic Elevation: E15

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 37**Opening(s):****(131.1) Food Prep/Food Storage****915 x 2134 x 44 PSF(F8) HMD(A6) -****Base Function: Credential Reader / Lever (Storeroom) / Electric Strike**

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side, Mount Plate for Concealed Stop)	4040XP REG 18TJ ST-1630	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Overhead Stop (Concealed Heavy Duty)	10_S	Stainless Steel (US32D)	Glynn Johnson	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E15**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 38

Opening(s):

(114.1) South Corr. 1/Entrance Lobby	915 x 2134 x 44 PSF(F3) HMD(A5) -
(168.1) East Corr. 1/East Corr. 3	915 x 2134 x 44 PSF(F3) HMD(A5) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			
			-	Pemko	✓

Electronic Elevation: E15

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 39**Opening(s):****(203.1) Volunteer/First Aid****915 x 2134 x 44 PSF(F6) HMD(A2) -****Base Function: Credential Reader / Lever (Storeroom) / Electric Strike**

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Electronic Elevation: E15**Mode of Operations:**

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 40

Opening(s):

(102.2) Entrance Lobby/Small Animal Corridor

915 x 2134 x 44 PSF(F3) HMD(A5) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike / AutoOperator

3	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✓
1	Automatic Operator (Push Side, Built-in Stop)	8100 w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✓
1	Actuator Set (Top + Bottom)	4ea - CM-35N/4	-	Camden	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			
			-	Pemko	✓

Electronic Elevation: E16

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 41

Opening(s):

(102.1) Entrance Lobby/Centre Corr. 2

915 x 2134 x 44 PSF(F3) HMD(A5) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike / AutoOperator

3	Hinge (5 knuckle, NRP)	5BB1 NRP 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage	K ✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✓
1	Automatic Operator (Push Side)	8100 w/ header key switch (On/Off/Hold Open)	Aluminum (US28)	Record	✓
1	Actuator Set (Top + Bottom)	4ea - CM-35N/4	-	Camden	✓
1	Kick Plate	8400- 5" [127] x (Dr Width - 1-1/2" [38]) B-CS	Stainless Steel (US32D)	Ives	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Advance Logic Relay	CX-33	-	Camden	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
		1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Corner Pad ACP122	-	Pemko	✓

Electronic Elevation: E17

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door. User has option to push actuator which automatically opens door.

Egress: Free egress. User has option to push actuator which automatically opens door.

During loss of power: Door remains locked (Fail Secure)

Connection to fire alarm: Not Required

Hardware Set: 42

Opening(s):

(G100.14) Seizure Yard Gate

915 x 2173 x 44 Gate() Gate(G1) -

Base Function: Lever (Storeroom) / Electric Strike / AutoOperator / Remote Release Button

1	Knob Mortise (Storeroom - 3/4" Latch)	L9080__ 42B	Satin Chrome (US26D)	Schlage	K	✓
1	Electric Strike (Lock and Strike Monitor) (1500lbs Static) Field Selectable (Fail Safe, Fail Secure)	1500C-LMS w/QC-C006P	Stainless Steel (US32D)	Hes	⚡	✓
1	Automatic Operator	By Gate Supplier	-	By Others	⚡	
1	Advance Logic Relay (Interlock One Relay per Interlock)	CX-33	-	Camden	⚡	✓
1	Remote Lock/Unlock Button	CM-450R/8	-	Camden	⚡	

Note: All other hardware by supplier

Electronic Elevation: E18
Mode of Operations:

Entry: Entrance by Remote Release Button or by Manual Key.
Egress: Free egress.
Interlock Function: Remote Release Button is deactivated when the interlock/permissive input opening is open or unlatched. When Remote Release Button is active, pressing the button unlocks and opens the opening. Pressing the button again closes the opening and relocks.
During loss of power: Opening remains locked.
Connected to fire alarm: Not required.

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 43**Opening(s):**

(G100.12) Seizure Yard Gate 915 x 2173 x 44 Gate() Gate(G1) -
(G100.13) Seizure Yard Gate 915 x 2173 x 44 Gate() Gate(G1) -

Base Function: Lever (Storeroom) / Latch Monitor / LED Indicator

1	Knob Mortise (Passage - 3/4" Latch)	L9010 42B	Satin Chrome (US26D)	Schlage	✓
1	Latch Monitor (Latch)	LML-1	-	Securitron	✗✓
1	LED Indicator (Red: Occupied, Green: UnOccupied)	CM-AF142SO	-	Camden	✗✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗

Note: All other hardware by supplier

Electronic Elevation: E19

Mode of Operations:

Entry: Free entry.

Egress: Free egress.

Interlock Function: Serves as an interlock/permissive input. Operation of associated controlled opening(s)/device(s) is permitted only when this opening is closed and latched.

Status Indication: Provide indicator light at this opening to show when associated controlled opening(s)/device(s) are open.

During loss of power: Opening remains unlocked.

Connected to fire alarm: Not required.

Hardware Set: 44

Opening(s):		2852 x 2875 x 38 Gate() Gate(G4) -	
(G100.9)			
Base Function: Lever (Storeroom)			
1	Lever Mortise (Storeroom, Less Outside Lever)	L9026__ 06B w/ Cyl to Suit	Satin Chrome (US26D) Schlage K ✓

Note: Gate Hardware to be confirmed with gate supplier.

Note: Keyed access to mortise lock through gate panel. No exterior lever.
Note: All other hardware by supplier

Hardware Set: 45

Opening(s):

(G100.10) 1524 x 2134 x 38 Gate() Gate(G3) -

Base Function: Padlock / Gate Flushbolt

1	Flush Bolt (Manual)	Gate Bolt to Secure Inactive Leaf (By Gate Supplier)	-	By Others	K
1	Padlock	(By Gate Supplier)	-	By Others	K

Note: All other hardware by supplier

Hardware Set: 46

Opening(s):	
(G100.2)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.3)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.15)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.16)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.17)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.18)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.19)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.21)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.22)	915 x 2173 x 44 Gate() Gate(G1) -

Base Function: Padlock

1	Padlock	(By Gate Supplier)	-	By Others	K
---	---------	--------------------	---	-----------	---

Note: All other hardware by supplier

Hardware Set: 47

Opening(s):

(G100.6)

4400 x 4300 x 38 OHD() OHD(G7) -

Base Function: Credential Reader / Long Distance Reader

1	Long Distance Reader	Supplied by Div 28	-	By Others	
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	

Note: CR requested to be keypad .

Electronic Elevation: E20
Mode of Operations:

Locked on entry
Entry: Long Range RF Receiver, detects licence plate or windshield credential. Access control triggers the overhead door to open or user can present valid credential to Pedestal mounted Card Reader.
Egress: Free Egress (Tigger by Overhead door)

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 48

Opening(s):

(G100.5)	915 x 2134 x 44 Gate() Gate(G6) -
(G100.8)	915 x 2134 x 44 Gate() Gate(G6) -

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull)

1	Exit Device - Rim (Storeroom, Less Pull, Outdoor Rated)	OUT 98NL-OP w/Cyl to Suit	Black (315)	Von Duprin	K	✓
1	Pull for Exit Device (Offset)	8190EZHD-2	US19	Ives		✓
1	Electric Strike Rim (2000lbs Static)	9600 w/QC-C006P	Black (BSP)	Hes		✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others		✓
1	Power Supply (Centralized)	Supplied by Div 26/28		By Others		✓
1	Astragal (Interlock)	2100 Series x (Door Height) (To Match Frame Color)	-	Frontline		✓

Note: All other hardware by supplier

Electronic Elevation: E21

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 49**Opening(s):**

(G100.1)	1220 x 2875 x 38 Gate() Gate(G5) -
(G100.4)	915 x 2134 x 44 Gate() Gate(G2) -
(G100.11)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.20)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.23)	915 x 2173 x 44 Gate() Gate(G1) -
(G100.24)	1100 x 2875 x 38 Gate() Gate(G5) -

Base Function: Credential Reader / Exit Device (Storeroom w/ Pull)

1	Exit Device - Rim (Storeroom, Less Pull, Outdoor Rated)	OUT 98NL-OP w/Cyl to Suit	Satin Chrome (626)	Von Duprin	K	✓
1	Pull for Exit Device (Offset)	8190EZHD-2	Stainless Steel (US32D)	Ives		✓
1	Electric Strike Rim (2000lbs Static)	9600 w/QC-C006P	Stainless Steel (US32D)	Hes	⚡	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	⚡	
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	⚡	

Note: All other hardware by supplier

Electronic Elevation: E21

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set: 50

Opening(s):

(G100.7)

4700 x 4300 x 38 OHD() OHD(G7) -

Base Function: Long Distance Reader / Credential Reader / Intercom

1	Intercom System	Supplied by Div 28	-	By Others	
1	Long Distance Reader	Supplied by Div 28	-	By Others	
1	Credential Reader with Integrated Keypad / Controller	Supplied by Div 28	-	By Others	

Electronic Elevation: E22
Mode of Operations:

Locked on entry

Entry: Long Range reader detects licence plate or windsheild credential. Access control triggers the overhead door to open or user can present valid credential to Pedistal mounted Card Reader or user can use enterphone to request access

Egress: Free Egress (Tigger by Overhead door)

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 51

Opening(s):

(206.1) Circulation/Waiting Lounge

915 x 2135 x 38 ALF() ALD(D2) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✗ ✓
1	Surface Closer (Push Side, Built in Stop, Blade Spacer, Drop Plate)	4040XP SCUSH 61 18PA	Aluminum (689)	LCN	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✗
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✗
Package/Kit:					
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Auto Door Bottom STC4131_PK x (Door Width) 1ea - Gasketing S44__ x (Door Perimeter) 1ea - Gasketing S773__ x (Door Perimeter) 1ea - Corner Pad ACP122	-	Pemko	✓

Note: Demountable supplier refer to hardware schedule for hardware requirements.

Note: Aluminum Door requires min 5" stiles

Electronic Elevation: E3

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 52

Opening(s):

(205.1) Meeting Room/Waiting Lounge

915 x 2134 x 38 ALF() ALD(D2) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	⚡ ✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	⚡
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	⚡
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
		1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Corner Pad ACP122	-	Pemko	✓

Note: Demountable supplier refer to hardware schedule for hardware requirements.

Note: Aluminum Door requires min 5" stiles

Electronic Elevation: E3

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 53

Opening(s):

(209.1) Circulation/Manager Office	915 x 2850 x 38 ALF() WD(D5) -
(210.1) Circulation/Flex Office	915 x 2850 x 38 ALF() WD(D5) -

Base Function: Lever (Classroom)

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Classroom w/ push button)	ND73__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Gasketing S44__ x (Door Perimeter)	-	Pemko	✓
		1ea - Gasketing S773__ x (Door Perimeter)			
		1ea - Corner Pad ACP122			

Note: Demountable supplier refer to hardware schedule for hardware requirements.

Hardware Set Specifications

Project: City of Vancouver Animal Shelter

Section 08 71 00.1

Submittal Date: 2026.04.30 (IFT)

Hardware Set: 54

Opening(s):

(205.2) Clerical Area/Meeting Room

915 x 2850 x 38 ALF() WD(D5) -

Base Function: Credential Reader / Lever (Storeroom) / Electric Strike

3	Hinge (5 Knuckle)	5BB1 4-1/2" x 4"	Satin Chrome (US26D)	Ives	✓
1	Lever (Storeroom)	ND80__ RHO	Satin Chrome (US26D)	Schlage K	✓
1	Electric Strike (1500lbs Static)	6400 w/ CON-6P	Stainless Steel (US32D)	Von Duprin	✓
1	Surface Closer (Pull Side Mount)	4040XP-REG	Aluminum (689)	LCN	✓
1	Stop (Wall)	409	Satin Chrome (US26D)	Rockwood	✓
1	Credential Reader / Controller	Supplied by Div 28	-	By Others	✓
1	Power Supply (Centralized)	Supplied by Div 26/28	-	By Others	✓
Package/Kit:		1ea - Auto Door Bottom STC4131_PK x (Door Width)			
		1ea - Gasketing S44__ x (Door Perimeter)			
		1ea - Gasketing S773__ x (Door Perimeter)			
1	Acoustic Seal Set - PemkoSTCset-1A (Surface - Wood or Metal Door)	1ea - Corner Pad ACP122	-	Pemko	✓

Note: Demountable supplier refer to hardware schedule for hardware requirements.

Note: CR to be located on meeting room side.

Electronic Elevation: E15

Mode of Operations:

Normal State: Locked on entry

Entry: User presents credential to Reader which releases door.

Egress: Free egress.

During loss of power: Door remains locked (Fail Secure)

Fire Alarm Connection: Not Required