

QEDES: A Local Proof-Audit Workstation for Undergraduate Mathematics

Dongwoo Lee

QEDesk project

<https://github.com/dev-heps/QEDesk>

Draft version: July 7, 2026

Abstract

QEDES is a local workstation for undergraduate mathematics that combines Lean 4, LaTeX, Python, OpenCode-style agent workflows, OpenRouter-compatible model calls, and model-context-protocol tooling. Its central design rule is that language models may audit, decompose, explain, and propose candidates, but Lean 4 remains the final verifier. The system is intended for students who write informal proofs in LaTeX and want structured feedback about missing justifications, quantifier mistakes, hidden hypotheses, set-membership errors, and statement drift before attempting a full formalization. This technical report describes the prototype architecture, the proof-audit data contracts, the blueprint-and-DAG workflow, and a budget-aware model-routing layer. We position QEDES as an educational proof-audit workstation rather than an autonomous theorem-proving benchmark system.

1 Introduction

Students often learn proof writing through a fragile loop: write an informal argument, receive delayed feedback, and then discover that a step described as “obvious” hides a missing hypothesis or a quantifier error. Large language models can give immediate feedback, but they can also smooth over precisely the logical gaps that the student needs to see. At the same time, theorem provers such as Lean 4 can certify formal proofs, but the jump from informal prose to fully formal proof scripts is steep for beginners.

QEDES is designed as a local bridge between these two modes. The student keeps a human-readable LaTeX notebook, writes or sketches Lean targets in a nearby file, and uses an assistant only as a proof auditor and candidate generator. The assistant is not allowed to declare success merely because a response sounds plausible. A mathematical claim is considered formally checked only after Lean 4 accepts it.

The project is deliberately modest. It is not a new theorem prover, not a replacement for Mathlib, and not a benchmark claim that one particular model is the best at mathematics. Its contribution is an engineering pattern for local, student-facing proof feedback: decompose first, audit locally, formalize one node at a time, and use the prover as the authority.

This report makes three concrete contributions:

1. a proof-audit protocol that classifies local gaps in informal undergraduate proofs before asking for Lean tactics;
2. an artifact structure that connects LaTeX notes, Lean declarations, Lean Blueprint pages, and a QEDesk-specific dependency sidecar; and

3. a budget-aware model-routing policy that records cost and treats model output as advisory until Lean verifies the relevant formal target.

2 Background and Related Work

Lean and Mathlib. Lean 4 is both a theorem prover and a programming language with an extensible elaborator, tactic framework, and editor-facing language server [1]. Mathlib provides the large mathematical library on which many Lean developments depend, together with a community process for maintaining formalized mathematics at scale [2]. QEDESKE builds on this ecosystem rather than replacing it: Lean provides the formal kernel and Mathlib supplies the mathematical vocabulary.

Open theorem-proving environments. Recent systems such as LeanDojo expose Lean programmatically for data extraction, premise selection, environment interaction, and reproducible machine-learning experiments [4]. REAL-Prover is another retrieval-augmented Lean 4 prover that focuses on stepwise theorem proving and college-level mathematical reasoning benchmarks [5]. These systems motivate the use of retrieval, local proof states, and iterative Lean feedback. QEDESKE differs in emphasis: it targets a study workstation whose default task is to audit a student’s informal reasoning, not to maximize Pass@ k on a prover benchmark.

Education-oriented Lean interfaces. Verbose Lean uses controlled natural language and custom Lean tooling to help undergraduate students transfer proof-assistant work back to traditional paper proofs [6]. QEDESKE shares this pedagogical concern but keeps the student’s primary artifact as LaTeX prose. Rather than replacing proof writing with a controlled language, it audits the prose, records a blueprint, and asks Lean to check only stable local targets.

Blueprints, automation, and budgeted model use. Lean Blueprint provides a way to organize formalization projects around definitions, lemmas, theorem statements, and dependency graphs [3]. Automated tactics such as Aesop show how bounded proof search can be useful when it remains inside Lean’s checking discipline [7]. On the model side, cascade-style approaches such as FrugalGPT motivate routing routine calls to cheaper models and reserving expensive calls for harder cases [8]. QEDESKE combines these ideas in a student-facing workflow: graph first, local proof state second, model hint third, and Lean verification last.

3 Design Requirements

QEDESKE follows four design requirements.

1. **Local first.** The workstation keeps the student’s LaTeX notes, Lean files, generated graphs, and cost ledger in the project directory or in explicitly disposable local build outputs.
2. **Verifier first.** The assistant can propose a repair, a lemma, or a tactic family, but Lean 4 is the only component allowed to verify a formal proof.
3. **Pedagogical hints before solutions.** The default response is a local hint or gap classification, not a polished complete proof.
4. **Replaceable models.** Model names and prices are configuration details. The workflow should continue to make sense when the cheap model, strong model, or provider changes.

4 Architecture

The workstation separates retrieval, proof-state communication, formal verification, and language-model reasoning. Table 1 summarizes the boundary between components.

Component	Responsibility	Non-responsibility
RAG/search	Retrieve definitions, lemmas, notes, examples	Decide correctness
MCP	Expose current Lean goals and diagnostics	Store global knowledge
Lean 4	Check formal statements and proof candidates	Teach prose style
Language model	Audit, decompose, explain, propose	Certify proofs
LaTeX	Preserve the student’s notebook	Serve as formal truth

Table 1: QEDesk component boundaries.

The intended loop is local rather than monolithic:

```

LaTeX proof note
-> local proof audit
-> blueprint DAG
-> one Lean statement or lemma
-> Lean check through Lake or MCP
-> repair hint
-> updated student note

```

This loop avoids sending the entire project, entire chat transcript, or full Mathlib context to a model on every request. It also avoids asking a model to produce a complete proof script before the statement and local dependencies are stable.

5 Proof-Audit Protocol

The proof-audit protocol begins by naming the assumptions, variables, quantifiers, and exact goal. The proof is then split into local inference steps. Each nontrivial step is marked as one of:

- `verified`;
- `missing-justification`;
- `false`;
- `unclear`.

For implementation, QEDesk uses a fixed gap taxonomy:

quantifier-jump	missing-hypothesis	missing-justification
false-inference	undefined-symbol	ambiguous-expression
set-membership-gap	calculation-gap	visual-dependence
statement-drift	unspecified	

Hint levels range from level 0, which only highlights the suspicious span, to level 4, which may include a Lean candidate patch. Level 4 output remains a candidate until Lean checks it.

The protocol is intentionally resistant to compressed answers. Phrases such as “clearly” or “trivially” are treated as insufficient unless they are backed by a named definition, theorem, calculation, or Lean-checkable argument.

6 Blueprint and DAG Workflow

For nontrivial exercises, QEDesk first builds a small blueprint. A blueprint contains definitions, local lemmas, the final theorem, and dependency edges. Each node may have an informal statement, an optional Lean declaration name, a status, and gap metadata. In the current prototype, the editable source of this graph is the student’s LaTeX file, using comments that do not affect PDF rendering:

```
% QEDesk[node=mem_power_set][kind=lemma]
% QEDesk[uses=def_power_set]
```

The command-line synchronizer reads these comments and the Lean declarations, then generates three disposable artifacts:

- Lean Blueprint source under `blueprint/src/content.tex`;
- a machine-readable sidecar at `build/qedesk-dag.json`;
- a Mermaid dependency graph at `build/qedesk-dag.mmd`.

The web view is generated by Lean Blueprint. QEDesk adds only a small view switching layer around the generated pages, while treating the upstream Blueprint renderer as the graph and document viewer.

7 Token-Aware Model Routing

QEDesk treats model calls as a budgeted resource. The default cascade is a cheap worker, then a stronger planner, then a deeper critic. In the current configuration these roles are mapped to OpenRouter-compatible DeepSeek model identifiers, but the architecture is not tied to those names.

Stage	Primary role	Escalation role	Context sent
Audit	cheap worker	strong planner	local node and snippet
Blueprint	cheap worker	strong planner	node plus parents
Formalize	cheap worker	strong planner	statement skeleton
Repair	cheap worker	critic	Lean error excerpt
Verify	Lean server	none	formal file

Table 2: Budget-aware routing policy.

The router prototype supports dry runs, real OpenRouter calls, and a SQLite cost ledger. It logs the worksheet id, node id, stage, model name, prompt and completion token counts, estimated cost, elapsed time, outcome, and Lean status. Its output is advisory JSON; it is not proof verification.

8 Implementation

The repository is organized around a small set of files:

```
src/main.tex student-facing LaTeX note
src/Proof.lean Lean statements and proofs
AGENTS.md assistant behavior rules
docs/ARCHITECTURE.md system design
```

```
docs/DATA_CONTRACTS.md gap labels and DAG contracts
tools/qeddesk_sync.py LaTeX/Lean/Blueprint synchronizer
tools/qeddesk_router.py OpenRouter routing prototype
bin/qeddesk command-line wrapper
```

The common local workflow is:

```
./bin/qeddesk audit --dry-run --max-nodes 1 src/main.tex
./bin/qeddesk sync
./bin/qeddesk lean
./bin/qeddesk pdf
./bin/qeddesk blueprint
```

The Docker-based workstation can provide Lean 4, Lake, LaTeX, Python, `lean-lsp-mcp`, Lean Blueprint, and related tools in one environment. For source-only review, the repository can also be cloned and inspected without running the container. This distinction is important for distribution: generated artifacts, cost ledgers, local API keys, Lean build products, and Docker images are not part of the source archive.

9 Current Status and Evaluation Plan

QEDesk is currently a prototype artifact. The implemented parts are the source layout, command wrappers, documentation, proof-audit contracts, Lean Blueprint synchronization, Mermaid sidecar generation, and a conservative OpenRouter routing prototype. The system does not yet include a controlled user study, a large benchmark evaluation, or learned routing thresholds.

For a tool paper of this kind, the relevant near-term evaluation is not a single theorem-proving score. We instead track four artifact-level questions:

1. **Faithfulness.** Does the Lean statement still match the student’s informal claim, or has statement drift occurred?
2. **Locality.** Does the assistant repair the failing node rather than rewriting the whole proof?
3. **Verification.** Does every claimed formal success correspond to a successful Lean check?
4. **Cost.** How many model tokens and retries are spent per useful proof-audit iteration?

Future quantitative evaluation should therefore report cost per checked node, number of repaired local gaps, statement-drift incidents, and Lean-verified successes. Until such an evaluation exists, QEDesk should be read as a reproducible workflow proposal and open-source prototype rather than as a state-of-the-art prover.

10 Example Use

Consider a typical set-theoretic statement about a function $f : A \rightarrow B$ and a subset $B_1 \subseteq B$:

$$f(f^{-1}(B_1)) \subseteq B_1.$$

A compressed informal proof may jump from $b \in f(f^{-1}(B_1))$ to $b \in B_1$ without expanding the definition of image and preimage. QEDesk should not immediately write the finished solution. Instead, it should expose the local obligation:

If $b \in f(f^{-1}(B_1))$, then there exists an a such that $a \in f^{-1}(B_1)$ and $f(a) = b$. To conclude $b \in B_1$, expand the definition of preimage to obtain $f(a) \in B_1$, then rewrite using $f(a) = b$.

At a higher hint level, the corresponding Lean node can be attempted and checked. If Lean rejects the candidate, the repair prompt should include only the local goal state or concise error excerpt, not the full worksheet.

11 Limitations

The current prototype is not a complete autonomous proof agent. Several parts are intentionally conservative:

- The synchronizer relies on explicit comments rather than unrestricted natural-language parsing.
- Router output is structured advice, not formal evidence.
- MCP integration depends on the editor and client environment.
- The system does not claim benchmark-level theorem-proving performance.
- Cost estimates depend on provider prices and must be refreshed.

These limitations are acceptable for the intended educational use case. The goal is to make logical gaps visible and to keep the student close to the verification loop, not to hide the work behind an automatic final answer.

12 Artifact Availability and Reproducibility

The project is released as open-source software under the MIT license:

<https://github.com/dev-heps/QEDesk>

The repository includes setup instructions, command wrappers, data contracts, and documentation for the proof-audit workflow. API keys, local cost ledgers, intermediate LaTeX build products, Lean build products, and Docker images are excluded from version control. The compiled draft of this report is checked in as a convenience artifact.

The intended source-level reproduction path is:

```
git clone https://github.com/dev-heps/QEDesk
cd QEDesk
./bin/qedesk audit --dry-run --max-nodes 1 src/main.tex
```

The optional full workstation path additionally starts the container and builds Lean and LaTeX artifacts:

```
./bin/qedesk start
./bin/qedesk prepare
./bin/qedesk lean
./bin/qedesk pdf
./bin/qedesk blueprint
```

Real model calls require a user-provided OpenRouter key in a local `.env` file. This key is deliberately not part of the archived source.

13 Conclusion

QEDesk frames AI-assisted mathematics as a disciplined verification loop. The student writes informal mathematics, the model audits and proposes local next steps, the blueprint records dependencies, and Lean 4 decides which formal candidates actually pass. This architecture shifts the engineering focus away from finding a single perfect model and toward building a workflow that remains useful as models, prices, and theorem-proving tools change.

References

- [1] Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*, 2021.
- [2] The mathlib community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs*, 2020.
- [3] Patrick Massot. Lean Blueprint. <https://github.com/PatrickMassot/leanblueprint>.
- [4] Kaiyu Yang, Aidan M. Swope, Alex Gu, Rahul Chalamala, Peiyang Song, Shixing Yu, Saad Godil, Ryan Prenger, and Anima Anandkumar. LeanDojo: Theorem proving with retrieval-augmented language models. *arXiv:2306.15626*, 2023.
- [5] Ziju Shen, Naohao Huang, Fanyi Yang, Yutong Wang, Guoxiong Gao, Tianyi Xu, Jiedong Jiang, Wanyi He, Pu Yang, Mengzhou Sun, Haocheng Ju, Peihao Wu, Bryan Dai, and Bin Dong. REAL-Prover: Retrieval augmented Lean prover for mathematical reasoning. *arXiv:2505.20613*, 2025.
- [6] Patrick Massot. Teaching mathematics using Lean and controlled natural language. In *15th International Conference on Interactive Theorem Proving (ITP 2024)*, 2024.
- [7] Jannis Limperg and Asta Halkjær From. Aesop: White-box best-first proof search for Lean. In *Proceedings of the 12th ACM SIGPLAN International Conference on Certified Programs and Proofs*, 2023.
- [8] Lingjiao Chen, Matei Zaharia, and James Zou. FrugalGPT: How to use large language models while reducing cost and improving performance. *arXiv:2305.05176*, 2023.
- [9] Model Context Protocol. <https://modelcontextprotocol.io/>.
- [10] QEDesk contributors. QEDesk source repository. <https://github.com/dev-heps/QEDesk>.