

CASH HANDLING SOLUTIONS



LIDIX F10 / F11 – One pocket Piece Counter



Pockets	1 Stacker	
Counterfeit detection	UV, MG, IR (Option)	
Speed	1000, 1200,1500 notes/ min	
Hopper Capacity	300 sheets	
Stacker Capacity	200 sheets	
Power	AC 110~240V 50/60 Hz	
Power Consume	40W	
Dimensions	284(W) x 232(D) x 194(H) mm	
Weight	Approx5.5kg	
Mode	Co, Batch & ADD	

LIDIX CL-2 / One pocket Value counter





General Specification

SPEED

Countable Note Size **Hopper Capacity**

Stacker Capacity

INTERFACE

WEIGHT

DIMENSION (WXDXH)

DISPLAY

SENSORS

Power **Power Consumption** – 2.5A, 60W

Piece Counting

Value Counting Serial No. Printing 1,500 notes/min

1,200 / 1,000 / 800 notes/min

800 notes/min

Max. 182 x 95 mm, Min. 100 x60 mm

Max. 500 notes

Max. 250 notes

SD Card, LAN, RS232C

Appx. 6kg

270mm x 232mm x 226mm

4.3" Color Touch LCD

Dual CIS, Ultrasonic, IR, UV, MG

AC 100~240V 50/60 Hz

Option

Serial No. Recognition & OCR

30 Currencies adoptable

AUTO & Multi Currency

TITO Scanning System

LAN

LCD Customer Display

Printer

LIDIX ML-2FS / 2VS – 2pocket Counter



Items	Description		
Image Scan	Cheque, Banknote, TITO, etc		
	Value Counting	1500 notes/min	
Speed	Dual Serial Number OCR	1200 notes/min	
	Fitness Sorting (ML-2FS)	1200 notes/mir	
Note Capacities St	Hopper Capacity	500 notes	
	Stacker Capacity	250 notes	
	Reject Capacity	100 notes	
Operating Mode	ML-2VS: Piece Counting, Value Counting, Denomination & Face & Orientation Sorting ML-2FS: Fitness Sorting		
Interface & Software Upgarde	LAN, SD Card, USB, RS232	2C	

VS – Value counter / FS – FITNESS counter

LIDIX SL-250 / 3 pocket Counter / Sorter



SPECIFICATION Value counting 1500 notes/min 1200 notes/min Fitness Sorting Speed Dual Serial Number Recog 1200 notes/min Countable Size of Notes Max. 90 x 183mm Min. 60 x 110mm 500 notes for Hopper Note Capacities 200 notes for Stacker 1 & Stacker 2 50~100 notes for Reject Piece Counting, Value Counting, Denomination Sorting, Face & Operating Mode Orientation Sorting, Fitness Sorting, TITO Scan Software Upgrade Off - line: USB, SD card On - line: Ethernet LAN, USB, SD card, RS232C Interface Multi Currencies processing Up to 50 Currencies (Auto Currency Function is available) Electrical Spec. AC 110- 240V, 50/60 Hz 15 kg 300(W) x 392(D) x 298(H) mm Weight Dimension 1) 5" Full Color LCD Touch Screen 2) Parallel Operation (Dual User) Etc. 3) 3 Second Booting System 1) Serial Number Printing, OCR, & TITO Scan 2) Additional '5' Full Color LCD Touch Screen – Left & Right Options 3) LCD Customer Display 4) Thermal Printer 5) LCMS Package (LIDIX Cash Management System)

LIDIX GL Series Sorters





Specifications | GL-Series

ltems		GL-Series				
		Expanded up to GL-13 (12+1)				
		GL-4	GL-5	GL-6	GL-7	GL-9
Number of Pocket		3+1	4+1	5 +1 (4+2)	6+1	8+1
Dimension		652 × 350 × 415	789 × 350 × 415	926 × 350 × 415	1063 × 350 × 415	1337 × 350 × 415
Weight(Kg)		33	38	42	46	54
Display		10" Full Color LCD Touch Screen				
Acceptable	Shorter Edge	60 ~ 90 (mm)				
Banknote Size	Longer Edge	100 ~ 183 (mm)				
Pocket Capacity	Hopper Capacity	1000 notes				
	Stacker Pocket	500 notes				
	Reject Pocket	500 notes				
Counting Speed	Fitness Mode	1,000				
(notes/min)	Count/Value/Sort Mode	1,200				
Multi Currency Processing		Available up to 60 Currencies				
S/N Reading		OCR & Image of Recognition for Serial No.				
Optional Scan		TITO Scan & Cheque & Voucher				
Fitness Parameter		Soil, Tape, Tear, Dog-ear, Deink, Corner, Multi, Stain, Graffiti, Stamp				
Multi Sensors		UV Dual CIS, UV, FL, MG, IR, Ultrasonic				
Power Source	Rated Power Source	AC100~240V ~ (Free Voltage), 50~60Hz				
Interface		LAN & SD Card & Serial Port				
Accessories		LCD Customer Display & Printer				

LIDIX GL Series — Scalable Stackers GL-5 / GL-6 / GL-7 / GL-9/GL-13







Currency Auto Binder –B1

All in one type(2Pocket value counting + Auto binding)



Specification

ltems	Description			
	Value Counting	5 bundle/min		
Speed	Fitness Sorting	Option		
	Dual Serial Number Recog.	Option		
Operating Mode	Binding Mode A- Standard Binding. Binding Mode B- Face for 1st and100th notes) Binding Mode C- Face/Orient for 1st and100th notes)			
Software Upgrade	RS-232C			
Interface	RS-232C			
Multi Currency Processing	Max 6 Currencies			
Electrical Spec.	AC110~240V 50/60H			
Dimension	410(W) x 388(W) x 572(W)			
Specification	Counterfeit Detection: UV, MG, MT, IR Color TFT LCD Display (3.2\")			
Options	External LCD Bending Position-1/2, 1/3 Bending Wide- 30mm.			

Pursuing Progress

