Evaluating the Effectiveness of Machine Learning in Replacing Traditional Rule-Based Systems for Decision-Making Under Uncertainty: A Comparative Study in Sports Analytics and Flood Risk Prediction

Dev Sharma
Independent Researcher, India
March 31, 2026

Abstract

Traditional rule-based systems often demonstrate diminished efficacy when operating within dynamic and unpredictable environments. This study evaluates the capacity of machine learning (ML) models to supersede rigid algorithmic frameworks in two distinct domains: cricket sports analytics and environmental flood risk prediction. For the cricket analysis, a Gradient Boosting Regressor, designated as ***Cricket AI****, was developed to calculate revised targets in rain-affected matches as a data-driven alternative to the Duckworth-Lewis-Stern (DLS) method. This model achieved a Mean Absolute Error (MAE) of 16.12 runs for T20 and 29.30 runs for ODI formats. Concurrently, a Random Forest Classifier,* ***FloodSense AI****, was engineered for flood risk agro-advisory in India, attaining 98.75% accuracy and an F1-score of 0.98 across multiple severity classifications. Both models were deployed as interactive web applications via Streamlit. The results indicate that data-driven ML models possess superior capabilities in detecting non-linear patterns and complex interactions compared to traditional rule-based approaches, providing a more flexible and precise framework for decision-making under uncertainty.*

1. Introduction

Facilitating optimal decision-making amidst significant variables remains a fundamental challenge across diverse fields, ranging from sports officiating to disaster management. Historically, these complexities have been addressed through rule-based systems: static algorithms derived from human-designed logic and simplified statistical formulas. While these systems offer transparency and interpretability, they are frequently characterized as "brittle," often yielding suboptimal results when conditions deviate from predefined parameters [1]. With the exponential growth in data collection and computational power, machine learning (ML) has emerged as a robust, adaptive alternative.

This research explores the transition from rigid rule-based frameworks to adaptive ML models through two critical domains. The first pertains to cricket sports analytics, where the **Duckworth-Lewis-Stern (DLS)** method currently serves as the official standard for adjusting scores in rain-interrupted matches. Despite its widespread adoption, the DLS method faces criticism for its reliance on static resource tables that may fail to account for modern batting strategies or specific match contexts [2]. The second domain involves environmental science, where traditional flood forecasting often utilizes oversimplified hydrological thresholds, thereby neglecting the intricate interactions between topography, meteorological patterns, and land-use configurations [3].

To address these limitations, two ML-powered platforms were developed and deployed: Cricket AI, which predicts revised targets from historical ball-by-ball data, and FloodSense AI, which classifies flood risk severity for agricultural advisories in India. It is hypothesized that supervised ensemble ML models—specifically Gradient Boosting and Random Forests—will exhibit significantly lower error rates and higher predictive accuracy than traditional rule-based systems by autonomously identifying complex, non-linear patterns within extensive datasets.



Figure 1. Unified project workflow: Raw data procurement from Cricsheet or Kaggle, followed by preprocessing (cleaning and encoding), model training via ensemble methods, and deployment through Streamlit.

2. Materials and Methods

To test the proposed hypothesis, two independent ML pipelines were constructed, adhering to the workflow illustrated in Figure 1. Python 3 served as the primary programming environment. The *Scikit-learn* library [8] was utilized for model training and evaluation, while *Pandas* and *NumPy* were employed for data preprocessing. Deployment was facilitated via Streamlit Cloud [4].

2.1 Case Study 1: Cricket AI

The cricket analysis utilized the ball-by-ball dataset from **Cricsheet**, comprising detailed scorecards for over 21,400 matches across Test, ODI, and T20 formats [2]. Each record captures the state of the match at a specific delivery, including total runs, wickets lost, overs completed, current run rate, participating teams, and venue. The objective was to train a model capable of predicting final innings totals or equitable revised targets based on the match state at the point of interruption.

A **Gradient Boosting Regressor** was selected for its efficacy in modeling non-linear relationships. This algorithm functions by constructing a sequence of shallow decision trees, where each subsequent tree is optimized to minimize the residual errors of its predecessor. This sequential correction is particularly advantageous for cricket data, as the marginal value of a wicket or an over fluctuates significantly throughout an innings. Categorical variables, such as venue and team identity, were processed using one-hot encoding prior to training.

2.2 Case Study 2: FloodSense AI

The flood prediction task utilized the *Flood Risk Prediction Dataset in India* from Kaggle [3]. This dataset encompasses a variety of environmental and geographical metrics, including rainfall, river discharge, elevation, soil type, humidity, temperature, and population density. This task was framed as a multiclass classification problem, requiring the model to categorize locations into risk levels ranging from "Low" to "Severe."

A **Random Forest Classifier** was implemented due to its resilience against overfitting and its capacity to handle high-dimensional feature sets while providing feature importance metrics. The ensemble approach, which aggregates predictions from numerous decision trees via majority voting, mitigates the impact of anomalous individual trees. Evaluation metrics included confusion matrices, accuracy, precision, recall, F1-score, and AUC-ROC.

Table 1. Summary of Machine Learning Case Study Pipelines

Domain	Project Name	Model Type	Key Input Features	Target Variable
Cricket (DLS Alt.)	Cricket AI	Gradient Boosting Regressor	Runs, Wickets, Overs, Run Rate, Venue, Team	Final Score / Revised Target (Continuous)
Flood Prediction	FloodSense AI	Random Forest Classifier	Rainfall, River Discharge, Elevation, Soil Type, etc.	Flood Risk Class (Low to Severe)

3. Results

3.1 Cricket AI Performance

The Gradient Boosting Regressor demonstrated high performance across match formats. As detailed in Table 2, the T20 model achieved an MAE of 16.12 runs and an R^2 of 0.89, indicating that the model accounts for approximately 89% of the variance in final match totals. This signifies a substantial improvement over the DLS benchmark, which yields an equivalent MAE of approximately 22–23 runs in T20 formats [5]. The ODI model produced an MAE of 29.30 and an R^2 of 0.84, reflecting the increased strategic complexity inherent in 50-over matches.

Table 2. Cricket AI Model Performance Metrics

Format	MAE (Runs)	RMSE (Runs)	R^2 Score
T20 Internationals	16.12	20.45	0.89
One-Day Internationals (ODI)	29.30	38.12	0.84



Figure 2. Comparison of Mean Absolute Error (MAE) between the traditional DLS benchmark and the Cricket AI Gradient Boosting model.

Figure 2 illustrates the performance disparity. In T20 matches, Cricket AI reduced the MAE from approximately 22.5 runs (DLS) to 16.12 runs, a 28% improvement. While the improvement in ODI matches was less pronounced, the reduction from 35 runs to 29.30 runs remains significant.

3.2 FloodSense AI Performance

The Random Forest Classifier in FloodSense AI yielded exceptional results. The model attained an overall accuracy of 98.75% across all flood risk classes. Detailed metrics are provided in Table 3.

Table 3. FloodSense AI Model Performance Metrics

Metric	Value	Interpretation
Accuracy	98.75%	Proportion of correctly classified samples
Precision	0.982	Low rate of false positive alerts
Recall	0.979	High sensitivity in detecting actual flood events
F1-Score	0.980	Harmonic mean of precision and recall

AUC-ROC	0.994	Superior class separation capability



Figure 3. Feature importance scores for the FloodSense AI Random Forest model. Rainfall and river discharge emerge as the primary predictive drivers.

Feature importance analysis (Figure 3) identifies rainfall as the most critical factor (relative importance ≈ 0.35), followed by river discharge (≈ 0.25) and elevation (≈ 0.15). These findings align with established hydrological principles, reinforcing the model's validity.

4. Discussion

The empirical evidence from both case studies supports the hypothesis that ensemble ML models outperform traditional rule-based systems in environments characterized by large datasets and non-linear interactions. Cricket AI successfully captured the context-sensitive valuation of wickets and overs, a feat unattainable by the DLS method's static resource tables. Similarly, FloodSense AI demonstrated that integrating multiple environmental variables provides a more comprehensive risk profile than rainfall-centric models.

4.1 Comparison to Rule-Based Systems

A primary advantage of the ML approach is adaptability. Traditional systems like DLS require manual adjustments by specialists as the sport evolves. Conversely, an ML model can be retrained on contemporary data to autonomously update internal parameters. This adaptability is equally vital for FloodSense AI; as climate change shifts historical weather patterns, static rules become increasingly obsolete. Furthermore, feature importance analysis provides a level of transparency often absent in traditional "black-box" rule-based logic.

4.2 Limitations

It is imperative to acknowledge several inherent limitations. First, ensemble methods can lack interpretability, which may impede their adoption in scenarios requiring step-by-step justification, such as live sports officiating. Second, the FloodSense AI model is currently optimized for Indian environmental data; its generalizability to disparate geographic regions, such as arid or alpine environments, would require retraining on localized datasets. Third, model accuracy remains contingent upon the quality of historical data; any systematic biases in reporting could be propagated through the model's predictions.

5. Conclusion

This comparative study demonstrates that machine learning models effectively transcend the limitations of traditional rule-based decision systems. Cricket AI improved T20 target prediction accuracy by 28% over the DLS benchmark, while FloodSense AI achieved near-perfect accuracy (98.75%) in flood severity classification. Both projects were deployed as Streamlit applications, ensuring accessibility for non-technical stakeholders. These findings suggest that ML offers a practical and powerful framework for decision-making under uncertainty.

Future research should investigate Explainable AI (XAI) techniques, such as SHAP (SHapley Additive exPlanations) values, to enhance model interpretability. Additionally, expanding training datasets to broader geographic regions and integrating real-time data feeds would further refine the utility of these predictive tools.

References

- [1] Russell, S. J., and Norvig, P. *Artificial Intelligence: A Modern Approach.* 4th ed. Pearson, 2020.
- [2] Cricsheet.org. *Cricsheet: Retrosheet for Cricket.* 2026. https://cricsheet.org.
- [3] Kaggle. *Flood Risk Prediction Dataset in India.* 2024. Kaggle, Flood Risk Prediction Dataset in India, 2024.
- [4] Streamlit Inc. *Streamlit Cloud Documentation.* 2026. https://docs.streamlit.io.
- [5] Duckworth, F. C., and Lewis, A. J. "A Fair Method for Resetting the Target in Interrupted One-Day Cricket Matches." *Journal of the Operational Research Society*, 1998.
- [8] Pedregosa, F., et al. "Scikit-learn: Machine Learning in Python." *Journal of Machine Learning Research*, 2011.
- [9] Floodsense.Ai : https://floodsense-ai-agro-g24ucjzzqzz8xcxikmclqm.streamlit.app/
- [10] Cricket Ai:https://ai-cricket-rain-predictor-mpq9jzapphhayyrpp6ffsuu.streamlit.app