

Experiment - 10

Student Name: Sumir Malhotra
Branch: CSE - AIML
Semester: 5
Subject Name: ADBMS

UID: 24BAI70227
Section/Group: 24AIT_KRG-1_A
Date of Performance: 21/9/26
Subject Code: 24CSP-310

(A)

Design a robust PostgreSQL transaction system for the students table where multiple student records are inserted in a single transaction.

If any insert fails due to invalid data, only that insert should be rolled back while preserving the previous successful inserts using savepoints.

The system should provide clear messages for both successful and failed insertions, ensuring data integrity and controlled error handling.

Solution:

```
CREATE OR REPLACE PROCEDURE insert_students()  
LANGUAGE PLPGSQL  
AS$$  
BEGIN
```

```
--Insert 1  
BEGIN
```

```
    INSERT INTO students(name, age, class)  
    VALUES ('Anisha', 16, 8);
```

```
    RAISE NOTICE 'Anisha inserted successfully';
```

```
EXCEPTION WHEN OTHERS THEN
```

```
    RAISE NOTICE 'Anisha insertion failed. Rolled back.';  
END;
```

```
--Insert 2  
BEGIN
```

```
INSERT INTO students(name, age, class)
VALUES ('Neha', 17, 8);
```

```
RAISE NOTICE 'Neha inserted successfully';
```

```
EXCEPTION WHEN OTHERS THEN
```

```
    RAISE NOTICE 'Neha insertion failed. Rolled back.';
END;
```

```
--Insert 3 - INVALID
```

```
BEGIN
```

```
    INSERT INTO students(name, age, class)
    VALUES ('Anisha', 19, 9);
```

```
    RAISE NOTICE 'Anisha inserted successfully';
```

```
EXCEPTION WHEN OTHERS THEN
```

```
    RAISE NOTICE 'Anisha insertion failed. Only this insertion was rolled back.';
END;
```

```
--Insert 4
```

```
BEGIN
```

```
    INSERT INTO students(name, age, class)
    VALUES ('Mayank', 19, 9);
```

```
    RAISE NOTICE 'Mayank inserted successfully';
```

```
EXCEPTION WHEN OTHERS THEN
```

```
    RAISE NOTICE 'Mayank insertion failed. Rolled back.';
END;
```

```
RAISE NOTICE 'Transaction Successfully Done';
```

```
END;
```

```
$$;
```

```
BEGIN;  
  
CALL insert_students();  
  
COMMIT;  
  
SELECT * FROM students;
```