

FarmOS Frontend API Guide

Tati FarmOS development backend · Django Ninja

This guide is for frontend engineers. Every endpoint lists what you send (URL pieces, query string, JSON body) and an example JSON response. Field names match the live OpenAPI schema generated from the code.

How to call the API

Base URL Local development Docker: `http://127.0.0.1:8002`. All routes below are prefixed with `/api`.

Docs Interactive Swagger UI: `/api/docs`. Raw OpenAPI: `/api/openapi.json`.

Auth After `POST /api/auth/login` the server sets cookies named `{app}_access_token`, `{app}_refresh_token`, and `{app}_csrf_token`. `app` is `client` or `admin` depending on the request host. Send cookies on later requests. For unsafe methods, send header `X-CSRFToken` matching the CSRF cookie.

JSON Most bodies are `application/json`. A few `animal-create` routes use `multipart/form-data` so you can attach an image. Dates are `YYYY-MM-DD`. Datetimes are `ISO-8601`. Money examples use `NGN`.

Permissions Most farm endpoints load the current user from the access cookie, resolve their organization, then check a permission code (for example `add_animal_details`) optionally scoped to that farm. Missing permission returns `HTTP 403` with the envelope below.

Standard success envelope

```
{
  "success": true,
  "message": "Human-readable summary",
  "data": {}
}
```

Standard paginated list

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

Typical errors

```
{
  "success": false,
  "message": "Permission denied",
  "data": null
}
```

Login failure uses a smaller shape: {"status": "Error", "message": "Invalid credentials"}. Some OTP failures return {"detail": "..."}.

v1 vs v2: older animal/farm/dashboard routes use species_id, breed_id, and unit_id. v2/v3 routes use livestock master data: livestock_species_id, livestock_breed_id, housing_unit_id. Prefer v2/v3 for new clients.

Frontend integration sequence

1. Create an account with POST /api/auth/new-account, then verify the emailed OTP with POST /api/auth/email-validate.
2. Log in with POST /api/auth/login and retain the HTTP-only auth cookies. Include credentials on every later authenticated request.
3. Create an organization with POST /api/organization/register/. Keep the returned organization UUID for organization-scoped requests.
4. Create a farm with POST /api/organization/farm/. A new is_primary: true farm automatically becomes the only primary farm in that organization.
5. Load scoped data with GET endpoints, passing the farm ID or organization ID requested by the endpoint.
6. For POST, PATCH, PUT, and DELETE calls, send X-CSRFToken using the CSRF cookie value. When the access cookie expires, call POST /api/auth/refresh-token; use POST /api/auth/signout to end the session.

Contents

1. Authentication (11 endpoints)
2. Admin panel (30 endpoints)
3. Contact (5 endpoints)
4. Global (5 endpoints)
5. Organization module (12 endpoints)
6. User and Role management (15 endpoints)
7. Farm (8 endpoints)
8. Animals (32 endpoints)
9. Production (3 endpoints)
10. Reproduction (20 endpoints)
11. Health (24 endpoints)
12. Feed (23 endpoints)
13. MovementRecords (15 endpoints)
14. Alerts (4 endpoints)
15. Dashboard (33 endpoints)
16. Finance (6 endpoints)
17. Pharmacy (9 endpoints)
18. Reports (14 endpoints)
19. Contract (2 endpoints)
20. Users (15 endpoints)
21. Organizations (5 endpoints)
22. Farms (8 endpoints)
23. Operations (19 endpoints)
24. Timeline (1 endpoints)
25. Notifications (4 endpoints)
26. Search (1 endpoints)

Authentication

POST /api/auth/new-account

Create Account

Registers a user with email + password. Sends a 6-digit OTP and sets an email cookie used by /email-validate.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.
password	string	yes	Account password. Must pass Django password validators.
confirm_password	string	yes	Must match password.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com",
  "password": "Str0ngPass!word",
  "confirm_password": "Str0ngPass!word"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Account created successfully"
}
```

POST /api/auth/email-validate

Email Validations

Confirms signup. Send the OTP. The email comes from the cookie set at registration, not from the body.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
otp	string	yes	6-digit one-time code sent to email.

EXAMPLE REQUEST BODY

```
{
  "otp": "123456"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Your email has been successfully verified.",
  "data": null
}
```

POST /api/auth/login

Login

Checks email and password. On success the JSON body is small; the real session is HTTP-only cookies (access, refresh, CSRF). Send those cookies on later calls.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.
password	string	yes	Account password. Must pass Django password validators.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com",
  "password": "Str0ngPass!word"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "status": "Success",
  "message": "Login successful",
  "is_admin": false
}
```

POST /api/auth/resend_otp

Resend Otp

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "The OTP has been resent to your email."
}
```

POST /api/auth/forgot-password

Forgot Password

Starts password reset. Sends an OTP to the email if the account exists.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "If that email exists, an OTP has been sent.",
  "data": null
}
```


POST /api/auth/verify-reset-otp

Verify Reset Otp

Checks the reset OTP. Response data.token is what you send to /reset-password.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.
otp	string	yes	6-digit one-time code sent to email.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com",
  "otp": "123456"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "OTP verified. Use the token to reset your password.",
  "data": {
    "token": "reset_token_from_verify_step"
  }
}
```

POST /api/auth/reset-password

Reset Password

Sets a new password using the token from verify-reset-otp. Does not take the OTP again.

Auth Public (no login cookie)

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
token	string	yes	Short-lived reset token returned after OTP verification.
new_password	string	yes	Replacement password.
confirm_password	string	yes	Must match password.

EXAMPLE REQUEST BODY

```
{
  "token": "reset_token_from_verify_step",
  "new_password": "Str0ngPass!word",
  "confirm_password": "Str0ngPass!word"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Password has been reset.",
  "data": null
}
```

POST /api/auth/refresh-token

Refresh Token

Uses the refresh cookie to issue a new access cookie. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Tokens rotated. New access cookie set.",
  "data": null
}
```

POST /api/auth/signout

Signout

Invalidates the refresh session and clears auth cookies.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Signed out.",
  "data": null
}
```

GET /api/auth/profile

Profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/auth/timezone

Timezone

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Admin panel

Platform master data: species, breeds, housing, lifecycle stages, weight ranges, permission seeding, and public contact/newsletter forms.

POST `/api/admin/species/`

Add Species

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/species/{page}/{page_size}

Get Species

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

PATCH /api/admin/species

Update Species

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
species_id	integer	yes	Legacy species ID (v1 endpoints).
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "species_id": 1,
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/breed/

Add Breed

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
species_id	integer	yes	Legacy species ID (v1 endpoints).
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "species_id": 1,
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/admin/breed/{page}/{page_size}

Get Breed

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

PATCH /api/admin/breed

Update Breed

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
breed_id	integer	yes	Legacy breed ID (v1 endpoints).
species_id	integer	no	Legacy species ID (v1 endpoints).
name	string	no	Name.

EXAMPLE REQUEST BODY

```
{
  "breed_id": 1,
  "species_id": 1,
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/unit-type/

Add Unit Type

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/unit-type/{page}/{page_size}

Get Get Unit Type

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

PATCH /api/admin/unit-type

Update Unit Type

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
unit_type_id	integer	yes	ID of the related unit type.
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "unit_type_id": 1,
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/seed-permissions/

Seed Permissions

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/admin/seed-nigeria-geo/

Seed Nigeria Geo

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/admin/seed-livestock-master/

Seed Livestock Master

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/livestock/species/

Get Livestock Species

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/admin/livestock/breeds/{species_id}/

Get Livestock Breeds

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


GET /api/admin/livestock/housing-unit-types/{species_id}/

Get Housing Unit Types

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/admin/livestock/housing-units/{farm_id}/

Get Farm Housing Units

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
species_id	integer	no	Legacy species ID (v1 endpoints).
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/admin/livestock/classifications/{species_id}/

Get Animal Classifications

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
sex	string	no	Sex.
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/admin/livestock/breeds/

Create Farm Breed

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
species_id	integer	yes	Legacy species ID (v1 endpoints).
name	string	yes	Name.
description	string	no	Description.
origin	string	no	Origin.

EXAMPLE REQUEST BODY

```
{
  "species_id": 1,
  "name": "Example name",
  "description": "Free-text notes",
  "origin": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

PATCH /api/admin/livestock/breeds/{breed_id}/

Update Farm Breed

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
breed_id	integer	Legacy breed ID (v1 endpoints).

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
description	string	no	Description.
origin	string	no	Origin.
is_active	boolean	no	Is active.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "description": "Free-text notes",
  "origin": "string",
  "is_active": true
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/livestock/housing-units/

Create Farm Housing Unit

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
capacity	integer	no	Capacity.
allowed_species_ids	array of integer	no	Allowed species ids.
location	string	no	Location.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "capacity": 1,
  "allowed_species_ids": [
    1
  ],
  "location": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

PATCH /api/admin/livestock/housing-unit/{unit_id}/

Update Farm Housing Unit

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
unit_id	integer	Legacy farm unit ID (v1 endpoints).

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
capacity	integer	no	Capacity.
allowed_species_ids	array of integer	no	Allowed species ids.
location	string	no	Location.
status	'active' 'inactive'	no	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "capacity": 1,
  "allowed_species_ids": [
    1
  ],
  "location": "string",
  "status": "active"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/lifecycle/seed/

Seed Lifecycle

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/lifecycle/stages/{species_id}/

Get Life Stages

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


GET /api/admin/lifecycle/animal/{animal_id}/

Get Animal Lifecycle

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

POST /api/admin/lifecycle/animal/{animal_id}/refresh/

Refresh Animal Lifecycle

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/admin/lifecycle/animal/{animal_id}/override/

Override Animal Lifecycle

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
stage	string	yes	Stage.
reason	string	yes	Reason.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/admin/weight-range/seed/

Seed Weight Range

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/admin/weight-range/

Create Farm Weight Range

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
species_id	integer	yes	Legacy species ID (v1 endpoints).
breed_id	integer	no	Legacy breed ID (v1 endpoints).
sex	string	no	Sex.
min_age_months	number	no	Min age months.
max_age_months	number	no	Max age months.
min_weight_kg	number	no	Min weight kg.
max_weight_kg	number	no	Max weight kg.
target_daily_gain_kg	number	no	Target daily gain kg.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/weight-range/{species_id}/

Get Weight Ranges

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/admin/weight-range/animal/{animal_id}/

Get Animal Weight Range

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

Contact

POST /api/admin/contact/enquiry/

Submit Contact Enquiry

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
full_name	string	yes	Full name.
farm_name	string	no	Farm name.
email	string (email)	yes	Account email. Used as the login username.
phone	string	no	Phone.
country	string	no	Country.
region	string	no	Region.
farm_type	'livestock' 'poultry' 'fishery' 'crop' 'mixed_farming' 'cooperative' 'government' 'ngo' 'other'	no	Allowed values: livestock, poultry, fishery, crop, mixed_farming, cooperative, government, ngo, other
farm_size	'small' 'medium' 'large' 'enterprise'	no	Allowed values: small, medium, large, enterprise
record_method	'paper' 'excel' 'existing_software' 'combination' 'other'	no	Allowed values: paper, excel, existing_software, combination, other
modules_of_interest	array of string	no	Modules of interest.
challenges	string	no	Challenges.
preferred_contact_method	'phone' 'email' 'whatsapp'	no	Allowed values: phone, email, whatsapp
consultation_date	string	no	Consultation date.

EXAMPLE REQUEST BODY

```
{
  "full_name": "Example name",
  "farm_name": "Example name",
  "email": "farmer@example.com",
  "phone": "08012345678",
  "country": "string",
  "region": "string",
  "farm_type": "livestock",
  "farm_size": "small",
  "record_method": "paper",
```

```
"modules_of_interest": [
  "string"
],
"challenges": "string",
"preferred_contact_method": "phone",
"consultation_date": "2026-03-15"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/admin/contact/enquiries/

List Contact Enquiries

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/admin/contact/enquiry/{enquiry_id}/

Get Contact Enquiry

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
enquiry_id	integer	ID of the related enquiry.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

PATCH /api/admin/contact/enquiry/{enquiry_id}/status/

Update Enquiry Status

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
enquiry_id	integer	ID of the related enquiry.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
status	'new' 'in_review' 'contacted' 'converted' 'closed'	yes	Record status filter or value.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "status": "new",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/admin/subscribe/

Newsletter Subscribe

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

Global

Shared lookup lists used across farms: unit types, group types, event types.

GET /api/global/unit-type/{page}/{page_size}

Get Get Unit Type

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/global/group-type/

Addgroup Type

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/global/group-type/{page}/{page_size}

Get Group Type

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


POST /api/global/event-type/

Event Type

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/global/event-type/{page}/{page_size}

Get Event Type

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

Organization module

Organizations and farms. A user belongs to an organization; farms belong to that organization.

GET `/api/organization/get-plan/`

Get Plan

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/organization/get-industry/

Get Industry

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/organization/get-countries/

Get Countries

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/organization/get-stateregion/{country_id}

Get State

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
country_id	integer	ID of the related country.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/organization/get-lga/{state_region_id}

Get Lga

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
state_region_id	integer	ID of the related state region.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/organization/organization/

Organisation

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
industry_id	integer	no	ID of the related industry.
country_id	integer	yes	ID of the related country.
state_region_id	integer	yes	ID of the related state region.
phone	string	no	Phone.
email	string (email)	no	Account email. Used as the login username.
address	string	no	Address.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "industry_id": 1,
  "country_id": 1,
  "state_region_id": 1,
  "phone": "08012345678",
  "email": "farmer@example.com",
  "address": "string",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/organization/organization/

Get Organization

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/organization/organization/logo/

Update Organization Logo

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

Input type multipart/form-data (form fields, not a JSON body). If an `image` field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
logo	string (binary)	yes	Logo.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "logo": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/organization/farm-type/

Farm Type

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/organization/farm/

Farm

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
client_request_id	string	no	ID of the related client request.
organization_id	string (uuid)	yes	UUID of the organization.
name	string	yes	Name.
country_id	integer	yes	ID of the related country.
state_region_id	integer	yes	ID of the related state region.
city	string	yes	City.
location_address	string	yes	Location address.
latitude	string	no	Latitude.
longitude	string	no	Longitude.
farm_type_id	integer	yes	ID of the related farm type.
is_primary	boolean	yes	Is primary.

EXAMPLE REQUEST BODY

```
{
  "client_request_id": "string",
  "organization_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "name": "Example name",
  "country_id": 1,
  "state_region_id": 1,
  "city": "string",
  "location_address": "string",
  "latitude": "string",
  "longitude": "string",
  "farm_type_id": 1,
  "is_primary": true
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/organization/farm/

Get Farm

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 1  
  }  
}
```

GET /api/organization/organization/dashboard/

Organization Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "totals": {
      "animals": 120,
      "active": 110,
      "sold": 6,
      "dead": 4
    },
    "trends": [
      {
        "period": "2026-03",
        "value": 18
      }
    ]
  }
}
```

User and Role management

Invite staff, assign roles, and attach permission codes. Roles can be scoped to a farm.

GET /api/role/permission/

Get Permission

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/role/role/

Role

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
description	string	no	Description.
web_access	boolean	no	Web access.
mobile_access	boolean	no	Mobile access.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "description": "Free-text notes",
  "web_access": true,
  "mobile_access": true,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/role/role/

Get Role

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

PATCH /api/role/role/

Update Role

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
active	boolean	no	Active.
web_access	boolean	no	Web access.
mobile_access	boolean	no	Mobile access.
client_request_id	string	no	ID of the related client request.
role_id	integer	yes	ID of the related role.
name	string	no	Name.
description	string	no	Description.

EXAMPLE REQUEST BODY

```
{
  "active": true,
  "web_access": true,
  "mobile_access": true,
  "client_request_id": "string",
  "role_id": 1,
  "name": "Example name",
  "description": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

DELETE /api/role/role/{role_id}

Delete Role

Removes or deactivates a record identified by the path.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
role_id	integer	ID of the related role.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": null
}
```

POST /api/role/user/

Add User

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/role/user/

Get User

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/role/new/user/activate/

Acitate User

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
email	string (email)	yes	Account email. Used as the login username.
otp	string	yes	6-digit one-time code sent to email.
password	string	yes	Account password. Must pass Django password validators.
confirm_password	string	yes	Must match password.

EXAMPLE REQUEST BODY

```
{
  "email": "farmer@example.com",
  "otp": "123456",
  "password": "Str0ngPass!word",
  "confirm_password": "Str0ngPass!word"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/role/new/user/activate/{email}

Resent Otp New User

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
email	string (email)	Account email. Used as the login username.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/role/user-role/

Assign User Role

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
client_request_id	string	no	ID of the related client request.
role_id	integer	yes	ID of the related role.
farm_id	integer	yes	Numeric ID of the farm this request applies to.
user_id	string (uuid)	yes	ID of the related user.

EXAMPLE REQUEST BODY

```
{
  "client_request_id": "string",
  "role_id": 1,
  "farm_id": 1,
  "user_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/role/user-role/

Get User Role

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

PATCH /api/role/user-role/{assignment_id}/

Update User Role

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
assignment_id	integer	ID of the related assignment.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
client_request_id	string	no	ID of the related client request.
farm_id	integer	no	Numeric ID of the farm this request applies to.
role_id	integer	no	ID of the related role.

EXAMPLE REQUEST BODY

```
{
  "client_request_id": "string",
  "farm_id": 1,
  "role_id": 1
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

DELETE /api/role/user-role/{assignment_id}/

Revoke User Role

Removes or deactivates a record identified by the path.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
assignment_id	integer	ID of the related assignment.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": null
}
```

POST /api/role/role-permission/

Assign Role Permission

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
client_request_id	string	no	ID of the related client request.
role_id	integer	yes	ID of the related role.
permission_ids	array of integer	yes	Permission ids.

EXAMPLE REQUEST BODY

```
{
  "client_request_id": "string",
  "role_id": 1,
  "permission_ids": [
    1
  ]
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/role/role-permission/

Get Role Permission

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Farm

Housing / farm units on a farm (v1 unit types and v2 housing units).

POST /api/farm/farm-unit/

Add Farm Unit

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
name	string	yes	Name.
unit_type_id	integer	yes	ID of the related unit type.
capacity	integer	yes	Capacity.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "name": "Example name",
  "unit_type_id": 1,
  "capacity": 1
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/farm/all-farm-unit/{page}/{page_size}

Get Farm Unit

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/farm/all-farm-unit-by-farm/{page}/{page_size}/{farm_id}

Get Farm Unit By Farm

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


POST /api/farm/farm-unit/v2/

Add Farm Unit V2

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
name	string	yes	Name.
capacity	integer	no	Capacity.
location	string	no	Location.
allowed_species_ids	array of integer	no	Allowed species ids.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "name": "Example name",
  "capacity": 1,
  "location": "string",
  "allowed_species_ids": [
    1
  ]
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

PATCH /api/farm/farm-unit/v2/{unit_id}

Update Farm Unit V2

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
unit_id	integer	Legacy farm unit ID (v1 endpoints).

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
capacity	integer	no	Capacity.
location	string	no	Location.
status	'active' 'inactive'	no	Record status filter or value.
allowed_species_ids	array of integer	no	Allowed species ids.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "capacity": 1,
  "location": "string",
  "status": "active",
  "allowed_species_ids": [
    1
  ]
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

GET /api/farm/all-farm-unit/v2/{page}/{page_size}

Get Farm Unit V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/farm/all-farm-unit-by-farm/v2/{page}/{page_size}/{farm_id}

Get Farm Unit By Farm V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/farm/all-farm-unit-by-species/v2/{page}/{page_size}/{farm_id}/{species_id}

Get Farm Unit By Species V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.
species_id	integer	Legacy species ID (v1 endpoints).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

Animals

Animal records, groups, weights, milk, images, growth, and acquisition costs. Prefer v2 endpoints for livestock master data (species/breed/housing).

POST /api/animals/animal/

New Animal

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

Input type multipart/form-data (form fields, not a JSON body). If an `image` field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
image	string (binary)	no	Image.
payload	AnimalsSchemaIn	yes	Payload.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "image": "string",
  "payload": {
    "status": "active",
    "gender": "male",
    "source": "born",
    "farm_id": 1,
    "unit_id": 1,
    "tag_id": "COW-001",
    "species_id": 1,
    "breed_id": 1,
    "dob": "2026-03-15",
    "estimated_age_months": 1,
    "mother_id": 1,
    "health_status": "healthy",
    "is_pregnant": true,
    "is_lactating": true,
    "is_quarantine": true,
    "is_active": true,
    "notes": "Free-text notes"
  }
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/animals/animal/{page}/{page_size}/{farm_id}

Get Animal

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
health_status	string	no	Health status.
gender	string	no	male or female.
source_type	string	no	How the animal entered the farm.
is_active	boolean	no	Is active.
species_id	integer	no	Legacy species ID (v1 endpoints).
breed_id	integer	no	Legacy breed ID (v1 endpoints).
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
```



```
"has_previous": false
}
```

GET /api/animals/animal-by-id/{animal_id}

Get Animal By Id

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

POST /api/animals/animal/image/{animal_id}

Update Animal Image

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

Input type multipart/form-data (form fields, not a JSON body). If an `image` field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
image	string (binary)	yes	Image.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "image": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

PATCH /api/animals/animal/{animal_id}/{farm_id}

Update Animal

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.
farm_id	integer	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
status	'active' 'pregnant' 'lactating' 'sick' 'quarantine' 'sold' 'dead'	no	Record status filter or value.
gender	'male' 'female'	no	male or female.
source	'born' 'purchased' 'imported'	no	How the animal entered the farm (born, purchased, imported, ...).
new_farm_id	integer	no	ID of the related new farm.
unit_id	integer	no	Legacy farm unit ID (v1 endpoints).
tag_id	string	no	Unique ear-tag / identifier for the animal.
species_id	integer	no	Legacy species ID (v1 endpoints).
breed_id	integer	no	Legacy breed ID (v1 endpoints).
dob	string (date)	no	Date of birth (YYYY-MM-DD).
estimated_age_months	integer	no	Use when exact DOB is unknown.
mother_id	integer	no	Dam animal ID. Required when source is born.
health_status	'healthy' 'sick' 'recovering' 'at_risk'	no	Allowed values: healthy, sick, recovering, at_risk
is_pregnant	boolean	no	Is pregnant.
is_lactating	boolean	no	Is lactating.
is_quarantine	boolean	no	Is quarantine.
is_active	boolean	no	Is active.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "status": "active",
  "gender": "male",
  "source": "born",
  "new_farm_id": 1,
  "unit_id": 1,
  "tag_id": "COW-001",
  "species_id": 1,
  "breed_id": 1,
  "dob": "2026-03-15",
  "estimated_age_months": 1,
  "mother_id": 1,
  "health_status": "healthy",
  "is_pregnant": true,
  "is_lactating": true,
  "is_quarantine": true,
  "is_active": true,
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/animals/animal-profile-attribute/{farm_id}

Animal Profile Attribute

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
animal_id	integer	yes	Numeric ID of the animal.
attribute_key	string	yes	Attribute key.
attribute_value	string	yes	Attribute value.

EXAMPLE REQUEST BODY

```
{
  "animal_id": 1,
  "attribute_key": "string",
  "attribute_value": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/animals/animal-profile-attribute/{page}/{page_size}/{animal_id}

Get Animal At Profile

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

DELETE /api/animals/animal-profile-attribute/delete/{animal_attribute_id}

Delete Animal At Proile

Removes or deactivates a record identified by the path.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_attribute_id	integer	ID of the related animal attribute.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": null
}
```

POST /api/animals/animal-group/

Animal Group

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
name	string	yes	Name.
group_type_id	integer	yes	ID of the related group type.
description	string	no	Description.
status	'ACTIVE' 'INACTIVE'	no	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "name": "Example name",
  "group_type_id": 1,
  "description": "Free-text notes",
  "status": "ACTIVE"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/animals/animal-group/{page}/{page_size}/{farm_id}

Get Animal Group

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

PATCH /api/animals/update-animal-group/{group_id}

Update Animal Group

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
group_id	integer	Numeric ID of the animal group.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
group_type_id	integer	no	ID of the related group type.
description	string	no	Description.
status	string	no	Record status filter or value.
farm_id	integer	no	Numeric ID of the farm this request applies to.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "group_type_id": 1,
  "description": "Free-text notes",
  "status": "active",
  "farm_id": 1
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/animals/animal-group-member/

Animal Group Member

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
group_id	integer	yes	Numeric ID of the animal group.
animal_id	integer	yes	Numeric ID of the animal.
status	'ACTIVE' 'REMOVED'	no	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "group_id": 1,
  "animal_id": 1,
  "status": "ACTIVE"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/animals/animal-group-member/{page}/{page_size}

Get Animal Group Member

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
group_id	integer	no	Numeric ID of the animal group.
animal_id	integer	no	Numeric ID of the animal.
status	'ACTIVE' 'REMOVED'	no	Record status filter or value.
joined_after	string (date-time)	no	Joined after.
joined_before	string (date-time)	no	Joined before.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

PATCH /api/animals/update-animal-group-member/{member_id}

Update Animal Group Member

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
member_id	integer	ID of the related member.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
group_id	integer	no	Numeric ID of the animal group.
animal_id	integer	no	Numeric ID of the animal.
status	'ACTIVE' 'REMOVED'	no	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "group_id": 1,
  "animal_id": 1,
  "status": "ACTIVE"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

GET /api/animals/animal-event/{page}/{page_size}/{farm_id}

Get Animal Event

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/animals/animal-weight/

Weight

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
weight	number	yes	Weight.
date	string (date)	yes	Date.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "weight": 10.5,
  "date": "2026-03-15"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/animals/animal-weight/{page}/{page_size}/{farm_id}

Get Animal Weight

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


GET /api/animals/animal-weight/animal/{animal_id}

Get Animal Weight By Animal

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

New Animal V2

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

Input type multipart/form-data (form fields, not a JSON body). If an image field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
status	'active' 'pregnant' 'lactating' 'sick' 'quarantine' 'sold' 'dead'	yes	Record status filter or value.
gender	'male' 'female'	yes	male or female.
source	'born' 'purchased' 'imported' 'transferred_in' 'donated' 'opening_record' 'other'	yes	How the animal entered the farm (born, purchased, imported, ...).
farm_id	integer	yes	Numeric ID of the farm this request applies to.
tag_id	string	yes	Unique ear-tag / identifier for the animal.
livestock_species_id	integer	yes	v2 species ID from livestock master data.
livestock_breed_id	integer	yes	v2 breed ID from livestock master data.
housing_unit_id	integer	yes	v2 housing unit ID on the farm.
dob	string (date)	no	Date of birth (YYYY-MM-DD).
estimated_age_months	integer	no	Use when exact DOB is unknown.
mother_id	integer	no	Dam animal ID. Required when source is born.
health_status	'healthy' 'sick' 'recovering' 'at_risk'	yes	Allowed values: healthy, sick, recovering, at_risk
is_pregnant	boolean	yes	Is pregnant.
is_lactating	boolean	yes	Is lactating.
is_quarantine	boolean	yes	Is quarantine.
is_active	boolean	yes	Is active.
notes	string	no	Notes.
image	string (binary)	no	Image.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "status": "active",
  "gender": "male",
  "source": "born",
  "farm_id": 1,
  "tag_id": "COW-001",
  "livestock_species_id": 1,
  "livestock_breed_id": 1,
  "housing_unit_id": 1,
  "dob": "2026-03-15",
  "estimated_age_months": 1,
  "mother_id": 1,
  "health_status": "healthy",
  "is_pregnant": true,
  "is_lactating": true,
  "is_quarantine": true,
  "is_active": true,
  "notes": "Free-text notes",
  "image": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "tag_id": "COW-001",
    "gender": "female",
    "species": "Cattle",
    "breed": "White Fulani",
    "housing_unit": "Pen A"
  }
}
```

POST /api/animals/animal/{animal_id}/acquisition/

Set Animal Acquisition

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
supplier	string	no	Supplier.
purchase_price	number	no	Purchase price.
currency	string	no	Currency.
payment_status	'paid' 'pending' 'partial'	no	Allowed values: paid, pending, partial
payment_method	string	no	Payment method.
transaction_reference	string	no	Transaction reference.
notes	string	no	Notes.
purchase_date	string (date)	no	Purchase date.
transportation_cost	number	no	Transportation cost.
veterinary_inspection_cost	number	no	Veterinary inspection cost.
other_acquisition_cost	number	no	Other acquisition cost.
country_of_origin	string	no	Country of origin.
import_date	string (date)	no	Import date.
shipping_cost	number	no	Shipping cost.
customs_clearance_cost	number	no	Customs clearance cost.
quarantine_cost	number	no	Quarantine cost.
veterinary_certification_cost	number	no	Veterinary certification cost.
insurance_cost	number	no	Insurance cost.
other_import_cost	number	no	Other import cost.

production_cost_dam_feeding	number	no	Production cost dam feeding.
production_cost_pregnancy_treatment	number	no	Production cost pregnancy treatment.
production_cost_delivery	number	no	Production cost delivery.
production_cost_breeding	number	no	Production cost breeding.
estimated_opening_value	number	no	Estimated opening value.
valuation_date	string (date)	no	Valuation date.
valuation_method	'market_comparison' 'book_value' 'professional_appraisal' 'owner_estimate'	no	Allowed values: market_comparison, book_value, professional_appraisal, owner_estimate
valuation_notes	string	no	Valuation notes.

EXAMPLE REQUEST BODY

```
{
  "supplier": "string",
  "purchase_price": 10.5,
  "currency": "NGN",
  "payment_status": "paid",
  "payment_method": "string",
  "transaction_reference": "string",
  "notes": "Free-text notes",
  "purchase_date": "2026-03-15",
  "transportation_cost": 10.5,
  "veterinary_inspection_cost": 10.5,
  "other_acquisition_cost": 10.5,
  "country_of_origin": "string",
  "import_date": "2026-03-15",
  "shipping_cost": 10.5,
  "customs_clearance_cost": 10.5,
  "quarantine_cost": 10.5,
  "veterinary_certification_cost": 10.5,
  "insurance_cost": 10.5,
  "other_import_cost": 10.5,
  "production_cost_dam_feeding": 10.5,
  "production_cost_pregnancy_treatment": 10.5,
  "production_cost_delivery": 10.5,
  "production_cost_breeding": 10.5,
  "estimated_opening_value": 10.5,
  "valuation_date": "2026-03-15",
  "valuation_method": "market_comparison",
  "valuation_notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
```

```
"message": "Request completed",  
"data": {  
  "id": 15  
}  
}
```

GET /api/animals/animal/v2/{page}/{page_size}/{farm_id}

Get Animal V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
health_status	string	no	Health status.
gender	string	no	male or female.
source	string	no	How the animal entered the farm (born, purchased, imported, ...).
is_active	boolean	no	Is active.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
housing_unit_id	integer	no	v2 housing unit ID on the farm.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
```

```
"total_items": 42,  
"has_next": true,  
"has_previous": false  
}
```

GET /api/animals/animal-by-id/v2/{animal_id}

Get Animal By Id V2

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": [  
    {  
      "id": 12,  
      "tag_id": "COW-001",  
      "gender": "female",  
      "status": "active",  
      "health_status": "healthy"  
    }  
  ]  
}
```


PATCH /api/animals/update-animal/v2/{animal_id}

Update Animal V2

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
status	'active' 'pregnant' 'lactating' 'sick' 'quarantine' 'sold' 'dead'	no	Record status filter or value.
gender	'male' 'female'	no	male or female.
source	'born' 'purchased' 'imported' 'transferred_in' 'donated' 'opening_record' 'other'	no	How the animal entered the farm (born, purchased, imported, ...).
new_farm_id	integer	no	ID of the related new farm.
tag_id	string	no	Unique ear-tag / identifier for the animal.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
housing_unit_id	integer	no	v2 housing unit ID on the farm.
dob	string (date)	no	Date of birth (YYYY-MM-DD).
estimated_age_months	integer	no	Use when exact DOB is unknown.
mother_id	integer	no	Dam animal ID. Required when source is born.
health_status	'healthy' 'sick' 'recovering' 'at_risk'	no	Allowed values: healthy, sick, recovering, at_risk
is_pregnant	boolean	no	Is pregnant.
is_lactating	boolean	no	Is lactating.
is_quarantine	boolean	no	Is quarantine.
is_active	boolean	no	Is active.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "status": "active",
  "gender": "male",
  "source": "born",
  "new_farm_id": 1,
  "tag_id": "COW-001",
  "livestock_species_id": 1,
  "livestock_breed_id": 1,
  "housing_unit_id": 1,
  "dob": "2026-03-15",
  "estimated_age_months": 1,
  "mother_id": 1,
  "health_status": "healthy",
  "is_pregnant": true,
  "is_lactating": true,
  "is_quarantine": true,
  "is_active": true,
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

GET /api/animals/animal-event/v2/{page}/{page_size}/{farm_id}

Get Animal Event V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/animals/animal-weight/v2/{page}/{page_size}/{farm_id}

Get Animal Weight V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/animals/animal-growth/{animal_id}/

Get Animal Growth

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/v2/animals/

List animals (card records)

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
search	string	no	Optional text filter (usually tag ID or name).
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
gender	string	no	male or female.
lifecycle_status	string	no	Lifecycle status.
health_status	string	no	Health status.
housing_unit_id	integer	no	v2 housing unit ID on the farm.
group_id	integer	no	Numeric ID of the animal group.
is_pregnant	boolean	no	Is pregnant.
is_lactating	boolean	no	Is lactating.
is_quarantine	boolean	no	Is quarantine.
needs_attention	boolean	no	Needs attention.
sort	string	no	Sort.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/v2/animals/

Progressive animal create (lifecycle status only)

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
tag_id	string	no	Unique ear-tag / identifier for the animal.
gender	string	yes	male or female.
source_type	string	yes	How the animal entered the farm.
status	string	no	Record status filter or value.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
housing_unit_id	integer	no	v2 housing unit ID on the farm.
dob	string (date)	no	Date of birth (YYYY-MM-DD).
estimated_age_months	integer	no	Use when exact DOB is unknown.
mother_id	integer	no	Dam animal ID. Required when source is born.
notes	string	no	Notes.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "tag_id": "COW-001",
  "gender": "string",
  "source_type": "string",
  "status": "active",
  "livestock_species_id": 1,
  "livestock_breed_id": 1,
  "housing_unit_id": 1,
  "dob": "2026-03-15",
  "estimated_age_months": 1,
  "mother_id": 1,
  "notes": "Free-text notes",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "tag_id": "COW-001",
    "gender": "female",
    "species": "Cattle",
    "breed": "White Fulani",
    "housing_unit": "Pen A"
  }
}
```


PATCH /api/v2/animals/{animal_id}/

Partial animal update

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
livestock_species_id	integer	no	v2 species ID from livestock master data.
housing_unit_id	integer	no	v2 housing unit ID on the farm.
notes	string	no	Notes.
tag_id	string	no	Unique ear-tag / identifier for the animal.
gender	string	no	male or female.
dob	string (date)	no	Date of birth (YYYY-MM-DD).
estimated_age_months	integer	no	Use when exact DOB is unknown.
client_request_id	string	no	ID of the related client request.
is_pregnant	boolean	no	Is pregnant.
is_lactating	boolean	no	Is lactating.
is_quarantine	boolean	no	Is quarantine.
needs_attention	boolean	no	Needs attention.
is_active	boolean	no	Is active.
status	string	no	Record status filter or value.
lifecycle_status	string	no	Lifecycle status.

EXAMPLE REQUEST BODY

```
{
  "livestock_breed_id": 1,
  "livestock_species_id": 1,
  "housing_unit_id": 1,
  "notes": "Free-text notes",
  "tag_id": "COW-001",
  "gender": "string",
  "dob": "2026-03-15",
```

```
"estimated_age_months": 1,  
"client_request_id": "string",  
"is_pregnant": true,  
"is_lactating": true,  
"is_quarantine": true,  
"needs_attention": true,  
"is_active": true,  
"status": "active",  
"lifecycle_status": "active"  
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 15,  
    "updated": true  
  }  
}
```

GET /api/v2/animals/{animal_id}/profile/

Animal operational profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/v2/animals/{animal_id}/timeline/

Animal timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/v2/animals/resolve-tag/{tag_id}/

Resolve an animal tag within the organization

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
tag_id	string	Unique ear-tag / identifier for the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

Production

POST /api/animals/milk/

Milk

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
record_date	string (date)	yes	Record date.
session	'morning' 'evening'	yes	Allowed values: morning, evening
quantity	number	yes	Quantity.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "record_date": "2026-03-15",
  "session": "morning",
  "quantity": 10.5,
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/animals/milk/{page}/{page_size}/{farm_id}

Get Milk

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/animals/milk/v2/{page}/{page_size}/{farm_id}

Get Milk V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


Reproduction

Insemination, pregnancy checks, births, offspring tags, and breeding eligibility rules.

POST /api/reproductions/insemination/

Insemination

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
service_date	string (date)	yes	Service date.
method	'natural' 'artificial'	yes	Allowed values: natural, artificial
sire_reference	string	no	Sire reference.
technician_name	string	no	Technician name.
notes	string	no	Notes.
override_reason	string	no	Required when staff override a breeding or sale restriction.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "service_date": "2026-03-15",
  "method": "natural",
  "sire_reference": "string",
  "technician_name": "Example name",
  "notes": "Free-text notes",
  "override_reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/insemination/{page}/{page_size}/{farm_id}

Get Insemination

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/reproductions/pregnancy/

Pregnancy

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
insemination_id	integer	no	ID of the related insemination.
check_date	string (date)	yes	Check date.
result	'pregnant' 'not_pregnant'	yes	Allowed values: pregnant, not_pregnant
expected_delivery_date	string (date)	no	Expected delivery date.
notes	string	no	Notes.
override_reason	string	no	Required when staff override a breeding or sale restriction.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "insemination_id": 1,
  "check_date": "2026-03-15",
  "result": "pregnant",
  "expected_delivery_date": "2026-03-15",
  "notes": "Free-text notes",
  "override_reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/pregnancy/{page}/{page_size}/{farm_id}

Get Pregnancy

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/reproductions/birth/

Birth

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
mother_id	integer	yes	Dam animal ID. Required when source is born.
birth_date	string (date)	yes	Birth date.
number_of_offspring	integer	yes	Number of offspring.
number_alive	integer	yes	Number alive.
number_dead	integer	yes	Number dead.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "mother_id": 1,
  "birth_date": "2026-03-15",
  "number_of_offspring": 1,
  "number_alive": 1,
  "number_dead": 1,
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/birth/{page}/{page_size}/{farm_id}

Get Birth

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/reproductions/birth-offspring/

Birth Offspring

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
birth_record_id	integer	yes	ID of the related birth record.
tag_id	string	yes	Unique ear-tag / identifier for the animal.
gender	'male' 'female'	yes	male or female.
birth_weight	number	no	Birth weight.
health_status	'healthy' 'sick' 'recovering' 'at_risk'	yes	Allowed values: healthy, sick, recovering, at_risk
status	'active' 'sick' 'dead'	yes	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "birth_record_id": 1,
  "tag_id": "COW-001",
  "gender": "male",
  "birth_weight": 10.5,
  "health_status": "healthy",
  "status": "active"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/reproductions/birth-offspring/{page}/{page_size}/{farm_id}

Get Birth Offspring

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reproductions/insemination/v2/{page}/{page_size}/{farm_id}

Get Insemination V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reproductions/pregnancy/v2/{page}/{page_size}/{farm_id}

Get Pregnancy V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reproductions/birth/v2/{page}/{page_size}/{farm_id}

Get Birth V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/reproductions/birth-offspring/v2/

Birth Offspring V2

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
birth_record_id	integer	yes	ID of the related birth record.
tag_id	string	yes	Unique ear-tag / identifier for the animal.
gender	'male' 'female'	yes	male or female.
birth_weight	number	no	Birth weight.
health_status	'healthy' 'sick' 'recovering' 'at_risk'	yes	Allowed values: healthy, sick, recovering, at_risk
status	'active' 'sick' 'dead'	yes	Record status filter or value.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "birth_record_id": 1,
  "tag_id": "COW-001",
  "gender": "male",
  "birth_weight": 10.5,
  "health_status": "healthy",
  "status": "active"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/birth-offspring/v2/{page}/{page_size}/{farm_id}

Get Birth Offspring V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/reproductions/breeding-rule/seed/

Seed Breeding Rule

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/breeding-rule/{species_id}/

Get Breeding Rule

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


POST /api/reproductions/breeding-rule/

Create Farm Breeding Rule

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
species_id	integer	yes	Legacy species ID (v1 endpoints).
breed_id	integer	no	Legacy breed ID (v1 endpoints).
min_breeding_age_months	number	no	Min breeding age months.
recommended_breeding_age_months	number	no	Recommended breeding age months.
max_breeding_age_months	number	no	Max breeding age months.
min_breeding_weight_kg	number	no	Min breeding weight kg.
min_postpartum_interval_days	integer	no	Min postpartum interval days.
max_births_lifetime	integer	no	Max births lifetime.
allow_pregnant_and_lactating	boolean	no	Allow pregnant and lactating.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/reproductions/breeding-eligibility/{animal_id}/

Get Breeding Eligibility

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
for_pregnancy	boolean	no	For pregnancy.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

POST /api/v2/reproduction/births/

Record a birth with live offspring registration slots

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
mother_id	integer	yes	Dam animal ID. Required when source is born.
birth_date	string (date)	yes	Birth date.
number_of_offspring	integer	yes	Number of offspring.
number_alive	integer	yes	Number alive.
number_dead	integer	yes	Number dead.
notes	string	no	Notes.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "mother_id": 1,
  "birth_date": "2026-03-15",
  "number_of_offspring": 1,
  "number_alive": 1,
  "number_dead": 1,
  "notes": "Free-text notes",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/reproduction/births/{birth_id}/

Birth record and offspring registration slots

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
birth_id	integer	ID of the related birth.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/v2/reproduction/births/{birth_id}/register-offspring/

Register one live offspring against a birth slot

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
birth_id	integer	ID of the related birth.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
tag_id	string	no	Unique ear-tag / identifier for the animal.
gender	string	yes	male or female.
offspring_sequence	integer	no	Offspring sequence.
birth_weight	number	no	Birth weight.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "tag_id": "COW-001",
  "gender": "string",
  "offspring_sequence": 1,
  "birth_weight": 10.5,
  "livestock_species_id": 1,
  "livestock_breed_id": 1,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

Health

Treatments, vaccinations, quarantine, mortality, health alerts, and treatments that draw from pharmacy stock.

POST /api/health/treatment/

Treatment

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
diagnosis	string	yes	Diagnosis.
treatment	string	yes	Treatment.
severity	'mild' 'moderate' 'severe'	yes	Allowed values: mild, moderate, severe
treatment_date	string (date)	yes	Treatment date.
next_follow_up_date	string (date)	no	Next follow up date.
notes	string	no	Notes.
drug_id	integer	no	ID of the related drug.
drug_batch_id	integer	no	ID of the related drug batch.
quantity_administered	number	no	Quantity administered.
dose	string	no	Dose.
frequency	string	no	Frequency.
duration_days	integer	no	Duration days.
administration_route	'oral' 'injection' 'topical' 'other'	no	Allowed values: oral, injection, topical, other
administered_by_id	integer	no	ID of the related administered by.
prescribed_by_id	integer	no	ID of the related prescribed by.
next_dose_date	string (date)	no	Next dose date.
withdrawal_end_date	string (date)	no	Withdrawal end date.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
```

```
"group_id": 1,
"diagnosis": "string",
"treatment": "string",
"severity": "mild",
"treatment_date": "2026-03-15",
"next_follow_up_date": "2026-03-15",
"notes": "Free-text notes",
"drug_id": 1,
"drug_batch_id": 1,
"quantity_administered": 10.5,
"dose": "string",
"frequency": "string",
"duration_days": 1,
"administration_route": "oral",
"administered_by_id": 1,
"prescribed_by_id": 1,
"next_dose_date": "2026-03-15",
"withdrawal_end_date": "2026-03-15"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/health/treatment/{page}/{page_size}/{farm_id}

Get Treatment

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/health/vaccination/

Vaccination

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
vaccine_name	string	yes	Vaccine name.
date_given	string (date)	yes	Date given.
next_due_date	string (date)	no	Next due date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "group_id": 1,
  "vaccine_name": "Example name",
  "date_given": "2026-03-15",
  "next_due_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/health/vaccination/{page}/{page_size}/{farm_id}

Get Vaccination

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/health/quarantine/

Quarantine

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
reason	string	yes	Reason.
start_date	string (date)	yes	Start date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "reason": "Free-text notes",
  "start_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/health/quarantine/{page}/{page_size}/{farm_id}

Get Quarantine

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/health/mortality/

Mortality

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
cause	string	yes	Cause.
death_date	string (date)	yes	Death date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "cause": "string",
  "death_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/health/mortality/{page}/{page_size}/{farm_id}

Get Mortality

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/health/treatment/v2/{page}/{page_size}/{farm_id}

Get Treatment V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


GET /api/health/vaccination/v2/{page}/{page_size}/{farm_id}

Get Vaccination V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/health/quarantine/v2/{page}/{page_size}/{farm_id}

Get Quarantine V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/health/mortality/v2/{page}/{page_size}/{farm_id}

Get Mortality V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/health/health-alert/scan/{animal_id}/

Scan Animal Health Alerts

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/health/health-alert/{page}/{page_size}/{farm_id}

Get Health Alerts

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
severity	string	no	Severity.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/health/health-alert/{alert_id}/resolve/

Resolve Health Alert

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
alert_id	integer	ID of the related alert.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
resolution_notes	string	no	Resolution notes.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/health/treatment/external/

Record External Medication

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
diagnosis	string	yes	Diagnosis.
treatment_date	string (date)	yes	Treatment date.
severity	'mild' 'moderate' 'severe'	no	Allowed values: mild, moderate, severe
drug_id	integer	no	ID of the related drug.
external_drug_name	string	yes	External drug name.
quantity_administered	number	yes	Quantity administered.
unit	string	yes	Unit.
external_unit_cost	number	yes	External unit cost.
external_source	string	yes	External source.
external_reason	string	yes	External reason.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "group_id": 1,
  "diagnosis": "string",
  "treatment_date": "2026-03-15",
  "severity": "mild",
  "drug_id": 1,
  "external_drug_name": "Example name",
  "quantity_administered": 10.5,
  "unit": "string",
  "external_unit_cost": 10.5,
  "external_source": "string",
  "external_reason": "Free-text notes",
```

```
"notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/health/treatment/{treatment_id}/reconcile-to-inventory/

Reconcile External Medication

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
treatment_id	integer	ID of the related treatment.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
batch_number	string	yes	Batch number.
minimum_stock_level	number	no	Minimum stock level.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


POST /api/v2/health/observations/

Record a health observation

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
case_id	integer	no	ID of the related case.
symptoms	string	yes	Symptoms.
severity	string	no	Severity.
observed_at	string (date-time)	no	Observed at.
create_task	boolean	no	Create task.
create_case	boolean	no	Create case.
assignee_id	string (uuid)	no	ID of the related assignee.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "group_id": 1,
  "case_id": 1,
  "symptoms": "string",
  "severity": "string",
  "observed_at": "2026-03-15T08:30:00Z",
  "create_task": true,
  "create_case": true,
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/v2/health/observations/

List health observations

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 1  
  }  
}
```

POST /api/v2/health/cases/

Open a health case

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
title	string	yes	Title.
notes	string	no	Notes.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "title": "string",
  "notes": "Free-text notes",
  "animal_id": 1,
  "group_id": 1,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/health/cases/

List health cases

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/v2/health/cases/{case_id}/close/

Close a health case

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
case_id	integer	ID of the related case.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
notes	string	no	Notes.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "notes": "Free-text notes",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/health/cases/{case_id}/

Health case detail

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
case_id	integer	ID of the related case.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/health/alerts/

Actionable health alerts

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Feed

Feed master data, inventory, batches, plans, issuance, and confirmation. v3 is the current master-data model.

POST /api/feed/feed-inventory/

Feed Inventory

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
feed_name	string	yes	Feed name.
quantity_available	number	yes	Quantity available.
unit	string	yes	Unit.
reorder_level	number	no	Reorder level.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "feed_name": "Example name",
  "quantity_available": 10.5,
  "unit": "string",
  "reorder_level": 10.5
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/feed/feed/{page}/{page_size}/{farm_id}

Get Feed

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/feed/feed-plan/

Feed Plan

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
plan_type	'species' 'group'	yes	Allowed values: species, group
species_id	integer	no	Legacy species ID (v1 endpoints).
group_id	integer	no	Numeric ID of the animal group.
feed_inventory_id	integer	yes	ID of the related feed inventory.
daily_feed_quantity	number	yes	Daily feed quantity.
unit	string	yes	Unit.
start_date	string (date)	yes	Start date.
end_date	string (date)	no	End date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "plan_type": "species",
  "species_id": 1,
  "group_id": 1,
  "feed_inventory_id": 1,
  "daily_feed_quantity": 10.5,
  "unit": "string",
  "start_date": "2026-03-15",
  "end_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/feed/feed-plan/{page}/{page_size}/{farm_id}

Get Feed Plan

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Fetched successfully",  
  "data": [  
    {  
      "id": 1,  
      "name": "North Paddock",  
      "farm_code": "NP-01"  
    }  
  ],  
  "num_pages": 3,  
  "current_page": 1,  
  "total_items": 42,  
  "has_next": true,  
  "has_previous": false  
}
```

POST /api/feed/feed-issue/

Feed Issue

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
target_type	'animal' 'group'	yes	Allowed values: animal, group
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
feed_inventory_id	integer	yes	ID of the related feed inventory.
quantity_issued	number	yes	Quantity issued.
issue_date	string (date)	yes	Issue date.
notes	string	no	Notes.
feed_batch_id	integer	no	ID of the related feed batch.
feeding_period	'morning' 'afternoon' 'evening' 'full_day'	no	Allowed values: morning, afternoon, evening, full_day
fed_by_id	integer	no	ID of the related fed by.
allocation_method	'equal' 'weight_based' 'consumption_based' 'life_stage_based' 'manual'	no	Allowed values: equal, weight_based, consumption_based, life_stage_based, manual
manual_allocations	array of FeedAllocationEntrySchema	no	Manual allocations.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "target_type": "animal",
  "animal_id": 1,
  "group_id": 1,
  "feed_inventory_id": 1,
  "quantity_issued": 10.5,
  "issue_date": "2026-03-15",
  "notes": "Free-text notes",
  "feed_batch_id": 1,
  "feeding_period": "morning",
  "fed_by_id": 1,
  "allocation_method": "equal",
  "manual_allocations": [
```

```
{
  "animal_id": 1,
  "quantity": 10.5
}
]
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed-issue/{page}/{page_size}/{farm_id}

Get Feed Issue

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/feed/feed-confirmation/

Feed Confirmation

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
status	'confirmed' 'variance_detected'	yes	Record status filter or value.
issuance_id	integer	yes	ID of the related issuance.
actual_used_quantity	number	yes	Actual used quantity.
confirmation_date	string (date)	yes	Confirmation date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "status": "confirmed",
  "issuance_id": 1,
  "actual_used_quantity": 10.5,
  "confirmation_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed-confirmation/{page}/{page_size}/{farm_id}

Get Feed Confirmations

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


POST /api/feed/feed-plan/v2/

Feed Plan V2

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
plan_type	'species' 'group'	yes	Allowed values: species, group
species_id	integer	no	Legacy species ID (v1 endpoints).
livestock_species_id	integer	no	v2 species ID from livestock master data.
group_id	integer	no	Numeric ID of the animal group.
feed_inventory_id	integer	yes	ID of the related feed inventory.
daily_feed_quantity	number	yes	Daily feed quantity.
unit	string	yes	Unit.
start_date	string (date)	yes	Start date.
end_date	string (date)	no	End date.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "plan_type": "species",
  "species_id": 1,
  "livestock_species_id": 1,
  "group_id": 1,
  "feed_inventory_id": 1,
  "daily_feed_quantity": 10.5,
  "unit": "string",
  "start_date": "2026-03-15",
  "end_date": "2026-03-15",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/feed/feed-plan/v2/{page}/{page_size}/{farm_id}

Get Feed Plan V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Fetched successfully",  
  "data": [  
    {  
      "id": 1,  
      "name": "North Paddock",  
      "farm_code": "NP-01"  
    }  
  ],  
  "num_pages": 3,  
  "current_page": 1,  
  "total_items": 42,  
  "has_next": true,  
  "has_previous": false  
}
```

GET /api/feed/feed-issue/v2/{page}/{page_size}/{farm_id}

Get Feed Issue V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/feed/feed-master/seed/v3/

Seed Feed Master V3

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed-category/v3/

Get Feed Categories V3

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/feed/feed-unit/v3/

Get Feed Units V3

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/feed/feed-unit/v3/

Create Farm Feed Unit V3

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
abbreviation	string	no	Abbreviation.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "abbreviation": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed-type/v3/{page}/{page_size}/{farm_id}

Get Feed Types V3

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
species_id	integer	no	Legacy species ID (v1 endpoints).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/feed/feed-type/v3/

Create Farm Feed Type V3

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
category_id	integer	yes	ID of the related category.
species_ids	array of integer	yes	Species ids.
description	string	no	Description.
manufacturer	string	no	Manufacturer.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "category_id": 1,
  "species_ids": [
    1
  ],
  "description": "Free-text notes",
  "manufacturer": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


PATCH /api/feed/feed-type/v3/{feed_type_id}/

Update Farm Feed Type V3

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
feed_type_id	integer	ID of the related feed type.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
category_id	integer	no	ID of the related category.
species_ids	array of integer	no	Species ids.
description	string	no	Description.
manufacturer	string	no	Manufacturer.
is_active	boolean	no	Is active.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "category_id": 1,
  "species_ids": [
    1
  ],
  "description": "Free-text notes",
  "manufacturer": "string",
  "is_active": true
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/feed/feed-type/v3/{feed_type_id}/deactivate/

Deactivate Farm Feed Type V3

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
feed_type_id	integer	ID of the related feed type.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/feed/feed-inventory/v3/

Feed Inventory V3

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
feed_type_id	integer	yes	ID of the related feed type.
quantity_available	number	yes	Quantity available.
feed_unit_id	integer	yes	ID of the related feed unit.
reorder_level	number	no	Reorder level.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "feed_type_id": 1,
  "quantity_available": 10.5,
  "feed_unit_id": 1,
  "reorder_level": 10.5
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed/v3/{page}/{page_size}/{farm_id}

Get Feed V3

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
species_id	integer	no	Legacy species ID (v1 endpoints).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/feed/feed-batch/

Create Feed Batch

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
feed_type_id	integer	yes	ID of the related feed type.
batch_number	string	yes	Batch number.
purchase_unit	'bag' 'kg' 'tonne' 'bale' 'sack' 'litre' 'container' 'other'	yes	Allowed values: bag, kg, tonne, bale, sack, litre, container, other
package_size	number	yes	Package size.
number_of_packages	number	yes	Number of packages.
base_unit_id	integer	yes	ID of the related base unit.
purchase_price	number	yes	Purchase price.
supplier	string	no	Supplier.
purchase_date	string (date)	no	Purchase date.
expiry_date	string (date)	no	Expiry date.
storage_location	string	no	Storage location.
minimum_stock_level	number	no	Minimum stock level.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "feed_type_id": 1,
  "batch_number": "string",
  "purchase_unit": "bag",
  "package_size": 10.5,
  "number_of_packages": 10.5,
  "base_unit_id": 1,
  "purchase_price": 10.5,
  "supplier": "string",
  "purchase_date": "2026-03-15",
  "expiry_date": "2026-03-15",
  "storage_location": "string",
  "minimum_stock_level": 10.5
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/feed/feed-batch/{page}/{page_size}/{farm_id}

Get Feed Batches

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
feed_type_id	integer	no	ID of the related feed type.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

MovementRecords

Move animals between housing units, record sales, sale policy, sale readiness, and profitability.

POST /api/movement-records/move/

Create Movement

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
from_unit_id	integer	no	ID of the related from unit.
to_unit_id	integer	no	ID of the related to unit.
move_date	string (date-time)	yes	Move date.
reason	string	no	Reason.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "group_id": 1,
  "from_unit_id": 1,
  "to_unit_id": 1,
  "move_date": "2026-03-15T08:30:00Z",
  "reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/movement-records/moves/{page}/{page_size}/{farm_id}

List Movements

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
q	string	no	Q.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/movement-records/move/{movement_id}

Get Movement

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
movement_id	integer	ID of the related movement.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/movement-records/sale/

Create Sale

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	yes	Numeric ID of the animal.
buyer_name	string	yes	Buyer name.
price	number	yes	Price.
sale_date	string (date-time)	yes	Sale date.
reason	string	no	Reason.
notes	string	yes	Notes.
override_reason	string	no	Required when staff override a breeding or sale restriction.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "buyer_name": "Example name",
  "price": 10.5,
  "sale_date": "2026-03-15T08:30:00Z",
  "reason": "Free-text notes",
  "notes": "Free-text notes",
  "override_reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/movement-records/sales/{page}/{page_size}/{farm_id}

List Sales

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
q	string	no	Q.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/movement-records/sale/{sale_id}

Get Sale

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
sale_id	integer	ID of the related sale.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/movement-records/move/v2/

Create Movement V2

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
from_housing_unit_id	integer	yes	ID of the related from housing unit.
to_housing_unit_id	integer	yes	ID of the related to housing unit.
move_date	string (date-time)	yes	Move date.
reason	string	no	Reason.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "animal_id": 1,
  "group_id": 1,
  "from_housing_unit_id": 1,
  "to_housing_unit_id": 1,
  "move_date": "2026-03-15T08:30:00Z",
  "reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/movement-records/moves/v2/{page}/{page_size}/{farm_id}

List Movements V2

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
q	string	no	Q.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/movement-records/move/v2/{movement_id}

Get Movement V2

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
movement_id	integer	ID of the related movement.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/movement-records/sale-policy/seed/

Seed Sale Policy

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/movement-records/sale-policy/{species_id}/

Get Sale Policy

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
species_id	integer	Legacy species ID (v1 endpoints).

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

POST /api/movement-records/sale-policy/

Create Farm Sale Policy

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
species_id	integer	yes	Legacy species ID (v1 endpoints).
breed_id	integer	no	Legacy breed ID (v1 endpoints).
target_sale_weight_kg	number	no	Target sale weight kg.
min_sale_age_months	number	no	Min sale age months.
allow_pregnant_sale	boolean	no	Allow pregnant sale.
require_sale_approval	boolean	no	Require sale approval.
expected_sale_expenses_pct	number	no	Expected sale expenses pct.
approaching_ready_threshold_pct	number	no	Approaching ready threshold pct.
sale_recommended_margin_pct	number	no	Sale recommended margin pct.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/movement-records/sale-readiness/{animal_id}/

Get Sale Readiness

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
expected_sale_price	number	no	Expected sale price.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/movement-records/animal-profitability/{animal_id}/

Get Animal Profitability

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
expected_sale_price	number	no	Expected sale price.
price_per_kg	number	no	Price per kg.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

POST /api/movement-records/sale-approval/{animal_id}/

Approve Animal Sale

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
reason	string	no	Reason.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

Alerts

Generic farm alerts (vaccination due, pregnancy due, feed variance, treatment follow-up).

GET /api/alerts/

Alerts api root

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/alerts/create/

Create Alert

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
alert_type	'vaccination_due' 'pregnancy_due' 'feed_variance' 'treatment_follow_up'	yes	Allowed values: vaccination_due, pregnancy_due, feed_variance, treatment_follow_up
priority	'critical' 'warning' 'info'	yes	Allowed values: critical, warning, info
reference_table	string	no	Reference table.
reference_id	integer	no	ID of the related reference.
title	string	yes	Title.
message	string	yes	Message.
status	'open' 'resolved'	yes	Record status filter or value.
due_date	string (date-time)	no	Due date.
resolved_at	string (date-time)	no	Resolved at.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "alert_type": "vaccination_due",
  "priority": "critical",
  "reference_table": "string",
  "reference_id": 1,
  "title": "string",
  "message": "Free-text notes",
  "status": "open",
  "due_date": "2026-03-15T08:30:00Z",
  "resolved_at": "2026-03-15T08:30:00Z"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/alerts/alerts/{page}/{page_size}/{farm_id}

List Alerts

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
q	string	no	Q.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Fetched successfully",  
  "data": [  
    {  
      "id": 1,  
      "name": "North Paddock",  
      "farm_code": "NP-01"  
    }  
  ],  
  "num_pages": 3,  
  "current_page": 1,  
  "total_items": 42,  
  "has_next": true,  
  "has_previous": false  
}
```


GET /api/alerts/alert/{alert_id}

Get Alert

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
alert_id	integer	ID of the related alert.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 4,
      "title": "Vaccination due",
      "priority": "warning",
      "status": "open"
    }
  ]
}
```

Dashboard

Read-only aggregates for the app home screens. Many routes exist in v1 and v2; v2 is the current livestock-master-data version.

GET /api/dashboard/main-dashboard/{farm_id}

Main Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/livestock-dashboard/{farm_id}

Livestock Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/animal-dashboard/{farm_id}

Animal Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/dashboard/reproduction-dashboard/{farm_id}

Reproduction Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/health-dashboard/{farm_id}

Health Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/mortality-dashboard/{farm_id}

Mortality Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/transaction-dashboard/{farm_id}

Transaction Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```


GET /api/dashboard/sales-dashboard/{farm_id}

Sales Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
species_id	integer	no	Legacy species ID (v1 endpoints).
date_from	string	no	Date from.
date_to	string	no	Date to.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-inventory-dashboard/{farm_id}

Feed Inventory Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/inventory-dashboard/{farm_id}

Inventory Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-plan-dashboard/{farm_id}

Feed Plan Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
plan_type	string	no	Plan type.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-issuance-dashboard/{farm_id}

Feed Issuance Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).
date_from	string	no	Date from.
date_to	string	no	Date to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-confirmation-dashboard/{farm_id}

Feed Confirmation Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).
date_from	string	no	Date from.
date_to	string	no	Date to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/livestock-report-dashboard/{farm_id}

Livestock Report Dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/production-report/{farm_id}

Production Report

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```


GET /api/dashboard/health-report/{farm_id}

Health Report

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-report/{farm_id}

Feed Report

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/main-dashboard/v2/{farm_id}

Main Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/livestock-dashboard/v2/{farm_id}

Livestock Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/animal-dashboard/v2/{farm_id}

Animal Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

GET /api/dashboard/reproduction-dashboard/v2/{farm_id}

Reproduction Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/health-dashboard/v2/{farm_id}

Health Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/mortality-dashboard/v2/{farm_id}

Mortality Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```


GET /api/dashboard/transaction-dashboard/v2/{farm_id}

Transaction Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/sales-dashboard/v2/{farm_id}

Sales Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.
species_id	integer	no	Legacy species ID (v1 endpoints).
date_from	string	no	Date from.
date_to	string	no	Date to.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-inventory-dashboard/v2/{farm_id}

Feed Inventory Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/feed-plan-dashboard/v2/{farm_id}

Feed Plan Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
plan_type	string	no	Plan type.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/livestock-report-dashboard/v2/{farm_id}

Livestock Report Dashboard V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/dashboard/production-report/v2/{farm_id}

Production Report V2

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/v2/dashboard/organization/

Organization operational dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "totals": {
      "animals": 120,
      "active": 110,
      "sold": 6,
      "dead": 4
    },
    "trends": [
      {
        "period": "2026-03",
        "value": 18
      }
    ]
  }
}
```

GET /api/v2/dashboard/farm/{farm_id}/

Farm manager dashboard

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```


GET /api/v2/dashboard/my-work/

My Work dashboard aggregate

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "totals": {
      "animals": 120,
      "active": 110,
      "sold": 6,
      "dead": 4
    },
    "trends": [
      {
        "period": "2026-03",
        "value": 18
      }
    ]
  }
}
```

GET /api/v2/dashboard/health/

Veterinarian / health workspace

Returns aggregated numbers and trend series for this screen. Path farm_id selects the farm. No JSON body.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "totals": {
      "animals": 120,
      "active": 110,
      "sold": 6,
      "dead": 4
    },
    "trends": [
      {
        "period": "2026-03",
        "value": 18
      }
    ]
  }
}
```

Finance

Income and expense transactions, plus per-animal financial profiles.

POST /api/finance/transaction-category/seed/

Seed Categories

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/finance/transaction-category/

Get Transaction Categories

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
type	string	no	Type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/finance/transaction/

Create Transaction

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
type	'expense' 'income'	yes	Allowed values: expense, income
category_id	integer	yes	ID of the related category.
amount	number	yes	Amount.
currency	string	no	Currency.
transaction_date	string (date)	yes	Transaction date.
description	string	no	Description.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
payment_status	'paid' 'pending' 'partial'	no	Allowed values: paid, pending, partial
payment_method	string	no	Payment method.
transaction_reference	string	no	Transaction reference.
notes	string	no	Notes.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "type": "expense",
  "category_id": 1,
  "amount": 10.5,
  "currency": "NGN",
  "transaction_date": "2026-03-15",
  "description": "Free-text notes",
  "animal_id": 1,
  "group_id": 1,
  "payment_status": "paid",
  "payment_method": "string",
  "transaction_reference": "string",
  "notes": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 15  
  }  
}
```

GET /api/finance/transaction/{page}/{page_size}/{farm_id}

Get Transactions

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
type	string	no	Type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/finance/animal-financial-summary/{animal_id}/

Animal Financial Summary

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```


GET /api/finance/animal-cost-timeline/{animal_id}/

Animal Cost Timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
animal_id	integer	Numeric ID of the animal.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

Pharmacy

Drug catalogue, batches, stock, and expiry/low-stock alerts.

POST /api/pharmacy/drug-master/seed/

Seed Pharmacy Master

Setup helper: inserts default catalogue rows (rules, species, permissions, etc.). Body is often empty.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/pharmacy/drug-category/

Get Drug Categories

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/pharmacy/drug/{page}/{page_size}/{farm_id}

Get Drugs

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
category_id	integer	no	ID of the related category.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/pharmacy/drug/

Create Farm Drug

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	yes	Name.
category_id	integer	yes	ID of the related category.
active_ingredient	string	no	Active ingredient.
brand_name	string	no	Brand name.
manufacturer	string	no	Manufacturer.
dosage_form	string	no	Dosage form.
strength_concentration	string	no	Strength concentration.
unit_of_measurement	string	yes	Unit of measurement.
withdrawal_period_days	integer	no	Withdrawal period days.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "category_id": 1,
  "active_ingredient": "string",
  "brand_name": "Example name",
  "manufacturer": "string",
  "dosage_form": "string",
  "strength_concentration": "string",
  "unit_of_measurement": "string",
  "withdrawal_period_days": 1
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

POST /api/pharmacy/drug-batch/

Create Drug Batch

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
drug_id	integer	yes	ID of the related drug.
batch_number	string	yes	Batch number.
quantity_received	number	yes	Quantity received.
purchase_unit	string	no	Purchase unit.
purchase_price	number	yes	Purchase price.
supplier	string	no	Supplier.
purchase_date	string (date)	no	Purchase date.
manufacturing_date	string (date)	no	Manufacturing date.
expiry_date	string (date)	yes	Expiry date.
storage_location	string	no	Storage location.
minimum_stock_level	number	no	Minimum stock level.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "drug_id": 1,
  "batch_number": "string",
  "quantity_received": 10.5,
  "purchase_unit": "string",
  "purchase_price": 10.5,
  "supplier": "string",
  "purchase_date": "2026-03-15",
  "manufacturing_date": "2026-03-15",
  "expiry_date": "2026-03-15",
  "storage_location": "string",
  "minimum_stock_level": 10.5
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
```

```
"message": "Request completed",
"data": {
  "id": 15
}
}
```

GET /api/pharmacy/drug-batch/{page}/{page_size}/{farm_id}

Get Drug Batches

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
drug_id	integer	no	ID of the related drug.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

POST /api/pharmacy/pharmacy-alert/scan/{farm_id}/

Scan Pharmacy Alerts

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```


GET /api/pharmacy/pharmacy-alert/{page}/{page_size}/{farm_id}

Get Pharmacy Alerts

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/pharmacy/animal-withdrawal/{farm_id}/

Get Animals Under Withdrawal

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ]
}
```

Reports

Paginated operational reports: animal cost, growth, feed/treatment cost, mortality, eligibility, sale readiness, stock valuation.

GET /api/reports/animal-cost/{page}/{page_size}/{farm_id}

Animal Cost Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
gender	string	no	male or female.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/cost-by-group/{page}/{page_size}/{farm_id}/

Cost By Group Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/feed-cost/{farm_id}/

Feed Cost Report

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
start_date	string	no	Start date.
end_date	string	no	End date.
animal_id	integer	no	Numeric ID of the animal.
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/reports/treatment-cost/{farm_id}/

Treatment Cost Report

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
start_date	string	no	Start date.
end_date	string	no	End date.
animal_id	integer	no	Numeric ID of the animal.
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/reports/growth-performance/{page}/{page_size}/{farm_id}

Growth Performance Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
gender	string	no	male or female.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


GET /api/reports/weight-exceptions/{page}/{page_size}/{farm_id}/

Weight Exceptions Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
severity	string	no	Severity.
alert_type	string	no	Alert type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/reproductive-eligibility/{page}/{page_size}/{farm_id}/

Reproductive Eligibility Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
is_eligible	boolean	no	Is eligible.
livestock_species_id	integer	no	v2 species ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/sale-ready-animals/{page}/{page_size}/{farm_id}/

Sale Ready Animals Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
livestock_species_id	integer	no	v2 species ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/sale-restricted-animals/{page}/{page_size}/{farm_id}/

Sale Restricted Animals Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
livestock_species_id	integer	no	v2 species ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/profitability/{page}/{page_size}/{farm_id}

Profitability By Animal Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
status	string	no	Record status filter or value.
gender	string	no	male or female.
livestock_species_id	integer	no	v2 species ID from livestock master data.
livestock_breed_id	integer	no	v2 breed ID from livestock master data.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/low-performance-animals/{page}/{page_size}/{farm_id}/

Low Performance Animals Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
severity	string	no	Severity.
alert_type	string	no	Alert type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 12,
      "tag_id": "COW-001",
      "gender": "female",
      "status": "active",
      "health_status": "healthy"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```

GET /api/reports/health-alert-summary/{farm_id}/

Health Alert Summary Report

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/reports/expiring-drugs/{page}/{page_size}/{farm_id}/

Expiring Drugs Report

Returns a paginated list. Set page and page_size in the URL. Optional query filters narrow the list. Response uses the list envelope (data + num_pages).

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
page	integer	1-based page number for paginated lists.
page_size	integer	How many rows to return per page.
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
days_ahead	integer	no	Days ahead.
status	string	no	Record status filter or value.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ],
  "num_pages": 3,
  "current_page": 1,
  "total_items": 42,
  "has_next": true,
  "has_previous": false
}
```


GET /api/reports/stock-valuation/{farm_id}/

Stock Valuation Report

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
feed_page	integer	no	Feed page.
feed_page_size	integer	no	Feed page size.
drug_page	integer	no	Drug page.
drug_page_size	integer	no	Drug page size.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

Contract

GET /api/v2/

Contract health

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/registry/

FarmOS MVP endpoint registry

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Users

GET /api/v2/users/me/

Current user operational profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

PATCH /api/v2/users/me/

Update current user profile

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
display_name	string	no	Display name.
phone	string	no	Phone.

EXAMPLE REQUEST BODY

```
{
  "display_name": "Example name",
  "phone": "08012345678"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/v2/users/{user_id}/deactivate/

Deactivate a user account

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
user_id	string (uuid)	ID of the related user.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
reason	string	no	Reason.

EXAMPLE REQUEST BODY

```
{
  "reason": "Free-text notes"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/users/{user_id}/reactivate/

Reactivate a user account

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
user_id	string (uuid)	ID of the related user.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/users/me/avatar/

Upload or replace current user avatar

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

Input type multipart/form-data (form fields, not a JSON body). If an `image` field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
avatar	string (binary)	yes	Avatar.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "avatar": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

DELETE /api/v2/users/me/avatar/

Remove current user avatar

Removes or deactivates a record identified by the path.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": null
}
```

GET /api/v2/users/me/capabilities/

Role-aware capabilities and navigation

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/users/me/activity/

Current user activity timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```


GET /api/v2/users/me/tasks/

Tasks assigned to the current user

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/users/

List organization people

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
search	string	no	Optional text filter (usually tag ID or name).

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/users/{user_id}/

Manager-visible user operational profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
user_id	string (uuid)	ID of the related user.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/users/{user_id}/activity/

Manager-visible user activity

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
user_id	string (uuid)	ID of the related user.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/users/{user_id}/tasks/

Manager-visible user tasks

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
user_id	string (uuid)	ID of the related user.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/roles/

List organization roles

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/permissions/

List permission catalog

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Organizations

GET /api/v2/organizations/{organization_id}/

Organization operational profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
organization_id	string (uuid)	UUID of the organization.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


PATCH /api/v2/organizations/{organization_id}/

Update organization profile

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
organization_id	string (uuid)	UUID of the organization.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
status	string	no	Record status filter or value.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "status": "active",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

GET /api/v2/organizations/{organization_id}/summary/

Organization summary counts

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
organization_id	string (uuid)	UUID of the organization.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/organizations/{organization_id}/activity/

Organization activity timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
organization_id	string (uuid)	UUID of the organization.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```

GET /api/v2/organizations/{organization_id}/farms/

Farms in the organization

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
organization_id	string (uuid)	UUID of the organization.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

Farms

GET /api/v2/farms/{farm_id}/

Farm profile

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

PATCH /api/v2/farms/{farm_id}/

Update farm profile

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
name	string	no	Name.
city	string	no	City.
location_address	string	no	Location address.
status	string	no	Record status filter or value.
is_primary	boolean	no	Is primary.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "name": "Example name",
  "city": "string",
  "location_address": "string",
  "status": "active",
  "is_primary": true,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

POST /api/v2/farms/{farm_id}/image/

Upload or replace a farm profile image

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

Input type multipart/form-data (form fields, not a JSON body). If an `image` field is listed, attach a file.

FORM FIELDS (INPUT)

Field	Type	Required	What to send
image	string (binary)	yes	Image.

EXAMPLE FORM VALUES (SHOWN AS JSON FOR CLARITY)

```
{
  "image": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/farms/{farm_id}/overview/

Farm operational overview

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```


GET /api/v2/farms/{farm_id}/timeline/

Farm timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
event_type	string	no	Event type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/v2/farms/{farm_id}/people/

People assigned to the farm

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/v2/farms/{farm_id}/units/

Farm housing units

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

GET /api/v2/farms/{farm_id}/alerts/

Farm attention alerts (not tasks)

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
farm_id	integer	Numeric ID of the farm this request applies to.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
status	string	no	Record status filter or value.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "North Paddock",
      "farm_code": "NP-01"
    }
  ]
}
```

Operations

POST /api/v2/operations/tasks/

Create an operations task

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
task_type	string	yes	Task type.
title	string	yes	Title.
description	string	no	Description.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
due_at	string (date-time)	no	Due at.
priority	string	no	Priority.
assignee_id	string (uuid)	no	ID of the related assignee.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "task_type": "string",
  "title": "string",
  "description": "Free-text notes",
  "animal_id": 1,
  "group_id": 1,
  "due_at": "2026-03-15T08:30:00Z",
  "priority": "string",
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

```
}  
}
```

GET /api/v2/operations/tasks/

List operations tasks

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
status	string	no	Record status filter or value.
task_type	string	no	Task type.
assigned_to_me	boolean	no	Assigned to me.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 1  
  }  
}
```

GET /api/v2/operations/tasks/{task_id}/

Task detail

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


POST /api/v2/operations/tasks/{task_id}/assign/

Assign or reassign a task

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
assignee_id	string (uuid)	yes	ID of the related assignee.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/operations/tasks/{task_id}/accept/

Accept an assigned task

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/operations/tasks/{task_id}/start/

Start a task

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/operations/tasks/{task_id}/complete/

Complete a task and write the domain record

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
notes	string	no	Notes.
evidence	string	no	Evidence.
client_request_id	string	no	ID of the related client request.
vaccine_name	string	no	Vaccine name.
date_given	string (date)	no	Date given.
next_due_date	string (date)	no	Next due date.
diagnosis	string	no	Diagnosis.
treatment	string	no	Treatment.
severity	string	no	Severity.
treatment_date	string (date)	no	Treatment date.
next_follow_up_date	string (date)	no	Next follow up date.
drug_id	integer	no	ID of the related drug.
drug_batch_id	integer	no	ID of the related drug batch.
quantity_administered	number	no	Quantity administered.
feed_inventory_id	integer	no	ID of the related feed inventory.
feed_batch_id	integer	no	ID of the related feed batch.
quantity_issued	number	no	Quantity issued.
target_type	string	no	Target type.
issue_date	string (date)	no	Issue date.
feeding_period	string	no	Feeding period.
allocation_method	string	no	Allocation method.

buyer_name	string	no	Buyer name.
price	number	no	Price.
sale_date	string (date-time)	no	Sale date.
override_reason	string	no	Required when staff override a breeding or sale restriction.
reason	string	no	Reason.
to_housing_unit_id	integer	no	ID of the related to housing unit.
to_unit_id	integer	no	ID of the related to unit.
move_date	string (date-time)	no	Move date.
symptoms	string	no	Symptoms.
observed_at	string (date-time)	no	Observed at.
case_id	integer	no	ID of the related case.
weight	number	no	Weight.
unit	string	no	Unit.
measured_at	string (date-time)	no	Measured at.
result	string	no	Result.
checked_at	string (date)	no	Checked at.
expected_delivery_date	string (date)	no	Expected delivery date.
died_at	string (date-time)	no	Died at.
cause	string	no	Cause.
related_case_id	integer	no	ID of the related related case.
performed_at	string (date-time)	no	Performed at.
device_id	string	no	ID of the related device.
recorded_at_device	string (date-time)	no	Recorded at device.
payload	any	no	Payload.

EXAMPLE REQUEST BODY

```
{
  "notes": "Free-text notes",
  "evidence": "string",
```

```

"client_request_id": "string",
"vaccine_name": "Example name",
"date_given": "2026-03-15",
"next_due_date": "2026-03-15",
"diagnosis": "string",
"treatment": "string",
"severity": "string",
"treatment_date": "2026-03-15",
"next_follow_up_date": "2026-03-15",
"drug_id": 1,
"drug_batch_id": 1,
"quantity_administered": 10.5,
"feed_inventory_id": 1,
"feed_batch_id": 1,
"quantity_issued": 10.5,
"target_type": "string",
"issue_date": "2026-03-15",
"feeding_period": "string",
"allocation_method": "string",
"buyer_name": "Example name",
"price": 10.5,
"sale_date": "2026-03-15T08:30:00Z",
"override_reason": "Free-text notes",
"reason": "Free-text notes",
"to_housing_unit_id": 1,
"to_unit_id": 1,
"move_date": "2026-03-15T08:30:00Z",
"symptoms": "string",
"observed_at": "2026-03-15T08:30:00Z",
"case_id": 1,
"weight": 10.5,
"unit": "string",
"measured_at": "2026-03-15T08:30:00Z",
"result": "string",
"checked_at": "2026-03-15",
"expected_delivery_date": "2026-03-15",
"died_at": "2026-03-15T08:30:00Z",
"cause": "string",
"related_case_id": 1,
"performed_at": "2026-03-15T08:30:00Z",
"device_id": "string",
"recorded_at_device": "2026-03-15T08:30:00Z",
"payload": null
}

```

EXAMPLE JSON RESPONSE (OUTPUT)

```

{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}

```

POST /api/v2/operations/tasks/{task_id}/cancel/

Cancel a task

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
reason	string	no	Reason.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "reason": "Free-text notes",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/operations/my-work/

My Work inbox

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```


GET /api/v2/operations/today/

Tasks due today

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/operations/overdue/

Overdue tasks

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/operations/schedules/

Task schedules

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/v2/operations/schedules/

Create a task schedule

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
farm_id	integer	yes	Numeric ID of the farm this request applies to.
task_type	string	yes	Task type.
title	string	yes	Title.
description	string	no	Description.
recurrence	string	no	Recurrence.
next_run_at	string (date-time)	yes	Next run at.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
assignee_id	string (uuid)	no	ID of the related assignee.
template_payload	any	no	Template payload.
run_now	boolean	no	Run now.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "farm_id": 1,
  "task_type": "string",
  "title": "string",
  "description": "Free-text notes",
  "recurrence": "string",
  "next_run_at": "2026-03-15T08:30:00Z",
  "animal_id": 1,
  "group_id": 1,
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "template_payload": null,
  "run_now": true,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
```

```
"message": "Request completed",
"data": {
  "id": 15
}
```

POST /api/v2/operations/schedules/{schedule_id}/run/

Generate a task from a schedule

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
schedule_id	integer	ID of the related schedule.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/operations/tasks/{task_id}/unable-to-complete/

Mark a task unable to complete

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
reason_code	string	yes	Reason code.
notes	string	no	Notes.
performed_at	string (date-time)	no	Performed at.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "reason_code": "Free-text notes",
  "notes": "Free-text notes",
  "performed_at": "2026-03-15T08:30:00Z",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/operations/tasks/{task_id}/reopen/

Reopen or reschedule unable work

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
task_id	integer	ID of the related task.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
due_at	string (date-time)	no	Due at.
assignee_id	string (uuid)	no	ID of the related assignee.
reason	string	no	Reason.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "due_at": "2026-03-15T08:30:00Z",
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "reason": "Free-text notes",
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

GET /api/v2/operations/schedules/{schedule_id}/

Schedule detail

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
schedule_id	integer	ID of the related schedule.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": [
    {
      "id": 1,
      "name": "Example"
    }
  ]
}
```


PATCH /api/v2/operations/schedules/{schedule_id}/

Update a schedule

Partially updates a record. Only send fields you want to change. Omitted fields stay as they are.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
schedule_id	integer	ID of the related schedule.

JSON BODY FIELDS (INPUT)

Field	Type	Required	What to send
title	string	no	Title.
description	string	no	Description.
recurrence	string	no	Recurrence.
next_run_at	string (date-time)	no	Next run at.
assignee_id	string (uuid)	no	ID of the related assignee.
animal_id	integer	no	Numeric ID of the animal.
group_id	integer	no	Numeric ID of the animal group.
is_active	boolean	no	Is active.
client_request_id	string	no	ID of the related client request.

EXAMPLE REQUEST BODY

```
{
  "title": "string",
  "description": "Free-text notes",
  "recurrence": "string",
  "next_run_at": "2026-03-15T08:30:00Z",
  "assignee_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "animal_id": 1,
  "group_id": 1,
  "is_active": true,
  "client_request_id": "string"
}
```

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15,
    "updated": true
  }
}
```

```
}  
}
```

POST /api/v2/operations/schedules/{schedule_id}/deactivate/

Deactivate a schedule without deleting history

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
schedule_id	integer	ID of the related schedule.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{  
  "success": true,  
  "message": "Request completed",  
  "data": {  
    "id": 15  
  }  
}
```

Timeline

GET /api/v2/timeline/

Unified organization timeline

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
farm_id	integer	no	Numeric ID of the farm this request applies to.
animal_id	integer	no	Numeric ID of the animal.
event_type	string	no	Event type.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Notifications

GET /api/v2/notifications/unread-count/

Unread notification badge count

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

GET /api/v2/notifications/

In-app notification inbox

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
page	integer	no	1-based page number for paginated lists.
page_size	integer	no	How many rows to return per page.
unread_only	boolean	no	Unread only.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

POST /api/v2/notifications/{notification_id}/read/

Mark a notification as read

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

URL PARAMETERS

Name	Type	What to send
notification_id	integer	ID of the related notification.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

POST /api/v2/notifications/read-all/

Mark all notifications as read

Creates a record. Send the input fields below. On success, data usually contains the new id or the created object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

No JSON body. Path (and optional query) parameters are the input.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 15
  }
}
```

Search

GET /api/v2/search/

Search animals, people, and tasks

Reads a record or a computed result. Path parameters identify the object.

Auth Logged-in user (access-token cookie). Farm-scoped permission checked inside the handler.

QUERY PARAMETERS (OPTIONAL UNLESS MARKED)

Name	Type	Required	What to send
q	string	yes	Q.
farm_id	integer	no	Numeric ID of the farm this request applies to.
limit	integer	no	Limit.

No JSON body. Input is the URL and any query parameters above.

EXAMPLE JSON RESPONSE (OUTPUT)

```
{
  "success": true,
  "message": "Request completed",
  "data": {
    "id": 1
  }
}
```

Generated from the Django Ninja OpenAPI schema. Regenerated by `python docs/generate_api_docs.py`.