

FarmOS v2 API Reference

Livestock Master Data Framework — Frontend Integration Guide

Base URL `/api` Auth `Authorization: Bearer <token>` Content-Type `application/json` unless noted

Paginated lists return `{ success, data[], num_pages, current_page, total_items, has_next, has_previous }`

ALL V2 ENDPOINTS

#	METHOD	ENDPOINT	DESCRIPTION	MODULE
1	POST	/admin/seed-livestock-master/	Seed all species, breeds, unit types, classifications	Admin
2	GET	/admin/livestock/species/	List all active livestock species	Admin
3	GET	/admin/livestock/breeds/{species_id}/	Breeds for a species (+ farm custom breeds)	Admin
4	POST	/admin/livestock/breeds/	Create a custom farm breed	Admin
5	PATCH	/admin/livestock/breeds/{breed_id}/	Update a custom farm breed	Admin
6	GET	/admin/livestock/housing-unit-types/{species_id}/	Housing unit types available for a species	Admin
7	GET	/admin/livestock/housing-units/{farm_id}/	All housing units on a farm	Admin
8	POST	/admin/livestock/housing-units/	Create a farm housing unit	Admin
9	PATCH	/admin/livestock/housing-units/{unit_id}/	Update a housing unit	Admin
10	GET	/admin/livestock/classifications/{species_id}/	Classifications for a species (filter by sex)	Admin
11	POST	/animals/animal/v2/	Register new animal with master data FKs	Animals
12	GET	/animals/animal/v2/{page}/{page_size}/{farm_id}	Paginated animal list with species/breed/classification	Animals
13	GET	/animals/animal-by-id/v2/{animal_id}	Single animal with raw v2 FK IDs	Animals
14	PATCH	/animals/animal/v2/{animal_id}/{farm_id}	Update animal fields + v2 FKs	Animals
15	GET	/animals/animal-profile/v2/{animal_id}	Full animal profile with housing/classification	Animals
16	GET	/animals/animal-event/v2/{page}/{page_size}/{farm_id}	Animal events enriched with livestock species/breed	Animals
17	GET	/animals/animal-weight/v2/{page}/{page_size}/{farm_id}	Weight records with species/breed/classification	Animals
18	GET	/animals/milk/v2/{page}/{page_size}/{farm_id}	Milk records with livestock species/breed	Animals
19	POST	/farm/farm-unit/v2/	Create FarmHousingUnit linked to master data	Farms
20	GET	/farm/all-farm-unit/v2/{page}/{page_size}	All org housing units with occupancy	Farms
21	GET	/farm/all-farm-unit-by-farm/v2/{page}/{page_size}/{farm_id}	Housing units for one farm with occupancy	Farms

#	METHOD	ENDPOINT	DESCRIPTION	MODULE
22	GET	/reproductions/insemination/v2/{page}/{page_size}/{farm_id}	Insemination records + livestock species/breed	Reproduction
23	GET	/reproductions/pregnancy/v2/{page}/{page_size}/{farm_id}	Pregnancy records + livestock species/breed	Reproduction
24	GET	/reproductions/birth/v2/{page}/{page_size}/{farm_id}	Birth records + species/breed on mother	Reproduction
25	POST	/reproductions/birth-offspring/v2/	Register offspring — inherits mother's v2 FKs	Reproduction
26	GET	/reproductions/birth-offspring/v2/{page}/{page_size}/{farm_id}	Offspring records + v2 species/breed/classification	Reproduction
27	GET	/health/treatment/v2/{page}/{page_size}/{farm_id}	Treatment records + livestock species/breed	Health
28	GET	/health/vaccination/v2/{page}/{page_size}/{farm_id}	Vaccination records + livestock species/breed	Health
29	GET	/health/quarantine/v2/{page}/{page_size}/{farm_id}	Quarantine records + livestock species/breed	Health
30	GET	/health/mortality/v2/{page}/{page_size}/{farm_id}	Mortality records + livestock species/breed	Health
31	POST	/feed/feed-plan/v2/	Create feed plan with livestock_species_id	Feed
32	GET	/feed/feed-plan/v2/{page}/{page_size}/{farm_id}	Feed plans with livestock species name	Feed
33	GET	/feed/feed-issue/v2/{page}/{page_size}/{farm_id}	Feed issuances with animal v2 species/breed	Feed
34	POST	/movement-records/move/v2/	Move animal between housing units	Movement
35	GET	/movement-records/moves/v2/{page}/{page_size}/{farm_id}	Movement records with housing unit names	Movement
36	GET	/movement-records/move/v2/{movement_id}	Single movement record detail	Movement
37	GET	/dashboard/main-dashboard/v2/{farm_id}	Main dashboard — species_distribution via livestock_species	Dashboard
38	GET	/dashboard/livestock-dashboard/v2/{farm_id}	Livestock dashboard — all blocks use v2 species/breed	Dashboard
39	GET	/dashboard/animal-dashboard/v2/{farm_id}	Animal dashboard — recent list with classification	Dashboard
40	GET	/dashboard/reproduction-dashboard/v2/{farm_id}	Reproduction dashboard — failed_cases with v2 species	Dashboard
41	GET	/dashboard/health-dashboard/v2/{farm_id}	Health dashboard — high_risk_alerts with v2 species	Dashboard
42	GET	/dashboard/mortality-dashboard/v2/{farm_id}	Mortality dashboard with v2 species/breed per record	Dashboard
43	GET	/dashboard/transaction-dashboard/v2/{farm_id}	Transaction dashboard — species_id filters livestock_species	Dashboard
44	GET	/dashboard/sales-dashboard/v2/{farm_id}	Sales dashboard with v2 species/breed on records	Dashboard
45	GET	/dashboard/feed-inventory-dashboard/v2/{farm_id}	Feed inventory — feed_plan_summary uses livestock_species	Dashboard

#	METHOD	ENDPOINT	DESCRIPTION	MODULE
46	GET	/dashboard/feed-plan-dashboard/v2/{farm_id}	Feed plan dashboard — search includes livestock_species name	Dashboard
47	GET	/dashboard/livestock-report-dashboard/v2/{farm_id}	Population report grouped by livestock_species	Dashboard
48	GET	/dashboard/production-report/v2/{farm_id}	Production report — species_breakdown via livestock_species	Dashboard

ADMIN — LIVESTOCK MASTER DATA

POST /admin/seed-livestock-master/			
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT	
Seeds the full default livestock master dataset. Creates 7 species (Cattle, Sheep, Goat, Pig, Poultry, Rabbit, Camel), 54 system breeds, 38 housing unit types, and 14 animal classifications. Safe to re-run — existing records are skipped. Superuser only.	No request body required.	<pre>{ "success": true, "message": "Seeded successfully", "data": { "species": 7, "breeds": 54, "unit_types": 38, "classifications": 14 } }</pre>	

GET /admin/livestock/species/			
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT	
Returns all active livestock species. Use the returned <code>id</code> as <code>livestock_species_id</code> when creating animals or feed plans.	No parameters.	<pre>{ "data": [{ "id": 1, "name": "Cattle", "category": "ruminant", "is_system": true, "is_active": true }] }</pre>	

GET /admin/livestock/breeds/{species_id}/			
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT	
Lists all active breeds for a species. Pass <code>?farm_id=</code> to also include that farm's custom breeds. ?farm_id={int} optional	Path param only.	<pre>{ "data": [{ "id": 3, "name": "Holstein Friesian", "description": null, "origin": "Netherlands", "is_system": true, "farm_id": null }] }</pre>	

POST /admin/livestock/breeds/																	
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT															
Creates a custom breed scoped to this farm. System breeds (<code>is_system: true</code>) cannot be created this way.	<table><tr><td><code>species_id</code></td><td>int</td><td>required</td></tr><tr><td><code>farm_id</code></td><td>int</td><td>required</td></tr><tr><td><code>name</code></td><td>string</td><td>required</td></tr><tr><td><code>description</code></td><td>string</td><td>optional</td></tr><tr><td><code>origin</code></td><td>string</td><td>optional</td></tr></table>	<code>species_id</code>	int	required	<code>farm_id</code>	int	required	<code>name</code>	string	required	<code>description</code>	string	optional	<code>origin</code>	string	optional	<pre>{ "success": true, "data": { "id": 42, "name": "Local Breed", "species": "Cattle", "is_system": false } }</pre>
<code>species_id</code>	int	required															
<code>farm_id</code>	int	required															
<code>name</code>	string	required															
<code>description</code>	string	optional															
<code>origin</code>	string	optional															

PATCH /admin/livestock/breeds/{breed_id}/														
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT												
Update a farm custom breed. Returns 403 for system breeds. Only the farm that created the breed may update it. All fields optional.	<table><tr><td><code>name</code></td><td>string</td><td>optional</td></tr><tr><td><code>description</code></td><td>string</td><td>optional</td></tr><tr><td><code>origin</code></td><td>string</td><td>optional</td></tr><tr><td><code>is_active</code></td><td>bool</td><td>optional</td></tr></table>	<code>name</code>	string	optional	<code>description</code>	string	optional	<code>origin</code>	string	optional	<code>is_active</code>	bool	optional	<pre>{ "success": true, "data": { "id": 42, "name": "Updated Name", "is_active": true } }</pre>
<code>name</code>	string	optional												
<code>description</code>	string	optional												
<code>origin</code>	string	optional												
<code>is_active</code>	bool	optional												

GET /admin/livestock/housing-unit-types/{species_id}/		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Lists all housing unit types for a given species. Use the returned <code>id</code> as <code>housing_unit_type_id</code> when creating farm housing units.	Path param only.	<pre>{ "data": [{ "id": 2, "name": "Barn", "is_system": true, "is_active": true }] }</pre>

GET /admin/livestock/housing-units/{farm_id}/		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
All farm housing units with live occupancy count and allowed species list. Filter by species using query param. <code>?species_id={int}</code> optional	Path param + optional query param.	<pre>{ "data": [{ "id": 5, "name": "Barn A", "unit_type": "Barn", "unit_type_id": 2, "capacity": 50, "occupancy": 23, "location": "North block", "status": "active", "allowed_species": ["Cattle"] }] }</pre>

POST /admin/livestock/housing-units/																				
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT																		
Creates a housing unit on a farm, linked to a unit type from master data. Optionally restricts which species may be housed here.	<table><tr><td>farm_id</td><td>int</td><td>required</td></tr><tr><td>name</td><td>string</td><td>required</td></tr><tr><td>housing_unit_type_id</td><td>int</td><td>required</td></tr><tr><td>capacity</td><td>int</td><td>optional</td></tr><tr><td>location</td><td>string</td><td>optional</td></tr><tr><td>allowed_species_ids</td><td>int[]</td><td>optional</td></tr></table>	farm_id	int	required	name	string	required	housing_unit_type_id	int	required	capacity	int	optional	location	string	optional	allowed_species_ids	int[]	optional	<pre>{ "success": true, "data": { "id": 5, "name": "Barn A", "unit_type": "Barn", "capacity": 50 } }</pre>
farm_id	int	required																		
name	string	required																		
housing_unit_type_id	int	required																		
capacity	int	optional																		
location	string	optional																		
allowed_species_ids	int[]	optional																		

PATCH /admin/livestock/housing-units/{unit_id}/																	
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT															
Update a housing unit. Passing <code>allowed_species_ids</code> replaces the existing list entirely. All fields optional.	<table><tr><td>name</td><td>string</td><td>optional</td></tr><tr><td>capacity</td><td>int</td><td>optional</td></tr><tr><td>allowed_species_ids</td><td>int[]</td><td>optional</td></tr><tr><td>location</td><td>string</td><td>optional</td></tr><tr><td>status</td><td>active inactive</td><td>optional</td></tr></table>	name	string	optional	capacity	int	optional	allowed_species_ids	int[]	optional	location	string	optional	status	active inactive	optional	<pre>{ "success": true, "data": { "id": 5, "name": "Barn A", "capacity": 60, "status": "active" } }</pre>
name	string	optional															
capacity	int	optional															
allowed_species_ids	int[]	optional															
location	string	optional															
status	active inactive	optional															

GET /admin/livestock/classifications/{species_id}/		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Lists animal classifications for a species (e.g. Bull, Heifer, Ram, Ewe). Filter by sex to show only classifications valid for the animal's gender before the user picks one. <code>?sex=male female</code> optional	Path param + optional query param.	<pre>{ "data": [{ "id": 1, "name": "Bull", "sex": "male", "is_system": true }] }</pre>

ANIMALS V2

Registration flow: 1. GET species → 2. GET breeds?farm_id= → 3. GET housing-unit-types → GET housing-units → 4. GET classifications?sex= → 5. POST /animals/animal/v2/ with the four IDs. All v2 list responses include species/breed fallback for animals registered via v1.

POST /animals/animal/v2/ Content-Type: multipart/form-data		
DESCRIPTION	PAYLOAD / INPUT (FORM-DATA)	RESPONSE / OUTPUT
Register a new animal using master data FKs. Validates that breed belongs to species, housing unit supports species, and classification sex matches gender. Writes both v2 and legacy FKs so v1 endpoints remain functional.	farm_id int required	<pre>{ "success": "data": { "id": 101, "tag_id": "TAG-001", "gender": "ma "species": "Cattle", "br "Holstein Fri "housing_unit "Barn A", "housing_unit "Barn", "classificati "Bull", "stat "active" } }</pre> 422 if: breed $\notin$ s housing unit $\notin$ f doesn't support classification se gender
	tag_id string required	
	livestock_species_id int required v2	
	livestock_breed_id int required v2	
	housing_unit_id int required v2	
	gender male female required	
	status active pregnant lactating sick quarantine sold dead required	
	source born purchased imported required	
	health_status healthy sick recovering at_risk required	
	is_pregnant bool required	
	is_lactating bool required	
	is_quarantine bool required	
	is_active bool required	
	classification_id int optional v2	
	dob YYYY-MM-DD optional	
	estimated_age_months int optional	
	mother_id int optional	
	notes string optional	
	image file optional	

GET /animals/animal/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Paginated animal list. Uses livestock_species/breed as primary with fallback to legacy species/breed for v1 animals.	Path params only.	<pre>{ "data": [{ "id", "tag_id", "gender", "status", "species": "Cattle", /* v2: livestock_species */ "breed": "Holstein", /* v2: livestock_breed */ "housing_unit": "Barn A", /* v2 new */ "housing_unit_type": "Barn", /* v2 new */ "classification": "Bull", /* v2 new */ "dob", "estimated_age_months", "health_status", "is_pregnant", "is_lactating", "is_quarantine", "mother_tag", "is_active" }], "num_pages", "total_items", ... }</pre>

GET /animals/animal-by-id/v2/{animal_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Returns a single animal with all v2 fields including the raw FK IDs, useful when pre-populating an edit form.	Path param only.	<pre>{ "data": { ...same as list item..., "livestock_species_id": 1, "livestock_breed_id": 3, "housing_unit_id": 5, "classification_id": 2 } }</pre>

PATCH /animals/animal/v2/{animal_id}/{farm_id}			
DESCRIPTION	PAYLOAD / INPUT (JSON)		
Update any animal fields. When v2 FKs are changed, the corresponding legacy FKs are also updated so v1 endpoints stay consistent. All fields optional.	livestock_species_id	int	optional v2
	livestock_breed_id	int	optional v2
	housing_unit_id	int	optional v2
	classification_id	int	optional v2
	tag_id	string	optional
	gender	male female	optional
	status	string	optional
	health_status	string	optional
	dob	YYYY-MM-DD	optional
	estimated_age_months	int	optional
	mother_id	int	optional
	is_pregnant, is_lactating, is_quarantine, is_active	bool	optional
	notes	string	optional
			<pre>{ "success": true, "message": "Animal updated", "data": { ... updated animal fields ... } }</pre>

GET /animals/animal-profile/v2/{animal_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Returns the full animal profile page data. All identification fields use v2 livestock FKs with legacy fallback. Includes housing unit and classification in the card section.	Path param only.	<pre>{ "data": { "card": { "tag_id", "species", "breed", "classification", "housing_unit", "housing_unit_type", "gender", "status", "age_months", "lifecycle_label", "image_url" }, "overview": { "species", "breed", "classification", "housing_unit", "housing_unit_type", "mother_tag", "source", "farm", "entry_date" }, "reproduction": { "last_insemination_date", "expected_delivery_date", "pregnancy_status" }, "production": { "lactation_status", "milk_production_today" }, "health": { "health_status", "is_quarantine", "last_vaccination", "last_treatment" }, "movement": { "last_move_date", "from_unit", "to_unit" } } }</pre>

GET /animals/animal-event/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED FIELDS
Same as v1 animal events list but each row's animal object includes livestock_species and livestock_breed (with legacy fallback).	Path params only.	<pre>/* added on each record's animal object */ "livestock_species": "Cattle", /* v2 new */ "livestock_breed": "Holstein" /* v2 new */</pre>

GET /animals/animal-weight/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED FIELDS
Weight records with v2 species, breed, and classification added to each row's animal context.	Path params only.	<pre>"livestock_species": "Cattle", "livestock_breed": "Holstein", "classification": "Bull"</pre>

GET /animals/milk/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED FIELDS
Milk records with livestock species/breed added per row.	Path params only.	<pre>"livestock_species": "Cattle", "livestock_breed": "Holstein"</pre>

POST /farm/farm-unit/v2/																				
DESCRIPTION	PAYLOAD / INPUT (JSON)	RESPONSE / OUTPUT																		
Creates a FarmHousingUnit linked to a HousingUnitType from master data. Optional allowed_species restricts which animals can be assigned to this unit.	<table><tr><td>farm_id</td><td>int</td><td>required</td></tr><tr><td>name</td><td>string</td><td>required</td></tr><tr><td>housing_unit_type_id</td><td>int</td><td>required</td></tr><tr><td>capacity</td><td>int</td><td>optional</td></tr><tr><td>location</td><td>string</td><td>optional</td></tr><tr><td>allowed_species_ids</td><td>int[]</td><td>optional</td></tr></table>	farm_id	int	required	name	string	required	housing_unit_type_id	int	required	capacity	int	optional	location	string	optional	allowed_species_ids	int[]	optional	<pre>{ "success": true, "data": { "id": 5, "name": "Barn A", "unit_type": "Barn", "capacity": 50, "occupancy": 0, "allowed_species": ["Cattle"] } }</pre>
farm_id	int	required																		
name	string	required																		
housing_unit_type_id	int	required																		
capacity	int	optional																		
location	string	optional																		
allowed_species_ids	int[]	optional																		

GET /farm/all-farm-unit/v2/{page}/{page_size} GET /farm/all-farm-unit-by-farm/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
List all housing units across the org, or filter by farm. Key v2 addition: occupancy (live animal count) and allowed_species (name list) are included on every row.	Path params only.	<pre>{ "data": [{ "id", "name", "farm", "unit_type", "unit_type_id", "capacity": 50, "occupancy": 23, /* v2 new */ "location", "status", "allowed_species": ["Cattle"] /* v2 new */ }] }</pre>

REPRODUCTION V2

All list endpoints in this section add **species**, **breed**, and **classification** to the animal object using **livestock_species/breed** as primary with legacy fallback.

GET /reproductions/insemination/v2/{page}/{page_size}/{farm_id} GET /reproductions/pregnancy/v2/... GET /reproductions/birth/v2/...		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED PER ROW
Insemination, pregnancy, and birth list endpoints. Identical to v1 in structure, with v2 species/breed/classification appended on the animal object per row. For birth, enrichment applies to the mother animal.	Path params only.	<pre>/* on each row's animal object */ "species": "Cattle", /* v2: livestock_species */ "breed": "Holstein", /* v2: livestock_breed */ "classification": "Cow" /* v2 new */</pre>

POST /reproductions/birth-offspring/v2/																	
DESCRIPTION	PAYLOAD / INPUT (JSON)	RESPONSE / OUTPUT															
Register a new offspring. Key v2 change: the created offspring animal automatically inherits the mother's <code>livestock_species</code> , <code>livestock_breed</code> , and <code>housing_unit</code> v2 FKs. Same payload as v1.	<table> <tr> <td><code>birth_id</code></td><td>int</td><td>required</td></tr> <tr> <td><code>tag_id</code></td><td>string</td><td>required</td></tr> <tr> <td><code>gender</code></td><td>male female</td><td>required</td></tr> <tr> <td><code>health_status</code></td><td>string</td><td>required</td></tr> <tr> <td><code>notes</code></td><td>string</td><td>optional</td></tr> </table>	<code>birth_id</code>	int	required	<code>tag_id</code>	string	required	<code>gender</code>	male female	required	<code>health_status</code>	string	required	<code>notes</code>	string	optional	<pre>{ "success": true, "data": { "offspring_id": 202, "tag_id": "CALF-001", "species": "Cattle", /* inherited */ "breed": "Holstein", /* inherited */ "housing_unit": "Barn A" /* inherited */ } }</pre>
<code>birth_id</code>	int	required															
<code>tag_id</code>	string	required															
<code>gender</code>	male female	required															
<code>health_status</code>	string	required															
<code>notes</code>	string	optional															

GET /reproductions/birth-offspring/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED PER ROW
Lists offspring records. v2 enrichment applies to the offspring animal. Note: field corrected from <code>mother_tag</code> (v1 bug) to <code>offspring_tag</code> .	Path params only.	<pre>"offspring_tag": "CALF-001", /* fixed name */ "species": "Cattle", "breed": "Holstein", "classification": "Heifer"</pre>

HEALTH V2

All four list endpoints add `species`, `breed`, and `classification` to each row's animal object (livestock_species/breed → legacy fallback).

GET GET /health/treatment/v2/... GET /health/vaccination/v2/... GET /health/quarantine/v2/... GET /health/mortality/v2/...		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED PER ROW
All health list endpoints follow the same v2 pattern. Path format: <code>/health/{endpoint}/v2/{page}/{page_size}/{farm_id}</code> . Response is identical to v1 with <code>species/breed/classification</code> enrichment added to the animal object on each row.	Path params only.	<pre>/* on each row's animal object */ "species": "Cattle", "breed": "Holstein", "classification": "Bull"</pre>

FEED V2

POST /feed/feed-plan/v2/																																			
DESCRIPTION	PAYLOAD / INPUT (JSON)	RESPONSE / OUTPUT																																	
Creates a feed plan. v2 adds livestock_species_id as the preferred species FK for species-type plans. Legacy species_id still accepted.	<table><tr><td>farm_id</td><td>int</td><td>required</td></tr><tr><td>plan_type</td><td>species group</td><td>required</td></tr><tr><td>feed_inventory_id</td><td>int</td><td>required</td></tr><tr><td>daily_feed_quantity</td><td>decimal</td><td>required</td></tr><tr><td>unit</td><td>string</td><td>required</td></tr><tr><td>start_date</td><td>YYYY-MM-DD</td><td>required</td></tr><tr><td>livestock_species_id</td><td>int</td><td>optional v2</td></tr><tr><td>species_id</td><td>int</td><td>optional</td></tr><tr><td>group_id</td><td>int</td><td>optional</td></tr><tr><td>end_date</td><td>YYYY-MM-DD</td><td>optional</td></tr><tr><td>status</td><td>active inactive completed</td><td>optional</td></tr></table>	farm_id	int	required	plan_type	species group	required	feed_inventory_id	int	required	daily_feed_quantity	decimal	required	unit	string	required	start_date	YYYY-MM-DD	required	livestock_species_id	int	optional v2	species_id	int	optional	group_id	int	optional	end_date	YYYY-MM-DD	optional	status	active inactive completed	optional	<pre>{ "success": true, "data": { "id": 10, "plan_type": "species", "livestock_species": "Cattle", "daily_feed_quantity": "5.00", "unit": "kg", "status": "active" } }</pre>
farm_id	int	required																																	
plan_type	species group	required																																	
feed_inventory_id	int	required																																	
daily_feed_quantity	decimal	required																																	
unit	string	required																																	
start_date	YYYY-MM-DD	required																																	
livestock_species_id	int	optional v2																																	
species_id	int	optional																																	
group_id	int	optional																																	
end_date	YYYY-MM-DD	optional																																	
status	active inactive completed	optional																																	

GET /feed/feed-plan/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED FIELD
Feed plan list. v2 adds livestock_species name resolved from the new FK with fallback to legacy species.	Path params only.	<pre>"livestock_species": "Cattle" /* v2 new, with fallback */</pre>

GET /feed/feed-issue/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED PER ANIMAL
Feed issuance records. For animal-type issuances, each row's animal object gains v2 species, breed, and classification.	Path params only.	<pre>"species": "Cattle", "breed": "Holstein", "classification": "Bull"</pre>

MOVEMENT RECORDS V2

POST /movement-records/move/v2/																							
DESCRIPTION	PAYLOAD / INPUT (JSON)	RESPONSE / OUTPUT																					
Records a movement between housing units. On success, updates <code>animal.housing_unit</code> to the destination unit so the animal's v2 location stays current.	<table> <tr> <td><code>farm_id</code></td><td>int</td><td>required</td></tr> <tr> <td><code>from_housing_unit_id</code></td><td>int</td><td>required v2</td></tr> <tr> <td><code>to_housing_unit_id</code></td><td>int</td><td>required v2</td></tr> <tr> <td><code>move_date</code></td><td>datetime</td><td>required</td></tr> <tr> <td><code>animal_id</code></td><td>int</td><td>optional</td></tr> <tr> <td><code>group_id</code></td><td>int</td><td>optional</td></tr> <tr> <td><code>reason</code></td><td>string</td><td>optional</td></tr> </table>	<code>farm_id</code>	int	required	<code>from_housing_unit_id</code>	int	required v2	<code>to_housing_unit_id</code>	int	required v2	<code>move_date</code>	datetime	required	<code>animal_id</code>	int	optional	<code>group_id</code>	int	optional	<code>reason</code>	string	optional	<pre>{ "success": true, "data": { "id": 30, "from_unit": "Barn A", "to_unit": "Paddock B", "unit_type": "Barn", "move_date": "2025-07-16T09:00:00Z" } }</pre>
<code>farm_id</code>	int	required																					
<code>from_housing_unit_id</code>	int	required v2																					
<code>to_housing_unit_id</code>	int	required v2																					
<code>move_date</code>	datetime	required																					
<code>animal_id</code>	int	optional																					
<code>group_id</code>	int	optional																					
<code>reason</code>	string	optional																					

GET /movement-records/moves/v2/{page}/{page_size}/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ADDED FIELDS
Movement record list enriched with housing unit names and types. Uses <code>from_housing_unit</code> / <code>to_housing_unit</code> as primary with fallback to legacy <code>from_unit</code> / <code>to_unit</code> .	Path params only.	<pre>"from_unit": "Barn A", "to_unit": "Paddock B", "from_unit_id": 5, "to_unit_id": 8, "unit_type": "Barn" /* v2 new */</pre>

GET /movement-records/move/v2/{movement_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT
Single movement record detail with same v2 housing unit enrichment as the list endpoint.	Path param only.	<pre>{ "data": { ...same fields as list row... } }</pre>

DASHBOARD V2

v2 dashboard key change: All species groupings and `species_id` filter params now target `livestock_species_id` instead of the legacy `species_id` FK. Animals registered via v1 without a `livestock_species` will not appear in grouped breakdowns — migrate them first using the PATCH animal endpoint.

GET /dashboard/main-dashboard/v2/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — CHANGED BLOCK
Main overview dashboard. Identical to v1 except species_distribution is grouped by <code>livestock_species_id / name</code> .	Path param only.	<pre>"species_distribution": [{ "livestock_species_id": 1, "livestock_species__name": "Cattle", "count": 45 }]</pre>

GET /dashboard/livestock-dashboard/v2/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — ENRICHED BLOCKS
Livestock-focused dashboard. All blocks use v2 species/breed: <code>recent_animals</code> includes classification, health_risks and <code>ready_for_sale</code> use livestock FK fallback, <code>population_trend</code> groups by livestock species.	Path param only.	<pre>"recent_animals": [{ "species", "breed", "classification" }] "population_trend": { "labels": ["Jan",...], "by_species": { "Cattle": [...] } }</pre>

GET /dashboard/animal-dashboard/v2/{farm_id} GET /dashboard/reproduction-dashboard/v2/{farm_id} GET /dashboard/health-dashboard/v2/{farm_id} GET /dashboard/mortality-dashboard/v2/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — V2 CHANGE PER ENDPOINT
Animal: <code>recent_animals</code> gets species/breed/classification. Reproduction: <code>failed_cases</code> use livestock fallback. Health: <code>high_risk_alerts</code> use livestock fallback. Mortality: each record's species/breed from livestock FKs.	Path param only. No body.	<pre>/* animal-dashboard */ "recent_animals": [{ ..., "classification": "Bull" }] /* reproduction-dashboard */ "failed_cases": [{ "species": "Cattle", ... }] /* health- dashboard */ "high_risk_alerts": [{ "species": "Cattle", ... }] /* mortality- dashboard */ "records": [{ "species": "Cattle", "breed": "Holstein" }]</pre>

GET /dashboard/transaction-dashboard/v2/{farm_id} GET /dashboard/sales-dashboard/v2/{farm_id}		
DESCRIPTION	PAYLOAD / INPUT	RESPONSE / OUTPUT — CHANGED GROUPING
Transaction and sales dashboards. v2 key change: <code>?species_id=</code> now filters by <code>animal__livestock_species_id</code> . Exit summary and sales records use livestock species/breed with fallback.	<pre>?species_id={int} ?status= ? date_from= ?date_to= ?search=</pre>	<pre>"exit_summary": [{ "animal__livestock_species_id": 1, "animal__livestock_species__name": "Cattle", "count": 12 }]</pre>

GET /dashboard/feed-inventory-dashboard/v2/{farm_id} dashboard/v2/{farm_id} GET /dashboard/feed-plan-		
DESCRIPTION Feed inventory: feed_plan_summary target name uses livestock_species → species → group fallback. Feed plan: search now matches livestock_species__name in addition to plan fields.	PAYLOAD / INPUT ?plan_type= ?status= ?search= {string}	RESPONSE / OUTPUT — CHANGED FIELD "feed_plan_summary": [{ "target_name": "Cattle", /* livestock → legacy */ "animal_count": 45, ... }]

GET /dashboard/livestock-report-dashboard/v2/{farm_id} report/v2/{farm_id} GET /dashboard/production-		
DESCRIPTION Livestock report: population_by_species and species_breakdown use livestock_species grouping. Production report: species_breakdown groups by animal__livestock_species. Both accept pagination.	PAYLOAD / INPUT ?page=1 ?page_size=10	RESPONSE / OUTPUT — CHANGED BLOCK "species_breakdown": [{ "livestock_species__id": 1, "livestock_species__name": "Cattle", "count": 45 }]