

API Documentation

Overview

- **API Endpoint:** `https://api.blackmamba.mobi/ashx/CheckAccount.ashx`
- **Supported Methods:** POST, GET (POST is recommended)
- **Authentication:** Authentication is performed using `keyAgent` (authorized operator) and `ApiKey` (authorization key).

API Endpoints

1. Add Player Account

- **Purpose:** To add a new player account.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter <code>adduser</code> .
keyAgent	Yes	Agent account associated with the operator's ApiKey.
agent	Yes	The player's superior Agent account.
userPwd	No	Player's login password, <code>String</code> data type, must not exceed 15 characters in length. (If not provided, a random password will be returned; if provided, the given password will be used as the registration password.)
scoreNum	No	Score (greater than or equal to 0; if a value is passed, it will add the specified score to the currently registered player by default)
time	Yes	A 13-digit timestamp.

Parameter	Required	Description
token	Yes	sA 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper.
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=addUser&token=DASDF44C06F63CD17751F47BB1B43DD5&userPwd=123456&time=170651
3506526&keyAgent=test&agent=testagent&ts=0.7216318002132696
```

- **Response Example:**

```
{
  "code": 0,
  "account": "22454122",
  "password": "437479",
  "msg": "ok.",
  "success": true
}
```

- **Response Codes:**

- code=0 : Success
- code=-10 : Incorrect action
- code=-99 : Token signature error
- code=-10001 : Request too frequent
- code=-107 : Incorrect hierarchy level
- code=-120 : Exception error

2. Change Player Score

Description: Increase or decrease a player's score. To control this more accurately and securely, the original interface has been split into four independent interfaces.

Order Number: The concept of order number has been added to prevent multiple requests of the same operation due to network communication failures or delays. Therefore, each request carries a unique order number to distinguish whether it is multiple requests of the same operation.

2.1. Increase/Decrease Player's ENTRIES

- Purpose: Increase or decrease a player's ENTRIE points.
- Parameters:

Parameter	Required	Description
action	Yes	Fixed parameter <code>setEntries</code> .
keyAgent	Yes	The agent account associated with the operator's ApiKey.
agent	No	The player's superior Agent account . If this parameter is passed, it must be the player's direct agent, otherwise an error will be returned.
account	Yes	The player's account.
scoreNum	Yes	The score to operate on; a positive number means increase, a negative number means decrease.
orderId	Yes	The order number for the current operation, within 25 characters.
time	Yes	13-digit timestamp.
token	Yes	A 32-character uppercase string, signature = MD5(keyAgent+ApiKey+time).ToUpper().
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=setEntries&token=C2BE16DE0B46247CDDFEA99B4E96797F&time=1711193709520&keyA
gent=demo&account=123456&scoreNum=10&orderId=123456_1711193709520&ts=0.820857005
2643074
```

- **Response Example:**

```
{
  "code": 0,
  "account": "123456",
  "scoreNum": "10",
  "msg": "ok.",
  "success": true
}
```

- **Response Codes:**

- `code=0` : Success
- `code=-10` : Action error
- `code=-99` : Token signature error

- `code=-10001` : Too many requests
- `code=-10002` : Network connection failure
- `code=-10003` : Score error
- `code=-10009` : agent error
- `code=-102` : Can only set scores for one's subordinates
- `code=-107` : Hierarchy level error
- `code=-120` : Interface exception

2.2. Increase/Decrease Player's WINNING

- Purpose: Increase or decrease a player's WINNING points.
- Parameters:

Parameter	Required	Description
action	Yes	Fixed parameter <code>setwinning</code> .
keyAgent	Yes	The agent account associated with the operator's ApiKey.
agent	No	The player's superior Agent account . If this parameter is passed, it must be the player's direct agent, otherwise an error will be returned.
account	Yes	The player's account.
scoreNum	Yes	The score to operate on; a positive number means increase, a negative number means decrease.
orderId	Yes	The order number for the current operation, within 25 characters.
time	Yes	13-digit timestamp.
token	Yes	A 32-character uppercase string, signature = MD5(keyAgent+ApiKey+time).ToUpper().
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=setwinning&token=093F1AF0709C9F82DA63F0FA8D227F14&time=1711194443756&keyA
gent=demo&account=123456&scoreNum=10&orderId=123456_1711194443756&ts=0.408777581
4724477
```

- **Response Example:**

```
{
  "code": 0,
  "account": "123456",
  "scoreNum": "10",
  "msg": "ok.",
  "success": true
}
```

- **Response Codes:**

- `code=0` : Success
- `code=-10` : Action error
- `code=-99` : Token signature error
- `code=-10001` : Too many requests
- `code=-10002` : Network connection failure
- `code=-10003` : Score error
- `code=-10009` : agent error
- `code=-102` : Can only set scores for one's subordinates
- `code=-107` : Hierarchy level error
- `code=-120` : Interface exception

2.3. Reset Player's Score

- Purpose: Completely reset the score of a specified player to zero.
- Parameters:

Parameter	Required	Description
action	Yes	Fixed parameter <code>clearScore</code> .
keyAgent	Yes	The agent account associated with the operator's ApiKey.
agent	No	The player's superior Agent account . If this parameter is passed, it must be the player's direct agent, otherwise an error will be returned.
account	Yes	The player's account.
time	Yes	13-digit timestamp.
token	Yes	A 32-character uppercase string, signature = MD5(keyAgent+ApiKey+time).ToUpper().
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=clearScore&token=F1D5D399EFBF51622A5914A7AB22DA2F&time=1711194895054&
keyAgent=demo&account=123456&ts=0.8137611040483206
```

- **Response Example:**

```
{
  "code": 0,
  "account": "123456",
  "scoreNum": "0",
  "msg": "ok.",
  "success": true
}
```

◦ **Response Codes:**

- `code=0` : Success
- `code=-10` : Action error
- `code=-99` : Token signature error
- `code=-10001` : Too many requests
- `code=-10002` : Network connection failure
- `code=-10003` : Score error
- `code=-10009` : agent error
- `code=-102` : Can only set scores for one's subordinates
- `code=-107` : Hierarchy level error
- `code=-120` : Interface exception

2.4. Special Bonus Points

- Purpose: Award extra bonus type points to a player.
- Parameters:

Parameter	Required	Description
action	Yes	Fixed parameter <code>setSpecial</code> .

Parameter	Required	Description
keyAgent	Yes	The agent account associated with the operator's ApiKey.
agent	No	The player's superior Agent account . If this parameter is passed, it must be the player's direct agent, otherwise an error will be returned.
account	Yes	The player's account.
scoreNum	Yes	The score to operate on
orderId	Yes	The order number for the current operation, within 25 characters.
time	Yes	13-digit timestamp.
token	Yes	A 32-character uppercase string, signature = MD5(keyAgent+ApiKey+time).ToUpper().
ts	No	A random number.

◦ **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=setSpecial&token=AF76FE2F9B28852838DFE82FAAC7CD63&time=1711195334955&
keyAgent=demo&account=123456&scoreNum=16&orderId=123456_1711195334955&ts=0.7
117210640479243
```

◦ **Response Example:**

```
{
  "code": 0,
  "account": "123456",
  "scoreNum": "16",
  "msg": "ok.",
  "success": true
}
```

◦ **Response Codes:**

- code=0 : Success
- code=-10 : Action error
- code=-99 : Token signature error
- code=-10001 : Too many requests
- code=-10002 : Network connection failure
- code=-10003 : Score error
- code=-10009 : agent error
- code=-102 : Can only set scores for one's subordinates
- code=-107 : Hierarchy level error
- code=-120 : Interface exception

3. Validate Player Account and Return Basic Score Information

- **Purpose:** To verify a player's account and password, returning their basic score information.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter <code>getUserInfo</code> .
keyAgent	Yes	The agent who possesses the ApiKey.
account	Yes	Player's account.
userPwd	Yes	Player's password.
time	Yes	A 13-digit timestamp.
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper.
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=getUserInfo&token=9487C03B48D5E9E4C357A8FF6E78587A&time=1707735960950&key
Agent=demo&account=123456&userPwd=112233&ts=0.49706100745098714
```

- **Response Example:**

```
{
  "account": "123456",
  "agent": "sales006", //Player's agent
  "code": 0,
  "entries": "8.4", //The player's entries
  "id": 27092, //The player's system ID
  "msg": "",
  "name": "adas",
  "state": 1,
  "success": true,
  "totalPay": "184.97", //The amount of the player's cumulative deposit
  "winning": "37.43", //Player's WINNING
  "isFirstPay": 0 // Indicates whether a recharge has been made today, 0: No
  recharge has been made, and recharge can enjoy the first recharge benefit; 1:
  Recharge has been made today, and the first recharge benefit cannot be activated
  again
}
```

- **Response Codes:**

- `code=0`: Success
- `code=-10`: Incorrect action
- `code=-99`: Token signature error

- `code=-101`: Incorrect player account
- `code=-102`: Incorrect account string length
- `code=-103`: Player password cannot be empty
- `code=-104`: Incorrect password string length
- `code=-1001`: Password not received
- `code=-1003`: Password does not match
- `code=-1002`: Account not found
- `code=-10002`: Network connection failed
- `code=-10001`: Request too frequent
- `code=-120`: API exception
- Other codes indicate the account does not exist

4. Reset the player's password

- **Purpose:** Reset the user's account password to the specified content.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter <code>resetUserPwd</code> .
keyAgent	Yes	The agent who possesses the ApiKey.
account	Yes	Player's account.
userPwd	Yes	Player's new password. Strings between 6 and 15 bits.
time	Yes	A 13-digit timestamp.
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper.
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=resetUserPwd&token=FCDF6DFAC9FA751461EFC64E20AF3C50&time=1709799307593&ke
yAgent=demo&account=1234567&userPwd=123456&ts=0.6835565623237503
```

- **Response Example:**

```
{
  "success": true,
  "msg": "OK",
  "pwd": "123456",
  "code": 0
}
```

- **Response Codes:**

- `code=0`: Success
- `code=-10`: Incorrect action

- `code=-99` : Token signature error
- `code=-101` : Incorrect player account
- `code=-102` : Incorrect account string length
- `code=-103` : Player password cannot be empty
- `code=-104` : Wrong length of player password string, must be greater than 6 and less than 15
- `code=-10002` : Network connection failed
- `code=-10001` : Request too frequent
- `code=-120` : API exception
- Other codes indicate the account does not exist

5. Get the current player's rechargeable credit

- **Purpose:** According to the player, the remaining points of the agent are obtained to prevent the problem that the agent balance is not enough to deduct after the player scores points.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter <code>getAgentScore</code> .
keyAgent	Yes	The agent who possesses the ApiKey.
account	Yes	Player's account.
time	Yes	A 13-digit timestamp.
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper.
ts	No	A random number.

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=getAgentScore&token=6C09C2066AF4388982B71EDD0CA71E36&time=1710586776074&keyAgent=demo&account=123456&ts=0.7089119051374082
```

- **Response Example:**

```
{
  "success": true,
  "msg": "OK",
  "maxScore": "10027.06",
  "code": 0
}
```

Response Codes:

- `code=0` : Success
- `code=-10` : Incorrect action
- `code=-90` : Failed to get scores
- `code=-99` : Token signature error

- `code=-101`: Incorrect player account
- `code=-102`: Incorrect account string length
- `code=-10002`: Network connection failed
- `code=-10001`: Request too frequent
- `code=-120`: API exception
- Other codes indicate the account does not exist

6. Implement One-Click Automatic Player Login via URL Parameters

- **Purpose:** Enable players to log in automatically without manual input by adding parameters to the access link.
- **Request Parameters:**

Parameter	Required	Description
acc	Yes	represents the player's game account
pw	Yes	the 32-bit MD5 hash of the player's login password

- **Example Request:**

```
https://blackmamba.mobi/?acc=1232342&pw=75023D2DA3F83AB2AF033AC6273BD6
```

- **Response Example:**

No response is returned. If successful, the player is directly logged into the game. If unsuccessful, the `default` game login process is initiated.

7. Get Player's Score Log for the Last 7 Days

- **Purpose:** Retrieve the player's score adjustment record for the past 7 days.
- **Request Parameters:**

Parameter	Required	Description
-----------	----------	-------------

Parameter	Required	Description
action	Yes	Fixed parameter <code>getScoreLog</code>
keyAgent	Yes	The agent who possesses the ApiKey
account	Yes	Player's account
pageIndex	Yes	Page number for pagination
pageSize	No	Default 20 items per page
time	Yes	A 13-digit timestamp
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper
ts	No	A random number

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=getScoreLog&token=745D7AFB0865BD00008F5185B1FD041F&time=1727953510825&key
Agent=demo&account=12345678&pageIndex=1&ts=0.8616495999191078
```

- **Response Example:**

```
{
  "dbScoreNum": "0",
  "dbcount": 0,
  "forderId": "",
  "ftime": 0,
  "msg": "ok",
  "psize": 0,
  "rdAll": 0,
  "rdDel": 0,
  "rdScoreNum": "0",
  "rdTotalCount": 0,
  "redissize": 0,
  "results": [
    {
      "Account": "demo",
      "ActionIP": "127.0.0.1",
      "Action_Type": 0,
      "AfterNum": "10.07",
      "C_DateTime": "2024-10-03 17:59:43.463",
      "Index_NO": 6997569,
      "OrderId": "202410031759438096149381457452",
      "Rownum": 1,
      "ScoreNum": "10",
      "UserName": "12345678"
    }
  ],
  "success": true,
  "total": 1,
  "totalScore": "10",
}
```

```
"totalSum": "10",
"useredis": 0
}
```

- **Response Codes:**

- code=0 : Success
- code=-10 : Incorrect action
- code=-99 : Token signature error
- code=-101 : Incorrect player account
- code=-10002 : Network connection failed
- code=-10001 : Request too frequent
- code=-120 : API exception

8. Get Login and Registration URL

- **Purpose:** Obtain the login and registration URL for players.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter getSkeyUr1
keyAgent	Yes	The agent who possesses the ApiKey
agent	Yes	The player's upper-level agent account
time	Yes	A 13-digit timestamp
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper
ts	No	A random number

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=getSkeyUr1&token=1704EAC51E8EA193DA0357D9B3E944BE&time=1728479854084&keyA
gent=demo&agent=salusa01&ts=0.883180280625462
```

- **Response Example:**

```
{
  "success": true,
  "id": 0,
  "msg": "ok",
  "url": "https://blackmamba.mobi/?skey=C19F2FF1D573B2D486EC259D5A0350E4",
  "code": 0
}
```

- **Response Codes:**

- code=0 : Success
- code=-10 : Incorrect action

- `code=-99` : Token signature error
- `code=-101` : Incorrect agent account
- `code=-103` : Failed
- `code=-104` : Agent account has no QR code
- `code=-10002` : Network connection failed
- `code=-10001` : Request too frequent
- `code=-120` : API exception

9. Check agent account balance

- **Purpose:** Check the available balance of the corresponding agent account.
- **Request Parameters:**

Parameter	Required	Description
action	Yes	Fixed parameter <code>getAgentBalance</code>
keyAgent	Yes	The agent who possesses the ApiKey
agent	Yes	Agent account
time	Yes	A 13-digit timestamp
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper
ts	No	A random number

- **Example Request:**

```
http://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=getAgentBalance&token=A857B52EEC5172F61B16A26DB5A3C919&time=1747832637700
&keyAgent=demo&agent=demo&ts=0.6220156700173558
```

- **Response Example:**

```
{
  "code": 0,
  "score": 2014.098, //Agent account balance
  "agent": "demo", //Agent account
  "msg": "ok.",
  "success": true
}
```

- **Response Codes:**

- `code=0` : Success
- `code=-10` : Incorrect action
- `code=-99` : Token signature error
- `code=-101` : Incorrect agent account
- `code=-102` : Incorrect agent account
- `code=-103` : Failed

- `code=-104` : Agent account has no QR code
- `code=-10002` : Network connection failed
- `code=-10001` : Request too frequent
- `code=-120` : API exception

10. Set agent to add or subtract score

- **Purpose:** Set agent score.
- **Request Parameters:**

Parameters	Required	Description
action	Yes	Fixed parameter <code>setAgentScore</code>
keyAgent	Yes	The agent who possesses the ApiKey
agent	Yes	Agent account
scoreNum	Yes	Score (greater than 0 means plus points, less than 0 means minus points)
time	Yes	A 13-digit timestamp
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper
ts	No	A random number

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=setAgentScore&token=C4CD1506B1FDBC3900F98B1DA825216D&time=1756545675327&k
eyAgent=demo&agent=demo-agent&scoreNum=50&ts=0.10341557880154484
```

- **Response Example:**

```
{
  "code": 0,
  "agentScore": "100.00", //After the operation, the agent
  "order": "demo-agent_1756906512347", //Set up the order number
  "agent": "demo-agent",
  "scoreNum": "50", //score number
  "msg": "ok.",
  "success": true
}
```

- **Response Codes:**
 - `code=0` : Success
 - `code=-10` : Incorrect action
 - `code=-99` : Token signature error
 - `code=-102` : No permission to operate
 - `code=-107` : No bypassing of the level
 - `code=-10005` : Failed to check agent score

- `code=-10006`: The superior agent account has insufficient points
- `code=-10002`: Network connection failed
- `code=-10001`: Request too frequent
- `code=-120`: API exception

11. Check the agent password

- **Purpose:** Check the agent password.
- **Request Parameters:**

Parameters	Required	Description
action	Yes	Fixed parameter <code>checkAgentInfo</code>
keyAgent	Yes	The agent who possesses the ApiKey
agent	Yes	Agent account
agentPwd	Yes	MD5 value of agent account password
time	Yes	A 13-digit timestamp
token	Yes	A 32-character uppercase string, signature=MD5(keyAgent+ApiKey+time).ToUpper
ts	No	A random number

- **Example Request:**

```
https://api.blackmamba.mobi/ashx/CheckAccount.ashx?
action=checkAgentInfo&token=4D456DF2BD67CD075FA8150BD80C722D&time=1760534927533&
keyAgent=demo&agent=testagent&agentPwd=f4dbca808e102c305cb92f192d16ef4d&ts=0.433
34534141520853
```

- **Response Example:**

```
{
  "code": 0,
  "msg": "OK.",
  "success": true
}
```

- **Response Codes:**
 - `code=0`: Success
 - `code=-10`: Incorrect action
 - `code=-99`: Token signature error
 - `code=-101`: Password error
 - `code=-10002`: Network connection failed
 - `code=-10001`: Request too frequent
 - `code=-120`: API exception

