Class-Imbalance Mitigation on TCGA-UT: Replacing Virchow2 with a LoRA-Adapted UNI2-h Encoder

Yannik Queisler

October 23, 2026

Abstract

With a Virchow2 encoder adapted through low-rank adaptation (LoRA), class imbalance at a ratio of 100 reduced balanced accuracy on TCGA-UT by 1.56 percentage points, and logit adjustment recovered approximately all of it in point estimate. This report repeats that experiment with UNI2-h as the only change; data, method settings, and bootstrap weights stay identical, so every UNI2-h estimate is paired with its Virchow2 counterpart. A rule fixed before training counts a quantity as *encoder-dependent* only if its paired difference has a 95% interval that excludes zero and a magnitude of at least one point. Of 20 pre-specified quantities, one meets the rule: classifier-only Gaussian clouded logit (GCL) adjustment lowers balanced accuracy on balanced data by 1.07 points more under UNI2-h. UNI2-h's balanced cross-entropy model is 0.94 points more accurate, yet at ratio 100 both encoders reach 69.95 percent, so the damage grows from 1.56 to 2.49 points. Most methods reach about the same imbalanced accuracy as under Virchow2, so their recoveries barely change while their shares of the larger damage fall. Logit adjustment recovers 1.61 points (train-time) and 1.51 points (post hoc), shares of 0.65 and 0.60 whose paired intervals exclude full recovery. A curriculum of data augmentation (CUDA) recovers the most, 1.79 points, and its imbalance-specific recovery becomes material (1.09 points, interval 0.64 to 1.54), as it did on BRACS. Logit adjustment and classifier-only GCL still restore most of the tail recall. Each method's imbalanced accuracy and the classes it helps thus transfer between encoders; how much of the damage it recovers does not, because the damage itself depends on the encoder.

1 Motivation

The companion mitigation study on TCGA-UT trained eight long-tailed method variants with a Virchow2 encoder (Zimmermann et al., 2024) adapted through rank-8 low-rank adaptation (LoRA) updates (Queisler, 2026c,b). At an imbalance ratio of $\rho = 100$, cross-entropy (CE) lost 1.56 points of balanced accuracy, about half of what a frozen linear readout lost on the same shards (Queisler, 2026e). Both forms of logit adjustment recovered all of that loss. The curriculum of data augmentation (CUDA) gain did not depend on imbalance, and classifier-only Gaussian clouded logit (GCL) adjustment corrected the most imbalance net of its effect on balanced data. That study was limited to one encoder.

A second encoder can change these results in two ways. It can change the damage to recover by changing balanced accuracy or sensitivity to the imbalanced allocation. It can also change how the methods act, because CUDA's image augmentation, GCL's feature clouds, and the classifier-only refits all operate on the encoder's representation. Two earlier comparisons bear on this question. Under a frozen linear readout on TCGA-UT, UNI2-h (Chen et al., 2024; Mahmood Lab, 2025) was 1.78 points more accurate than Virchow2 on balanced data and lost 0.86 points less under imbalance (Queisler, 2026a). Under LoRA on BRACS, no damage or recovery contrast between the two encoders met the encoder-dependence rule used here, but the paired intervals there spanned up to four points (Queisler, 2026d). This report asks: *on*

TCGA-UT, do the LoRA damage and each method's recovery depend on the encoder, or do the conclusions drawn under Virchow2 transfer to UNI2-h?

2 Design

The experiment replicates the Virchow2 mitigation study on TCGA-UT (Queisler, 2026c) with one change, the encoder. Data, methods, and analysis are held fixed. Both encoders see the same 30 split-draw shards, ten draws from each of three patient-disjoint splits with $G = 20$ training patients per cancer type and a budget of 19,200 patches; each shard fixes its patients, patches, and assignment of classes to allocation ranks. Both also share the eight method variants and their strength grids (Table 1), the training length, and the bootstrap seed. The identical shards and allocations give both encoders the same training data. Differences between them can therefore be attributed to the encoder and its interaction with the fixed recipe.

Two allocations are trained: balanced ($\rho = 1$) and $\rho = 100$, at which the largest class receives 2,843 patches and the rarest 28. The allocations $\rho = 50$ and native class shares of the Virchow2 study are not repeated. Their CE damage under Virchow2 was below one point (0.67 and 0.42), so the study focuses on the allocation with the largest reference damage. This scope choice leaves encoder effects at the omitted allocations unmeasured; small Virchow2 damage does not rule them out. Balanced sampling and both forms of logit adjustment reduce to CE on the balanced allocation and are trained only at $\rho = 100$.

The experiment uses UNI2-h's pinned public release (Mahmood Lab, 2025), the same checkpoint used in the frozen comparison (Queisler, 2026a). The patch embedding is UNI2-h's own pooled token (1,536 dimensions), whereas Virchow2 concatenates its class token with the mean patch token (2,560 dimensions); each encoder thus keeps the pooling its authors recommend. Both encoders use the same adaptation: a rank-8 LoRA update ($\alpha = 16$) on the query-key-value and output projections of every attention block, trained with a linear head (a cosine head for GCL, with scale $s = 30$ and a second-stage sampler of effective-number range $a = 0.9999$, $b = 10^{-5}$). The 2,400 end-to-end training steps (batch size 256, learning rate 10^{-4}) were chosen for CE under Virchow2 and were not retuned, keeping the training recipe identical across encoders; classifier-only fits use 200 steps. Per shard, the grid contains 18 end-to-end and 17 classifier-only configurations, giving 540 and 510 fits across the 30 shards. Every configured fit completed and entered the analysis.

Training	Method	Strength	Grid at $\rho = 100$ (balanced)
End to end	CE (reference)	–	–
End to end	Balanced sampling	s	0.5, 1.0
End to end	CUDA	p_{aug}	0.25, 0.5, 1.0 (same)
End to end	Logit adjustment (train-time)	τ	0.25, 0.5, 1.0
End to end	GCL	σ	0.01, 0.02, 0.05, 0.2 (0.05)
Classifier only	Logit adjustment (post hoc)	τ	0.25, 0.5, 1.0, 1.5, 2.0
Classifier only	DisAlign	γ	0.5, 1.0, 1.5, 2.0 (1.0)
Classifier only	cRT	–	– (same)
Classifier only	GCL	σ of its source	as GCL (0.05)

Table 1: Both encoders share the same strength grids, copied from the Virchow2 study. Values in parentheses apply to the balanced allocation, where methods that reduce to CE are not trained. CUDA (curriculum of data augmentation) uses a fixed acceptance threshold (0.6), check size (10), and maximum strength (10). GCL: Gaussian clouded logit adjustment; DisAlign: distribution alignment; cRT: classifier re-training. Classifier-only GCL starts from the end-to-end GCL model with the same σ; the other classifier-only methods start from the CE model.

3 Evaluation

Each encoder is first analysed with the endpoints of the Virchow2 study. The primary endpoint is test patient-macro balanced accuracy (BA). For method m with validation-selected strength m^*, the CE damage, the recovery, its share of the damage, the balanced gain, and the imbalance-specific recovery at $\rho = 100$ are

$$\begin{aligned} D_{100} &= \mathrm{BA}(\mathrm{CE}, 1) - \mathrm{BA}(\mathrm{CE}, 100), \qquad R_m = \mathrm{BA}(m^*, 100) - \mathrm{BA}(\mathrm{CE}, 100), \\ G_m &= \mathrm{BA}(m^*, 1) - \mathrm{BA}(\mathrm{CE}, 1), \qquad R_m - G_m = D_{100} - \big[\mathrm{BA}(m^*, 1) - \mathrm{BA}(m^*, 100)\big], \end{aligned} \tag{1}$$

with $\mathrm{share}_m = R_m / D_{100}$ computed per replicate. The bracket in the last term is the method's own damage, so $R_m - G_m$ measures how much less a method suffers from imbalance than CE does. A recovery is *material* if it is at least one point and its interval lies above zero, and meets the pre-specified *full-recovery criterion* if the interval of $\mathrm{BA}(m^*, 100)$ contains the point estimate of $\mathrm{BA}(\mathrm{CE}, 1)$. This marginal-interval criterion does not establish equivalence to balanced CE. Separately, a paired share interval entirely below 1 indicates residual damage; an interval containing 1 is compatible with full recovery. Balanced sampling and both forms of logit adjustment have $G_m = 0$ by construction. The uncertainty analysis combines Bayesian bootstrap weights on test patients (Rubin, 1981) with resampling of draws within each split over 2,000 replicates, and reports 95 percent percentile intervals.

The encoder contrast was fixed in the configuration before any fit. For each quantity X among $\mathrm{BA}(\mathrm{CE}, 1)$, D_{100}, R_m, G_m, and $R_m - G_m$,

$$\delta X = X(\text{UNI2-h}) - X(\text{Virchow2}), \tag{2}$$

using the same replicate weights for both encoders, so every δ is paired. A quantity counts as *encoder-dependent* only if the interval of δX excludes zero and $|\delta X| \geq 1$ point. With eight recoveries and five balanced gains and imbalance-specific recoveries, 20 quantities enter the rule.

All other analyses are descriptive: agreement between encoders on each method's material-recovery verdict; the Spearman rank correlation of R_m across the eight variants; a check of the Virchow2 study's main conclusions, which was not pre-specified; head, body, and tail recall by assigned class rank; macro negative log-likelihood (NLL) and expected calibration error (ECE), raw and after validation temperature scaling; and the frequency of each selected strength. The frozen UNI2-h readout reached 73.98 percent BA on balanced data and lost $D_{100} = 2.29$ points $[1.88, 2.69]$ (Queisler, 2026a). That study used a different set of draws, so the comparison with it has no paired interval.

4 Results

The results first describe the UNI2-h experiment on its own, with the endpoints of the Virchow2 study, and then compare the two encoders through the pre-specified paired contrast and the conclusions of the Virchow2 study.

4.1 Damage under UNI2-h

The balanced CE model reaches 72.45 percent BA $[71.15, 73.60]$, 0.94 points above its Virchow2 counterpart. At $\rho = 100$ it reaches 69.95 percent $[68.68, 71.06]$, the same point estimate as under Virchow2, so it loses $D_{100} = 2.49$ points $[2.01, 2.94]$ against Virchow2's 1.56. UNI2-h's advantage on balanced data thus disappears under imbalance. The frozen UNI2-h readout lost a similar 2.29 points, from a balanced BA of 73.98 percent to 71.69 percent at $\rho = 100$. The LoRA model is 1.53 points less accurate than the frozen readout on balanced data and 1.74 points less accurate at $\rho = 100$. Under Virchow2, the LoRA model was 0.55 points less accurate than the frozen readout on balanced data but 0.81 points more accurate at $\rho = 100$, which




Figure 1: Under UNI2-h, CUDA recovers more than under Virchow2 and the other recoveries change by less than half a point, while the damage they are measured against grows; net of their balanced loss, both GCL forms correct almost the full damage. Paired recovery R_m (left) and imbalance-specific recovery $R_m - G_m$ (right) at $\rho = 100$ with 95% intervals for Virchow2 (blue) and UNI2-h (red). Dashed lines mark each encoder's CE damage D_{100}, the solid line zero, and the dotted line the one-point threshold. Balanced sampling and both forms of logit adjustment have $G_m = 0$ by construction, so both panels show the same values for them. †Classifier only, frozen encoder.

halved its damage. Adapting UNI2-h with this recipe does not reproduce that reduction. The frozen values come from different draws and are descriptive.

4.2 Recovery per method

Figure 1 (left) gives each method's paired recovery under UNI2-h next to its Virchow2 value. Four of eight variants recover a material part of the damage: CUDA (1.79 points $[1.43, 2.17]$), train-time logit adjustment (1.61 $[1.26, 1.98]$), post-hoc logit adjustment (1.51 $[1.28, 1.74]$), and balanced sampling (1.18 $[0.88, 1.47]$). The other four recover between 0.68 and 0.88 points, below the one-point threshold. CUDA's share of the damage, 0.72 $[0.58, 0.89]$, is the largest, followed by the two forms of logit adjustment (0.65 $[0.54, 0.76]$ and 0.60 $[0.52, 0.72]$). No share interval reaches 1, and the point estimates leave between 0.28 and 0.40 of the damage unrecovered. CUDA and both forms of logit adjustment still meet the pre-specified full-recovery criterion, but only because their marginal accuracy intervals span about 2.5 points and contain the balanced CE point estimate of 72.45 percent; the paired shares are the more informative reading.

4.3 Imbalance-specific recovery

The right panel of Figure 1 removes each method's effect on balanced data. On balanced data, CUDA improves the CE model by $G = 0.70$ points $[0.34, 1.07]$, close to its 0.81 points under Virchow2, cRT loses 0.56 points $[-0.69, -0.45]$, and DisAlign is indistinguishable from CE. Both GCL forms lose more than under Virchow2: 1.45 points $[-1.80, -1.11]$ end to end and 1.67 points $[-2.03, -1.32]$ classifier only.

Net of these balanced effects, the two GCL forms correct the most imbalance: 2.38 points $[1.82, 2.95]$ classifier only and 2.33 points $[1.77, 2.86]$ end to end, shares of 0.96 and 0.93 whose intervals include 1. Both models lose less than 0.2 points of their own balanced accuracy at $\rho = 100$; their recovery against CE stays below one point only because they start from a lower




Figure 2: Only classifier-only GCL's balanced gain meets the encoder-dependence rule (red); nine further contrasts exclude zero at less than one point. Paired contrast δX (Eq. 2) with 95% intervals for the CE reference, the recoveries R_m, the balanced gains G_m, and the imbalance-specific recoveries $R_m - G_m$ at $\rho = 100$. Hollow markers: interval contains zero; grey band: ± 1 point. †Classifier only.

balanced accuracy. cRT corrects 1.24 points $[1.02, 1.47]$ and DisAlign 0.72 points. CUDA's imbalance-specific recovery, 1.09 points $[0.64, 1.54]$ or a share of 0.44, is material under UNI2-h, whereas under Virchow2 its interval included zero (0.20 points $[-0.17, 0.57]$).

4.4 Encoder contrast

Figure 2 shows all 20 pre-specified contrasts. One meets the rule for encoder dependence: the balanced gain of classifier-only GCL, which is 1.07 points lower under UNI2-h $[-1.58, -0.59]$. End-to-end GCL's balanced gain falls by a similar 0.90 points $[-1.39, -0.43]$, just below the one-point threshold.

Nine further contrasts have intervals that exclude zero but magnitudes below one point. Two of them describe CE itself: UNI2-h's balanced model is 0.94 points more accurate $[0.45, 1.38]$, and its damage is 0.94 points larger $[0.47, 1.40]$. Because both CE models reach the same accuracy at $\rho = 100$, each recovery contrast δR_m equals the difference in the method's own accuracy at $\rho = 100$. CUDA recovers 0.77 points more $[0.36, 1.18]$ and balanced sampling 0.47 points more $[0.08, 0.88]$; logit adjustment, end-to-end GCL, and cRT stay within 0.1 points of their Virchow2 values. The imbalance-specific recoveries of CUDA (0.88 points $[0.28, 1.45]$) and end-to-end GCL (0.90 points $[0.25, 1.54]$) are larger under UNI2-h. DisAlign's recovery and imbalance-specific recovery are about 0.1 points smaller, with intervals that exclude zero.

Method rankings change despite the small recovery contrasts. Six of eight material-recovery verdicts agree between encoders. The two that differ lie near the threshold: balanced sampling

Conclusion at $\rho = 100$	Virchow2	UNI2-h	Verdict
(i) Logit adjustment gives the largest R_m and its paired share interval contains 1	1.54 (train-time), share 0.99 $[0.80, 1.24]$	1.61, share 0.65 $[0.54, 0.76]$; CUDA 1.79	Fails
(ii) Logit adjustment and GCL† restore most of the tail recall	Tail 61.2 to 69.4, 69.9, and 72.2; others $\leq$66.6	Tail 60.0 to 68.9, 69.3, and 69.5; others $\leq$67.5	Holds
(iii) Post-hoc logit adjustment matches its train-time form	1.41 vs. 1.54	1.51 vs. 1.61	Holds
(iv) CUDA's gain is general ($R_m - G_m$ includes 0)	0.20 $[-0.17, 0.57]$	1.09 $[0.64, 1.54]$	Fails
(v) GCL† gives the largest $R_m - G_m$	1.73; next 1.42 (GCL)	2.38; next 2.33 (GCL)	Holds
(vi) LoRA damage smaller than the frozen readout's	1.56 vs. 2.91	2.49 vs. 2.29	Fails

Table 2: Three of six conclusions of the Virchow2 study carry over to UNI2-h; logit adjustment's paired share intervals exclude 1, CUDA's gain is partly imbalance-specific, and LoRA no longer reduces the damage. Values in BA points or recall points; tail recall is the patient-macro recall of the rarest third of classes for CE, the two logit-adjustment forms, and classifier-only GCL. The frozen readouts in (vi) come from the same draws for Virchow2 and from different draws for UNI2-h. †Classifier only.

is material only under UNI2-h (0.70 against 1.18 points) and classifier-only GCL only under Virchow2 (1.13 against 0.71 points). The Spearman correlation of R_m across the eight variants is 0.57. All eight recoveries lie between 0.68 and 1.79 points under both encoders, so a shift of a few tenths of a point reorders them.

4.5 Conclusions of the Virchow2 study

Table 2 checks six conclusions of the Virchow2 study at $\rho = 100$. Three carry over to UNI2-h. Logit adjustment and classifier-only GCL remain the methods that restore most of the tail recall (Section 4.6). Post-hoc logit adjustment again recovers nearly as much as its train-time form, 1.51 against 1.61 points. Classifier-only GCL again gives the largest imbalance-specific recovery, only 0.05 points ahead of end-to-end GCL. Three do not carry over. Logit adjustment no longer has paired recovery shares compatible with 1: its shares of 0.65 and 0.60 have upper bounds of 0.76 and 0.72, and CUDA now gives the largest recovery. Both forms still meet the marginal-interval full-recovery criterion; the conclusion here concerns the paired shares. CUDA's imbalance-specific recovery is material, so its gain is no longer purely general. Finally, the LoRA model is no longer less sensitive to imbalance than the frozen readout. Differences between methods are not tested, and the frozen comparison is descriptive.

4.6 Recovery by class rank

Under UNI2-h, the CE model at $\rho = 100$ loses 13.0 points of tail recall by assigned class rank (72.9 to 60.0 percent; Virchow2: 10.4) and gains 6.6 points in the head (Figure 3). Logit adjustment raises the tail to about 69 percent at a cost of four to five points of head recall. Classifier-only GCL raises it to 69.5 percent while keeping head recall near the balanced model's (71.6 against 72.1 percent); unlike under Virchow2, its tail recall stays below the balanced model's, by 3.4 points. End-to-end GCL follows at 67.5 percent. CUDA, balanced sampling, cRT, and DisAlign




Figure 3: Under both encoders, logit adjustment and classifier-only GCL restore most of the tail recall at $\rho = 100$, at the cost of head recall; CUDA and balanced sampling keep the head-heavy profile of CE. Patient-macro recall of the head and tail thirds of classes by assigned rank, averaged over shards, for Virchow2 (blue) and UNI2-h (red). †Classifier only.

leave the tail between 62.9 and 64.9 percent and keep CE's head-heavy profile; CUDA instead gains in the body (72.6 against 71.2 percent). Each method thus recovers recall in the same rank group as under Virchow2. Rank-group recalls are point estimates.

4.7 Selected strengths and probability quality

Validation selects stronger prior corrections under UNI2-h. Both forms of logit adjustment mostly select the full correction $\tau = 1$ (21 and 24 of 30 shards), where Virchow2 mostly selected $\tau = 0.5$, and balanced sampling selects full balancing in 25 shards (Virchow2: 19). Three methods concentrate on a grid edge: CUDA on its lowest augmentation probability $p_{\text{aug}} = 0.25$ (18 of 30 shards at $\rho = 100$, 21 on the balanced allocation), DisAlign on its largest $\gamma = 2$ (22; Virchow2 mostly 1.5), and classifier-only GCL on its lowest $\sigma = 0.01$ (15).

Both CE models are overconfident, with validation temperatures of 1.80 (balanced) and 1.69 ($\rho = 100$), similar to Virchow2 and unlike the underconfident frozen UNI2-h readout. Imbalance worsens the probabilities slightly: from the balanced allocation to $\rho = 100$, NLL after temperature scaling rises from 1.03 to 1.13 nats and ECE from 4.1 to 5.1 points (raw: 1.37 to 1.43 nats and 17.9 to 18.2 points). CUDA has the lowest raw NLL, 1.07 nats $[1.01, 1.14]$, and raw ECE, 11.4 points $[10.4, 12.5]$. After temperature scaling, all methods lie at or below CE, between 0.98 and 1.12 nats and between 2.6 and 4.7 points ECE, with overlapping unpaired intervals. As under Virchow2, CUDA curbs raw overconfidence, and temperature scaling brings the other methods close to it.

5 Discussion

Does mitigation under LoRA depend on the encoder? Most recovery contrasts are small. Among the 20 pre-specified quantities, only classifier-only GCL's balanced gain meets the encoder-dependence rule, and at $\rho = 100$ seven of eight methods reach within half a point of their Virchow2 accuracy. The reference accuracy changes. UNI2-h's balanced CE model is about one point more accurate, but its $\rho = 100$ model is not, so the damage grows by about one point. Measured against that larger damage, recoveries that stay the same in points become smaller shares, and logit adjustment's paired share intervals exclude full recovery. The material-recovery

verdicts of balanced sampling and classifier-only GCL change because their estimates lie near one point, not because their contrasts meet the encoder-dependence rule. The conclusions of the Virchow2 study (Queisler, 2026c) that concern where methods act transfer: logit adjustment and classifier-only GCL restore the tail, post-hoc correction matches train-time correction, and GCL corrects the most imbalance net of its balanced loss. The conclusions that concern how much of the damage is recovered do not.

Why does CUDA's imbalance-specific recovery become material? CUDA's own damage is the accuracy it loses from the balanced allocation to $\rho = 100$. It is similar under both encoders (1.41 and 1.35 points), as is CUDA's balanced gain. CE's damage grows by 0.94 points, so the difference between the two damages, CUDA's imbalance-specific recovery, grows by about the same amount. GCL behaves the same way: under both encoders it loses less than 0.2 points to imbalance, and its imbalance-specific recovery grows with CE's damage. Logit adjustment, cRT, and DisAlign instead lose 0.8 to 1.0 points more to imbalance under UNI2-h, so their recoveries stay flat. These own-damage values are point estimates without intervals. On BRACS, CUDA's imbalance-specific recovery also became material under UNI2-h, with an unresolved contrast of 0.51 points (Queisler, 2026d); on TCGA-UT the contrast of 0.88 points excludes zero. Across both datasets, CUDA's gain is therefore not purely general under UNI2-h, but whether it corrects imbalance by itself or merely resists the greater damage that CE suffers with this encoder cannot be separated with these endpoints.

Why does GCL lose more on balanced data? With a uniform class prior, all of GCL's clouds have the same size and GCL reduces to CE with a cosine head, so its balanced loss reflects the cosine head and its fixed scale $s = 30$ rather than any imbalance correction. That loss is 0.9 to 1.1 points larger under UNI2-h. The scale and noise level were taken from the reference implementation and the Virchow2 grid; UNI2-h's adapted features may have different norms and angular spread, so the same scale may fit this encoder less well. A check on six shards, added after the main analysis, refitted both GCL forms on balanced data with $s = 16$ and $s = 64$. The scale is part of the story, not all of it: raising s to 64 removes most of end-to-end GCL's gap to Virchow2 (0.78 to 0.14 points) but only a third of classifier-only GCL's (0.92 to 0.57 points), short of the criterion fixed before the check. The encoder-dependence verdict stands.

How large a difference could have been missed? Much less than on BRACS. The paired intervals of the recovery contrasts span 0.16 to 0.94 points and those of the imbalance-specific recoveries up to 1.31 points, against up to four points on BRACS (Queisler, 2026d). Of the 20 quantities, 12 have intervals that lie entirely within ± 1 point, including all recoveries except CUDA's; these intervals exclude encoder effects of one point in either direction. The other eight intervals reach beyond one point: the balanced accuracy, the damage, CUDA's recovery, both GCL balanced gains, and the imbalance-specific recoveries of CUDA and both GCL forms. This equivalence reading was not pre-specified and is descriptive.

Does UNI2-h change the frozen-versus-LoRA picture? Yes. Under Virchow2, adaptation made the imbalanced model 0.81 points more accurate than the frozen readout and halved the damage. Under UNI2-h, the LoRA model is less accurate than the frozen readout on both allocations, and its damage, 2.49 points, is as large as the frozen readout's 2.29. The best mitigated UNI2-h model at $\rho = 100$, CUDA at 71.74 percent, stays 2.24 points below the frozen UNI2-h readout on balanced data and only matches the frozen readout at $\rho = 100$ (71.69 percent). For TCGA-UT, adapting UNI2-h with the recipe tuned for Virchow2 and then mitigating does not improve on a frozen UNI2-h readout. The frozen values come from different draws.

Limitations. The study adds a second encoder but keeps one dataset, one adaptation scheme, and one imbalance ratio; the contrast at $\rho = 50$ and at native class shares is not measured. All settings were tuned under Virchow2 and transferred unchanged: the 2,400 training steps, the LoRA rank and target modules, GCL's scale, and the strength grids. This keeps the comparison paired, but it measures UNI2-h under a recipe tuned for the other encoder, and UNI2-h's 1.53-point gap to its own frozen readout may partly reflect that. Three methods

frequently select grid endpoints: DisAlign's largest γ (22 of 30 shards), CUDA's lowest p_{aug} (18), and classifier-only GCL's lowest σ (15). The grids were not extended, so these methods' recoveries, and DisAlign's small negative contrasts, may partly reflect truncation. The encoders also differ in their pooled embedding (1,536 against 2,560 dimensions), so the contrast describes two complete encoder-plus-pooling pipelines. The UNI2-h fits accumulate gradients over four micro-batches of 64 patches into the same 256-patch update and use compiled kernels; in a short run on one shard, compiled and uncompiled training differed by 0.35 points of validation BA, less than the 0.88 points between two uncompiled repeats. Imbalance-specific recovery assumes that a method's balanced effect carries over additively to the imbalanced allocation. The comparisons with the frozen readouts and with BRACS are descriptive.

References

Richard J. Chen, Tong Ding, Ming Y. Lu, Drew F. K. Williamson, Guillaume Jaume, Andrew H. Song, Bowen Chen, Andrew Zhang, Daniel Shao, Muhammad Shaban, Mane Williams, Lukas Oldenburg, Luca L. Weishaupt, Judy J. Wang, Anurag Vaidya, Long Phi Le, Georg Gerber, Sharifa Sahai, Walt Williams, and Faisal Mahmood. Towards a general-purpose foundation model for computational pathology. *Nature Medicine*, 30(3):850–862, March 2024. doi: 10.1038/s41591-024-02857-3.

Mahmood Lab. UNI2-h: Hugging Face model card and checkpoint. `https://huggingface.co/MahmoodLab/UNI2-h`, commit d517a8dd47902dd7c308b3c36f63bce47e7b9a43, 2025. Accessed 2026-09-24.

Yannik Queisler. Class imbalance in histopathology: Replacing Virchow2 with UNI2-h lowers TCGA-UT's damage and leaves BRACS unresolved. Technical report, TU Berlin, 2026a. Companion encoder-transfer report, Experiment 39.

Yannik Queisler. Mitigation methods for class imbalance in histopathology patch classification. Technical report, TU Berlin, 2026b. Companion mitigation-methods definitions report, Experiment 40.

Yannik Queisler. Class-imbalance mitigation on TCGA-UT with a LoRA-adapted foundation-model encoder. Technical report, TU Berlin, 2026c. Companion TCGA-UT mitigation report, Experiment 43.

Yannik Queisler. Class-imbalance mitigation on BRACS: Replacing Virchow2 with a LoRA-adapted UNI2-h encoder. Technical report, TU Berlin, 2026d. Companion BRACS encoder-contrast mitigation report, Experiment 42.

Yannik Queisler. Class imbalance in histopathology: Prevalence alone costs little accuracy on TCGA-UT. Technical report, TU Berlin, 2026e. Companion TCGA-UT prevalence report, Experiment 25.

Donald B. Rubin. The Bayesian bootstrap. *The Annals of Statistics*, 9(1):130–134, 1981. doi: 10.1214/aos/1176345338.

Eric Zimmermann, Eugene Vorontsov, Julian Viret, Adam Casson, Michal Zelechowski, George Shaikovski, Neil Tenenholtz, James Hall, Thomas Fuchs, Nicolo Fusi, Siqi Liu, and Kristen Severson. Virchow2: Scaling self-supervised mixed magnification models in pathology. *arXiv preprint arXiv:2408.00738*, 2024. doi: 10.48550/arXiv.2408.00738.