Class Imbalance in Histopathology Patch Classification

Yannik Queisler

September 25, 2026

1 Motivation

Histopathology datasets are long-tailed almost by construction. Common cancers and benign tissue dominate archives, while rare subtypes and atypical lesions, often diagnostically decisive, contribute few patients and patches. In convolutional neural networks, imbalance degrades classification, and the network absorbs the training class prior (Buda et al., 2018). In medical imaging, metrics dominated by the majority class can hide poor minority-class performance in both discrimination and calibration (Mosquera et al., 2024). Researchers continue to propose histopathology-specific models (Cong et al., 2022). Pathology foundation models such as UNI and Virchow2 are commonly evaluated with linear classifiers trained on their frozen patch features (Chen et al., 2024; Zimmermann et al., 2024). Yet how much class imbalance costs such classifiers, and why, remains insufficiently measured in isolation.

Three questions guide this work. How much do discrimination and calibration degrade as the training class distribution becomes more skewed (Section 3)? What causes this damage, and why are some classes and tasks more vulnerable than others (Section 4)? How much of the damage can mitigation methods recover (Section 5)?

2 Setup

Multinomial logistic regression on Virchow2 patch features (Zimmermann et al., 2024) addresses two tasks: TCGA-UT, 30 cancer types (Komura et al., 2022), and BRACS, 7 breast-lesion subtypes from normal tissue to invasive carcinoma (Brancati et al., 2022). Allocation conditions use the same patients per class (20 on TCGA-UT, 10 on BRACS) and total patch budget; only class shares change. An exponential profile sets the largest-to-smallest class ratio ρ from 1 to 100 (Figure 1). Class-to-rank assignment is randomized over 30 draws (3 splits $\times$ 10 draws); a native condition preserves each dataset's class shares. The outcome is *damage*, $\Delta(\rho) = \mathrm{BA}(1) - \mathrm{BA}(\rho)$: the loss in test patient-macro balanced accuracy (BA) relative to the balanced condition, with paired bootstrap 95% intervals. Damage counts as material from 1 percentage point (pp).

The encoder stays frozen when measuring damage and its causes. Mitigation methods that adapt the encoder fine-tune it through low-rank adaptation (LoRA) (Hu et al., 2022). To rule out dependence on one encoder, the conditions at $\rho = 10$ and $\rho = 100$ are repeated on the same patients and patches with UNI2-h, the successor of UNI (Mahmood Lab, 2025).




Figure 1: Training class distributions sorted from head to tail: balanced, native shares of one split, and $\rho = 100$. The tested ratios are $\rho \in \{1, 2, 5, 10, 20, 50, 100\}$; intermediate profiles lie between balanced and $\rho = 100$. Class-to-rank assignment is randomized per draw. T: total training patch budget.




Figure 2: (a) Balanced-accuracy damage versus ρ with 95% bands; diamonds mark native class shares, dotted line the 1-pp threshold. (b) Expected calibration error (ECE) of the raw predicted probabilities (solid) and after a single global confidence correction fitted on validation data (dashed).

3 Effects of class imbalance

Balanced accuracy in the balanced condition reaches 72.1% on TCGA-UT and 39.6% on BRACS. Published evaluations show the same broad gap: region-of-interest (ROI)-level benchmarks report 59.5–67.5% for UNI, Virchow2, and UNI2-h on the 32-class TCGA-UT task (Mahmood Lab, 2025), while slide-level linear probes score 31.8–48.1% on BRACS (Vaidya et al., 2025). TCGA-UT spans cancer types across organs, while BRACS separates breast lesions with similar morphology, such as atypical ductal hyperplasia (ADH) and ductal carcinoma in situ (DCIS) (Brancati et al., 2022). These evaluations make the gap plausible, though their training budgets and evaluation units differ. This study computes patient-macro balanced accuracy from patch predictions.

Imbalance damage differs strongly between the two tasks (Figure 2a). On TCGA-UT, damage is small but accelerates as ρ increases: 0.57 pp [0.30, 0.84] at $\rho = 10$, reaching the 1-pp threshold at $\rho = 20$ (1.01 pp [0.67, 1.36]) and 2.91 pp [2.48, 3.34] at $\rho = 100$. On BRACS, damage appears at $\rho = 2$ and grows steadily by about 1.15 pp per doubling of ρ: 1.15 pp [0.14, 2.35] at $\rho = 2$, 4.02 pp [2.50, 5.66] at $\rho = 10$, and 7.65 pp [5.77, 9.78] at $\rho = 100$, a fifth of the balanced accuracy. The native allocations lie on their respective curves (1.18 pp [0.85, 1.48] on TCGA-UT and 4.05 pp [2.69, 5.57] on BRACS). Aggregate damage hides a large shift in recall from tail to head. At $\rho = 100$, the TCGA-UT tail third loses 11.8 pp while the head gains 5.4 pp; on BRACS, the two tail classes drop from 38.7% to 7.3% recall.

Calibration deteriorates far more than accuracy (Figure 2b). Expected calibration error (ECE), the average gap between the model's confidence and its accuracy, rises from 5.5 to 17.8 pp on TCGA-UT and from 12.3 to 35.7 pp on BRACS at $\rho = 100$: the model becomes overconfident, but uniformly so. Temperature scaling divides all logits by one scalar fitted on validation data (Guo et al., 2017). This global confidence correction removes 92–96% of the increase.

Replacing Virchow2 with UNI2-h changes the damage little. On TCGA-UT, UNI2-h's balanced baseline is 1.78 pp higher, and its damage at $\rho = 100$ is 0.86 pp lower (97.5% interval 0.40 to 1.33): a resolved difference, but below the 1-pp threshold. On BRACS, the difference is unresolved, and tail-class recall falls to about 9% with both encoders.

4 Causes of class imbalance damage

Two questions explain the damage. The first is which changes in the training data cause it (Section 4.1). The second is why the same imbalance ratio costs more for some rare classes than for others (Section 4.2).

4.1 Sources of damage

When a tail class receives fewer training patches, two things change. Its errors contribute less often to the training loss, so common classes have more influence on the fitted decision boundary. This is the

frequency effect: how strongly each class's available examples shape the classifier. The model also sees fewer distinct tail patches, only one or two per patient at $\rho = 100$, so it has less evidence about how that class varies. This is the *coverage* effect: giving those few patches more weight cannot supply the missing examples.

The conditions in Table 1 separate these effects. F keeps all patches from the balanced condition but gives head classes more weight, isolating the frequency effect. C keeps the sparse patches from the imbalanced condition but weights classes equally, isolating the coverage effect. The ratio condition r combines both effects. The interaction $I = \Delta_r - \Delta_F - \Delta_C$ measures any additional damage when both occur together.

Class influence	Many tail patches	Few tail patches
Equal	balanced (ref.)	C: coverage only
Head-favoured	F: frequency only	r: ratio (both)

Table 1: Four training conditions separate the effect of unequal class influence (frequency) from the effect of fewer tail examples (coverage) at each ρ.




Figure 3: Damage at $\rho = 100$ by component; diamonds give the total with its 95% interval.

The damage components differ between tasks (Figure 3). On TCGA-UT, the frequency effect accounts for damage at moderate ratios (0.73 of 1.01 pp at $\rho = 20$), while low tail coverage alone costs nothing. At $\rho = 100$, the two effects compound: frequency 1.20 pp [0.87, 1.53], coverage 0.53 pp [0.36, 0.70], and a positive interaction of 1.18 pp [1.00, 1.37]. On BRACS, both factors are material at $\rho = 100$: frequency 4.47 pp [2.84, 6.30] and coverage 3.29 pp [1.99, 4.67]. Their sum matches the total damage. The interaction is near zero, −0.11 pp, but its interval [−1.74, 1.36] cannot rule out compounding of up to 1.4 pp. Low tail coverage alone costs BRACS more than total TCGA-UT imbalance damage.

4.2 Vulnerable classes

On BRACS, rotating every class through every rank shows that easy classes cost most when rare. Damage at $\rho = 100$ ranges from 5.73 pp (usual ductal hyperplasia, UDH, in the tail) to 9.99 pp (invasive carcinoma), because a class with high balanced recall has the most to lose (Figure 4a).

On TCGA-UT, a class is especially vulnerable when it receives few patches but a frequent confusion partner receives many. A score built from the balanced model's confusion rates ordered new class-to-rank assignments by damage. The score was chosen after exploratory checks on the same stored outputs and uses test predictions, so this shows the mechanism on these patients and is not an out-of-sample prediction. The assignment ranked most damaging costs 4.51 pp (a lower bound on the worst case, found by hill climbing), the least damaging 1.34 pp, and random assignments 2.91 pp (Figure 4b). Reversing the most damaging assignment preserves pairwise rank gaps but lowers damage by 1.11 pp [0.47, 1.73]. Damage is therefore greatest when the class prone to confusion is the rarer one.

5 Mitigation of class imbalance damage

Section 4 traced the damage to the frequency and coverage effects. This section asks how much of it established long-tailed methods recover compared with standard cross-entropy (CE) training. Six methods cover the three families of Krawczyk (2016) (Table 2). Data-level methods change the training data, algorithm-level methods change the loss or the decision rule, and hybrid methods do both.

Several of these methods act on the learned representation, not only on the classifier. The encoder is therefore adapted through LoRA together with a linear head. The patients, patch budgets, and class-to-rank assignments match those in Section 3. CE and each method are trained at $\rho = 100$, $\rho = 50$, and native shares, and a CE model trained on the balanced allocation provides the undamaged reference. Each method except cRT has one control parameter that sets how strongly it acts, such as




Figure 4: Damage at $\rho = 100$ with 95% intervals. (a) BRACS tail-class identity versus balanced recall (Spearman correlation 0.96, $n = 7$). ADH: atypical ductal hyperplasia; UDH: usual ductal hyperplasia; PB: pathological benign; DCIS: ductal carcinoma in situ; FEA: flat epithelial atypia; N: normal; IC: invasive carcinoma. (b) TCGA-UT class-to-rank assignments.

the scale of the logit adjustment or the probability that CUDA augments a patch; it is selected per draw on validation patients.

Under LoRA, CE loses 4.95 pp [3.25, 6.74] on BRACS and 1.56 pp [1.17, 1.94] on TCGA-UT at $\rho = 100$. Recovery is measured against this LoRA-specific damage, not the frozen-readout damage of Section 3; the BRACS figure is lower mainly because the adapted balanced reference is weaker (Section 5.2). A method's *recovery* is its gain in balanced accuracy over CE at the same allocation; its *share* is recovery divided by CE's damage. Methods whose effect on balanced data is not zero by construction are also fitted on the balanced allocation. Recovery minus this *balanced gain* is the part that corrects the imbalance. Results refer to Virchow2 and $\rho = 100$ unless stated otherwise.

Family	Method	What changes
Data	Balanced sampling (Kang et al., 2020)	Every class is drawn equally often.
	CUDA (Ahn et al., 2023)	Image patches are augmented per class, more strongly once the model has learned the class.
Algorithm	Logit adjustment (Menon et al., 2021)	The training class prior is subtracted from the class scores, in the loss or after training.
	DisAlign (Zhang et al., 2021)	A loss that weights rare classes more trains a per-class score correction.
Hybrid	cRT (Kang et al., 2020)	The head is refitted with balanced sampling.
	GCL (Li et al., 2022)	Random noise lowers the scores of rarer classes more during training; optionally, the head is then refitted with near-balanced sampling.

Table 2: The six mitigation methods change the data, the learner, or both. Logit adjustment is tested in the loss and after training, GCL with and without the head refit, giving eight variants. CUDA: curriculum of data augmentation; DisAlign: distribution alignment; cRT: classifier re-training; GCL: Gaussian clouded logit adjustment.

5.1 What mitigation achieves

1. Cheap fixes already recover much of the damage. Logit adjustment removes the training prior from the class scores (Menon et al., 2021). Applied to the CE model after training, it needs no retraining and recovers as much as its train-time form: 1.41 against 1.54 pp on TCGA-UT and 1.94 against 1.96 pp on BRACS. On TCGA-UT this is essentially the full damage (Figure 5a). The train-time share is 0.99 [0.80, 1.24], and recall of the tail third of classes rises from 61.2% to 69.4%, against 71.6% when balanced. On BRACS, both forms recover about two-fifths (Figure 5b). Balanced sampling, which changes only how often each class is drawn, recovers at least 1 pp in three of the four dataset–encoder settings.

2. Augmentation improves the model in general. CUDA recovers 0.46 to 0.72 of the damage across the four settings, the largest share in all but TCGA-UT with Virchow2, where logit adjustment




Figure 5: Only logit adjustment on TCGA-UT with Virchow2 recovers the full damage; on BRACS no method recovers much more than half of it. Each method's share of its encoder's CE damage recovered at $\rho = 100$; thin whiskers: paired 95% interval, thick bars: 68% interval (16th–84th percentile). Intervals are wide because each share divides one small, noisy accuracy difference by another, and BRACS has few test patients per class. Dashed line: full recovery. UNI2-h's lower TCGA-UT shares reflect its larger damage (2.49 against 1.56 pp), not smaller recovery. Grey lines separate the method families of Table 2.

recovers more. Most of this gain does not depend on imbalance: CUDA also improves the balanced model, by 0.81 pp on TCGA-UT and 1.39 pp on BRACS. After subtracting this balanced gain, it corrects 0.20 pp [−0.17, 0.57] of the imbalance on TCGA-UT and 1.20 pp [−0.16, 2.62] on BRACS. At native shares it is the only method that gains at least 1 pp (1.01 and 1.21 pp). On TCGA-UT, CUDA also lowers temperature-scaled negative log-likelihood (NLL) below that of CE, by 0.09 nats [0.07, 0.12] with Virchow2 and 0.15 nats [0.13, 0.17] with UNI2-h (99.84% intervals), and below that of the balanced CE model. The gain does not depend on adapting the encoder: with a frozen Virchow2, CUDA gains 1.83 pp over CE on BRACS and 0.89 pp on TCGA-UT, against 2.59 and 1.02 pp with LoRA. The best CUDA model on TCGA-UT is still the adapted one, by 2.77 pp (99.17% interval 2.13 to 3.38), because LoRA already raises CE by 2.64 pp there.

3. Mitigation does not fix calibration; one temperature does. The adapted CE models are overconfident even on balanced data, with raw ECE of 28–31 pp on BRACS and 17–18 pp on TCGA-UT across the two encoders. At $\rho = 100$, raw ECE with Virchow2 rises to 36.4 pp on BRACS and stays at 16.0 pp on TCGA-UT. Mitigation reduces this only in part. CUDA reduces it most, to 20.8 and 11.5 pp. cRT and balanced sampling can raise it. Without temperature scaling, every method stays at least 6.3 pp above the ECE of scaled CE. After scaling, as in Section 3, every method is as well calibrated as CE or slightly better, by at most 3.7 pp. Apart from CUDA, scaled NLL differs from that of scaled CE by −0.06 to +0.03 nats. CUDA's lower scaled NLL on TCGA-UT (finding 2) comes without lower ECE, so it reflects its accuracy gain rather than better calibration.

5.2 Limits of mitigation

1. Mitigation cannot add missing knowledge of a class. No method closes the gap on BRACS. The highest upper bound of the share intervals is 0.82 with Virchow2 and 0.71 with UNI2-h. The two tasks differ in what the imbalanced CE model still knows. On TCGA-UT it retains 61% tail recall at $\rho = 100$: the model has learned the rare classes, and the main problem is a misplaced decision boundary, which shifting the class scores can correct. On BRACS, tail recall falls to 5.1%, against 34.5% when balanced. Logit adjustment and GCL's head refit raise it only to 20–27%. This fits the sources of damage in Section 4.1. Rebalancing acts on the frequency effect but cannot supply missing tail coverage, which alone cost 3.29 pp on BRACS and 0.53 pp on TCGA-UT.

2. Mitigation has a cost. Rebalancing shifts recall from head to tail: logit adjustment gives up about 4 pp of head recall on TCGA-UT and 9 pp on BRACS. Methods that change the head can also lower accuracy without imbalance. GCL and cRT lose 0.3 to 0.6 pp on the balanced allocation, and

GCL loses up to 1.7 pp with UNI2-h on TCGA-UT. Their recovery over CE therefore understates how much imbalance they correct. Accounting for this balanced loss, GCL's head refit corrects about half of the damage on BRACS and about all of it on TCGA-UT. Logit adjustment and balanced sampling reduce to CE on balanced data and carry no such cost.

3. Mitigation matters only under severe imbalance. With the encoder adapted, native class shares cost little: 0.42 pp [0.06, 0.79] on TCGA-UT and 0.85 pp [−0.31, 2.08] on BRACS, against 1.18 and 4.05 pp for the frozen readout. On BRACS, this reflects a weaker balanced reference: the adapted balanced model is 3 pp less accurate than the frozen readout (36.53 against 39.57%), while the imbalanced models are as accurate as the frozen readout. With logit adjustment at $\rho = 100$, a frozen Virchow2 even beats the adapted model by 2.22 pp (99.17% interval 0.43 to 3.97). At native shares, only CUDA gains 1 pp; on TCGA-UT at $\rho = 50$, no method does.

Repeating the mitigation experiments with UNI2-h on the same patients and patches (on TCGA-UT at $\rho = 100$ only) leaves unchanged where each method acts. The same methods lift tail recall, post-hoc and train-time logit adjustment agree, and GCL's head refit corrects the most imbalance. Recovery point estimates change by less than 1 pp, but shares change with the damage. On TCGA-UT, UNI2-h's damage is 0.94 pp larger, so logit adjustment no longer recovers it fully (share 0.65 [0.54, 0.76]). On both tasks, CUDA's correction after subtracting its balanced gain becomes material with UNI2-h.

6 Discussion

Three questions connect the effects, causes, and mitigation of class imbalance.

Do the causes set how much damage mitigation can recover? Largely, yes. Rebalancing acts on the frequency effect and on its interaction with low coverage, but it cannot supply missing tail patches. On TCGA-UT, frequency and interaction make up 0.82 of the damage at $\rho = 100$, and logit adjustment recovers about all of it. On BRACS, low coverage alone accounts for 0.43 of the damage, and no method recovers much more than half; the largest imbalance-specific correction, by GCL's head refit, is also about half.

Does calibration need its own mitigation? No; one temperature suffices. Imbalance raises raw ECE far more than it lowers accuracy (Section 3), and the skewed prior drives this. When only the prior is skewed, the temperature fitted on validation data rises from 0.84 to 1.71 on TCGA-UT and from 0.65 to 5.37 on BRACS at $\rho = 100$, whereas low coverage alone leaves it near its balanced value. Temperature scaling corrects exactly this kind of uniform overconfidence. The mitigation methods target accuracy instead: none fixes raw calibration, and after scaling, only CUDA on TCGA-UT reaches a lower NLL than scaled CE, through its accuracy gain. Calibration and accuracy therefore need separate fixes: a temperature for the first and a mitigation method for the second.

Which classes pay for imbalance, and does mitigation reach them? Mitigation repairs a misplaced decision boundary but only partly restores a class that the model has stopped recognizing. On TCGA-UT, rare classes remain recognizable and lose recall mainly to a more frequent confusion partner (Section 4.2). Logit adjustment shifts the boundary back and raises tail recall from 61.2% to 69.4%, close to the balanced 71.6%. On BRACS, rare classes collapse: in the tail position, six of seven classes keep at most 4% recall, and classes with high balanced recall lose most. Rebalancing recovers half to three quarters of the lost tail recall, from 5.1% to 20–27% against 34.5% when balanced.

References

S. Ahn, J. Ko, and S.-Y. Yun. CUDA: Curriculum of data augmentation for long-tailed recognition. In *International Conference on Learning Representations*, 2023. URL https://arxiv.org/abs/2302.05499.

N. Brancati, A. M. Anniciello, P. Pati, D. Riccio, G. Scognamiglio, G. Jaume, G. De Pietro, M. Di Bonito, A. Foncubierta, G. Botti, M. Gabrani, F. Feroce, and M. Frucci. BRACS: A Dataset for BReAst Carcinoma Subtyping in H&E Histology Images. *Database*, 2022:baac093, 2022.

M. Buda, A. Maki, and M. A. Mazurowski. A systematic study of the class imbalance problem in convolutional neural networks. *Neural Networks*, 106:249–259, 2018.

R. J. Chen, T. Ding, M. Y. Lu, et al. Towards a general-purpose foundation model for computational pathology. *Nature Medicine*, 30(3):850–862, Mar. 2024.

C. Cong, Y. Yang, S. Liu, et al. Imbalanced Histopathology Image Classification Using Deep Feature Graph Attention Network. In *2022 IEEE 19th International Symposium on Biomedical Imaging (ISBI)*, pages 1–4, 2022.

C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger. On Calibration of Modern Neural Networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 1321–1330, 2017.

E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

B. Kang, S. Xie, M. Rohrbach, Z. Yan, A. Gordo, J. Feng, and Y. Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=r1gRTCVFvB.

D. Komura, A. Kawabe, K. Fukuta, et al. Universal encoding of pan-cancer histology by deep texture representations. *Cell Reports*, 38(9):110424, 2022.

B. Krawczyk. Learning from imbalanced data: open challenges and future directions. *Progress in Artificial Intelligence*, 5(4):221–232, 2016. doi: 10.1007/s13748-016-0094-0.

M. Li, Y. ming Cheung, and Y. Lu. Long-tailed visual recognition via Gaussian clouded logit adjustment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6919–6928, 2022. doi: 10.1109/CVPR52688.2022.00680.

Mahmood Lab. UNI: Towards a General-Purpose Foundation Model for Computational Pathology – UNI 2 ROI benchmarks. https://github.com/mahmoodlab/UNI, 2025.

A. K. Menon, S. Jayasumana, A. S. Rawat, et al. Long-Tail Learning via Logit Adjustment. In *International Conference on Learning Representations*, 2021.

C. Mosquera, L. Ferrer, D. H. Milone, et al. Class imbalance on medical image classification: towards better evaluation practices for discrimination and calibration performance. *European Radiology*, 34 (12):7895–7903, 2024.

A. Vaidya, A. Zhang, G. Jaume, A. H. Song, T. Ding, S. J. Wagner, M. Y. Lu, et al. Molecular-driven Foundation Model for Oncologic Pathology. *arXiv preprint arXiv:2501.16652*, 2025. doi: 10.48550/arXiv.2501.16652.

S. Zhang, Z. Li, S. Yan, X. He, and J. Sun. Distribution alignment: A unified framework for long-tail visual recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2361–2370, 2021. doi: 10.1109/CVPR46437.2021.00239.

E. Zimmermann, E. Vorontsov, J. Viret, et al. Virchow2: Scaling Self-Supervised Mixed Magnification Models in Pathology. *arXiv preprint arXiv:2408.13910*, 2024.