Can the Strongest Practical Mitigations Omit LoRA? A Frozen-Encoder Follow-Up on BRACS and TCGA-UT

Yannik Queisler

October 26, 2026

Abstract

Train-time logit adjustment, post-hoc logit adjustment, and the curriculum of data augmentation (CUDA) recovered most of the accuracy lost to class imbalance when a Virchow2 encoder was adapted through low-rank adaptation (LoRA). This protocol asks whether the same three methods lose no more than one percentage point of balanced accuracy at an imbalance ratio of 100 when the foundation model stays entirely unchanged. Six paired contrasts, one per dataset and method, decide the question; omitting LoRA counts as supported in the tested scope only if all six are noninferior. The study adds 390 training fits and 270 score-only candidates and trains no encoder. The results section is empty until the fits and the paired analysis exist.

1 Question

The mitigation studies adapted Virchow2 (Zimmermann et al., 2024) through LoRA before fitting any head (Queisler, 2026a,c). Logit adjustment recovered the most accuracy on TCGA-UT; CUDA (Ahn et al., 2023) led in the other settings (Queisler, 2026b). This follow-up asks: *do these methods retain their balanced accuracy when the foundation model is not adapted at all?*

Each method is compared with its own LoRA counterpart under the same imbalanced allocation. A plain linear probe is a reference, not a substitute for applying the same mitigation without LoRA. The experiment allows a LoRA advantage or an inconclusive outcome; it does not assume the desired conclusion.

2 Design

Both datasets use the 30 split-draw shards of the mitigation studies (three patient-disjoint splits, ten draws each) at one allocation, the severe imbalance $\rho = 100$. No balanced, native-share, or intermediate allocation is added. The adapted comparison reuses the final matching records of the BRACS and TCGA-UT mitigation studies. The frozen comparison trains only a linear head on the unchanged pretrained Virchow2 and uses exactly the same training patients, patches, order, labels, and class counts, and the same validation and test partitions.

The first-stage recipe of the source studies is kept: AdamW, batch size 256, learning rate 10^{-4}, weight decay 10^{-4}, a cosine schedule, and 600 (BRACS) or 2,400 (TCGA-UT) updates, with empirical row sampling and a linear head. Cross-entropy (CE) and train-time logit adjustment (LA) train on cached fp16 features, with no image or encoder loading. One CE head per split and draw is reused for every post-hoc LA strength. CUDA keeps its image operations, per-class learning levels, classifier checks, and constants ($\gamma = 0.6$, check size 10, maximum strength 10). Augmented images still pass through the frozen encoder in evaluation mode; only the head is optimized, with effective batch 256 in micro-batches of 64. Head initialization is seeded with $10000 + 100\,\text{split} + \text{draw}$ for every candidate; the sampling seed is the draw index. The historical

head initialization was not recorded, so the data and inference are paired but the initialization is not.

Strength is selected per method, representation, split, and draw by validation patient-macro balanced accuracy alone, with ties broken by configuration order. Table 1 lists the grids. No strength is transferred from the adapted runs, and no grid is extended after test results are visible.

Method	BRACS	TCGA-UT
Train-time LA, τ	0.5, 1.0	0.25, 0.5, 1.0
Post-hoc LA, τ	0.5, 1.0, 1.5, 2.0	0.25, 0.5, 1.0, 1.5, 2.0
CUDA, p_{aug}	0.25, 0.5, 1.0	0.25, 0.5, 1.0
Updates	600	2,400

Table 1: Fixed strength grids at $\rho = 100$. CE has no strength and is the supporting control and the source head of post-hoc LA. LA: logit adjustment; CUDA: curriculum of data augmentation.

Compute. The 390 training fits are 60 CE, 150 train-time LA, and 180 CUDA fits; the 270 post-hoc candidates only score a stored CE head, giving 660 records. The 210 CE and LA fits run on CPU. The 180 CUDA fits need image forwards and normally run on a GPU; CUDA totals 270,000 optimizer updates, or 6.9×10^7 batch-row encoder forwards before curriculum checks. This is a workload count, not a runtime estimate. A pilot on split 0, draw 0 of both datasets (13 fits and 9 score-only candidates) measures runtime and memory before any full run.

Consistency check. CUDA evaluates from the unchanged pretrained feature caches. Before reuse, the cached features of the first 32 validation rows of each manifest must match direct forwards of the untouched encoder (per-row cosine similarity at least 0.999 and relative L_2 error at most 0.01; zero or nonfinite vectors fail). A mismatch blocks cache reuse pending diagnosis.

3 Decision rule

For each dataset and method, the primary contrast at $\rho = 100$ is

$$\delta = \text{BA(without LoRA)} - \text{BA(with LoRA)}, \tag{1}$$

in percentage points, with patient-macro balanced accuracy (BA) pooled over splits and draws. The six contrasts use the repository's patient-clustered bootstrap with shared draw-resampling weights, so each is paired across representations. Ten thousand bootstrap replicates give a two-sided percentile interval from the $0.05/12$ and $1 - 0.05/12$ quantiles of the replicate columns only (about 99.17%); the observed estimate is excluded. The six intervals share Bonferroni 95% familywise coverage, subject to the bootstrap approximation.

With the practical margin of one point, a lower bound strictly above -1 supports omitting LoRA for that dataset and method. An upper bound strictly below -1 means that the LoRA pipeline has an advantage larger than one point. Any other outcome, including a bound equal to -1, is inconclusive. The joint claim requires all six contrasts to be noninferior and supports "no material accuracy loss from omitting LoRA in the tested scope", not equality or the absence of any LoRA benefit. A nonsignificant difference is not evidence of noninferiority.

Secondary diagnostics are descriptive: absolute BA, each representation's gain over its CE control, tail recall, validation selections, runtime, and peak memory.

4 Limits

The follow-up reuses data already inspected in the mitigation studies; it is not an independent test set. It covers three methods, one encoder, one allocation, fixed training recipes, and the existing 30-draw design. Execution devices, precision, and micro-batching differ from the adapted runs, so training is not bitwise comparable; these settings are recorded. A LoRA advantage under these recipes does not show that every optimizer setting needs LoRA, and noninferiority does not establish equivalence for other methods, encoders, or ratios. Existing outputs and caches were not checked on the cluster when this protocol was written.

5 Results

No results yet: the 390 training fits, 270 post-hoc scores, and their paired analysis have not been run.

References

Sumyeong Ahn, Jongwoo Ko, and Se-Young Yun. CUDA: Curriculum of data augmentation for long-tailed recognition. In *International Conference on Learning Representations*, 2023. URL `https://arxiv.org/abs/2302.05499`.

Yannik Queisler. Class-imbalance mitigation on BRACS with a LoRA-adapted foundation-model encoder. Technical report, TU Berlin, 2026a. Companion BRACS mitigation report, Experiment 41.

Yannik Queisler. Mitigation methods for class imbalance in histopathology patch classification. Technical report, TU Berlin, 2026b. Companion mitigation-methods definitions report, Experiment 40.

Yannik Queisler. Class-imbalance mitigation on TCGA-UT with a LoRA-adapted foundation-model encoder. Technical report, TU Berlin, 2026c. Companion TCGA-UT mitigation report, Experiment 43.

Eric Zimmermann, Eugene Vorontsov, Julian Viret, Adam Casson, Michal Zelechowski, George Shaikovski, Neil Tenenholtz, James Hall, Thomas Fuchs, Nicolo Fusi, Siqi Liu, and Kristen Severson. Virchow2: Scaling self-supervised mixed magnification models in pathology. *arXiv preprint arXiv:2408.00738*, 2024. doi: 10.48550/arXiv.2408.00738.