go to windows

start SQL Plus

user name: scott

password: tiger

```
SQL>clear screen
SQL> create table student90
(rollno number(3), sname varchar(20));
SQL - Structured Query Language
Table created...
SQL> DESCRIBE STUDENT90;

SQL> alter table student90
add (course varchar(10));

SQL> DESCRIBE STUDENT90;
SQL> insert into student90 values(101,'Smith','BCA');
SQL> insert into student90 values(102,'Ram','MCA');
SQL> commit;
SQL> select * from STUDENT90;
SQL> update STUDENT90 set course='BCA H' where rollno=101;
SQL> select * from STUDENT90;
SQL> commit;
SQL> delete from STUDENT90 where rollno=101;
SQL> select * from emp where deptno=10;
SQL> select * from emp where deptno<>10;
SQL> select * from emp where sal>2000;
SQL> select * from emp where sal between 1000 and 2000;
```

```
SQL> select * from emp where comm is null;

SQL> select * from emp where deptno=10;

SQL> select * from emp where ENAME LIKE 'S%';

SQL> select * from emp where ENAME LIKE '%a';

SQL> select * from emp where ENAME LIKE 'S_O%';

SQL> select * from emp where comm is not null;

SQL> select * from emp where sal>2000 and deptno=10;

SQL> select hiredate from emp;

SQL> select to_char(hiredate,'dd/mm/yyyy') from emp;

SQL> select to_char(hiredate,'dd/month/year') from emp;

SQL> select to_char(sysdate,'dd-mm-yy') from dual;

SQL> select upper(ename) from emp;

SQL> select lower(ename) from emp;

SQL> select initcap(ename) from emp;

SQL> select sqrt(625) from dual;

SQL> select power(2,4) from dual;

SQL> select round(24.657,2) from dual;

SQL> select trunc(24.657,2) from dual;
```