



DEVA DHARSHINI P 2024-CSE ▾

**D2****Started on** Wednesday, 17 September 2025, 10:21 AM**State** Finished**Completed on** Wednesday, 8 October 2025, 10:13 AM**Time taken** 20 days 23 hours**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct | Mark 1.00 out of 1.00**Problem Statement**

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int findFirstZero(int arr[], int low, int high) {
3     if (low > high) {
4         return -1;
5     }
6     int mid = low + (high - low) / 2;
7     if (arr[mid] == 0) {
8         if (mid == 0 || arr[mid - 1] == 1) {
9             return mid;
10        } else {
11            return findFirstZero(arr, low, mid - 1);
12        }
13    }
14    return findFirstZero(arr, mid + 1, high);
15 }
16 int main() {
17     int m;
18     scanf("%d", &m);
19     int arr[m];
20     for (int i = 0; i < m; i++) {
21         scanf("%d", &arr[i]);
22     }
23     int firstZeroIndex = findFirstZero(arr, 0, m - 1);
24     if (firstZeroIndex == -1) {
25         printf("0\n");
26     } else {
27         printf("%d\n", m - firstZeroIndex);
28     }
29     return 0;
30 }
31

```

	Input	Expected	Got	
✓	5 1 1 1 0 0	2	2	✓

	Input	Expected	Got	
✓	10 1 1 1 1 1 1 1 1 1 1 1 1	0	0	✓
✓	8 0 0 0 0 0 0 0 0 0	8	8	✓
✓	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



DEVA DHARSHINI P 2024-CSE ▾

**D2****Started on** Wednesday, 17 September 2025, 10:28 AM**State** Finished**Completed on** Wednesday, 8 October 2025, 10:13 AM**Time taken** 20 days 23 hours**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct | Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than  $\lfloor n / 2 \rfloor$  times. You may assume that the majority element always exists in the array.

**Example 1:**

Input: `nums = [3,2,3]`

Output: 3

**Example 2:**

Input: `nums = [2,2,1,1,1,2,2]`

Output: 2

**Constraints:**

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-231 <= nums[i] <= 231 - 1`

**For example:**

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

**Answer:** (penalty regime: 0 %)

```
1 | #include <stdio.h>
2 | int majorityElement(int* nums, int numsSize) {
3 |     int candidate = nums[0];
4 |     int count = 1;
5 |     for (int i = 1; i < numsSize; i++) {
6 |         if (nums[i] == candidate) {
7 |             count++;
8 |         } else {
9 |             count--;
10 |        }
11 |        if (count == 0) {
12 |            candidate = nums[i];
13 |            count = 1;
14 |        }
15 |    }
16 |    return candidate;
17 | }
18 | int main() {
19 |     int n;
20 |     scanf("%d", &n);
21 |     int nums[n];
22 |     for (int i = 0; i < n; i++) {
23 |         scanf("%d", &nums[i]);
24 |     }
25 |     printf("%d\n", majorityElement(nums, n));
26 |     return 0;
27 | }
28 |
```

	Input	Expected	Got	
✓	3 3 2 3	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



DEVA DHARSHINI P 2024-CSE ▾

**D2****Started on** Wednesday, 17 September 2025, 10:30 AM**State** Finished**Completed on** Wednesday, 8 October 2025, 10:15 AM**Time taken** 20 days 23 hours**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct | Mark 1.00 out of 1.00**Problem Statement:**

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

**Input Format**

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

**Output Format**

First Line Contains Integer – Floor value for x

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int findFloor(int arr[], int n, int x) {
3      int low = 0, high = n - 1;
4      int floorValue = -1;
5      while (low <= high) {
6          int mid = low + (high - low) / 2;
7          if (arr[mid] == x) {
8              return arr[mid];
9          }
10         else if (arr[mid] < x) {
11             floorValue = arr[mid];
12             low = mid + 1;
13         } else {
14             high = mid - 1;
15         }
16     }
17     return floorValue;
18 }
19 int main() {
20     int n;
21     scanf("%d", &n);
22     int arr[n];
23     for (int i = 0; i < n; i++) {
24         scanf("%d", &arr[i]);
25     }
26     int x;
27     scanf("%d", &x);
28     printf("%d\n", findFloor(arr, n, x));
29     return 0;
30 }
31

```

	Input	Expected	Got	
✓	6	2	2	✓
	1			
	2			
	8			
	10			
	12			
	19			
	5			



	Input	Expected	Got	
✓	5 10 22 85 108 129 100	85	85	✓
✓	7 3 5 7 9 11 13 15 10	9	9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



DEVA DHARSHINI P 2024-CSE ▾

**D2****Started on** Wednesday, 17 September 2025, 10:37 AM**State** Finished**Completed on** Wednesday, 8 October 2025, 10:16 AM**Time taken** 20 days 23 hours**Marks** 1.00/1.00**Grade** **10.00** out of 10.00 (**100%**)

**Question 1** | Correct | Mark 1.00 out of 1.00**Problem Statement:**

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

**Input Format**

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

**Output Format**

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int findPairWithSum(int arr[], int low, int high, int x) {
3      if (low >= high) {
4          return 0;
5      }
6      int sum = arr[low] + arr[high];
7      if (sum == x) {
8          printf("%d\n", arr[low]);
9          printf("%d\n", arr[high]);
10         return 1;
11     } else if (sum < x) {
12         return findPairWithSum(arr, low + 1, high, x);
13     } else {
14         return findPairWithSum(arr, low, high - 1, x);
15     }
16 }
17 int main() {
18     int n;
19     scanf("%d", &n);
20     int arr[n];
21     for (int i = 0; i < n; i++) {
22         scanf("%d", &arr[i]);
23     }
24     int x;
25     scanf("%d", &x);
26     if (!findPairWithSum(arr, 0, n - 1, x)) {
27         printf("No\n");
28     }
29     return 0;
30 }
31

```

	Input	Expected	Got	
✓	4 2 4 8 10 14	4 10	4 10	✓
✓	5 2 4 6 8 10 100	No	No	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



DEVA DHARSHINI P 2024-CSE ▾

**D2****Started on** Wednesday, 17 September 2025, 10:39 AM**State** Finished**Completed on** Wednesday, 8 October 2025, 10:17 AM**Time taken** 20 days 23 hours**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct | Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n

The next n lines contain the elements.

Output:

Sorted list of elements

For example:

Input	Result
5	12 34 67 78 98
67 34 12 98 78	

Answer:

```

1  #include <stdio.h>
2  void swap(int *a, int *b) {
3      int temp = *a;
4      *a = *b;
5      *b = temp;
6  }
7  int partition(int arr[], int low, int high) {
8      int pivot = arr[high];
9      int i = low - 1;
10     for(int j = low; j <= high - 1; j++) {
11         if(arr[j] <= pivot) {
12             i++;
13             swap(&arr[i], &arr[j]);
14         }
15     }
16     swap(&arr[i + 1], &arr[high]);
17     return (i + 1);
18 }
19 void quickSort(int arr[], int low, int high) {
20     if(low < high) {
21         int pi = partition(arr, low, high);
22
23         quickSort(arr, low, pi - 1);
24         quickSort(arr, pi + 1, high);
25     }
26 }
27 int main() {
28     int n;
29     scanf("%d", &n);
30     int arr[n];
31     for(int i = 0; i < n; i++) {
32         scanf("%d", &arr[i]);
33     }
34     quickSort(arr, 0, n - 1);
35     for(int i = 0; i < n; i++) {
36         printf("%d ", arr[i]);
37     }
38     printf("\n");
39     return 0;
40 }
41

```

	Input	Expected	Got	
✓	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✓

	Input	Expected	Got	
✓	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✓
✓	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)