12:28 PM | 2.7KB/s

Online C Com...
programiz.com

Programiz
C Online Compiler

Programiz PRO

main.c | Output

```c
#include<stdio.h>
#include<string.h>
struct book
  {
    char  title[100];
    char author[100];
    int pages;
    float price;
  };
 int main()
 {
  int n, i;
  struct book b[100];
  printf ("enter the limit\t");
  scanf("%d",&n);
  for(i=0;i<n;i++)
   {
    printf("\nenter details of book\t"
        );
    scanf("\n%s\n%s\n%d\n%f",b[i].title
        ,b[i].author,&b[i].pages,&b[i]
        .price);
   }
    for(i=0;i<n;i++)
   {
    printf("\ndetails of book:
        \n%s\n%s\n%d\n%f",b[i].
        ,b[i].author,b[i].pages,b[i]
```

Run

12:28 PM | 0.0KB/s

Online C Com...
programiz.com

Programiz
C Online Compiler

Programiz PRO

main.c | Output

```c
{
 int n, i;
 struct book b[100];
 printf ("enter the limit\t");
 scanf("%d",&n);
 for(i=0;i<n;i++)
  {
   printf("\nenter details of book\t"
       );
   scanf("\n%s\n%s\n%d\n%f",b[i].title
       ,b[i].author,&b[i].pages,&b[i]
       .price);
  }
   for(i=0;i<n;i++)
  {
   printf("\ndetails of book:
       \n%s\n%s\n%d\n%f",b[i].title
       ,b[i].author,b[i].pages,b[i]
       .price);
  }
   return 0;
 }
```

Run

12:28 PM | 0.0KB/s

Online C Com...
programiz.com

Programiz
C Online Compiler

Programiz PRO

main.c | Output

```
enter the limit 2

enter details of book   dracula bramstoker
    200 345.8

enter details of book   spiderman stanLee 26
    567.3

details of book:
dracula
bramstoker
200
345.799988
details of book:
spiderman
stanLee
26
567.299988

=== Code Execution Successful ===
```