

Introduction: Computing Runtimes

Daniel Kane

Department of Computer Science and Engineering
University of California, San Diego

Algorithmic Design and Techniques
Algorithms and Data Structures

Learning Objectives

- Describe some of the issues involved with computing the runtime of an actual program.
- Understand why finding exact runtimes is a problem.

Outline

- 1 Revisit Fibonacci
- 2 Other Things to Consider

Runtime Analysis

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Runtime Analysis

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

$2n + 2$ lines of code. Does this really describe the runtime of the algorithm?

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Depends on memory management system.

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Assignment.

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Assignment.

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Increment, comparison, branch.

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Lookup, assignment, addition of big integers.

Individual Lines

Function FibList(n)

create an array $F[0 \dots n]$

$F[0] \leftarrow 0$

$F[1] \leftarrow 1$

for i from 2 to n :

$F[i] \leftarrow F[i - 1] + F[i - 2]$

return $F[n]$

Lookup, return.

Outline

- 1 Revisit Fibonacci
- 2 Other Things to Consider


Computing Runtime

To figure out how long this simple program would actually take to run on a real computer, we would also need to know things like:


Speed of the Computer




The System Architecture



The Compiler Being Used



Details of the Memory Hierarchy



Problem

- Figuring out accurate runtime is a huge mess

Problem

- Figuring out accurate runtime is a huge mess
- In practice, you might not even know some of these details

Goal

Want to:

- Measure runtime without knowing these details.
- Get results that work for large inputs.