

1 Inline loader in the HTML
wpmLoader({ shopId,
webPixelsConfigList: [{
id, type: APP|CUSTOM,
runtimeContext:
STRICT|LAX|OPEN,
privacyPurposes: [
ANALYTICS, MARKETING,
PREFERENCES,
SALE_OF_DATA],
configuration }]})
Each pixel's container and declared purposes are readable in the HTML before any script runs.
2 Manager bundle /cdn/wpm/b<hash>m.js (runs in the main thread)
Event bus
replay buffer of 1,000 events; every event carries document.location.href (full URL with query string)
Consent state: first one found
1 cachedConsent (Privacy API)
2 injectedConsent
3 _cs URL parameter
4 _tracking_consent cookie
5 Server-Timing: _cmp
none readable: allow (fail-open)
gate
Per pixel: start it only when the state allows every purpose it declares; otherwise wait for visitorConsentCollected. No purpose declared: start now.
No code path terminates a started pixel; Shopify documents that its events stop at an opt-out.
3 What sets the state
Region setting. The server writes 3.AMPS_USCA… (allowed) or 3.ampS_USCA… (denied) into the navigation response.
Banner (CMP). It calls setTrackingConsent({…}), but only if it is wired to Shopify.
GPC. Sec-GPC: 1 makes the server decline S; a main-thread script calls setCCPAConsent(false) in sale-of-data regions.
4 Runtime container
chosen by runtimeContext
runs in a Shopify sandbox
runs in the main thread
Manager build c8540278…, fetched 25–26 Sep 2026.
STRICT: web worker
new Worker(url, {credentials:'omit'}) → importScripts (vendor library) → fetch (vendor endpoint).
Every navigator property except userAgentData is overwritten, so pixel code reads GPC as undefined.
LAX: sandboxed iframe
Hidden <iframe sandbox="allow-scripts allow-forms"> with an opaque origin; it cannot reach the top frame. Runs merchants' custom pixels and some app pixels.
OPEN: main-thread script
pixel.modern.js, served from the store's own origin, injects the vendor's <script>, which a CMP blocker can see (the Meta and Google apps).