

PNEUMATIC ENERGY STORAGE VESSELS • WRV SERIES

Industrial Air Receiver Buffer Tanks

Vertical & Horizontal Compressed Air Storage Tanks Certified to IS 2825 & ASME Section VIII Div 1

Dampens Pulsation & Guarantees System Pressure Stability: Acts as a pneumatic flywheel that absorbs peak cyclic demands from air tools, prevents compressor motor frequent cycling, and separates bulk condensation.

Win Equipments WRV Series pressure vessels are fabricated from certified boiler-quality SA 516 Gr. 70 or IS 2062 carbon steel plate using automated submerged arc welding (SAW). Every vessel is subjected to 1.5× hydrostatic test pressure and certified with third-party inspection (TPI).

IS 2825 / ASME VIII 1.5× HYDRO-TESTED SA 516 GR. 70 SAFETY KIT INCLUDED



250–10,000 L
VOLUME RANGE

7–40 bar g
WORKING PRESSURE

1.5× Test
HYDROSTATIC PRESSURE

100% NDT
WELD RADIOGRAPHY

CORE ENGINEERING ADVANTAGES

Dished End Precision

Torispherical 2:1 semi-ellipsoidal dished ends pressed and flanged with smooth transitions eliminate localized stress concentrations.

Internal Epoxy Coating

Vessels receive shot-blasting to SA 2.5 followed by anti-rust epoxy primer to prevent internal moisture scaling and corrosion pitting.

Certified Safety Kit

Supplied complete with spring-loaded brass safety relief valve, calibrated glycerine pressure gauge, and bottom manual drain cock.

TARGET INDUSTRIAL APPLICATIONS

Central Compressor Room Buffer Storage

High-Pressure PET Blow Molding (40 bar)

Pneumatic Conveying & Cement Silo Aeration

Textile Weaving Mill Ring Frames

Laser Cutting High-Pressure Auxiliary Air

ENGINEERING SPECIFICATIONS MATRIX

WRV Series Technical Data (250 to 1,000 Liters)

Design Standards: IS 2825 Class II / ASME Sec VIII Div 1, 100% Radiography on T-joints, 1.5× Hydrostatic Test

MODEL NO.	CAPACITY	WORKING PRESS.	DESIGN PRESS.	HYDRO TEST	OUTER DIA	TOTAL HEIGHT	CONNECTION	INSPECTION
Model Code	Liters	bar g	bar g	bar g	mm	mm	Inlet / Outlet	Type
WRV 025 (7 bar)	250 L	7.0 bar	8.0 bar	12.0 bar	490 mm	1620 mm	3/4" BSP	Hand Hole
WRV 050 (7 bar)	500 L	7.0 bar	8.0 bar	12.0 bar	650 mm	1850 mm	1" BSP	Hand Hole
WRV 100 (7 bar)	1000 L	7.0 bar	8.0 bar	12.0 bar	850 mm	2150 mm	1.5" BSP	Man Hole
WRV 025 (10 bar)	250 L	10.0 bar	11.0 bar	16.5 bar	490 mm	1620 mm	3/4" BSP	Hand Hole
WRV 050 (10 bar)	500 L	10.0 bar	11.0 bar	16.5 bar	650 mm	1850 mm	1" BSP	Hand Hole
WRV 100 (10 bar)	1000 L	10.0 bar	11.0 bar	16.5 bar	850 mm	2150 mm	1.5" BSP	Man Hole
WRV 050 (16 bar)	500 L	16.0 bar	17.6 bar	26.4 bar	650 mm	1850 mm	1" BSP	Hand Hole
WRV 100 (16 bar)	1000 L	16.0 bar	17.6 bar	26.4 bar	850 mm	2150 mm	1.5" BSP	Man Hole

Custom High-Pressure & Stainless Steel Vessels: Win Equipments manufactures custom air receivers up to 10,000 Liters and 40 bar g pressure in vertical and horizontal orientations, including pharmaceutical-grade SUS304/SUS316 stainless steel vessels.

Request Technical Submittal & Commercial Quotation

Direct factory engineering consultation for custom capacity sizing, P&ID schematics & dimensional drawings.

+91 95972 28969

info@winequipments.com