

CONDENSATE DISCHARGE SYSTEMS • WADV SERIES

Automatic Zero Air Loss & Electronic Timer Drain Valves

Energy-Saving Capacitive & Solid-State Condensate Drains for Air Receivers, Dryers & Filters

Zero Air Loss Saves ₹38,000+ Annually per Compressor: Standard manual crack-valves or poorly adjusted timer valves waste valuable compressed air. Capacitive zero-loss valves discharge only when liquid water accumulates, keeping air lines fully pressurized.

Win Equipments WADV Series includes solid-state electronic timer valves with built-in stainless steel strainers, contactless capacitive zero-air-loss electronic drains, and heavy-duty 40 bar high-pressure valves for PET compressor installations.



ZERO AIR LOSS

ENERGY SAVING

FORGED BRASS BODY

IP65 WATERPROOF

0-40 bar g

PRESSURE RANGE

0 CFM

AIR LOSS (CAPACITIVE)

IP65

ENCLOSURE RATING

100% Brass

VALVE BODY

CORE ENGINEERING ADVANTAGES

Contactless Capacitive Sensor

Non-mechanical sensor detects water level through the housing wall without moving floats that could jam from oil emulsion or particulate grime.

Integrated Mesh Strainer

Built-in stainless steel mesh ball-valve strainer traps rust particles before they reach the pilot orifice, preventing valve stuck-open failures.

Direct-Acting Pilot Valve

High-power electromagnetic solenoid actuator ensures positive shutoff even in heavily contaminated oil-water slurry condensates.

TARGET INDUSTRIAL APPLICATIONS

Screw & Reciprocating Compressor Aftercoolers

Air Receiver Tank Sump Discharge

Refrigerated Air Dryer Moisture Separators

Main Header Distribution Low-Point Drain Legs

ENGINEERING SPECIFICATIONS MATRIX

WADV Series Technical Data & Selection

High-Reliability Condensate Evacuation for Pressures up to 40 bar g

MODEL NO.	DRAIN MECHANISM	OPERATING PRESSURE	PORT SIZE	DISCHARGE CYCLE	SUPPLY VOLTAGE	COMPRESSED AIR LOSS
Model Code	Technology	bar g	Inlet / Outlet	Timing	Electrical	Loss per Cycle
WADV-T16	Electronic Timer Solenoid Drain	0 to 16 bar g	1/2" BSP Female	0.5-10s ON / 0.5-45m OFF adj.	230V AC / 1Ph / 50Hz	~4 CFM during blast
WADV-Z16	Capacitive Zero-Air-Loss Drain	0.8 to 16 bar g	1/2" BSP Female	Automatic Level Sensing	230V AC or 24V DC	0.0 CFM (Zero Air Loss)
WADV-HP40	High-Pressure Timer Drain	0 to 40 bar g	1/2" BSP Female	0.5-10s ON / 0.5-45m OFF adj.	230V AC / 1Ph / 50Hz	High-Pressure rated

Payback Calculation Example: A standard 1/4" manual cracked valve open continuously at 7 bar wastes approximately 28 CFM of compressed air, costing over ₹1,20,000 in electricity each year. Installing a Win WADV-Z16 zero-loss valve pays for itself in less than 3 weeks!

Request Technical Submittal & Commercial Quotation

Direct factory engineering consultation for custom capacity sizing, P&ID schematics & dimensional drawings.

+91 95972 28969

info@winequipments.com