

CRITICAL CLOSED-LOOP THERMAL REJECTION • WCC SERIES

Closed Circuit Evaporative Coil Cooling Towers

100% Contamination-Free Indirect Cooling for Induction Furnaces, Continuous Casters & Compressors

Zero Scaling & Pure Fluid Recirculation: Process water circulates inside heavy-duty hot-dip galvanized or SS304 prime surface serpentine coils, completely isolated from airborne dust, algae, and atmospheric dirt.

Win Equipments WCC Series combines the clean operating advantages of an indirect heat exchanger with the thermodynamic power of evaporative heat rejection. Secondary spray water evaporates on the outer coil surface, delivering low process fluid temperatures without fouling furnace coils.

CLOSED LOOP SERPENTINE

ZERO FLUID CONTAMINATION

HDG / SS304 COILS

FRP OUTER CASING



40-150 TR

CAPACITY RANGE

100% Closed

CIRCUIT INTEGRITY

2.5 MPa

COIL TEST PRESSURE

< 0.005%

DRIFT LOSS

CORE ENGINEERING ADVANTAGES

Serpentine Tube Coil

Continuous smooth-bend serpentine tubing hot-dip galvanized after fabrication ensures total external zinc protection and zero mechanical tube joint leaks.

Protected Furnace Coils

Eliminates lime scale, rust, and sludge deposits inside costly induction furnace power coils, thyristor heat sinks, and vacuum pump jackets.

Spray Water Circuit

Dedicated self-priming recirculation spray pump with wide-orifice clog-resistant spray nozzles and multi-pass cellular drift eliminators.

TARGET INDUSTRIAL APPLICATIONS

Steel Induction Melting & Heating Furnaces

Vacuum Heat Treatment Furnaces

Continuous Casting Machines (CCM)

High-Frequency Induction Hardening

Compressor High-Purity Water Jackets

ENGINEERING SPECIFICATIONS MATRIX
WCC Series Technical Data (40 to 150 TR)

Standard Ratings: 37°C entering fluid, 32°C leaving fluid, 28°C wet bulb temperature

MODEL NO.	CAPACITY	FAN MOTORS	FAN SPEED	FAN DIA	IN / OUT PIPE	INTERNAL VOLUME	DIMENSIONS (L×W×H)
Model Code	TR	HP × Qty	RPM	mm	NB	Liters	mm
WCC 40	40 TR	3.0 HP × 2	960 RPM	1060 mm	3" / 3"	72 L	3300 × 1500 × 1400
WCC 50	50 TR	3.0 HP × 2	960 RPM	1060 mm	3" / 3"	90 L	3300 × 1700 × 1400
WCC 75	75 TR	3.0 HP × 2	960 RPM	1060 mm	4" / 4"	135 L	3300 × 2000 × 1400
WCC 100	100 TR	5.0 HP × 2	960 RPM	1200 mm	4" / 4"	180 L	3600 × 2400 × 1600
WCC 150	150 TR	7.5 HP × 2	720 RPM	1400 mm	6" / 6"	270 L	4200 × 2800 × 1800

Coil Metallurgy Options: Standard heat exchanger bundles are fabricated from seamless carbon steel tubing hot-dip galvanized to ASTM A123. For ultra-pure deionized (DI) water or food/pharmaceutical processes, coils are available in 100% SUS304 or SUS316L stainless steel.

Request Technical Submittal & Commercial Quotation

Direct factory engineering consultation for custom capacity sizing, P&ID schematics & dimensional drawings.

+91 95972 28969
info@winequipments.com