

COMPRESSED AIR FILTRATION SYSTEMS • WMF SERIES

Sub-Micron Coalescing In-Line Compressed Air Filters

Multi-Stage Particulate, Oil Aerosol & Hydrocarbon Vapor Filtration for ISO 8573-1 Class 1 Air Quality

Residual Oil Down to < 0.003 mg/m³: Protects critical pneumatic instruments, breathing air circuits, food contact lines, and laser optical mirrors from oil vapor carryover.

Win Equipments WMF Series filter housings are manufactured from corrosion-resistant die-cast aluminum with electrostatic powder coating. Internal microglass borosilicate pleated elements deliver 99.999% coalescing efficiency with ultra-low differential pressure drop.



0.01M FILTRATION

ISO 8573-1 CLASS 1

DIE-CAST ALUMINUM

BOROSILICATE MEDIA

40-1000 CFM

FLOW RATING RANGE

0.01 Micron

PARTICLE RETENTION

< 0.003 ppm

RESIDUAL OIL CONTENT

16 bar g

DESIGN PRESSURE

FOUR SEQUENTIAL FILTRATION GRADES

Grade P: Pre-Filter (3.0 µm)

Coarse mechanical separator removing bulk liquid water droplets, rust particles, and pipe scale down to 3 microns.

Grade X: Particulate (1.0 µm)

High-capacity micro-fiber element capturing fine dust and oil aerosols down to 1 micron with residual oil < 0.5 mg/m³.

Grade Y: Coalescer (0.01 µm)

Ultra-fine borosilicate coalescing sleeve capturing sub-micron aerosols down to 0.01 micron with residual oil < 0.01 mg/m³.

TARGET INDUSTRIAL APPLICATIONS

Food & Beverage Packaging Direct Contact

Laser Cutting Resonator & Beam Path

Automotive Surface Finishing Paint Lines

Medical & Dental Hospital Air Networks

ENGINEERING SPECIFICATIONS MATRIX

WMF Series Technical Data (40 to 1,000 CFM)

Standard Ratings: 7.0 bar g operating pressure, 20°C air temperature, 16 bar g max body rating

MODEL NO.	NOMINAL CFM	FLOW RATE	PORT CONNECTION	AVAILABLE GRADES	BODY MATERIAL	DRAIN VALVE
Model Code	CFM	m ³ /hr	BSP Thread	P / X / Y / A	Housing	Standard
WMF 004	40 CFM	68.5 m ³ /hr	1/2" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 008	80 CFM	136 m ³ /hr	3/4" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 012	120 CFM	204 m ³ /hr	1" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 016	160 CFM	272 m ³ /hr	1" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 020	200 CFM	340 m ³ /hr	1.5" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 030	300 CFM	510 m ³ /hr	1.5" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 050	500 CFM	850 m ³ /hr	2" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 065	650 CFM	1105 m ³ /hr	2.5" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 080	800 CFM	1360 m ³ /hr	3" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain
WMF 100	1000 CFM	1700 m ³ /hr	3" BSP	Grade P, X, Y, A	Die-Cast Aluminum	Auto Float Drain

Differential Pressure Pop-Up Indicator: All WMF filter housings include an integrated differential pressure indicator that signals when the element is saturated and requires replacement, preventing excessive line pressure loss.

Request Technical Submittal & Commercial Quotation

Direct factory engineering consultation for custom capacity sizing, P&ID schematics & dimensional drawings.

+91 95972 28969

info@winequipments.com