

Coil cooling towers / dry coolers

WCC series

A coil cooling tower cools process hot water inside a sealed finned-coil heat exchanger, so the water never touches the air. WCC units are built for diesel genset jacket water and other closed loops, cooling water to ambient + 4 °C.



Capacity	Diesel genset duty	Inlet water temperature	Outlet water
40 to 280 TR	150 to 2000 kVA	75 to 90 °C	Ambient + 4 °C

Inside this catalogue

Models & rating conditions	2	How it works & construction	3
Selection & applications	4		



Specifications online

Layout edition 2026-10 · Product-range information. Confirm the selected model and duty with Win Equipments before ordering.

Models & rating conditions

Rating conditions

Inlet water pressure	2 to 3 bar g	Pressure drop	0.5 bar max.
Motors	IP55, extended SS shaft	Enclosure	Fibre glass / GI panels

Capacity & operating data

Model	Capacity TR	Motor power HP	Motor speed rpm	Motors qty	Fan diameter mm
WCC 40	40	3	960	2	1060
WCC 60	60	5	960	2	1060
WCC 80	80	5	960	2	1200
WCC 100	100	5	960	2	1200
WCC 120	120	7.5	960	2	1200
WCC 140	140	7.5	960	2	1200
WCC 160	160	7.5	960	3	1200
WCC 180	180	7.5	960	3	1200
WCC 200	200	7.5	960	4	1200
WCC 220	220	7.5	960	4	1200
WCC 240	240	7.5	960	4	1200
WCC 280	280	7.5	960	6	1200

Construction, dimensions & connections

Model	L × W × H mm	Pressure drop bar max.	Water holding litres	In / out NB
WCC 40	3300 × 1500 × 1400	0.5	72	3" / 3"
WCC 60	3500 × 1500 × 1400	0.5	110	3" / 3"
WCC 80	3300 × 1500 × 1700	0.5	140	3" / 3"
WCC 100	3500 × 1500 × 2750	0.5	180	3" / 3"
WCC 120	3750 × 1500 × 2750	0.5	220	3" / 3"
WCC 140	4300 × 1500 × 2750	0.5	250	3" / 3"
WCC 160	4800 × 1500 × 2750	0.5	280	4" / 4"
WCC 180	5400 × 1500 × 2750	0.5	325	4" / 4"
WCC 200	6000 × 1500 × 2500	0.5	360	4" / 4"
WCC 220	6500 × 1500 × 2500	0.5	390	4" / 4"
WCC 240	7000 × 1500 × 2500	0.5	430	4" / 4"
WCC 280	7000 × 1500 × 2500	0.5	430	4" / 4"

■ Outlet water temperature is ambient + 4 °C. Inlet water 75–90 °C at 2–3 bar g.

How it works & construction

How it works

The coil cooling tower works on heat transfer through a heat exchanger with extended fins, cooled by fan-driven air. The process water stays inside the coil.

1 Hot water in

Hot water from the diesel engine (or other load) enters the coil inlet header.

3 Cold water out

Cooled water leaves the outlet header and a pump returns it to the engine to pick up heat again.

2 Finned coil

Water flows through copper tubes with extended fins; aerodynamically balanced axial fans push air across them.

Construction & features

Coil

- Imported copper tubes
- Extended fins for heat transfer
- Heavy-wall steel header pipes

Structure

- Heavy-duty channel base frame
- Galvanised steel frame
- Non-corrosive fibre glass / GI panels

Fans & motors

- High-efficiency, low-noise axial fans
- IP55 motors with extended SS shaft
- Low motor speed reduces noise

Selection & applications

Applications: Diesel genset cooling · Automobile · Chemical · Electronics · Food & beverage · Glass · Pharmaceutical · Textile · Cement · Distilleries & breweries · Health care & hospitals

How is a coil cooling tower different from an FRP cooling tower?

In an FRP tower the water is sprayed into the air and cooled by evaporation, reaching wet bulb + 4 °C. In a WCC coil tower the water stays sealed inside finned copper tubes and is cooled by air alone, reaching ambient + 4 °C, with no water loss or contamination.

What inlet water temperature can they handle?

Inlet water from 75 to 90 °C at 2 to 3 bar g.

Which genset sizes do WCC units suit?

WCC coil cooling towers cover diesel gensets from 150 to 2000 kVA.

Confirm your selection

Send the model, required capacity, operating temperatures, pressure and site conditions. For a model-specific datasheet or GA drawing, include your installation requirement.

Win Equipments

SF No. 4/195 B, Kallangadu, Nadu Arasur, Arasur Post,
Coimbatore 641 407, Tamil Nadu, India
+91 95972 28969 · +91 95972 28975
info@winequipments.com
winequipments.com

Catalogue values are for product selection. Confirm duty, materials, connections and final dimensions with Win Equipments before ordering. Layout edition 2026-10.