

Assignment 1

Submitted by Devashish Sathawane

check the current directory and make new directory name linux

also make dir1 inside /tmp

use -p to create parent directory if not exist new learning

```
ubuntu@ip-172-31-32-106: ~/ × + v
ubuntu@ip-172-31-32-106:~$ pwd
/home/ubuntu
ubuntu@ip-172-31-32-106:~$ mkdir linux
ubuntu@ip-172-31-32-106:~$ ls
linux  sathawane
ubuntu@ip-172-31-32-106:~$ cd linux
ubuntu@ip-172-31-32-106:~/linux$ mkdir Assignment-01
ubuntu@ip-172-31-32-106:~/linux$ ls
Assignment-01
ubuntu@ip-172-31-32-106:~/linux$ mkdir /tmp/dir1
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp
dir1
snap-private-tmp
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-ModemManager.service-r8QwmC
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-chrony.service-zsJYn6
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-fwupd.service-K7A1tF
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-polkit.service-22TBi8
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-logind.service-MP6l64
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-resolved.service-fgt2fH
ubuntu@ip-172-31-32-106:~/linux$ mkdir -p /tmp/dir1/dir2/dir3
```

verify the directories recursively

```
ubuntu@ip-172-31-32-106:~/linux$ ls -R /tmp/dir1
/tmp/dir1:
dir2

/tmp/dir1/dir2:
dir3

/tmp/dir1/dir2/dir3:
```

Remove the dir3

```
ubuntu@ip-172-31-32-106:~/linux$ rmdir /tmp/dir1/dir2/dir3
ubuntu@ip-172-31-32-106:~/linux$ ls -R /tmp/dir1
/tmp/dir1:
dir2

/tmp/dir1/dir2:
```

Create the first name file inside /tmp

```
ubuntu@ip-172-31-32-106:~/linux$ touch /tmp/devashish
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp
devashish
dirl
snap-private-tmp
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-ModemManager.service-r8QwmC
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-chrony.service-zsJYn6
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-fwupd.service-K7A1tF
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-polkit.service-22TBi8
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-logind.service-MP6l64
systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-resolved.service-fgt2fH
```

Add first line without using any text editor

```
ubuntu@ip-172-31-32-106:~/linux$ echo "This is my first file" > /tmp/devashish
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/devashish
This is my first file
```

add additional line inside same file

```
ubuntu@ip-172-31-32-106:~/linux$ echo "this is a additional content" >> /tmp/devashish
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/devashish
This is my first file
this is a additional content
```

create last name file inside /tmp and add fist line without using text editor

```
ubuntu@ip-172-31-32-106:~/linux$ touch /tmp/sathawane
ubuntu@ip-172-31-32-106:~/linux$ echo "sathawane is my last name" > /tmp/sathawane
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/sathawane
sathawane is my last name
```

here first created the temporary file

then append it with the old file using >>

then replace the original file with the temporary file

```
ubuntu@ip-172-31-32-106:~/linux$ echo "this is line at the beginning" > /tmp/temp
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/sathawane >> /tmp/temp
ubuntu@ip-172-31-32-106:~/linux$ mv /tmp/temp /tmp/sathawane
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/sathawane
this is line at the beginning
sathawane is my last name
```

here I learn the new command << EOF >> instead using the echo command for multiple lines
EOF used to enter multiple lines

```
ubuntu@ip-172-31-32-106:~/linux$ cat << EOF >> /tmp/sathawane
> This is line 1
> This is line 2
> This is line 3
> This is line 4
> This is line 5
> This is line 6
> This is line 7
> This is line 8
> This is line 9
> This is line 10
> EOF
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/sathawane
this is line at the beginning
sathawane is my last name
This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
This is line 6
This is line 7
This is line 8
This is line 9
This is line 10
```

head tails command

```
ubuntu@ip-172-31-32-106:~/linux$ head -5 /tmp/sathawane
this is line at the beginning
sathawane is my last name
This is line 1
This is line 2
This is line 3
ubuntu@ip-172-31-32-106:~/linux$ tail -2 /tmp/sathawane
This is line 9
This is line 10
ubuntu@ip-172-31-32-106:~/linux$ head -6 /tmp/sathawane | tail -1
This is line 4
ubuntu@ip-172-31-32-106:~/linux$ head -8 /tmp/sathawane | tail -6
This is line 1
This is line 2
This is line 3
This is line 4
This is line 5
This is line 6
```

here -la used to display hidden files

```
ubuntu@ip-172-31-32-106:~/linux$ ls -la /tmp
total 64
drwxrwxrwt 14 root root 4096 Jul 27 14:00 .
drwxr-xr-x 22 root root 4096 Jul 27 13:40 ..
drwxrwxrwt 2 root root 4096 Jul 27 13:40 .ICE-unix
drwxrwxrwt 2 root root 4096 Jul 27 13:40 .X11-unix
drwxrwxrwt 2 root root 4096 Jul 27 13:40 .XIM-unix
drwxrwxrwt 2 root root 4096 Jul 27 13:40 .font-unix
-rw-rw-r-- 1 ubuntu ubuntu 51 Jul 27 13:56 devashish
drwxrwxr-x 3 ubuntu ubuntu 4096 Jul 27 13:49 dir1
-rw-rw-r-- 1 ubuntu ubuntu 207 Jul 27 14:04 sathawane
drwx----- 2 root root 4096 Jul 27 13:40 snap-private-tmp
drwx----- 3 root root 4096 Jul 27 13:40 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-ModemManager.service-r8QwmC
drwx----- 3 root root 4096 Jul 27 13:40 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-chrony.service-zsJYn6
drwx----- 3 root root 4096 Jul 27 13:42 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-fwupd.service-K7A1tF
drwx----- 3 root root 4096 Jul 27 13:40 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-polkit.service-22TBi8
drwx----- 3 root root 4096 Jul 27 13:40 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-logind.service-MP6l64
drwx----- 3 root root 4096 Jul 27 13:40 systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-resolved.service-fgt2fH
```

here find command used to search directory or files

-maxdepth 1 search only in particular one directory

-type f represent files

-type d represent directories

```
ubuntu@ip-172-31-32-106:~/linux$ find /tmp -maxdepth 1 -type f
/tmp/devashish
/tmp/sathawane
ubuntu@ip-172-31-32-106:~/linux$ find /tmp -maxdepth 1 -type d
/tmp
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-fwupd.service-K7A1tF
/tmp/.font-unix
/tmp/dir1
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-polkit.service-22TBi8
/tmp/snap-private-tmp
/tmp/.XIM-unix
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-logind.service-MP6l64
/tmp/.X11-unix
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-systemd-resolved.service-fgt2fH
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-ModemManager.service-r8QwmC
/tmp/.ICE-unix
/tmp/systemd-private-8cd1860b3ef144c390dd1ea444e4700e-chrony.service-zsJYn6
```

here I copy Sathawane file to dir2 directory

```
ubuntu@ip-172-31-32-106:~/linux$ cp /tmp/sathawane /tmp/dir1/dir2
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp/dir1/dir2
sathawane
```

I again copy but with the different name same file

```
ubuntu@ip-172-31-32-106:~/linux$ cp /tmp/sathawane /tmp/dir1/dir2/sathawane.copy
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp/dir1/dir2/
sathawane sathawane.copy
```

here I rename the Devashish file to Kashish using mv command

```
ubuntu@ip-172-31-32-106:~/linux$ mv /tmp/devashish /tmp/kashish
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp | grep kashish
kashish
```

move Sathawane file to dir1

```
ubuntu@ip-172-31-32-106:~/linux$ mv /tmp/sathawane /tmp/dir1
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp/dir1/
dir2  sathawane
```

> file_location used to empty file

then use rm to remove file

```
ubuntu@ip-172-31-32-106:~/linux$ > /tmp/dir1/dir2/sathawane.copy
ubuntu@ip-172-31-32-106:~/linux$ cat /tmp/dir1/dir2/sathawane.copy
ubuntu@ip-172-31-32-106:~/linux$ rm /tmp/dir1/dir2/sathawane.copy
ubuntu@ip-172-31-32-106:~/linux$ ls /tmp/dir1/dir2/
sathawane
```