DATE:

HTML

H → Hyper
T → Text
M → Markup
L → Language

It's a markup language not a programming L.

Purpose → defines structure and meaning of webpage content (heading, paragraph, images, links)

Briler plate code

```
<!DOCTYPE html>
<html>
<head>
<title> Document </title>
</head>
<body>
</body>
</html>
```

HTML 5
living standard & continuously updated.

HTML4 & XHTML are outdated

Tag & Element

<body> Content </body>

single → tag

Element.

Types of Tags

Paired tag → It contains starting & closing tag

Void / Self-closing tag → don't have closing tag

DAY: _____ DATE: _____

Starting page name → index.html

<> angular brackets

For headings

<h1> to <h6> levels h1 → biggest } for providing
h6 → smallest } structure.

ctrl+R
↓
Refresh key

For paragraph

<p>

if no content is provided then we use Lorem.

for bold <b> ← previous
 — Now

for Italic/ Emphasis <i> ← Previous
 ← now

Alt+Z
↓
for stop scrolling.

Comments

→ increase readiability

→ comment out the code if unnessary

Ctrl+?

→ To find error debugging

Nesting

if we use tag inside tage this is called nesting

 Myself

DAY _____ DATE: _____

List

Two types of list
order list (ol)
unorder list (ul)

We use this code to write a list
Such like that

List of Stationary
<ul>
<li> Pens </li>
<li>Markers </li>
<li> Sheets </li>
<li> Gel Pens </li>

Superscript (paired tag)

We use <sup> if we want to write something in power

$a^2 \rightarrow$ so, a²

Subscript (paired tag)

We use <sub> if we want to write something in base

$a_2 \rightarrow$ a₂

DAY: _____ DATE: _____

Linking Internal Linking
(Points to another page/resource on same website/domain)
Same

External Linking
(Points to a page/resource on another website) different domain

attribute (Extra information you add to an HTML element)

for linking we use attribute tag

Anchor tag:
<a>

<a href = " link " > Home </a>

hypertext reference. Show on web

→ HTML attribute give additional details or instructions to an HTML tag

→ Always goes inside the opening tag

attribute name = "value"

→ Some attributes are Boolean they don't need a value like

Always use target attribute to open link in new tab if it is in External Linking.	Don't use in internal Linking.

Linking from E2E :-

relative link

Link ↓ from element to element

<a href = "[#] id-name">

↓

sharp

↓

it tells the browser its a same page fragment.

Images

For insert image

We use,

img tag

<img src = " " alt = " ">

↓

here we paste the image address

alt → write relevent text for web excessibility / alternative text.

Don't take images from google

For images

Unsplash

free pic

pixel

DATE: _____ DATE: _____

Forms (paired tag)

We use <form> tag to make forms.

lable tag Firstname

input type="text" → self writing

placeholder → printed on the blank space for example

for moving on next line.

radio → for one choice

checkbox → for more choices

select → selecting one thing (Drop down List)

options → for multiple writing options.

Table

<table>

<tr> → table row

<th> → table header cell

<td> → table data cell

<thead> first row

<tbody> All row between These two.

<tfoot> last row

DATE:

DATE:

colspan

for merging multiple rows

<th colspan = "2">

Rowspan

for merging multiple columns.

Semantic and non-semantic elements:-

Semantic	Non-semantic
meaningful tag	meaningless tag
We identify them	We don't identify them.
<body>	
	footer
	copyrighted dance

Video & audio

Same as images

audio → source link

video → source link → control

↓

if you don't want to skip

mute

loop

Autoplay