```
#include <iostream.h>
#include <conio.h>
#include <string.h>
#include <ctype.h>

void makeLower(char message[])
{
    int i = 0;

    while (message[i] != '\0')
    {
        message[i] = tolower(message[i]);
        i++;
    }
}

void chatbot(char message[])
{
    if (strstr(message, "hello") != NULL ||
        strstr(message, "hi") != NULL)
    {
        cout << "Bot: Hello! How can I help you?\n";
    }
    else if (strstr(message, "your name") != NULL)
    {
        cout << "Bot: I am C++ Chatbot.\n";
    }
    else if (strstr(message, "how are you") != NULL)
    {
        cout << "Bot: I am fine! How are you?\n";
    }
    else if (strstr(message, "college") != NULL)
    {
        cout << "Bot: College is a great place to learn!\n";
    }
    else if (strstr(message, "cpp") != NULL ||
             strstr(message, "c++") != NULL)
    {
        cout << "Bot: C++ is a powerful programming language.\n";
    }
    else if (strstr(message, "ai") != NULL)
    {
        cout << "Bot: AI helps machines perform intelligent tasks.\n";
    }
    else if (strstr(message, "thank") != NULL)
    {
        cout << "Bot: You are welcome!\n";
    }
    else if (strstr(message, "bye") != NULL)
    {
        cout << "Bot: Goodbye! Have a nice day!\n";
    }
    else
    {
        cout << "Bot: Sorry, I don't understand that yet.\n";
    }
}

int main()
{
    char message[200];
    clrscr();
```

```
    cout << "================================\n";
    cout << "       C++ AI CHATBOT\n";
    cout << "================================\n";
    cout << "Type bye to end the conversation.\n\n";

    while (1)
    {
        cout << "You: ";
        cin.getline(message, 200);

        makeLower(message);
        chatbot(message);

        if (strstr(message, "bye") != NULL)
            break;
    }

    cout << "\nChat ended.\n";

    getch();
    return 0;
}
```