

Problem

Let $A = \{ \langle R \rangle \mid R \text{ is a regular expression describing a language containing at least one string } w \text{ that has } 111 \text{ as a substring (i.e., } w = x111y \text{ for some } x \text{ and } y) \}$. Show that A is decidable.

Step-by-step solution


Step 1 of 3

Consider the language,

$$A = \left\{ \langle R \rangle \mid R \text{ is a regular expression describing a language which contains at least one string } w \text{ containing } 111 \text{ as its substring} \right\}$$

The decidability of the language A is proved as follows:

- Define a language S such that $S = \{w \in \Sigma^* \mid w \text{ consists of } 111 \text{ as a substring}\}$.
- The regular expression (RE) for the language S is $(0 \cup 1)^* 111 (0 \cup 1)^*$.
- The DFA D_S for the language S is shown below:



[Comment](#)

Step 2 of 3

- Now think about some RE R on input alphabet Σ .
- If $S \cap L(R) \neq \emptyset$, then R produces a string containing 111 as a substring. Thus, $\langle R \rangle \in A$.
- Similarly, if $S \cap L(R) = \emptyset$ then R produces a string that does not contain 111 . Thus, $\langle R \rangle$ does not belong to A .
- Since $L(R)$ is described by regular language, $L(R)$ is a regular language. Both S and $L(R)$ are regular languages.
- $S \cap L(R)$ is regular because, regular languages are closed under intersection. Thus, $S \cap L(R)$ has some DFA $D_{S \cap L(R)}$.
- Theorem 4.4 shows that $E_{DFA} = \{ \langle K \rangle \mid K \text{ is a DFA with } L(K) \neq \emptyset \}$ is decidable. Thus, there exists a Turing Machine TM which determines E_{DFA} .
- Relate TM T to $D_{S \cap L(R)}$ to determine if $L(R) \cap S \neq \emptyset$.

[Comments \(2\)](#)

Step 3 of 3

Summarization of the above discussion contributes the subsequent Turing machine M to decide A :

$M =$ "On input $\langle R \rangle$, where R is a regular expression:

- Transform R into a DFA D_R by means of the algorithm in the proof of Kleene's Theorem.
- Build a DFA $D_{S \cap L(R)}$ for the language $S \cap L(R)$ from the DFAs D_S and D_R .
- Run TM T that decides E_{DFA} on input $\langle D_{S \cap L(R)} \rangle$.

- If T accepts, reject. If T rejects, accept.

The Turing machine T decides A . Therefore, the language A is decidable.

[Comment](#)