

Problem

Let $A = \{ \langle R, S \rangle \mid L(R) \cap L(S)^C = \emptyset \}$. Show that A is decidable.

Step-by-step solution

Step 1 of 3

The idea of the proof is as follows:

- $L(R)$ is a subset of $L(S)$ iff $L(R) \cap L(S)^C$ is the empty set.
- Use the Theorem 4.4 (or its equivalent for regular expressions) to prove that the condition " $L(R) \cap L(S)^C = \emptyset$ " is decidable.

[Comment](#)

Step 2 of 3

Proof:

The following Turing machine T decides the language A .

"On input string w ,

1. Check that w encodes a pair $\langle R, S \rangle$ where R and S are regular expressions

If it does not, then reject w .

2. Translate R into an equivalent DFA D_R and S into an equivalent DFA D_S .
 3. Build a DFA D_{S^C} that accepts the language $L(D_S)^C$.
 4. Build a DFA D that is the intersection of D_R with D_{S^C} that is, $L(D) = L(D_R) \cap L(D_{S^C})$.
 5. Now, run the Turing machine T with input $\langle D \rangle$ to determine if $L(D)$ is empty.
- If T accepts $\langle D \rangle$ (which means that $L(D)$ is empty), then accept w .
- If T rejects $\langle D \rangle$ (which means that $L(D)$ is NOT empty), then reject w ."

[Comment](#)

Step 3 of 3

Now prove that the Turing machine T decides the language A .

- First of all, prove that T halts on all inputs.
- Let w be any word. There are two possibilities.
- Either w codifies a pair of regular expressions or it doesn't. Checking this will take a finite amount of time.
- If w doesn't codify a pair of regular expressions, then T stops rejecting w .
- Otherwise, assume w codifies a pair $\langle R, S \rangle$.
- Constructing the DFAs described in steps 2, 3, and 4 above is possible (regular languages are closed under intersection and complementation) and takes finite time.

Hence, in all cases T stops on any input w after a finite amount of time.

Hence, it is proved that language A is decidable.

[Comments \(2\)](#)