

If you want to **include source maps in an Angular production build**, Angular CLI supports this via the **--source-map** flag (or **sourceMap** option in **angular.json**).

However, you should be aware of **security implications**:

- **Publicly serving source maps in production** exposes your original TypeScript code to anyone.
- Best practice: generate them but **do not serve them publicly** — instead, upload them to an error tracking service (e.g., Sentry, Rollbar) for debugging.

Option 1 – One-time CLI Command

```
ng build --configuration production --source-map=true
```

This will generate **.map** files alongside your production JS bundles in **dist/**.

Option 2 – Permanent in **angular.json**

Edit your **angular.json**:

```
"configurations": {  
  "production": {  
    "optimization": true,  
    "outputHashing": "all",  
    "sourceMap": {  
      "scripts": true,  
      "styles": true,  
      "vendor": true
```

```
    },  
    "extractCss": true,  
    "namedChunks": false,  
    "aot": true,  
    "extractLicenses": true,  
    "buildOptimizer": true  
  }  
}
```

This ensures **source maps are always generated** for production builds.

Option 3 – Hidden Source Maps for Safe Debugging

If you want to debug production issues **without exposing code to users**:

```
ng build --configuration production --source-map=true
```

Then:

- **Do not deploy .map files** to your public server.
- Upload them to a private error tracking service (e.g., Sentry CLI: **sentry-cli upload-dif**).
- This way, you can still map stack traces to TypeScript without leaking code.

✅ Recommendation:

For public-facing apps, **never serve .map files directly** in production. Use hidden source maps + private storage for debugging.

If you want, I can give you a **secure Angular build script** that generates source maps for debugging but automatically strips them from the

public deployment.

Do you want me to prepare that?