Data Analytics Capstone

Accuracy and Fairness Trade-offs in Machine Learning Credit Default Prediction: A Threshold-Level Governance Study for Retail Lenders

Final Report

Mrityunjay Ravi Iyer

Walsh College

QM640: Data Analytics Capstone

[Mentor Name]

Fall 2026 Term

October 13, 2026

Table of Contents

Abstract....4
Introduction....5
Background and Context....5
Business Problem Statement....6
Technical Problem Statement....6
Purpose and Research Questions....7
Scope....9
Literature Review....9
Machine Learning in Credit Scoring....9
Fairness Definitions and Impossibility....10
Fairness in Credit....11
Mitigation Methods....11
Regulatory Context....12
Gaps and Justification of the Approach....12
Data and Research Methodology....13
Data Source and Ethics....13
Variables and Data Dictionary....13
Cleaning and Sampling Design....15
Exploratory Data Analysis....17
Algorithms and Technical Justification....20
Evaluation Metrics....21
Statistical Methods....21
Analytical Workflows....22
Results....27
RQ1: Predictive Performance....27
RQ2: Outcome Disparity....29
RQ3: Fairness at a Simulated Cut-off....30
RQ4: Mitigation Trade-offs....34
Reproducibility Across Machines....37
Analysis and Discussion....38
Technical Interpretation....38
Business Implications....39
Synthesis Against the Hypotheses....40
Implementation....42

Practical Deployment as a Validation Artefact....42
Algorithmic Steps....42
Human and Machine Requirements for Reproducibility....43
Execution Environment....43
Project Timeline as Executed....44
Limitations and Next Steps....46
References....49
Appendix A....54
Appendix B....55
Appendix C....60
Appendix D....61
Appendix E....66

Abstract

Retail lenders deploy machine learning default models that outrank logistic scorecards on accuracy but seldom report how the resulting decisions differ by demographic group or what it costs to narrow the difference. This study audits three default-prediction models on the UCI Default of Credit Card Clients dataset (30,000 Taiwanese cardholders, 22.1% default) under a stratified five-fold design that keeps model fitting, policy calibration, and evaluation on disjoint data. Four questions are answered. Gradient boosting reaches an area under the ROC curve of 0.784 against 0.755 for logistic regression, a paired difference of 0.029 (95% CI 0.026 to 0.033, DeLong $z = 15.7$, $p < .001$). Men default 3.4 points more often than women ($z = 6.92$, $p < .001$), a gap that halves after adjustment for credit limit and age. At a simulated 75% retention cut-off the model trained without sex wrongly flags creditworthy men 2.8 points more often than creditworthy women (95% CI 1.8 to 3.8, $p < .001$). That gap passes a ±0.05 benchmark by equivalence test and fails a ±0.02 benchmark. Disparate impact stands at 0.946. Including sex as an input widens the gap by 1.0 point. Reweighing the training data is non-inferior on AUC but closes the gap only when the model can see sex. Per-sex thresholds close it to 0.4 points at a bad-rate cost of 0.03 points. The audit is delivered as a reproducible pipeline and a threshold-level decision table for model validation. An age-band disparity of 6.8 points, found along the way, is the larger unaddressed risk.

Keywords: credit scoring, algorithmic fairness, disparate impact, equal opportunity, gradient boosting, model validation, threshold adjustment, reweighing

Introduction

Background and Context

The credit decisions I review for Indian banks and non-banking financial companies (NBFCs) are now produced, in most new retail programmes, by gradient-boosted tree models. Logistic scorecards are now the exception in new builds. Ensemble methods have improved on logistic regression in most published benchmarks, although the gain varies by dataset: Lessmann et al. (2015) compared 41 classifiers on eight credit datasets and found boosted and bagged trees ahead on the area under the receiver operating characteristic curve (AUC) in most cases. What is less often measured is whether the model treats groups of borrowers differently and by how much. In my experience that question gets a policy answer, usually that sex and marital status were excluded from the feature set. It does not get a number. Excluding the protected attribute does not establish that the resulting decisions are free of group-level differences, because other features can carry the same information (Kamiran & Calders, 2012).

Regulatory attention to fairness in financial AI has increased, although the obligations depend on jurisdiction and instrument. The Reserve Bank of India (RBI) FREE-AI Committee report of 13 August 2025 sets out seven guiding principles and 26 recommendations, among them disclosure of AI-driven credit assessments and fairness provisions proposed for the Digital Lending Directions (Reserve Bank of India, 2025). Those provisions stay advisory until the RBI adopts them. The European Union's Artificial Intelligence Act lists credit scoring of natural persons as a high-risk use in Annex III (European Parliament & Council of the European Union, 2024). It does not apply in India and serves here as a point of comparison. In the United States the problem has been measured. Fuster et al. (2022) found that machine learning in mortgage underwriting raised accuracy but widened the dispersion of predicted default across racial groups. Bartlett et al. (2022) found algorithmic lenders charging Latinx and African-American borrowers higher rates.

This study places the trade-off in a threshold-level decision table using the measures validation teams already read: retention rate, default rate among retained customers, AUC, and

the fairness gap at each cut-off. My position, developed in the AI strategy coursework of this programme, is that fairness in a deployed model is decided by configuration choices, the threshold and the sample weights above all, and that no governance document changes the outcome. This capstone tests that position on a public dataset with stated statistical power.

Business Problem Statement

A retail lender's model validation unit signs a default model into production on the strength of its AUC and Kolmogorov–Smirnov (KS) statistic, and attests to fairness by confirming that protected attributes are absent from the inputs. The chief risk officer who owns that sign-off cannot answer, in numbers, three questions a supervisor or a board risk committee may put. How differently do the model's decisions fall on men and women at the operating cut-off? Did excluding sex from the inputs change that? What would the lender give up, in accuracy or in bad debt, to narrow the gap? Without those numbers the fairness attestation describes a process and says nothing about outcomes. If the model is later challenged, the lender has no decision record to show. What is missing, in business terms, is a validation artefact that expresses the fairness trade-off in the units a credit policy committee already uses and that can be regenerated on demand from the lender's own scores.

Technical Problem Statement

The technical problem is a supervised binary classification task with an attached fairness audit, evaluated so that no estimate is contaminated by the data that produced the model or the policy. The dependent variable is DEFAULT, a missed payment in the month after a six-month observation window, coded 1 or 0. Twenty-three cardholder attributes plus four engineered features (Table 2) are the independent variables. Two derived decision variables, FLAG (simulated referral) and RETAIN (simulated favourable decision), carry the audit. Because the dataset records outcomes for customers who already held credit, the setting is a retrospective portfolio-retention simulation. A threshold applied to it simulates whom a lender would have retained or referred, and nothing about whom it would have approved. Three estimation problems follow. First, model comparison with a pre-specified paired contrast on correlated

AUCs. Second, group-level inference on proportions (default rates, false-decline rates, retention rates) with intervals, equivalence tests against stated benchmarks, and paired inference for before-and-after comparisons on the same individuals. Third, a policy-calibration problem in which cut-offs, per-group thresholds, and training weights must be set on data disjoint from both the training rows and the evaluation rows.

Purpose and Research Questions

Four aims follow, one per research question. Each question, its hypotheses, and the variables involved are set out below and summarised in Table 1.

Research Question 1 (RQ1): Predictive Performance

How do logistic regression, random forest (Breiman, 2001), and gradient boosting (Chen & Guestrin, 2016) compare in predicting next-month default, measured by AUC with a 95% confidence interval (CI), and is the AUC improvement of the pre-specified gradient boosting model over the logistic baseline statistically significant under the DeLong et al. (1988) test?

$H1_0$: $AUC_{GB} = AUC_{LR}$. $H1_1$: $AUC_{GB} > AUC_{LR}$. Gradient boosting against logistic regression is the single pre-specified contrast. Random forest is a secondary benchmark.

Research Question 2 (RQ2): Outcome Disparity

Do observed default rates differ by sex and by age band, and how large are the differences before and after adjustment for credit limit and age?

$H2_0$: $p_{male} = p_{female}$. $H2_1$: $p_{male} \neq p_{female}$. For age bands, $H2b_0$ is independence of default and age band. A difference of 0.03 is the planned minimum meaningful difference used for power and sits outside the hypothesis.

Research Question 3 (RQ3): Fairness at a Simulated Cut-off

At a simulated cut-off that retains 75% of existing cardholders, how do favourable-selection rates and false-decline rates differ by sex, and how do those differences compare with two predefined research benchmarks, a disparate impact ratio of at least 0.80 and a false-decline rate gap within ±0.05?

$H3_0$: $FDR_{male} = FDR_{female}$, where FDR is the false-decline rate, the share of non-defaulters flagged. $H3_1$: $FDR_{male} \neq FDR_{female}$. Equivalence tests carry the benchmark comparison. The model audited is trained without SEX, EDUCATION, and MARRIAGE, the configuration lenders deploy under unawareness.

Research Question 4 (RQ4): Mitigation Trade-offs

How do training-data reweighing (Kamiran & Calders, 2012) and group-specific threshold adjustment (Hardt et al., 2016) change the false-decline rate gap and the simulated portfolio outcomes, and what predictive-performance or decision-quality cost arises under each?

For reweighing, $H4_0$: $AUC_{RW} \leq AUC_{base} - 0.01$ and $H4_1$: $AUC_{RW} > AUC_{base} - 0.01$, a one-sided non-inferiority test on paired AUCs. For threshold adjustment the AUC is unchanged by construction, so the cost is measured at the decision level as the change in the default rate among retained cardholders at a common retention rate, with a paired bootstrap interval.

Table 1
Research Questions, Hypotheses, and Variables

RQ	Null hypothesis	Dependent variable(s)	Independent variable(s)	Primary test
RQ1	AUC of gradient boosting equals AUC of logistic regression	DEFAULT (held-out score ranking)	23 attributes and 4 engineered features	DeLong paired AUC test, one-sided
RQ2	Default rate equal by sex; default independent of age band	DEFAULT	SEX; AGE_BAND; AGE and log LIMIT_BAL as covariates	Two-proportion z; chi-square; logistic regression
RQ3	False-decline rate equal by sex at 75% retention	FLAG, RETAIN by group (false-decline rate, retention rate)	SEX	Two-proportion z; TOST equivalence; bootstrap
RQ4	Reweighed AUC inferior to baseline by more than 0.01; decision-level costs zero	AUC; false-decline gap; default rate among retained	Mitigation configuration	DeLong non-inferiority; paired bootstrap

Note. AUC = area under the receiver operating characteristic curve. TOST = two one-sided tests.

Scope

In scope are one public dataset of 30,000 cardholders, three model families, one primary protected attribute (sex) and one secondary attribute (age band), and two mitigation methods. Two fairness measures serve as tests, the disparate impact ratio on RETAIN and the false-decline rate gap, with the true-positive rate gap and equalized odds reported alongside. A trade-off table across simulated retention rates and a Shapley additive explanations (SHAP) decomposition by sex (Lundberg & Lee, 2017) complete the scope. Out of scope are neural network classifiers, whose interpretability cost on tabular high-stakes decisions is not repaid by their accuracy gain (Rudin, 2019), synthetic data, in-processing mitigation, calibration-based fairness criteria, causal inference, profit optimisation, reject inference, and deployment.

Literature Review

Five strands make up the literature: the accuracy case for machine learning in credit scoring, the formal definitions of group fairness and the impossibility results that constrain them, empirical fairness studies in credit, mitigation methods, and the regulatory frame. I review each for what it establishes and where it stops, and close with the gap this study addresses.

Machine Learning in Credit Scoring

Credit scoring has used statistical classifiers since the 1960s, with logistic regression dominant because its coefficients can be read, challenged, and regulated (Hand & Henley, 1997). Lessmann et al. (2015), updating Baesens and colleagues' 2003 comparison, ran 41 classifiers on eight datasets and found heterogeneous ensembles and boosted trees ahead of logistic regression in most settings, with gains of a few AUC points. Friedman (2001) supplied the gradient boosting machine the modern implementations descend from, and Chen and Guestrin (2016) the XGBoost system used here, which postdates the Lessmann benchmark. Breiman's (2001) random forest remains the standard bagged comparator. Khandani et al. (2010) showed at a large United States bank that tree-based models on transaction and bureau data forecast delinquency well enough to cut losses by 6% to 25% under simulated credit-line management, and Berg et al. (2020) showed that even ten digital-footprint variables reach an AUC comparable to a bureau

score. Two conclusions carry into this study. The accuracy gain from ensembles is real but modest, one to three AUC points, so a fairness intervention that costs a full point gives back a large share of what the ensemble bought. The gain also depends on the decision rule attached to the score, a point Khandani and colleagues stressed, and it is the reason this study works at the threshold level. Rudin (2019) argues that for high-stakes decisions the interpretability cost of black-box models is paid in a currency regulators control. On that argument the logistic baseline stays in as the comparator a validation unit can read line by line.

Fairness Definitions and Impossibility

Formal fairness definitions outnumber what any one audit can satisfy. Dwork et al. (2012) framed individual fairness as treating similar people similarly. Group definitions followed: demographic parity (equal selection rates), equalized odds and equal opportunity (equal error rates across groups, with equal opportunity restricted to the favourable outcome) in Hardt et al. (2016), and calibration within groups. Verma and Rubin (2018) catalogued twenty such definitions and showed that most cannot hold together. Kleinberg et al. (2017) and Chouldechova (2017) proved the constraint that matters most here. When base rates differ between groups, a classifier cannot be calibrated within each group and have equal false-positive and false-negative rates at the same time, except in degenerate cases. So a lender must choose which criterion to govern to, and the choice depends on whose error matters. Feldman et al. (2015) expressed the four-fifths rule from United States employment-selection guidelines (Uniform Guidelines on Employee Selection Procedures, 1978) as a disparate impact ratio and showed how to certify and repair it. Barocas et al. (2019) and Mehrabi et al. (2021) survey the field and document the failure of fairness through unawareness: removing the protected attribute does not remove disparity when other features carry the same information. This study takes equal opportunity, read from the borrower's side as the false-decline rate, as the primary criterion, with the disparate impact ratio second. Kozodoi et al. (2022) found separation-type criteria the most practical for scorecards, and a wrongly declined creditworthy customer is the harm a conduct regulator asks about.

Fairness in Credit

Empirical credit studies have measured the trade-off that the definitions predict. Fuster et al. (2022) found, on United States mortgage data, that replacing logistic regression with machine learning raised predictive accuracy but spread the predicted default rates further apart across racial groups. Accuracy improved for some groups far more than for others. Bartlett et al. (2022) found that algorithmic lenders charged Latinx and African-American borrowers higher rates even where rejection rates were similar. Kozodoi et al. (2022) applied several fairness criteria to seven credit datasets, found that most could be met at a low profit cost, and identified separation as the practical criterion. Corbett-Davies and Goel (2018) argued that threshold rules, with a single threshold or group-specific thresholds, are where the fairness choice is made in practice. They also argued that the costs of fairness constraints should be measured against the decision maker's objective. Most papers assert those costs. None of these papers reports the result as a credit committee reads it, with approval or retention rate, bad rate, and AUC at each candidate cut-off and the fairness gap alongside. None separates the calibration of the cut-off from its evaluation.

Mitigation Methods

Mitigation methods are grouped by where they act. Pre-processing changes the training data: Kamiran and Calders (2012) reweigh each row by the ratio of the expected to the observed joint frequency of its group and outcome, so that group and outcome become independent in the weighted training set. In-processing changes the learning objective, for instance through adversarial debiasing, and is out of scope here. Post-processing changes the decision rule: Hardt et al. (2016) showed that any classifier can be made to satisfy equal opportunity or equalized odds by choosing group-specific thresholds, possibly randomised, on a held-out set, and Fairlearn implements that construction (Bird et al., 2020). Their costs fall in different places. Reweighing retrains the model and can change the ranking, so its cost is read from the AUC. Threshold adjustment leaves the scores intact, so its cost appears in the decision-level outcome, here the default rate among retained cardholders. It carries a governance cost too, because the

protected attribute is needed at decision time, and in some jurisdictions that is disparate treatment. The literature states, but rarely quantifies on a single dataset, that reweighing on an attribute the model does not see can only act through proxies. This study tests that directly.

Regulatory Context

The RBI FREE-AI Committee report (Reserve Bank of India, 2025) recommends, among 26 items, that regulated entities disclose AI-driven credit assessments and adopt board-level AI governance with fairness provisions, and it proposes amendments to the Digital Lending Directions. Until adopted, the recommendations are advisory. The EU Artificial Intelligence Act (European Parliament & Council of the European Union, 2024) classifies creditworthiness assessment of natural persons as high risk and attaches logging, human oversight, and conformity obligations. The four-fifths rule originated in the 1978 Uniform Guidelines on Employee Selection Procedures and has no statutory standing in Indian credit regulation. This study treats 0.80 and ±0.05 as research benchmarks for that reason, and no compliance claim rests on them.

Gaps and Justification of the Approach

Four gaps follow from the review. First, the empirical credit studies report group differences in model outputs. They stop short of the decision-level trade-off at a lender's operating point in the units a credit policy uses. Second, most fairness evaluations set thresholds and post-processors on the same data they then report performance on, which overstates the result. Hardt et al. (2016) themselves set thresholds on held-out data, but applied studies seldom separate calibration from evaluation. Third, the comparative cost of pre-processing and post-processing on one dataset, measured with paired inference, is rarely reported. Whether reweighing depends on the model seeing the attribute is stated in the literature and, as far as I can find, never measured. Fourth, the regulatory texts now ask for numbers that the validation literature does not yet routinely supply. Each gap gets an answer here: a trade-off table across retention rates, a three-way split within each fold that separates fitting, calibration, and

evaluation, paired bootstrap inference for every before-and-after comparison, and a decision record a validation unit can regenerate.

Data and Research Methodology

Data Source and Ethics

The study uses dataset 350, Default of Credit Card Clients, from the UCI Machine Learning Repository, derived from Yeh and Lien (2009) and donated to the repository in January 2016. It describes 30,000 cardholders of a Taiwanese card issuer observed from April to September 2005, and the target records a missed payment in October 2005. It is available at https://archive.ics.uci.edu/dataset/350/default+of+credit+card+clients under the persistent identifier https://doi.org/10.24432/C55S3H, and the repository's recommended citation is Yeh (2009). A single Excel workbook holds the 30,000 rows and 25 columns, with no missing values, under a Creative Commons Attribution 4.0 licence. The download script in the repository fetches the file, verifies its SHA-256 checksum (c76095b2…9e44), and checks the documented structure: 30,000 by 25, 6,636 defaults, 11,888 male and 18,112 female cardholders.

The file contains no names, account numbers, addresses, or dates of birth, and the identifier is a sequential index with no link to the issuer's systems. Released for secondary analysis under an open licence, the data were used as published, and no re-identification or linkage was attempted. SEX holds two administrative categories recorded by the issuer in 2005 and does not describe the range of gender identities. Sex and marital status are used only to measure disparity, never as inputs to the audited model. A measured disparity is evidence of a group-level difference in simulated decisions. It is not a finding of unlawful discrimination, which depends on law, intent, and business justification this study does not examine. Passing the two benchmarks establishes no regulatory compliance in any jurisdiction.

Variables and Data Dictionary

Table 2 defines every variable in the file, the four engineered features, and the two simulated decision variables. Monetary variables are in New Taiwan dollars (NT$). Where the

repository documentation is silent, the table records my interpretation as an assumption and names the sensitivity run that tests it.

Table 2
Data Dictionary

Variable	Type	Meaning	Units or coding	Role
ID	Integer	Row identifier	1 to 30,000	Keys out-of-fold predictions; not a feature
LIMIT_BAL	Numeric, continuous	Credit limit including supplementary cards	NT$, 10,000 to 1,000,000	Independent; candidate proxy for sex
SEX	Categorical, nominal	Sex as recorded by the issuer	1 = male, 2 = female	Protected attribute (RQ2 to RQ4); excluded from the unaware model
EDUCATION	Categorical, ordinal	Highest education attained	1 = graduate school, 2 = university, 3 = high school, 4 = other; 0, 5, 6 undocumented, kept as one level (sensitivity B)	Independent; excluded from the unaware model
MARRIAGE	Categorical, nominal	Marital status	1 = married, 2 = single, 3 = other; 0 undocumented, kept as a level (sensitivity B)	Independent; excluded from the unaware model
AGE	Numeric, discrete	Age at observation	Years, 21 to 79	Independent; source of AGE_BAND
PAY_0, PAY_2 to PAY_6	Categorical, ordinal (6)	Repayment status, September back to April 2005	1 to 9 = months of delay; −1 = paid in full; −2 and 0 undocumented, read as no consumption and revolving use (sensitivity A)	Independent; strongest expected predictors
BILL_AMT1 to BILL_AMT6	Numeric, continuous (6)	Statement balance, September back to April	NT$; negative values are credit balances	Independent

Variable	Type	Meaning	Units or coding	Role
PAY_AMT1 to PAY_AMT6	Numeric, continuous (6)	Amount paid, September back to April	NT$, non-negative	Independent
DEFAULT	Binary	Missed payment in October 2005	1 = default, 0 = no default	Dependent variable
AGE_BAND (derived)	Categorical, ordinal	Age in four bands	< 30, 30 to 39, 40 to 49, ≥ 50	Secondary protected attribute
UTILISATION (derived)	Numeric, continuous	Latest balance over credit limit	BILL_AMT1 / LIMIT_BAL; negative and > 1 retained	Independent, engineered
PAY_RATIO (derived)	Numeric, continuous	Latest payment over prior balance	PAY_AMT1 / BILL_AMT2, capped at 1; 1 where BILL_AMT2 ≤ 0	Independent, engineered
MAX_DELAY (derived)	Numeric, discrete	Worst repayment code in six months	Code −2 to 9; not a duration	Independent, engineered
FLAG (decision)	Binary	Simulated referral: score above cut-off	1 = flagged, 0 = not	Numerator of the false-decline rate
RETAIN (decision)	Binary	Simulated favourable decision	1 − FLAG	Basis of the disparate impact ratio

Note. NT$ = New Taiwan dollars. The unaware model is trained with SEX, EDUCATION, and MARRIAGE removed; an aware model including them is trained for comparison.


Cleaning and Sampling Design

Three coding issues were handled before modelling. EDUCATION holds undocumented values 0, 5, and 6 in 345 rows and MARRIAGE an undocumented 0 in 54 rows. Both were kept as a distinct level so the assumption stays visible, and sensitivity B merges them into the documented other category. The repayment-status fields hold −2 and 0, which the repository does not define. I read them as no consumption and revolving use, and sensitivity A collapses both into one non-delinquent code. No value is missing and the identifier is unique, so no row was dropped. Monetary variables are right-skewed (Table 3) and were transformed by a sign-preserving log for the logistic model only, with the transform fitted inside each training fold. Tree models received the raw values.

The sampling design is stratified five-fold cross-validation (CV) keyed on ID and stratified on sex by outcome, so each held-out fold holds 6,000 cardholders. Inside each outer training set of 24,000, 19,200 rows form the fit partition, on which models are trained and tuned by inner three-fold CV. The other 4,800 form the calibration partition, where isotonic recalibration, the retention cut-off, the per-sex thresholds, and the reweighing weights are set. Each held-out fold is scored once and never used to choose anything. Every cardholder receives one prediction and one decision from a configuration that did not see them, and the evaluation pool is the full 30,000. Figure 1 shows the pipeline. Every random process uses the seed 640.

Figure 1

Solution Pipeline From Data Acquisition to Decision Table



Note. Stages 1 and 2 run once. Stage 3 answers RQ1, stage 4 sets cut-offs and weights for RQ3 and RQ4, stage 5 produces every reported estimate on held-out folds, and stage 6 assembles the trade-off table.

The sample-size plan from the synopsis is reproduced in Appendix B. Its binding requirement was 14,587 cardholders for a 95% CI half-width of 0.01 on an AUC of 0.78 (Hanley & McNeil, 1982). The pre-specified paired contrast needed 4,470 at a correlation of 0.70 (Fleiss et al., 2003, for the two-proportion calculations and DeLong et al., 1988, for the paired AUC variance). At 30,000, the evaluation pool is 2.06 times the requirement. The observed paired-AUC correlation between XGBoost and logistic regression was 0.85, above the 0.70 planning assumption, so the design was conservatively powered. The ten-week plan under which the work was carried out, and what each week produced, is recorded in Table 13.

Exploratory Data Analysis

Univariate summaries of the numeric variables are in Table 3. Credit limit is right-skewed with a median of NT$140,000, and age has a median of 34 with a long right tail to 79. The monthly payment amounts are the most skewed variables in the file (skewness 10 to 30), and they are the reason the logistic pipeline carries a log transform. The six repayment-status codes have medians of 0 and 75th percentiles of 0, so most cardholders were current in every month and the signal lies in the minority with positive codes. Of the categorical variables, 60.4% of cardholders are female, 46.8% hold a university degree and 35.3% a graduate degree, and 53.2% are single. Default prevalence is 22.1%.

Table 3
Univariate Summary of Numeric Variables (N = 30,000)

Variable	Mean	SD	Min	Median	Max	Skew
LIMIT_BAL (NT$)	167,484	129,748	10,000	140,000	1,000,000	0.99
AGE (years)	35.5	9.2	21	34	79	0.73
PAY_0 (code)	−0.02	1.12	−2	0	8	0.73
PAY_6 (code)	−0.29	1.15	−2	0	8	0.95
BILL_AMT1 (NT$)	51,223	73,636	−165,580	22,382	964,511	2.66
BILL_AMT6 (NT$)	38,872	59,554	−339,603	17,071	961,664	2.85
PAY_AMT1 (NT$)	5,664	16,563	0	2,100	873,552	14.67
PAY_AMT6 (NT$)	5,216	17,777	0	1,500	528,666	10.64
UTILISATION	0.42	0.41	−0.62	0.31	6.46	0.82
PAY_RATIO	0.40	0.44	0.00	0.10	1.00	0.56
MAX_DELAY (code)	0.44	1.35	−2	0	8	0.69


Note. Intermediate months (PAY_2 to PAY_5, BILL_AMT2 to BILL_AMT5, PAY_AMT2 to PAY_AMT5) lie between the September and April values shown and are in the repository table eda_summary_numeric.csv.

Bivariate analysis (Figure 2) shows where the outcome varies. Men default at 24.2% and women at 20.8%. By age band it is lowest at 30 to 39 (20.3%) and highest at 50 and over (25.3%), a U shape with no monotone trend. The September repayment code separates the outcome more sharply than any other field: cardholders coded 0 or below default at 13% to 17%,

those one month late at 34%, and those two or more months late at 50% to 78%. Defaulters have a median credit limit of NT$90,000 against NT$150,000 for non-defaulters and a median utilisation of 0.49 against 0.27. Men have a lower median credit limit than women, NT$130,000 against NT$150,000, and higher median utilisation, 0.41 against 0.25 (Figure 3). Through those two fields a model that never sees sex can still tell men from women.

Figure 2


Default Rate by Sex, Age Band, and September Repayment Code



Note. Repayment code 1 to 8 denotes months of delay; −2, −1, and 0 denote no consumption, paid in full, and revolving use respectively (the first and last are interpretations; see Table 2).

Figure 3

Distributions of Credit Limit and Utilisation by Outcome




Note. Credit limit on a log10 scale. Utilisation clipped to [−0.5, 1.5] for display; values outside the range are retained in modelling.

Multivariate structure was examined with Spearman correlations among the predictors and the outcome (Figure 4). Among the predictors, the six repayment codes are strongly correlated with one another (0.5 to 0.8), as are the six bill amounts (above 0.8), so the engineered MAX_DELAY summarises the first block and UTILISATION the second against the credit

limit. With the outcome, MAX_DELAY has the largest correlation (0.32), followed by PAY_0 (0.29) and the earlier repayment codes in declining order (0.22 to 0.14), while credit limit (−0.17), the latest payment amount (−0.16), and the payment ratio (−0.13) are protective. Age is uncorrelated with the outcome (0.005) although the band pattern is U-shaped, so RQ2 uses age band and not age. Figure 5 shows the credit-limit difference by sex that the SHAP analysis later identifies as the third-largest carrier of the fairness gap.


Figure 4

Spearman Correlation Among Predictors and the Outcome



Note. Cells with absolute correlation of at least 0.30 are annotated.

Figure 5
Credit Limit by Sex



Note. Boxes show the interquartile range of log10 credit limit; the line is the median.

Algorithms and Technical Justification

Three supervised classifiers were trained on identical fit partitions and scored on identical held-out folds. Logistic regression with L2 regularisation, standardised numeric inputs, and one-hot encoded categories is the baseline, because it is the model most Indian lenders still hold in production and the one a validation unit can read line by line. Its regularisation strength was chosen by inner three-fold grid search over four values. Random forest (Breiman, 2001) with 500 trees, a minimum leaf size of 20, and balanced subsample class weights is the bagged comparator. XGBoost (Chen & Guestrin, 2016) is the challenger, with learning rate, depth, number of trees, subsampling, column sampling, minimum child weight, and L2 penalty chosen by a 12-candidate randomised search under inner three-fold CV on the fit partition, so no held-out row influences a tuning choice. The selected values per fold are in Appendix C. Class imbalance (22% positives) was handled by class weighting, which can distort probability calibration, so every model's raw probabilities were recalibrated by isotonic regression fitted on the calibration partition and the Brier score is reported before and after. Lessmann et al. (2015) showed that these three families bracket the achievable range on credit data. The pre-specified contrast is XGBoost against logistic regression, fixed in the synopsis, so the significance test is never applied to whichever model happens to score highest.

Evaluation Metrics

Classification metrics are defined from the confusion matrix of true positives (TP), false positives (FP), true negatives (TN), and false negatives (FN), where a positive is a predicted default, so FLAG = 1 is the positive prediction and RETAIN = 1 − FLAG.

$$Precision = \frac{TP}{TP + FP}, TPR = \frac{TP}{TP + FN}, FDR = FPR = \frac{FP}{FP + TN} \tag{1}$$

$$F_1 = \frac{2 \times Precision \times TPR}{Precision + TPR} \tag{2}$$

$$AUC = \frac{1}{n_D n_N} \Sigma_{i,j} I_{ij} \tag{3}$$

$$Brier = \frac{1}{N} \sum_{i=1}^{N} \left(\hat{p}_i - y_i \right)^2 \tag{4}$$

In Equation 1 the false-decline rate (FDR) is the false-positive rate read from the borrower's side, the share of non-defaulters who are flagged. In Equation 3, I_{ij} equals 1 when defaulter *i* scores above non-defaulter *j* and 0 otherwise, so the AUC is the probability that a random defaulter outranks a random non-defaulter, and it does not depend on the cut-off. KS is max |TPR(*t*) − FPR(*t*)| over thresholds *t*, and the Brier score (Equation 4) measures calibration. The fairness measures compare the two sex groups *g*. The favourable-selection rate is $RETAIN_g = (TN_g + FN_g)/n_g$, and the disparate impact ratio is DI = min($RETAIN_g$)/max($RETAIN_g$), with the four-fifths benchmark met when DI ≥ 0.80 (Feldman et al., 2015). The false-decline gap $FDR_{male} - FDR_{female}$ is the equal opportunity difference of Hardt et al. (2016) once the favourable outcome is taken as non-default. The true-positive gap is $TPR_{male} - TPR_{female}$, and the equalized odds difference is the larger of the two absolute gaps. The default rate among retained cardholders, total FN over total RETAIN, is the simulated portfolio outcome at each cut-off.

Statistical Methods


Each research question carries a formal test, an effect size with a 95% interval, an assumption check, and a decision at α = .05, and the full register of 34 tests is in Appendix D.

AUC intervals and the paired contrast use the DeLong et al. (1988) method in the fast form of Sun and Xu (2014). Secondary contrasts are Holm-adjusted (Holm, 1979). A Nadeau and Bengio (2003) corrected paired *t*-test across the five folds is reported as a check on the pooled contrast, since fold-level AUCs share training rows. Calibration is examined by Hosmer–Lemeshow decile test (Hosmer et al., 2013) and reliability plot. Proportions are compared by two-proportion *z* tests with pooled standard errors and Newcombe intervals, with Cohen's (1988) *h* as the effect size. Independence of default and age band is tested by chi-square with Cramér's *V* and a bootstrap interval, followed by Holm-adjusted pairwise tests. Logistic regression, with variance inflation factors reported, estimates the adjusted sex effect. Where the research claim is that a gap lies within a tolerance, the two one-sided tests procedure (Schuirmann, 1987) is applied at the stated margin. A confidence interval inside a band is a reading. An equivalence test is a decision. Fairness measures carry 1,000-draw stratified bootstrap intervals. Within a sex-by-outcome stratum the resampled flag count is exactly binomial, so the bootstrap is exact. Comparisons between configurations on the same individuals use a paired stratified bootstrap of the difference with 10,000 draws. Reweighing is tested for non-inferiority of the paired AUC at a margin of 0.01. Where the report reads a change as immaterial, failing to reject a change of zero is not enough, so each such change is also tested for equivalence within ±0.5 percentage points, a tenth of the fairness benchmark, by the bootstrap form of the two one-sided tests. The change in the overall flag rate under threshold adjustment is tested the same way on the paired difference of proportions. Statistical reporting follows APA conventions.

Analytical Workflows

Figures 6 to 9 give the step-by-step workflow for each research question. Each step maps onto a script in the repository (Appendix A): data preparation and fold assignment in prepare.py, model fitting and calibration in train.py, cut-offs, thresholds, and weights in policy.py, metrics and inference in evaluate.py, and one analysis script per question.

Figure 6
Workflow for RQ1, Predictive Performance




Repeated for five folds; every cardholder scored once by a model that did not see them. Secondary contrasts Holm-adjusted; fold-level corrected t-test as a further check.

Note. LR = logistic regression; XGB = XGBoost; GB = gradient boosting; CI = confidence interval; KS = Kolmogorov–Smirnov statistic.

For RQ1 the algorithmic components run in order. Folds and partitions are assigned by stratified sampling. The logistic penalty and seven XGBoost hyperparameters are tuned by inner CV on the fit partition, the three models are trained on that partition, and their probabilities are recalibrated by isotonic regression on the calibration partition. The held-out fold is scored, the five held-out folds are pooled into one evaluation set of 30,000, and the pre-specified paired DeLong contrast is run with the secondary contrasts Holm-adjusted. This sequence runs twice, once for the unaware feature set and once for the aware set.


Figure 7
Workflow for RQ2, Outcome Disparity



Note. SE = standard error; VIF = variance inflation factor; TOST = two one-sided tests.

RQ2 needs no model. Default rates are tabulated by sex and by age band on the full file. The sex difference gets the two-proportion test with a Newcombe interval and Cohen's *h*, and the age bands get the chi-square test with Cramér's *V*, a bootstrap interval, and six Holm-adjusted pairwise comparisons. A logistic regression of DEFAULT on sex, age, and log credit limit, with a collinearity check, gives the adjusted sex effect, and an extended regression adds education and marital status. An equivalence test at a margin of 0.03 asks whether the sex gap is small enough to be immaterial by the planning threshold.


Figure 8
Workflow for RQ3, Fairness at a Simulated Cut-off



Note. FDR = false-decline rate; TPR = true-positive rate; DI = disparate impact ratio; SHAP = Shapley additive explanations.

RQ3 takes the unaware XGBoost scores from RQ1. In each fold the 75th percentile of the calibration partition's scores becomes the cut-off, which is applied to the held-out fold to produce FLAG and RETAIN. Pooled decisions are audited by sex through confusion matrices, from which the retention rate, false-decline rate, true-positive rate, disparate impact ratio, and gaps follow. Inference uses the two-proportion test on the false-decline rate, binomial bootstrap intervals on every measure, and equivalence tests at margins of 0.05 and 0.02. The audit is repeated for the aware model and the paired bootstrap of the gap difference tests whether unawareness changed anything. SHAP attributions by sex, computed on fold 0, list the candidate carriers of the gap, and the audit is repeated by age band.

Figure 9
Workflow for RQ4, Mitigation Trade-offs



Note. Reweighing and threshold adjustment are applied separately to the RQ3 baseline and judged on different measures.

RQ4 applies two mitigations to the RQ3 baseline. Reweighing computes Kamiran–Calders weights on each fold's fit partition, retrains XGBoost with the tuned hyperparameters and those weights, recalibrates the cut-off, and scores the held-out fold, after which the paired DeLong non-inferiority test and the fairness audit follow. Threshold adjustment keeps the scores and searches the calibration partition for the pair of per-sex thresholds that equalises the false-decline rates while holding overall retention at 75%, then applies them to the held-out fold. Fairlearn's ThresholdOptimizer is run as a cross-check. A trade-off table repeats the audit at retention rates of 65% to 85% for the unmitigated and both mitigated configurations, and the paired bootstrap tests every change in gap, disparate impact, and default rate among retained cardholders. Reweighing is also applied to the aware model to test whether its effect depends on the model seeing the attribute.

Results

All results are computed on the pooled held-out predictions and decisions of the 30,000 cardholders. Unless stated, the feature set is the unaware set. Effect sizes carry 95% intervals and every hypothesis decision is at $\alpha = .05$. Appendix D lists the 34 tests with their statistics, assumptions, and decisions.

RQ1: Predictive Performance

Table 4 reports the discrimination and calibration of the three models. XGBoost reached an AUC of .784, 95% CI [.778, .791], and random forest .784 [.777, .790], against logistic regression at .755 [.748, .762]. The pre-specified paired contrast gave a difference of .029 in favour of XGBoost, 95% CI [.026, .033], DeLong $z = 15.66$, one-sided $p < .001$, with a paired-AUC correlation of .85. $H1_0$ was rejected. The secondary contrasts, Holm-adjusted, found random forest ahead of logistic regression by .029 [.025, .033], $z = 14.38$, $p < .001$, and no difference between XGBoost and random forest, .0004 [−.0012, .0020], $z = 0.50$, $p = .62$. The fold-level Nadeau–Bengio corrected t-test agreed, $t(4) = 9.85$, one-sided $p < .001$, with the XGBoost advantage over logistic regression lying between .024 and .032 in every fold (Table 5). Adding the three demographic fields raised the XGBoost AUC by .0015 to .786 [.779, .792] and the logistic AUC by .0018. Those fields carry almost nothing the repayment and balance history does not. KS was .43 for both ensembles and .40 for logistic regression. Before recalibration the Brier scores were .179 for XGBoost and .166 for random forest, the former inflated by the class-weighting. After isotonic recalibration both were .135 against .143 for logistic regression. The Hosmer–Lemeshow test on the recalibrated XGBoost probabilities rejected at $\chi^2(8) = 19.02$, $p = .015$, with the largest decile deviation between observed and mean predicted default rates at 1.3 percentage points. At $N = 30{,}000$ the test is sensitive to deviations of that size, and the reliability plot (Figure 10) lies on the diagonal across all ten deciles. At this sample size and power .80 the minimum detectable AUC difference was .005. F1 at the 75% retention cut-off was .544 for XGBoost and .516 for logistic regression.

Table 4
Model Performance on Pooled Held-Out Folds (N = 30,000)

Feature set	Model	AUC [95% CI]	KS	Brier, raw	Brier, calibrated	F1 at cut-off
Unaware	Logistic regression	.755 [.748, .762]	.399	.196	.143	.516
Unaware	Random forest	.784 [.777, .790]	.430	.166	.135	.545
Unaware	XGBoost	.784 [.778, .791]	.428	.179	.135	.544
Aware	Logistic regression	.756 [.750, .763]	.398	.195	.143	.517
Aware	Random forest	.784 [.778, .791]	.429	.165	.134	.546
Aware	XGBoost	.786 [.779, .792]	.428	.179	.134	.544

Note. AUC intervals by DeLong et al. (1988). The cut-off for F1 retains 75% of cardholders and is set on each fold's calibration partition. Calibrated Brier scores use isotonic regression fitted on the calibration partition.


Table 5
Pre-specified and Secondary AUC Contrasts, Unaware Feature Set

Contrast	AUC difference [95% CI]	z	p (Holm)	Paired correlation	Decision
XGBoost vs logistic (pre-specified, one-sided)	.029 [.026, .033]	15.66	< .001	.85	Reject $H1_0$
Random forest vs logistic (secondary)	.029 [.025, .033]	14.38	< .001	.83	Reject
XGBoost vs random forest (secondary)	.0004 [−.0012, .0020]	0.50	.62	.97	Retain
XGBoost vs logistic, fold-level corrected t-test	.029 [.021, .038]	t(4) = 9.85	< .001		Reject

Note. Holm adjustment applies to the three secondary two-sided contrasts. The fold-level test uses the Nadeau and Bengio (2003) variance correction for overlapping training sets.

Figure 10

ROC Curves and Reliability by Decile, Unaware Feature Set



Note. Reliability uses isotonic-calibrated probabilities. Curves are computed on the pooled held-out folds.

RQ2: Outcome Disparity

Men defaulted at 24.17% (2,873 of 11,888) and women at 20.78% (3,763 of 18,112). The difference of 3.39 percentage points, Newcombe 95% CI [2.42, 4.36], was significant, $z = 6.92$, $p < .001$. $H2_0$ was rejected. Cohen's h was .08, a small effect, and the minimum detectable difference at this sample size was 1.4 points. An equivalence test at the planning margin of 0.03 did not find the gap within the margin (upper one-sided $p = .79$), so the difference is material by the threshold set in the synopsis. Across age bands (Table 6) the default rate was 22.8% under 30, 20.3% at 30 to 39, 23.0% at 40 to 49, and 25.3% at 50 and over. The chi-square test rejected independence, $\chi^2(3) = 44.11$, $p < .001$, with Cramér's $V = .038$, bootstrap 95% CI [.027, .050], a negligible effect by Cohen's benchmark ($w < .10$). Five of the six Holm-adjusted pairwise comparisons were significant, the exception being under-30 against 40 to 49 (difference −0.1 points, $p = .85$). The largest was 30 to 39 against 50 and over, −5.0 points [−6.9, −3.3], $p < .001$.

Adjustment reduced but did not remove the sex difference. Unadjusted, the odds ratio for male was 1.22, 95% CI [1.15, 1.28]. Controlling for age and log credit limit, the adjusted odds ratio was 1.12 [1.06, 1.18], Wald $z = 3.88$, $p < .001$, and the average marginal difference in predicted default fell from 3.39 to 1.88 points. Credit limit was the dominant covariate (odds

ratio 0.64 per log unit [0.63, 0.66]) and age a weak positive one (1.009 per year [1.006, 1.012]), and variance inflation factors were at most 1.03. Adding education and marital status left the male odds ratio at 1.14 [1.07, 1.20], $z = 4.39$, $p < .001$. Men have a lower median credit limit than women (NT$130,000 against NT$150,000), so roughly half of the raw sex gap in default is accounted for by the limits the issuer had set before the observation window. These are descriptive adjustments. I do not read them causally, because the limit-setting process that produced them is unobserved.

Table 6
Default Rate by Sex and Age Band With Tests

Group	n	Default rate [95% CI]	Comparison	Difference [95% CI]	Test statistic	p
Male	11,888	24.17% [23.40, 24.94]	Male − female	3.39 [2.42, 4.36]	z = 6.92	< .001
Female	18,112	20.78% [20.19, 21.37]	Cohen's h	.08		
Under 30	9,618	22.84% [22.00, 23.68]	Independence of DEFAULT and AGE_BAND	Cramér's V = .038 [.027, .050]	$\chi^2(3) = 44.11$	< .001
30 to 39	11,238	20.25% [19.51, 21.00]	30 to 39 vs 50 and over (Holm)	−5.05 [−6.88, −3.27]	z = −5.74	< .001
40 to 49	6,464	22.97% [21.95, 24.00]	Under 30 vs 40 to 49 (Holm)	−0.13 [−1.46, 1.19]	z = −0.19	.85
50 and over	2,680	25.30% [23.65, 26.94]	Adjusted male odds ratio	1.12 [1.06, 1.18]	z = 3.88	< .001

Note. Differences in percentage points. The adjusted odds ratio controls for AGE and log LIMIT_BAL. Full pairwise results are in the repository table rq2_age_band_posthoc_holm.csv.

RQ3: Fairness at a Simulated Cut-off

At the cut-off that retained 74.8% of cardholders, the unaware XGBoost model retained 72.3% of men and 76.4% of women, a disparate impact ratio of .946, bootstrap 95% CI [.934, .958], above the .80 benchmark (Table 7). Among cardholders who went on to pay, 17.55% of men and 14.76% of women were flagged: a false-decline gap of 2.79 percentage points, Newcombe 95% CI [1.82, 3.77], $z = 5.68$, $p < .001$. $H3_0$ was rejected. In all five folds the


gap was positive, ranging from 1.97 to 4.33 points with a standard deviation of 0.96. The equivalence test at the ±0.05 benchmark rejected non-equivalence (upper one-sided $p < .001$), so the gap is within the benchmark by test as well as by interval, whereas the equivalence test at ±0.02 did not ($p = .94$). Among defaulters, 59.6% of men and 57.2% of women were flagged. That true-positive gap of 2.37 points [−0.03, 4.75], $z = 1.94$, $p = .053$, did not reach significance. Among retained cardholders the default rate was 13.5% for men and 11.6% for women, 12.4% overall. Figure 11 shows the three measures with intervals for the four configurations audited.

Table 7
Fairness Audit at 75% Simulated Retention, by Configuration

Configuration	Retention, male / female	DI ratio [95% CI]	FDR, male / female	FDR gap [95% CI]	z, p	TPR gap [95% CI]
XGBoost, unaware (primary)	.723 / .764	.946 [.934, .958]	.176 / .148	.028 [.018, .038]	5.68, < .001	.024 [.000, .050]
XGBoost, aware	.715 / .768	.931 [.919, .942]	.183 / .145	.038 [.028, .048]	7.77, < .001	.041 [.018, .065]
Logistic, unaware	.727 / .766	.949 [.937, .961]	.179 / .156	.023 [.014, .034]	4.55, < .001	.038 [.013, .061]
Random forest, unaware	.724 / .763	.949 [.938, .961]	.174 / .149	.025 [.016, .035]	5.16, < .001	.021 [−.002, .045]

Note. DI = disparate impact ratio on RETAIN. FDR = false-decline rate among non-defaulters. TPR = true-positive rate among defaulters. Intervals are 1,000-draw stratified bootstrap percentiles. Cut-offs set per fold on the calibration partition.

Figure 11
Fairness Measures With 95% Intervals for Four Model Configurations



Note. Dashed lines mark the .80 benchmark for the DI ratio and the ±.05 benchmark for the false-decline gap.

Including sex, education, and marital status as inputs widened the gap. The aware XGBoost model's false-decline gap was 3.82 points [2.83, 4.84]. The paired stratified bootstrap of the difference between the two models' gaps on the same individuals gave 1.03 points, 95% CI [0.67, 1.39], bootstrap $p < .001$. Excluding the attributes narrowed the gap by about one point. It did not remove it. Table 8 holds the per-sex confusion matrices behind every figure in this section. The SHAP decomposition on fold 0 (Figure 12) placed MAX_DELAY (mean |SHAP| .44), PAY_0 (.32), LIMIT_BAL (.14), UTILISATION (.14), and BILL_AMT1 (.13) as the five largest contributors overall. Three of them raised male risk relative to female risk on average: MAX_DELAY by .029 log-odds, LIMIT_BAL by .022, and PAY_0 by .017. Two of them, MAX_DELAY and PAY_0, reflect worse repayment histories among men in the file. LIMIT_BAL reflects the lower credit limits the issuer had assigned to men, the proxy mechanism the EDA anticipated. SHAP values on one fold are candidates for investigation, and I would not read them as proof that a feature acts as a proxy.

Table 8


Per-Sex Confusion Matrices at 75% Retention, Unaware and Aware XGBoost

Configuration	Sex	n	TP	FP	FN	TN	Retain rate	FDR	TPR	Default rate, retained
Unaware	Male	11,888	1,711	1,582	1,162	7,433	.723	.176	.596	.135
Unaware	Female	18,112	2,152	2,118	1,611	12,231	.764	.148	.572	.116
Aware	Male	11,888	1,741	1,648	1,132	7,367	.715	.183	.606	.133
Aware	Female	18,112	2,128	2,075	1,635	12,274	.768	.145	.566	.118

Note. A positive prediction is FLAG = 1. TP = flagged defaulters; FP = flagged non-defaulters (false declines); FN = retained defaulters; TN = retained non-defaulters.

Figure 12

SHAP Attributions by Sex, Unaware XGBoost, Fold 0 Held-Out Rows



Note. Left: mean absolute attribution by sex. Right: difference in mean attribution, male minus female; positive values raise male predicted risk relative to female.

The same audit by age band (Table 9) found larger differences than by sex. The false-decline rate was 14.1% for cardholders aged 30 to 39 and 20.9% for those 50 and over, a gap of 6.80 points, 95% CI [4.92, 8.76], $z = 7.63$, Holm-adjusted $p < .001$. That gap exceeds the ±0.05 benchmark the sex comparison met. Five of the six pairwise band comparisons were significant after Holm correction. Between the 50-and-over band and the 30-to-39 band the disparate impact ratio was .88, above .80. Age band was a secondary attribute in the design, so the age result is reported as a supporting finding and the answer to RQ3 stays with sex. It is, though, the larger disparity in this portfolio.

Table 9

Fairness Audit by Age Band at 75% Retention, Unaware XGBoost

Age band	n	Retention rate	FDR [95% CI]	TPR	Default rate, retained	DI vs 30 to 39
Under 30	9,618	.736	.163 [.155, .172]	.606	.122	.945
30 to 39	11,238	.778	.141 [.134, .148]	.540	.120	1.000
40 to 49	6,464	.739	.163 [.152, .173]	.590	.127	.950
50 and over	2,680	.685	.209 [.191, .227]	.630	.137	.880

Note. FDR intervals are Wald intervals on the group proportion. The largest pairwise FDR difference, 30 to 39 against 50 and over, is 6.80 points [4.92, 8.76], Holm-adjusted p < .001.

RQ4: Mitigation Trade-offs

Reweighing the unaware model was non-inferior on AUC and ineffective on the gap. The reweighed model's AUC was .7839 against .7841 for the baseline, a paired difference of −.0001 with a one-sided 95% lower bound of −.0004, well inside the −.01 margin, $z = 54.1$, $p < .001$. $H4_0$ was rejected and non-inferiority concluded. Paired correlation between the two AUCs was .998, because the Kamiran–Calders weights, computed on each fit partition, lay between 0.92 and 1.06 and the model never saw sex. The false-decline gap moved from 2.79 to 2.69 points, a paired change of −0.10 points, 95% CI [−0.34, 0.14], bootstrap $p = .39$. Only 263 of 30,000 decisions changed, and the default rate among retained cardholders did not move (+0.00 points [−0.07, 0.07], $p = .97$). Both changes passed the equivalence test at ±0.5 points: the 90% intervals were [−0.30, 0.10] for the gap and [−0.06, 0.06] for the bad rate, TOST $p < .001$ for each, so the reading that reweighing left the unaware model where it was rests on a test of equivalence rather than on a failure to reject. On the aware model, where the weights can act on an attribute the model sees, reweighing was also non-inferior (AUC .7852 against .7856, lower bound −.0008, $z = 35.0$). There it cut the gap from 3.82 to 1.98 points, a paired change of −1.84 points [−2.13, −1.55], $p < .001$, again at no cost in bad rate (+0.01 points [−0.07, 0.08], $p = .92$, within ±0.5 points by equivalence test, 90% interval [−0.06, 0.07]).

Per-sex threshold adjustment closed the gap at the common 75% retention rate. Set on each fold's calibration partition, the searched thresholds were higher for men than for women in every fold (for example .563 against .549 in fold 0), so men needed a higher risk score to be flagged. On the held-out folds the false-decline gap fell to 0.43 points, 95% CI [−0.51, 1.35], $z = 0.87$, $p = .38$, a paired change of −2.36 points [−2.64, −2.08], $p < .001$. The equivalence test at ±0.02 rejected non-equivalence (upper one-sided $p < .001$). Disparate impact rose from .946 to .978 [.966, .990]. The cost was a rise in the default rate among retained cardholders from 12.36% to 12.39%, a paired change of 0.03 points [−0.04, 0.11], $p = .38$, and within ±0.5 points by equivalence test (90% interval [−0.03, 0.10], TOST $p < .001$). The overall flag rate moved by 0.04 points [−0.09, 0.16], within ±0.5 points by the paired equivalence test ($z = −7.36$, $p < .001$),

with 357 decisions changed (184 newly flagged, 173 newly retained). Fairlearn's ThresholdOptimizer with a false-positive-rate parity constraint and a balanced-accuracy objective chose a retention rate of 70.2% and reached a gap of 0.97 points [−0.09, 2.09]. At that same retention the direct search gave 0.82 points [−0.21, 1.86], so the two implementations agree.

Table 10 is the trade-off table across retention rates from 65% to 85%, and Figure 13 plots it. Three patterns hold at every retention rate. The unmitigated gap sits between 2.0 and 2.8 points with every interval excluding zero and lying inside ±0.05. Reweighing tracks the unmitigated line within 0.4 points. Threshold adjustment holds the gap between 0.3 and 0.9 points with every interval including zero, raises the disparate impact ratio to .97 or above, and costs at most 0.1 points of default rate among retained cardholders. The default rate among retained cardholders rises from 11.0% at 65% retention to 14.7% at 85% for all three configurations. That rise is the cost of retaining more cardholders, and no mitigation adds to it. AUC is .7841 for the unmitigated and threshold-adjusted configurations by construction and .7839 for reweighing. Neither sensitivity run (Table 11) changed an estimate by more than .001.

Table 10
Trade-off Table Across Simulated Retention Rates


Retention	Configuration	Default rate, retained [95% CI]	AUC	DI ratio	FDR gap [95% CI]
65%	Unmitigated	.110 [.107, .114]	.784	.943	.026 [.015, .038]
65%	Reweighing	.110 [.107, .114]	.784	.949	.022 [.011, .033]
65%	Threshold adjustment	.111 [.108, .114]	.784	.972	.006 [−.005, .017]
70%	Unmitigated	.116 [.113, .120]	.784	.946	.027 [.017, .038]
70%	Reweighing	.116 [.113, .120]	.784	.951	.024 [.013, .034]
70%	Threshold adjustment	.116 [.113, .120]	.784	.970	.009 [−.002, .020]
75%	Unmitigated	.124 [.121, .127]	.784	.946	.028 [.018, .038]
75%	Reweighing	.124 [.121, .127]	.784	.947	.027 [.018, .037]

Retention	Configuration	Default rate, retained [95% CI]	AUC	DI ratio	FDR gap [95% CI]
75%	Threshold adjustment	.124 [.121, .127]	.784	.978	.004 [−.005, .014]
80%	Unmitigated	.135 [.132, .138]	.784	.949	.028 [.020, .037]
80%	Reweighing	.135 [.132, .138]	.784	.951	.026 [.018, .034]
80%	Threshold adjustment	.136 [.133, .139]	.784	.978	.007 [−.001, .016]
85%	Unmitigated	.147 [.145, .150]	.784	.961	.020 [.013, .027]
85%	Reweighing	.147 [.145, .150]	.784	.962	.019 [.012, .026]
85%	Threshold adjustment	.148 [.145, .151]	.784	.985	.003 [−.003, .010]

Note. All configurations use the unaware XGBoost scores. Reweighing AUC is .7839; the others are .7841. Achieved retention rates lie within 0.3 points of the target. Intervals are 1,000-draw stratified bootstrap percentiles.

Figure 13

False-Decline Gap, Disparate Impact Ratio, and Default Rate Among Retained Cardholders Across Retention Rates



Note. Dotted lines mark the ±.05 benchmark for the gap and the .80 benchmark for the DI ratio.

Table 11

Sensitivity of the Primary Estimates to the Coding Assumptions

Run	AUC [95% CI]	DI ratio	FDR gap [95% CI]	Default rate, retained
Primary: unaware XGBoost	.784 [.778, .791]	.946	.028 [.018, .038]	.124
A: PAY codes −2 and 0 collapsed (unaware)	.784 [.778, .791]	.945	.027 [.018, .037]	.124
Primary: aware XGBoost	.786 [.779, .792]	.931	.038 [.028, .048]	.124

Run	AUC [95% CI]	DI ratio	FDR gap [95% CI]	Default rate, retained
B: undocumented EDUCATION and MARRIAGE merged into other (aware)	.786 [.780, .792]	.929	.039 [.030, .049]	.123

Note. Sensitivity runs reuse the tuned hyperparameters of the primary run for each fold.

Reproducibility Across Machines

The pipeline was run end to end on two hosts with the same seed: a cloud container (Python 3.13, xgboost 3.4.1, scikit-learn 1.9.1, two cores) and an Ubuntu 22.04 Docker container on an Apple Silicon Mac Studio (Python 3.10, xgboost 3.2.0, scikit-learn 1.6.1, four cores). Checksum, fold assignment, logistic regression AUCs, and every RQ2 statistic matched to four decimals. XGBoost quantities differed by at most .0005 in AUC and .003 in a fairness gap, because the two xgboost versions score the inner-CV candidates slightly differently and the random search selected different hyperparameters in some folds. That first replication used the library versions the Mac Studio container had installed, which were older than the pinned ones. With the fold file identical and the seed fixed, 32 of the 34 register decisions matched, including every primary hypothesis, and two did not. The paired change in the false-decline gap under reweighing of the unaware model was −0.10 points [−0.34, 0.14], $p = .39$, in the cloud run and −0.22 points [−0.44, −0.00], $p = .047$, on the older libraries. The bad-rate cost of threshold adjustment was +0.03 points [−0.04, 0.11], $p = .38$, against +0.07 points [0.01, 0.14], $p = .028$. Both effects are under a quarter of a point, and a test of a change equal to zero is unstable at that size. Two things were done about it. First, the pipeline was rerun on the Mac in a second environment with the exact versions in requirements.txt (Python 3.12.14, xgboost 3.4.1, scikit-learn 1.9.1, installed with uv). Every table and all 34 register rows then matched the cloud run to the reported precision, including the XGBoost hyperparameters selected in each fold, so the differences were the library versions and not the hardware. Second, each change the report reads as immaterial was given an equivalence test at ±0.5 points, and those decisions agree on all three runs, because the question they ask, whether the change is inside a stated band, does not turn on

the fourth decimal. Appendix A names the repository file, reproducibility_cross_machine.csv, that holds the full comparison, and both Mac registers are stored beside it. The execution environments are described in the Implementation section (Table 14) and the terminal captures from the Mac runs are in Appendix E.

Analysis and Discussion

Technical Interpretation

RQ1 confirms the accuracy case at the size the literature predicted. Its three-point AUC gain over logistic regression is within the one to three points Lessmann et al. (2015) reported, it is identical for random forest and XGBoost, and it is stable across folds. Once the class-weighted probabilities are recalibrated the gain carries no calibration cost, and by Brier score the recalibrated ensembles are better calibrated than logistic regression. Demographic fields add .0015 AUC. That near-zero contribution is the first sign that the audit question concerns proxies, because the attributes themselves add nothing the model needs.

RQ2 establishes that the base rates differ, which by Kleinberg et al. (2017) and Chouldechova (2017) rules out a model that is both calibrated within each sex and equal in its error rates across sexes. This study governs to equal opportunity, read as the false-decline rate, and reports calibration separately. Half the raw sex difference in default disappears once credit limit is controlled, and that matters for the mechanism. The issuer's own earlier limit-setting decisions are part of what the model learns, alongside the cardholders' behaviour. The age-band association, though significant, is negligible in effect size, and the U shape means a linear age term would not capture it.

RQ3 answers the question lenders usually answer with a policy statement. The unaware model does treat creditworthy men and women differently, by 2.8 points in the false-decline rate, and the difference is statistically unambiguous, reproducible across folds, and within the ±0.05 benchmark by equivalence test. The two readings sit together without strain, because a gap can be real and acceptable at once. The equivalence test at ±0.02 shows exactly where the benchmark would stop accepting it. Pairing the unaware model with the aware one gives fairness through

unawareness its number. Excluding sex narrowed the gap by one point and left 2.8 points. That agrees with Mehrabi et al. (2021) and with the SHAP result that repayment history and credit limit, both legitimately predictive, carry the group difference. The true-positive gap did not reach significance, so the lender-risk reading of equal opportunity is less affected than the borrower reading. The study made the borrower reading primary for that reason.

RQ4 separates the two mitigations more sharply than the synopsis anticipated. Reweighing's non-inferiority on AUC was trivially satisfied because the method barely changed the unaware model, and the gap moved by a tenth of a point, against 1.84 points on the aware model. The equivalence test places that change inside ±0.5 points on every run, so reweighing is ineffective on the unaware model by a test that can say so, where a failure to reject never could. On the aware model the same weights halved the gap. The mechanism is simple. Weights indexed by sex can only shift a model that has sex as an input or strong proxies for it, and the unaware model's proxies (limit, utilisation, repayment codes) are left where they were by weights that depend on sex and outcome alone. Threshold adjustment acts directly on the decision. It closed the gap to within ±0.02 at a cost of 0.03 points of bad rate, which the equivalence test places inside ±0.5 points on every run. The cost is real in the sense that it is not exactly zero on the older libraries, and immaterial in the sense that matters to a credit committee. Fairlearn's ThresholdOptimizer confirms the direct search. None of this depends on the 75% operating point. The unmitigated gap, the failure of reweighing on the unaware model, and the near-zero cost of threshold adjustment all hold from 65% to 85% retention in the trade-off table.

Business Implications

For the chief risk officer and the validation unit, the first implication is that the fairness attestation can be a number. At the lender's chosen cut-off the audit yields a retention rate by group, a disparate impact ratio with an interval, and a default rate among retained customers. It also yields the false-decline gap with an interval and an equivalence verdict against a stated tolerance. Each row of Table 10 is a configuration a committee can sign, with the cost of each alternative visible beside it. A process attestation (protected attributes excluded) becomes an

outcome attestation (gap of 2.8 points, within a 5-point tolerance, outside a 2-point tolerance). The RBI FREE-AI recommendations on disclosure of AI-driven credit assessments would, if adopted, require a regulated entity to produce exactly that (Reserve Bank of India, 2025).

For the head of retail credit, the second implication is that the operating cut-off is a fairness lever as well as a credit lever. In the trade-off table the gap narrows as retention rises, from 2.8 points at 75% to 2.0 points at 85%, at a cost of 2.4 points of bad rate among retained customers. A lender that wants to narrow the gap without group-specific thresholds has that option, and the table prices it. For the compliance function, the third implication concerns the choice of mitigation. Per-sex thresholds are the effective fix in this portfolio, but they require the protected attribute at decision time and amount to disparate treatment in several jurisdictions. Reweighing, the single-threshold option that avoids that problem, does not work on a model that cannot see the attribute. For an Indian lender the legally safer method is the one that does not work here, and the question belongs to legal review before it belongs to the model team. For the mid-sized NBFC buying scores from a vendor, the fourth implication is that the audit needs only scores, outcomes, and the protected attribute joined at evaluation time. It works as an independent check on a vendor model with no access to the model's internals.

A fifth implication is one the study did not set out to find. The false-decline gap by age band, 6.8 points between cardholders aged 30 to 39 and those 50 and over, is more than twice the sex gap and outside the benchmark the sex audit met. A validation unit that audits only the attribute the policy names would have certified this model and missed the larger disparity. What follows is a recommendation that the audit be run on every attribute the lender treats as protected, and on age whether or not it is formally protected, before a benchmark verdict is recorded.

Synthesis Against the Hypotheses

Table 12 consolidates the decisions. $H1_0$ was rejected: gradient boosting outperforms logistic regression by .029 AUC. $H2_0$ and $H2b_0$ were rejected: default rates differ by sex by 3.4 points and by age band with a negligible effect size, and the sex difference halves under

adjustment for credit limit. $H3_0$ was rejected: the false-decline rate differs by sex by 2.8 points at 75% retention, within the ±0.05 benchmark by equivalence test and outside ±0.02, with the disparate impact benchmark met. $H4_0$ was rejected for reweighing on both models: the method is non-inferior on AUC, and it is effective only on the aware model. Threshold adjustment closed the gap to within ±0.02 at a decision-level cost that an equivalence test places inside ±0.5 points of bad rate. Taken together, the findings support the position stated in the introduction. In this portfolio the fairness of the deployed model is decided by the threshold and by what the model is allowed to see. A policy statement that sex was excluded decides nothing.

Table 12
Summary of Hypothesis Decisions

RQ	Hypothesis	Key statistic	Effect [95% CI]	Decision
RQ1	$H1_0$: $AUC_{GB} = AUC_{LR}$	DeLong z = 15.66, p < .001	ΔAUC = .029 [.026, .033]	Rejected; XGBoost superior
RQ2	$H2_0$: $p_{male} = p_{female}$	z = 6.92, p < .001	3.39 points [2.42, 4.36]; adjusted OR 1.12 [1.06, 1.18]	Rejected; difference material at 0.03
RQ2	$H2b_0$: DEFAULT independent of AGE_BAND	$\chi^2(3) = 44.11$, p < .001	Cramér's V = .038 [.027, .050]	Rejected; negligible effect
RQ3	$H3_0$: $FDR_{male} = FDR_{female}$	z = 5.68, p < .001; TOST(.05) p < .001; TOST(.02) p = .94	2.79 points [1.82, 3.77]; DI = .946 [.934, .958]	Rejected; within ±.05, outside ±.02; DI benchmark met
RQ3	Unawareness effect = 0	paired bootstrap p < .001	1.03 points [0.67, 1.39]	Rejected; aware model has the larger gap
RQ4	$H4_0$: $AUC_{RW} \leq AUC_{base}$ − .01 (unaware)	z = 54.1, p < .001	ΔAUC = −.0001, lower bound −.0004; Δgap −0.10 [−0.34, 0.14], within ±0.5 by TOST	Rejected (non-inferior); gap unchanged
RQ4	$H4_0$ (aware model)	z = 35.0, p < .001	ΔAUC = −.0004; Δgap −1.84 [−2.13, −1.55]	Rejected (non-inferior); gap halved
RQ4	Threshold adjustment: Δgap = 0; |Δbad rate| < 0.5 pts	paired bootstrap p < .001; TOST p < .001	Δgap −2.36 [−2.64, −2.08]; Δbad +0.03 [−0.04, 0.11]	Gap closed within ±.02; cost within ±0.5 pts by equivalence test

Note. Differences in gaps and bad rates are in percentage points. OR = odds ratio. TOST = two one-sided tests at the stated margin.

Implementation

Practical Deployment as a Validation Artefact

The deliverable is an audit, not a scoring model. A lender runs it as a step in model validation, after a candidate model has produced held-out scores and before the cut-off is signed. Its inputs are three columns joined at evaluation time: the held-out score, the observed outcome, and the protected attribute. Its outputs are the fairness table (Table 7), the trade-off table (Table 10), and the hypothesis register (Appendix D), which together form the decision record. A credit policy committee selects a row of the trade-off table, and the row, its date, and the signatory are recorded in the model inventory. The committee's tolerance, here DI ≥ .80 and |gap| ≤ .05 as research benchmarks, is set in advance and treated as a hard gate. Once set, it is never traded against bad rate, and the cost of meeting it is recorded as the price of the policy, a line the committee owns and the modelling team does not. For a lender that buys scores from a vendor, the same three columns suffice, so the audit runs without access to the vendor's model.

Algorithmic Steps

The pipeline in Figure 1 runs as a sequence of scripts under a Makefile, each writing its outputs to a results folder from which every table and figure in this report was generated. Stage 1 fetches the data file, verifies its checksum, applies the recoding in Table 2, and builds the engineered variables. Stage 2 assigns the five outer folds and the fit and calibration partitions, keyed on the identifier and stratified by sex and outcome. It saves the assignment to disk, so every later stage uses identical splits. Stage 3 trains the three model families on each fit partition with inner-CV tuning, fits isotonic recalibration on the calibration partition, and scores both the calibration partition and the held-out fold, for the unaware and aware feature sets. Stage 4 sets the retention cut-off, the per-sex thresholds by direct search, and the reweighing weights, all on the calibration partition only, then retrains the reweighed model on the fit partition. Stage 5 scores the held-out folds under every configuration, pools them, and computes the performance

measures, fairness measures, bootstrap intervals, and formal tests. Stage 6 assembles the trade-off table, the hypothesis register, and the figures. A validation analyst applies the audit to a new portfolio by pointing the download step at the lender's own extract with the same column names, or by supplying the three evaluation columns directly to stages 4 to 6.

Human and Machine Requirements for Reproducibility

The code is Python 3.10 or later with pandas, scikit-learn, XGBoost, Fairlearn, SHAP, statsmodels, and matplotlib, pinned in a requirements file, with a second file of compatible versions for Python 3.10. Every random process uses the seed 640 and the fold assignment is written to disk. A rerun reproduces the same held-out predictions on the same library versions, and on different versions it agreed to within .003 in the cross-machine comparison. A full run takes about seven minutes on two cores and under four on four cores. The 1,000-draw bootstraps are exact binomial draws and take seconds. Memory use is under 2 GB. Appendix A gives the repository layout and run instructions. On the human side, the requirement is a validation analyst who can run a Makefile and read a confusion matrix. The interpretive requirement is a credit policy committee that sets the tolerance in advance and a legal function that rules on whether group-specific thresholds are permissible in the lender's jurisdiction. The pipeline reports the cost of each option. It does not choose between them.

Execution Environment

Table 14 records the three environments in which the pipeline ran. The primary results in this report come from the cloud container, a two-core Ubuntu 24.04 x86_64 host with Python 3.13. Both replications ran in a Docker container on my Mac Studio, an Ubuntu 22.04 image on Apple silicon with four cores and 3.8 GiB of memory. The first used the container's own Python 3.10 and the older library set in requirements-py310.txt. The second used a Python 3.12 environment created with uv and the exact versions in requirements.txt, and it reproduced the cloud run in full. Appendix E holds terminal captures of both container runs and screenshots of the public repository.

Table 14
Execution Environments for the Primary Run and the Two Replications

Item	Cloud container (primary run)	Mac Studio, unpinned libraries	Mac Studio, pinned libraries
Hardware	Cloud virtual machine, x86_64, 2 vCPU, 7.8 GiB	Mac Studio (Apple silicon), Docker container, aarch64, 4 vCPU, 3.8 GiB	Same machine and container
Operating system	Ubuntu 24.04.5 LTS	Ubuntu 22.04.5 LTS (kernel 6.8)	Ubuntu 22.04.5 LTS
Python	3.13.16	3.10.12 (container image)	3.12.14 (uv-managed)
numpy / pandas / SciPy	2.5.3 / 3.0.5 / 1.18.1	2.2.6 / 2.3.3 / 1.15.3	2.5.3 / 3.0.5 / 1.18.1
scikit-learn / XGBoost	1.9.1 / 3.4.1	1.6.1 / 3.2.0	1.9.1 / 3.4.1
Fairlearn / SHAP / statsmodels	0.14.0 / 0.53.0 / 0.15.0	0.14.0 / 0.49.1 / 0.15.0	0.14.0 / 0.53.0 / 0.15.0
matplotlib	3.11.2	3.10.9	3.11.2
Seed and folds	640, folds.csv committed to the run	640, same folds.csv (same MD5)	640, same folds.csv (same MD5)
Training time per fold (three models, inner CV)	25 s	12 to 14 s	10 to 15 s
Full pipeline (make all)	About 7 minutes	Under 4 minutes, run fold by fold with the PART option	Under 4 minutes, the same way
Agreement with the primary run	Reference	Fourth decimal in XGBoost quantities; 32 of 34 register decisions	Identical tables and register, all 34 rows

Note. Library versions as reported by each interpreter at run time. The container runs were split fold by fold with the PART option of train.py because the container session capped each command at three minutes.

Project Timeline as Executed

The synopsis set a ten-week plan at roughly twelve hours a week alongside full-time work, front-loaded with data work because every later week depends on a clean, fold-assigned file, and with RQ2 ahead of RQ1 because its result decides which fairness criterion leads in RQ3 and RQ4. Table 13 records that plan beside what was done. Weeks 1 to 6 ran as planned. Two things moved. The mentor's request for full statistical depth after the interim report added the

hypothesis-test register and the RQ4 extensions (ThresholdOptimizer cross-check, reweighing on the aware model, age-band audit) to weeks 7 and 8, and the cross-machine reproduction was run in week 9 once the code was frozen. The effort stayed inside the plan because the pipeline was scripted from week 1, so every addition was a new script over the same fold file and not a rerun of earlier work.

Table 13
Ten-Week Project Plan and Execution

Week	Phase	Planned activities	Executed outputs
1	Set-up and acquisition	Repository and environment; download and checksum; verify data dictionary; agree scope and benchmarks with mentor	Repository, README, dictionary, download.py with SHA-256 check, sample_size.py
2	EDA and splitting	Univariate, bivariate, multivariate EDA; recoding; engineered variables; outer folds and fit/calibration partitions	01_eda, prepare.py, clients_clean.parquet, folds.csv (seed 640), Figures 2 to 5
3	RQ2 statistical tests	Two-proportion test, chi-square with Cramér's V, adjusted logistic regression	02_rq2_outcome_disparity, Table 6, VIF table
4	Baseline modelling	Logistic pipeline; nested CV; calibration check; KS, Brier; held-out scoring	train.py, baseline AUC with DeLong CI
5	Challenger modelling	Random forest and XGBoost with randomised search; DeLong contrast; aware and unaware runs	03_rq1_models, Tables 4 and 5, Figure 10
6	Fairness audit	Cut-off on calibration partitions; per-sex confusion matrices; DI, FDR gap, TPR gap, equalized odds; bootstrap CIs	04_rq3_fairness_audit, Tables 7 and 8, Figure 11; interim report
7	Mitigation, reweighing	Weights on fit partitions; retrain; non-inferiority test; re-audit	05_rq4_mitigation (reweighing), 07_rq4_extensions (aware-model reweighing), register begun
8	Mitigation, threshold adjustment	Per-sex thresholds by direct search; ThresholdOptimizer cross-check; trade-off table; SHAP	policy.py thresholds, Table 10, Figure 13, 06_sensitivity_shap, age-band audit (Table 9), 08_statistical_depth (Table D1)

Week	Phase	Planned activities	Executed outputs
9	Synthesis	Decision record, recommendations, limitations; code freeze; README	Cross-machine reproduction on a second host, frozen repository, draft report
10	Final report	Mentor review, revisions, presentation, submission	Pinned-version replication on the Mac, equivalence tests added to the register, this report and the presentation

Note. Script names refer to analysis/ and src/ in the repository (Appendix A). EDA = exploratory data analysis.

Limitations and Next Steps

The first limitation is the data. The file describes one Taiwanese card issuer in 2005, over-represents women (60%) and university graduates (82% with a degree), and records one issuer's collection outcome in one month. A model that learns it inherits any unevenness in how that issuer pursued late payers. It holds no income, no bureau score, and no regional field, and the attributes an Indian lender would audit first, such as religion, caste, or state, are absent. What transfers to Indian retail lending is the audit method and the decision table. Nothing here is a finding about Indian borrowers. Replication on a second portfolio that carries a sex field and a default outcome is the next step. Two public candidates pass that filter: the Home Credit Default Risk data (307,511 applications with a gender field) and the Bondora peer-to-peer lending data (about 180,000 loans with gender, age, and country). Three patterns would need to reproduce there: unawareness narrows the gap without removing it, reweighing works only when the model sees the attribute, and threshold adjustment closes the gap at negligible bad-rate cost. If they did, a single-portfolio result would become a general one.

The second limitation is the setting. Because the data observe customers who already held credit, every decision in this study is a retention simulation and nothing can be said about approval. A lender's real approval decision operates on applicants the file does not contain, and reject inference, which was out of scope, would be needed to extend the audit to that population. The 75% retention cut-off is a stated scenario and no issuer's observed policy. A trade-off table softens that choice but cannot remove it.

The third limitation is the fairness criteria. This study governs to equal opportunity and disparate impact and reports equalized odds. It does not test calibration within groups or any individual-fairness criterion, and by Kleinberg et al. (2017) a model that satisfies the criteria used here will not satisfy within-group calibration when base rates differ. Both benchmarks, .80 and ±.05, are research conventions borrowed from employment-selection practice and have no standing in Indian credit regulation, and the equivalence test at ±.02 shows how much the verdict depends on the tolerance chosen. The age-band finding shows that an audit confined to one attribute can certify a model that fails on another. A multi-attribute audit with intersectional cells is the next step there. The sample supports sex by age band, but finer intersections run out of defaulters per cell.

The fourth limitation is the mitigation set. Two methods were tested, one pre-processing and one post-processing. In-processing methods such as constrained optimisation or adversarial debiasing were out of scope. They might close the gap under a single threshold, and a single threshold is the configuration the legal constraint favours. What the reweighing result covers is Kamiran–Calders weights indexed by sex and outcome only, and it and does not rule out reweighing schemes indexed by proxies. The threshold search used one parameterisation and the Fairlearn cross-check one constraint. Both agreed, but neither explores randomised thresholds, which Hardt et al. (2016) showed can be needed for exact equalized odds. The SHAP decomposition was computed on one fold. It identifies candidate carriers of the gap, and I make no causal claim from it.

The fifth limitation is statistical. The Hosmer–Lemeshow test rejected at $N = 30{,}000$ for a deviation of 1.3 points in one decile. At that sample size the test detects deviations no committee would act on, so the reliability plot is the better evidence. A 12-candidate random search for XGBoost was chosen for a two-core budget, and a wider search raised the inner-CV AUC by less than .002 in a spot check and would not change the contrasts. Minimum detectable effects at $N = 30{,}000$ were .005 AUC and 1.4 points of default rate. Smaller differences than those reported cannot be excluded, and none were claimed. The cross-machine runs add a caution of their own.

With library versions pinned, every decision reproduced on a second host, but with older versions two tests of a change equal to zero flipped on effects under a quarter of a point. The equivalence tests added in response hold on every run, and the margin of ±0.5 points was set after that check, which I state so that it is not mistaken for a pre-registered threshold. In order of value, the next steps are the second-portfolio replication, the multi-attribute audit with age as a named attribute, and a single-threshold in-processing method tested on the same folds with the same paired inference.

References

Barocas, S., Hardt, M., & Narayanan, A. (2019). *Fairness and machine learning: Limitations and opportunities*. fairmlbook.org. https://fairmlbook.org

Bartlett, R., Morse, A., Stanton, R., & Wallace, N. (2022). Consumer-lending discrimination in the FinTech era. *Journal of Financial Economics, 143*(1), 30–56. https://doi.org/10.1016/j.jfineco.2021.05.047

Berg, T., Burg, V., Gombović, A., & Puri, M. (2020). On the rise of FinTechs: Credit scoring using digital footprints. *The Review of Financial Studies, 33*(7), 2845–2897. https://doi.org/10.1093/rfs/hhz099

Bird, S., Dudík, M., Edgar, R., Horn, B., Lutz, R., Milan, V., Sameki, M., Wallach, H., & Walker, K. (2020). *Fairlearn: A toolkit for assessing and improving fairness in AI* (Technical Report MSR-TR-2020-32). Microsoft. https://www.microsoft.com/en-us/research/publication/fairlearn-a-toolkit-for-assessing-and-improving-fairness-in-ai/

Breiman, L. (2001). Random forests. *Machine Learning, 45*(1), 5–32. https://doi.org/10.1023/A:1010933404324

Chen, T., & Guestrin, C. (2016). XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 785–794). ACM. https://doi.org/10.1145/2939672.2939785

Chouldechova, A. (2017). Fair prediction with disparate impact: A study of bias in recidivism prediction instruments. *Big Data, 5*(2), 153–163. https://doi.org/10.1089/big.2016.0047

Cohen, J. (1988). *Statistical power analysis for the behavioral sciences* (2nd ed.). Lawrence Erlbaum Associates.

Corbett-Davies, S., & Goel, S. (2018). *The measure and mismeasure of fairness: A critical review of fair machine learning* (arXiv:1808.00023). arXiv. https://doi.org/10.48550/arXiv.1808.00023

DeLong, E. R., DeLong, D. M., & Clarke-Pearson, D. L. (1988). Comparing the areas under two or more correlated receiver operating characteristic curves: A nonparametric approach. *Biometrics, 44*(3), 837–845. https://doi.org/10.2307/2531595

Dwork, C., Hardt, M., Pitassi, T., Reingold, O., & Zemel, R. (2012). Fairness through awareness. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference* (pp. 214–226). ACM. https://doi.org/10.1145/2090236.2090255

European Parliament & Council of the European Union. (2024). Regulation (EU) 2024/1689 of the European Parliament and of the Council of 13 June 2024 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act). *Official Journal of the European Union*, L, 2024/1689. https://eur-lex.europa.eu/eli/reg/2024/1689/oj

Feldman, M., Friedler, S. A., Moeller, J., Scheidegger, C., & Venkatasubramanian, S. (2015). Certifying and removing disparate impact. In *Proceedings of the 21st ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 259–268). ACM. https://doi.org/10.1145/2783258.2783311

Fleiss, J. L., Levin, B., & Paik, M. C. (2003). *Statistical methods for rates and proportions* (3rd ed.). John Wiley & Sons. https://doi.org/10.1002/0471445428

Friedman, J. H. (2001). Greedy function approximation: A gradient boosting machine. *The Annals of Statistics, 29*(5), 1189–1232. https://doi.org/10.1214/aos/1013203451

Fuster, A., Goldsmith-Pinkham, P., Ramadorai, T., & Walther, A. (2022). Predictably unequal? The effects of machine learning on credit markets. *The Journal of Finance, 77*(1), 5–47. https://doi.org/10.1111/jofi.13090

Hand, D. J., & Henley, W. E. (1997). Statistical classification methods in consumer credit scoring: A review. *Journal of the Royal Statistical Society: Series A (Statistics in Society), 160*(3), 523–541. https://doi.org/10.1111/j.1467-985X.1997.00078.x

Hanley, J. A., & McNeil, B. J. (1982). The meaning and use of the area under a receiver operating characteristic (ROC) curve. *Radiology, 143*(1), 29–36. https://doi.org/10.1148/radiology.143.1.7063747

Hardt, M., Price, E., & Srebro, N. (2016). Equality of opportunity in supervised learning. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, & R. Garnett (Eds.), *Advances in Neural Information Processing Systems 29* (pp. 3315–3323). Curran Associates.

Holm, S. (1979). A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics, 6*(2), 65–70.

Hosmer, D. W., Lemeshow, S., & Sturdivant, R. X. (2013). *Applied logistic regression* (3rd ed.). John Wiley & Sons. https://doi.org/10.1002/9781118548387

Kamiran, F., & Calders, T. (2012). Data preprocessing techniques for classification without discrimination. *Knowledge and Information Systems, 33*(1), 1–33. https://doi.org/10.1007/s10115-011-0463-8

Khandani, A. E., Kim, A. J., & Lo, A. W. (2010). Consumer credit-risk models via machine-learning algorithms. *Journal of Banking & Finance, 34*(11), 2767–2787. https://doi.org/10.1016/j.jbankfin.2010.06.001

Kleinberg, J., Mullainathan, S., & Raghavan, M. (2017). Inherent trade-offs in the fair determination of risk scores. In C. H. Papadimitriou (Ed.), *8th Innovations in Theoretical Computer Science Conference (ITCS 2017)* (LIPIcs Vol. 67, pp. 43:1–43:23). Schloss Dagstuhl. https://doi.org/10.4230/LIPIcs.ITCS.2017.43

Kozodoi, N., Jacob, J., & Lessmann, S. (2022). Fairness in credit scoring: Assessment, implementation and profit implications. *European Journal of Operational Research, 297*(3), 1083–1094. https://doi.org/10.1016/j.ejor.2021.06.023

Lessmann, S., Baesens, B., Seow, H.-V., & Thomas, L. C. (2015). Benchmarking state-of-the-art classification algorithms for credit scoring: An update of research. *European Journal of Operational Research, 247*(1), 124–136. https://doi.org/10.1016/j.ejor.2015.05.030

Lundberg, S. M., & Lee, S.-I. (2017). A unified approach to interpreting model predictions. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, & R. Garnett (Eds.), *Advances in Neural Information Processing Systems 30* (pp. 4765–4774). Curran Associates.

Mehrabi, N., Morstatter, F., Saxena, N., Lerman, K., & Galstyan, A. (2021). A survey on bias and fairness in machine learning. *ACM Computing Surveys, 54*(6), Article 115. https://doi.org/10.1145/3457607

Nadeau, C., & Bengio, Y. (2003). Inference for the generalization error. *Machine Learning, 52*(3), 239–281. https://doi.org/10.1023/A:1024068626366

Reserve Bank of India. (2025). *FREE-AI Committee report: Framework for Responsible and Ethical Enablement of Artificial Intelligence*. https://www.rbi.org.in/scripts/FS_Publications.aspx?id=1306

Rudin, C. (2019). Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence, 1*(5), 206–215. https://doi.org/10.1038/s42256-019-0048-x

Schuirmann, D. J. (1987). A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics, 15*(6), 657–680. https://doi.org/10.1007/BF01068419

Sun, X., & Xu, W. (2014). Fast implementation of DeLong's algorithm for comparing the areas under correlated receiver operating characteristic curves. *IEEE Signal Processing Letters, 21*(11), 1389–1393. https://doi.org/10.1109/LSP.2014.2337313

Uniform Guidelines on Employee Selection Procedures, 29 C.F.R. § 1607 (1978). https://www.ecfr.gov/current/title-29/subtitle-B/chapter-XIV/part-1607

Verma, S., & Rubin, J. (2018). Fairness definitions explained. In *Proceedings of the International Workshop on Software Fairness (FairWare '18)* (pp. 1–7). ACM. https://doi.org/10.1145/3194770.3194776

Yeh, I.-C. (2009). *Default of credit card clients* [Data set]. UCI Machine Learning Repository. https://doi.org/10.24432/C55S3H

Yeh, I.-C., & Lien, C.-H. (2009). The comparisons of data mining techniques for the predictive accuracy of probability of default of credit card clients. *Expert Systems with Applications, 36*(2), 2473–2480. https://doi.org/10.1016/j.eswa.2007.12.020

Appendix A

Repository Layout and Run Instructions

The repository at https://github.com/develmj/walsh-qm640-capstone holds the code, data dictionary, results, and this report. Clone it, create a Python 3.11 environment, install the pinned dependencies with pip install -r requirements.txt (or requirements-py310.txt on Python 3.10), and run make all. The targets run in order: data (download with checksum, recode, folds), rq2 (exploratory analysis and RQ2), train (fit, calibrate, score), rq1, rq3, rq4, sensitivity, extensions (ThresholdOptimizer cross-check, reweighing on the aware model, age-band audit), register (the hypothesis-test register), and sample-size (the synopsis Table 1). On a host with short per-command limits, PART=unaware:0,1 python3 src/train.py trains a subset of folds and PART=merge assembles the outputs.

```
qm640-credit-fairness/
|-- README.md                  results summary and run instructions
|-- requirements.txt           pinned dependencies (Python 3.11+)
|-- requirements-py310.txt     compatible versions for Python 3.10
|-- Makefile                   make all | data | train | rq1 .. rq4
|-- data/
|   |-- data_dictionary.csv    source of Table 2
|   |-- raw/                   fetched by download.py, not committed
|   |-- processed/             clients_clean.parquet, folds, scores
|-- src/
|   |-- common.py              constants, DeLong, KS, Brier
|   |-- download.py            fetch, verify SHA-256, structural checks
|   |-- prepare.py             recoding, engineered variables, folds
|   |-- train.py               three models, inner-CV tuning, calibration
|   |-- policy.py              cut-offs, per-sex thresholds, reweighing
|   |-- evaluate.py            audit, bootstrap, non-inferiority
|   |-- sample_size.py         reproduces the synopsis Table 1
|-- analysis/                  01_eda .. 08_statistical_depth (scripts)
|-- notebooks/                 the same eight steps as notebooks
|-- results/
|   |-- tables/                40 CSV files, one per analysis
|   |-- figures/               8 PNG figures
|   |-- reproducibility_cross_machine.csv
|-- reports/                   synopsis.pdf, final_report.pdf
```

Appendix B

Sample-Size Plan From the Synopsis

The synopsis sized each research question before any data were analysed, and this appendix reproduces the derivation so that the planning assumptions can be checked against what was observed. src/sample_size.py regenerates every figure below. All four research questions are evaluated on pooled held-out predictions from stratified five-fold cross-validation, so the evaluation pool is the full 30,000. The calculations use α = .05, power 1 − β = .80, $z_{0.975}$ = 1.960, $z_{0.95}$ = 1.645, and $z_{0.80}$ = 0.842 throughout, the observed default prevalence of 22.12% (6,636 of 30,000), and the observed sex split of 39.63% male (11,888, with 2,873 defaulters) and 60.37% female (18,112, with 3,763 defaulters). The method for each question follows from its analysis type: a precision target for an estimate that is reported with an interval (RQ1), a power calculation for a test of two proportions (RQ2 and RQ3), and a power calculation for a one-sided non-inferiority test on correlated AUCs (RQ4).

RQ1: Confidence Interval for the AUC and Power for the Paired Contrast

RQ1 reports each model's AUC to a stated precision and tests one pre-specified paired contrast, so the primary method is the confidence-interval approach of Hanley and McNeil (1982). It gives the standard error of an AUC A from the numbers of defaulters n_D and non-defaulters n_N, where $Q_1 = A/(2 - A)$ and $Q_2 = 2A^2/(1 + A)$.

$$SE(A) = \sqrt{\frac{A(1-A) + (n_D - 1)(Q_1 - A^2) + (n_N - 1)(Q_2 - A^2)}{n_D n_N}} \tag{B1}$$

Step 1 set the planning AUC at A = 0.78, the value I expected for tuned gradient boosting on a card portfolio of this kind. Step 2 computed the constants: Q_1 = 0.78/1.22 = 0.6393, Q_2 = 1.2168/1.78 = 0.6836, and A^2 = 0.6084, so $Q_1 - A^2$ = 0.0309 and $Q_2 - A^2$ = 0.0752. Step 3 substituted the prevalence. With n_D = 0.2212n and n_N = 0.7788n, and n large enough that the minus-one terms are immaterial, Equation B1 reduces to SE^2 = [0.2212(0.0309) + 0.7788(0.0752)] / (0.2212 × 0.7788 × n) = 0.0654/(0.1723n) = 0.3797/n. Step 4 set the precision

target: a 95% CI half-width of 0.01 requires SE ≤ 0.01/1.960 = 0.005102, so SE² ≤ 2.603 × 10^{-5}. Step 5 solved for n: $n \geq 0.3797/(2.603 \times 10^{-5}) = 14{,}587$, and the exact solution of Equation B1 gives the same figure. At $A = 0.75$ the constant rises to 0.4114 and the requirement to 15,805.

The second calculation powered the DeLong test of H1. Two AUCs estimated on the same cardholders are correlated, and with equal standard errors $\mathrm{Var}(A_{GB} - A_{LR}) = 2(1 - r)\mathrm{SE}^2$, where r is the correlation between the two estimates. Step 6 set the minimum detectable improvement at Δ = 0.02, below the gain I expected, with two-sided α = .05 and power .80. Step 7 set $r = 0.70$. Step 8 solved $n \geq 2(1 - r) \times 0.3797 \times (z_{0.975} + z_{0.80})^2/\Delta^2 = 0.6 \times 0.3797 \times 7.849/0.0004 = 4{,}470$, or 7,450 at $r = 0.50$. The paired test is powered at any sample that meets the precision target, so RQ1 takes 14,587 as its minimum. The observed AUC was .784 and the observed paired correlation .85, so both planning values were conservative.

RQ2: Power Analysis for Two Proportions

RQ2 compares two independent proportions with unequal group sizes, so the method is the power formula for a two-sided two-proportion z test with allocation ratio k (Fleiss et al., 2003), where n_1 is the smaller group (male), $n_2 = kn_1$ is the larger (female), $\bar{p} = (p_1 + kp_2)/(1 + k)$, and $\Delta = p_1 - p_2$.

$$n_1 = \frac{\left[z_{1-\alpha/2}\sqrt{(1+1/k)\,\bar{p}(1-\bar{p})} + z_{1-\beta}\sqrt{p_1(1-p_1) + p_2(1-p_2)/k} \right]^2}{\Delta^2} \qquad \text{(B2)}$$

Step 1 set the planned minimum meaningful difference at Δ = 0.03, with planning values $p_1 = 0.24$ and $p_2 = 0.21$, because a three-point gap moves a segment across the pricing bands most card issuers use. Step 2 set $k = 18{,}112/11{,}888 = 1.524$. Step 3 computed $\bar{p} = (0.24 + 1.524 \times 0.21)/2.524 = 0.2219$ and $1 - \bar{p} = 0.7781$. Step 4 evaluated the two terms in the bracket. The first is $1.960 \times \sqrt{[(1 + 1/1.524) \times 0.2219 \times 0.7781]} = 1.960 \times \sqrt{(1.656 \times 0.1727)} = 1.960 \times \sqrt{0.2860} = 1.960 \times 0.5348 = 1.048$. The second is $0.842 \times \sqrt{[0.24 \times 0.76 + 0.21 \times 0.79/1.524]} = 0.842 \times \sqrt{(0.1824 + 0.1089)} = 0.842 \times \sqrt{0.2913} = 0.842 \times 0.5397 = 0.454$. Step 5 squared and divided: $n_1 = (1.048 + 0.454)^2/0.03^2 = 2.257/0.0009 = 2{,}508$ male cardholders, and $n_2 = 1.524 \times 2{,}508 =$

3,821 female cardholders, 6,329 in total. Step 6 converted to a dataset size: N = 2,508/0.3963 = 6,329, since the sexes are drawn in the file's own proportions. Cohen's (1988) h for this difference is 2 arcsin√0.24 − 2 arcsin√0.21 = 0.072, a small effect. The age-band test is a secondary 2 × 4 chi-square with three degrees of freedom. For a small effect w = 0.10 at α = .05 and power .80 the non-centrality parameter is 10.91 (Cohen, 1988), so N = 10.91/0.10² = 1,091, which the sex comparison dominates. The observed difference was 3.39 points, above the planning Δ.

RQ3: Power Analysis for the False-Decline Rate Gap

RQ3 tests a difference in false-decline rates, which only non-defaulters enter, so the comparison groups are the 9,015 male and 14,349 female non-defaulters, and Equation B2 applies with the counts restricted to non-defaulters and then inflated to the full population. Step 1 set the minimum detectable gap at Δ = 0.05, the benchmark in RQ3, with planning values FDR_{male} = 0.19 and FDR_{female} = 0.14, bracketing the overall rate of about 0.165 implied by a 25% flag rate at an AUC near 0.78. Step 2 set k = 14,349/9,015 = 1.592. Step 3 computed $\bar{p}$ = (0.19 + 1.592 × 0.14)/2.592 = 0.1593 and 1 − $\bar{p}$ = 0.8407. Step 4 evaluated the bracket. The first term is 1.960 × √[(1 + 1/1.592) × 0.1593 × 0.8407] = 1.960 × √(1.628 × 0.1339) = 1.960 × √0.2181 = 1.960 × 0.4670 = 0.915. The second is 0.842 × √[0.19 × 0.81 + 0.14 × 0.86/1.592] = 0.842 × √(0.1539 + 0.0756) = 0.842 × √0.2295 = 0.842 × 0.4791 = 0.403. Step 5 squared and divided: (0.915 + 0.403)²/0.05² = 1.738/0.0025 = 695 male non-defaulters, and 1.592 × 695 = 1,107 female non-defaulters, 1,802 in total. Step 6 inflated to the full population. Male non-defaulters are 0.3963 × 0.7583 = 0.3005 of all cardholders, so N = 695/0.3005 = 2,314. At the full 30,000 the 95% CI for the gap has a half-width of about 1.960 × √[0.165 × 0.835 × (1/9,015 + 1/14,349)] = 0.010, which is the width observed in Table 7.

RQ4: Non-Inferiority Test for Paired AUCs After Reweighing

RQ4's inferential test applies to reweighing only, because threshold adjustment does not change the scores. The baseline and reweighed models score the same cardholders, so their AUCs are correlated, and the method is the correlated-AUC test of DeLong et al. (1988) framed

as a one-sided non-inferiority test. Step 1 set the margin at $\delta = 0.01$, the largest AUC loss the lender accepts in exchange for closing the fairness gap, with one-sided $\alpha = .05$, power .80, and a true difference of zero. Step 2 set $r = 0.70$ as a planning assumption, chosen below the correlation two models fitted to the same features on the same rows would usually show, and checked in Step 6. Step 3 set the requirement $\delta/SE_{diff} \geq z_{0.95} + z_{0.80} = 1.645 + 0.842 = 2.487$, so $SE_{diff} \leq 0.01/2.487 = 0.00402$. Step 4 converted to the single-AUC standard error: $SE_{diff} = \sqrt{(2 \times 0.30)} \times SE = 0.7746 \times SE$, so $SE \leq 0.00402/0.7746 = 0.00519$. Step 5 applied the RQ1 variance constant: $n \geq 0.3797/0.00519^2 = 0.3797/(2.694 \times 10^{-5}) = 14{,}094$, and the exact solution of Equation B1 gives 14,086. Step 6 checked sensitivity: at $r = 0.85$ the requirement falls to 7,042, and at $r = 0.50$ it rises to 23,475, still inside the available 30,000. The observed paired correlation between the baseline and reweighed AUCs was .998, far above the planning value. The decision-level measures for threshold adjustment carry 1,000-draw stratified bootstrap intervals and were not sized by power.

Table B1

Sample Size Requirement by Research Question (From the Synopsis)

Research question	Method	Key parameters	Minimum N
RQ1 model performance	Confidence interval for AUC (Hanley & McNeil, 1982), plus paired DeLong power	A = .78, prevalence .2212, half-width .01, z = 1.960; paired: Δ = .02, r = .70, α = .05 two-sided, power .80	14,587 (precision); 4,470 (paired)
RQ2 outcome disparity	Power analysis, two-proportion z test, unequal allocation (Fleiss et al., 2003)	α = .05 two-sided, power .80, p1 = .24, p2 = .21, Δ = .03, k = 1.524, Cohen's h = .072	6,329 (2,508 male, 3,821 female)
RQ3 fairness at cut-off	Power analysis, two-proportion z test on the false-decline rate within non-defaulters, inflated by non-default share	α = .05, power .80, FDR .19 vs .14, Δ = .05, k = 1.592, male non-defaulter share .3005	2,314 (1,802 non-defaulters)

Research question	Method	Key parameters	Minimum N
RQ4 mitigation	Power analysis, one-sided non-inferiority of correlated AUCs (DeLong et al., 1988), reweighing only	α = .05 one-sided, power .80, margin δ = .01, r = .70 (sensitivity .50 to .85), A = .78	14,086 (23,475 at r = .50)

Note. All calculations use the dataset's observed prevalence (22.12%) and sex split (39.63% male). Threshold adjustment in RQ4 is evaluated with bootstrap intervals on decision-level measures and is not sized by power.

Final Sample Size Decision

The final minimum sample size is the maximum across the four research questions under the primary assumptions:

$$N_{min} = max(14{,}587, 6{,}329, 2{,}314, 14{,}086) = 14{,}587 \quad \text{(B3)}$$

The binding requirement is the AUC precision target in RQ1. The dataset holds 30,000 cardholders, 2.06 times the minimum, so the full file was used for every research question and no subsample was drawn. The most conservative sensitivity case, RQ4 at r = .50, requires 23,475, which the full file also covers. Every planning value proved conservative against the observed data: AUC .784 against a planned .78, paired correlation .85 against .70 for RQ1 and .998 against .70 for RQ4, and a sex difference of 3.39 points against a planned Δ of 3.0.

Appendix C

Selected XGBoost Hyperparameters by Fold

Table C1 lists the hyperparameters selected by the 12-candidate randomised search under inner three-fold cross-validation on each fold's fit partition, with the inner-CV AUC of the selected candidate. The search space was: trees in {200, 300, 400, 600}, learning rate in {.02, .03, .05, .10}, maximum depth in {3, 4, 5, 6}, row subsample in {.7, .8, .9, 1.0}, column subsample in {.6, .8, 1.0}, minimum child weight in {1, 5, 10, 20}, and L2 penalty in {1, 3, 10}. Positive-class weight was set to the ratio of negatives to positives in the fit partition.

Table C1

XGBoost Hyperparameters Selected per Fold

Feature set	Fold	Inner-CV AUC	Trees	Learning rate	Depth	Subsample	Column sample	Min child weight	L2
Unaware	0	.783	300	.03	3	.8	.8	1	10
Unaware	1	.783	600	.02	4	.9	.8	1	10
Unaware	2	.783	200	.03	3	.7	.8	5	3
Unaware	3	.787	200	.02	5	1.0	.6	1	10
Unaware	4	.784	300	.02	4	.9	1.0	10	1
Aware	0	.784	300	.03	3	.8	.8	1	10
Aware	1	.785	600	.02	4	.9	.8	1	10
Aware	2	.784	200	.02	5	.7	.8	5	3
Aware	3	.788	200	.02	5	1.0	.6	1	10
Aware	4	.785	300	.02	4	.9	1.0	10	1

Note. Values from the cloud-container run. The Mac Studio run selected different candidates in some folds with AUC differences under .001.

Appendix D

Hypothesis-Test Register

Table D1 lists every formal test in the study with its statistic, p value, effect size, 95% interval (90% for the bootstrap equivalence rows), and decision at α = .05. The repository file hypothesis_test_register.csv adds the assumption check and the minimum detectable effect for each row.

Table D1
Formal Hypothesis Tests for RQ1 to RQ4

RQ	Hypothesis	Test	Statistic	p	Effect [95% CI]	Decision
RQ1	$H1_0$: AUC_{GB} = AUC_{LR} vs $H1_1$: AUC_{GB} > AUC_{LR} (pre-specified, one-sided)	DeLong paired AUC test	z = 15.659	< .001	0.0294 [0.0257, 0.033]	Reject $H1_0$
RQ1	Secondary: AUC equal for XGBoost vs logistic (two-sided, Holm-adjusted)	DeLong paired AUC test	z = 15.659	< .001	0.0294 [0.0257, 0.033]	Reject
RQ1	Secondary: AUC equal for Random forest vs logistic (two-sided, Holm-adjusted)	DeLong paired AUC test	z = 14.379	< .001	0.029 [0.025, 0.0329]	Reject
RQ1	Secondary: AUC equal for XGBoost vs random forest (two-sided, Holm-adjusted)	DeLong paired AUC test	z = 0.5	.617	0.0004 [-0.0012, 0.002]	Retain
RQ1	Fold-level: mean AUC difference GB - LR = 0 (one-sided)	Nadeau-Bengio corrected paired t-test across 5 folds	t = 9.849, df = 4.0	< .001	0.0294 [0.0211, 0.0376]	Reject
RQ1	Calibration: observed = expected default rate across deciles (isotonic-calibrated XGBoost)	Hosmer-Lemeshow chi-square	chi2 = 19.02, df = 8.0	.015	0.1346	Reject (decile deviation)

RQ	Hypothesis	Test	Statistic	p	Effect [95% CI]	Decision
RQ2	$H2_0$: $p_{male} = p_{female}$ vs $H2_1$: $p_{male} != p_{female}$	Two-proportion z test (pooled SE), Newcombe CI	z = 6.921	< .001	3.39 pts [2.42, 4.36]	Reject $H2_0$
RQ2	Equivalence: $\|p_{male} - p_{female}\| < 0.03$ (TOST, margin 0.03)	Two one-sided z tests	z (upper) = 0.79	.785	3.39 pts [2.42, 4.36]	Retain (not equivalent within 0.03)
RQ2	$H2b_0$: DEFAULT independent of AGE_BAND	Chi-square test of independence (2 x 4)	chi2 = 44.11, df = 3.0	< .001	0.0383 [0.0274, 0.0501]	Reject $H2b_0$
RQ2	Adjusted: male coefficient = 0 given AGE and log LIMIT_BAL	Wald z test in logistic regression	z = 3.883	< .001	1.119 [1.057, 1.184]	Reject
RQ2	Adjusted (full): male coefficient = 0 given AGE, log LIMIT_BAL, EDUCATION, MARRIAGE	Wald z test in logistic regression	z = 4.394	< .001	1.136 [1.073, 1.203]	Reject
RQ3	$H3_0$: $FDR_{male} = FDR_{female}$ at 75% retention (unaware XGBoost)	Two-proportion z test (pooled SE), Newcombe CI	z = 5.682	< .001	2.79 pts [1.82, 3.77]	Reject $H3_0$
RQ3	Benchmark: $\|FDR_{male} - FDR_{female}\| < 0.05$ (TOST, margin 0.05)	Two one-sided z tests	z (upper) = -4.44	< .001	2.79 pts [1.82, 3.77]	Reject (gap within 0.05)
RQ3	Stricter benchmark: | gap| < 0.02 (TOST, margin 0.02)	Two one-sided z tests	z (upper) = 1.582	.943	2.79 pts [1.82, 3.77]	Retain (not within 0.02)
RQ3	Benchmark: DI ratio >= 0.80 on RETAIN	Stratified bootstrap (1,000) percentile interval	DI = 0.946		0.946 [0.934, 0.9576]	Benchmark met (lower bound > .80)

RQ	Hypothesis	Test	Statistic	p	Effect [95% CI]	Decision
RQ3	$H3_0$ (chi-square form): FLAG independent of SEX among non-defaulters	Chi-square 2 x 2 without continuity correction	chi2 = 32.29, df = 1.0	< .001	0.0372	Reject
RQ3	Secondary: TPR_{male} = TPR_{female} among defaulters	Two-proportion z test, Newcombe CI	z = 1.936	.053	2.37 pts [-0.03, 4.75]	Retain
RQ3	Unawareness effect: FDR gap (aware) - FDR gap (unaware) = 0	Paired stratified bootstrap (10,000), percentile interval	difference of gaps = 0.0103	< .001	1.03 pts [0.67, 1.39]	Reject
RQ3	Consistency: FDR gap across the five folds	Descriptive: mean and SD of fold-level gaps	mean gap = 0.0279, df = 4.0		0.0096 [0.0197, 0.0433]	All five folds positive
RQ3	Age band: FDR equal for 30-39 vs >=50 (largest of six pairs, Holm-adjusted)	Two-proportion z test, Newcombe CI	z = -7.634	< .001	-6.80 pts [-8.76, -4.92]	Reject
RQ4	$H4_0$: AUC_{RW} <= AUC_{base} - 0.01 vs $H4_1$: AUC_{RW} > AUC_{base} - 0.01 (unaware model)	One-sided non-inferiority, DeLong paired variance	z = 54.06	< .001	-0.00012 (lower bound -0.00042)	Reject $H4_0$ (non-inferior)
RQ4	Extension: AUC_{RW} <= AUC_{base} - 0.01 (aware model)	One-sided non-inferiority, DeLong paired variance	z = 35.04	< .001	-0.00039 (lower bound -0.00084)	Reject (non-inferior)
RQ4	Reweighing (unaware) vs unmitigated: change in FDR gap = 0	Paired stratified bootstrap (10,000)	difference = -0.001	.394	-0.10 pts [-0.34, 0.14]	Retain
RQ4	Reweighing (unaware) vs unmitigated: change in default rate among retained = 0	Paired stratified bootstrap (10,000)	difference = 1e-05	.969	0.00 pts [-0.07, 0.07]	Retain

RQ	Hypothesis	Test	Statistic	p	Effect [95% CI]	Decision
RQ4	Threshold adjustment vs unmitigated: change in FDR gap = 0	Paired stratified bootstrap (10,000)	difference = -0.0236	< .001	-2.36 pts [-2.64, -2.08]	Reject
RQ4	Threshold adjustment vs unmitigated: change in default rate among retained = 0	Paired stratified bootstrap (10,000)	difference = 0.00033	.375	0.03 pts [-0.04, 0.11]	Retain
RQ4	Reweighing (aware) vs aware unmitigated: change in FDR gap = 0	Paired stratified bootstrap (10,000)	difference = -0.0184	< .001	-1.84 pts [-2.13, -1.55]	Reject
RQ4	Reweighing (aware) vs aware unmitigated: change in default rate among retained = 0	Paired stratified bootstrap (10,000)	difference = 5e-05	.921	0.01 pts [-0.07, 0.08]	Retain
RQ4	Reweighing (unaware) vs unmitigated: change in FDR gap within ±0.5 pts (TOST)	Bootstrap two one-sided tests (10,000 draws)	90% interval bound = -0.00303	< .001	-0.10 pts [-0.30, 0.10]	Reject (within 0.5 pts)
RQ4	Reweighing (unaware) vs unmitigated: change in default rate among retained within ±0.5 pts (TOST)	Bootstrap two one-sided tests (10,000 draws)	90% interval bound = 0.00058	< .001	0.00 pts [-0.06, 0.06]	Reject (within 0.5 pts)
RQ4	Threshold adjustment vs unmitigated: change in default rate among retained within ±0.5 pts (TOST)	Bootstrap two one-sided tests (10,000 draws)	90% interval bound = 0.00097	< .001	0.03 pts [-0.03, 0.10]	Reject (within 0.5 pts)
RQ4	Reweighing (aware) vs aware unmitigated: change in default rate among retained within ±0.5 pts (TOST)	Bootstrap two one-sided tests (10,000 draws)	90% interval bound = 0.00065	< .001	0.01 pts [-0.06, 0.07]	Reject (within 0.5 pts)

RQ	Hypothesis	Test	Statistic	p	Effect [95% CI]	Decision
RQ4	Threshold adjustment: residual | FDR gap| < 0.02 (TOST, margin 0.02)	Two one-sided z tests	z (upper) = -3.186	< .001	0.43 pts [-0.53, 1.40]	Reject (gap within 0.02)
RQ4	Threshold adjustment: change in overall flag rate within ±0.5 pts (TOST)	Two one-sided z tests on paired proportions	z (upper) = -7.357	< .001	0.04 pts [-0.09, 0.16]	Reject (within 0.5 pts)

Note. p values below .001 are shown as < .001. Effects are AUC differences, proportion differences in percentage points, odds ratios, or ratios as named in the hypothesis. Paired bootstrap p values are two-sided percentile p values.


Appendix E

Repository and Execution Record

Figures E1 and E2 are screenshots of the public repository at https://github.com/develmj/walsh-qm640-capstone taken after the commit that holds the code, results, and this report. Figures E3 to E8 are terminal captures from the Docker container on the Mac Studio described in Table 14, recorded on 13 October 2026 in the cloned repository under the container's own Python 3.10 and older libraries. They show the environment, the data verification, model training for two folds, and the three analysis scripts whose outputs feed the Results section, with the wall-clock time of each. The numbers in those six captures are the unpinned replication values discussed under Reproducibility Across Machines, so XGBoost quantities differ from the report tables in the fourth decimal. Figures E9 and E10 are from the pinned replication in a Python 3.12 environment with the exact versions in requirements.txt, and their numbers match the report tables.

Figure E1


Repository Root on GitHub After the Commit



Note. Public repository develmj/walsh-qm640-capstone, main branch, commit db87e52.

Figure E2

Repository README as Rendered on GitHub



Note. The README carries the data source, the run instructions, and the results summary.

Figure E3

Environment, Repository State, and Data Verification

```
Terminal: environment, repository and data verification (Mac Studio container)

mj@mjs-mac-studio-local walsh-qm640-capstone % uname -srm; python3 --version; nproc; free -h | head -2
Linux 6.8.0-138-generic aarch64
Python 3.10.12
4
               total        used        free      shared  buff/cache   available
Mem:           3.8Gi       169Mi       286Mi       4.0Mi       3.4Gi       3.5Gi

mj@mjs-mac-studio-local walsh-qm640-capstone % git log --oneline -3 && git remote -v
db87e52 Capstone pipeline, results and reports
a26035b Add project title to README.md
origin  git@github.com:develmj/walsh-qm640-capstone.git (fetch)
origin  git@github.com:develmj/walsh-qm640-capstone.git (push)

mj@mjs-mac-studio-local walsh-qm640-capstone % python3 src/download.py
sha256 c76095b2a65c6e1b0ef6bdfab785346065b02f3f50cab6751d5a46b4c01c9e44
structure verified: 30,000 x 25, 6,636 defaults, 11,888 male / 18,112 female
```

Note. download.py verifies the SHA-256 checksum and the documented structure of the raw file before any analysis runs.

Figure E4

Model Training for Two Folds With the PART Option

```
Terminal: model training, two folds (Mac Studio container)

mj@mjs-mac-studio-local walsh-qm640-capstone % time PART=unaware:0,1 python3 src/train.py
[unaware] fold 0 done in 12s
[unaware] fold 1 done in 14s

real    0m26.444s
user    0m52.336s
sys     0m0.464s

mj@mjs-mac-studio-local walsh-qm640-capstone % ls data/processed/parts
best_unaware_fold0.json
best_unaware_fold1.json
scores_unaware_fold0.parquet
scores_unaware_fold1.parquet
```

Note. Each fold trains logistic regression, random forest, and XGBoost with inner-CV tuning and writes a part file that PART=merge assembles.

Figure E5

RQ1 Analysis Script Output

```
Terminal: RQ1 analysis script (Mac Studio container)


mj@mjs-mac-studio-local walsh-qm640-capstone % time python3 analysis/03_rq1_models.py
feature_set              model     n    AUC  AUC_se  AUC_ci95_low  AUC_ci95_high     KS  Brier_raw  Brier_calibrated  F1_at_cutoff
    retain_rate_at_cutoff
    unaware Logistic regression 30000 0.7547  0.0035        0.7478         0.7616 0.3988     0.1959            0.1428        0.5158
    0.7503
    unaware       Random forest 30000 0.7838  0.0033        0.7773         0.7903 0.4298     0.1658            0.1345        0.5440
    0.7474
    unaware             XGBoost 30000 0.7836  0.0033        0.7771         0.7900 0.4287     0.1799            0.1346        0.5436
    0.7459
      aware Logistic regression 30000 0.7565  0.0035        0.7496         0.7633 0.3982     0.1954            0.1427        0.5172
    0.7490
      aware       Random forest 30000 0.7844  0.0033        0.7779         0.7908 0.4284     0.1648            0.1345        0.5451
    0.7471
      aware             XGBoost 30000 0.7858  0.0033        0.7794         0.7922 0.4305     0.1790            0.1342        0.5433
    0.7463
feature_set                              contrast  AUC_a  AUC_b  difference  ci95_low  ci95_high       z  p_two_sided
    unaware   XGBoost vs logistic (pre-specified) 0.7836 0.7547      0.0289    0.0253     0.0325 15.5698       0.0000
    unaware Random forest vs logistic (secondary) 0.7838 0.7547      0.0291    0.0251     0.0330 14.4397       0.0000
    unaware  XGBoost vs random forest (secondary) 0.7836 0.7838     -0.0002   -0.0019     0.0015 -0.2370       0.8126
      aware   XGBoost vs logistic (pre-specified) 0.7858 0.7565      0.0293    0.0257     0.0330 15.8103       0.0000
      aware Random forest vs logistic (secondary) 0.7844 0.7565      0.0279    0.0239     0.0319 13.6111       0.0000
      aware  XGBoost vs random forest (secondary) 0.7858 0.7844      0.0014   -0.0002     0.0031  1.6860       0.0918

real    0m2.045s
user    0m2.525s
sys     0m0.050s
```

Note. Performance table and DeLong contrasts for both feature sets, as written to results/tables/rq1_performance.csv and rq1_delong_contrasts.csv.

Figure E6

RQ3 Fairness Audit Script Output



```
Terminal: RQ3 fairness audit script (Mac Studio container)


mj@mjs-mac-studio-local walsh-qm640-capstone % time python3 analysis/04_rq3_fairness_audit.py
            configuration  DI_ratio  DI_ci95_low  DI_ci95_high  male_FDR  female_FDR  FDR_gap  FDR_gap_ci95_low  FDR_gap_ci95_high FDR_gap_p  TPR_gap
    overall_default_rate_retained
XGBoost, unaware (primary)    0.9470       0.9345        0.9580    0.1768      0.1500   0.0268            0.0174             0.0373  5.68e-08   0.0235
    0.1234
          XGBoost, aware    0.9332       0.9214        0.9453    0.1826      0.1459   0.0367            0.0267             0.0461  1.03e-13   0.0378
    0.1235
       Logistic, unaware    0.9489       0.9366        0.9611    0.1786      0.1559   0.0227            0.0136             0.0335   5.3e-06   0.0379
    0.1330
    Random forest, unaware    0.9488       0.9360        0.9597    0.1749      0.1487   0.0262            0.0173             0.0364  9.53e-08   0.0198
    0.1235
            configuration    sex     n   TP   FP   FN    TN  retain_rate    FDR    TPR  precision  default_rate_retained
XGBoost, unaware (primary)   male 11888 1716 1594 1157  7421       0.7216 0.1768 0.5973     0.5184                0.1349
XGBoost, unaware (primary) female 18112 2159 2153 1604 12196       0.7619 0.1500 0.5737     0.5007                0.1162
          XGBoost, aware   male 11888 1737 1646 1136  7369       0.7154 0.1826 0.6046     0.5134                0.1336
          XGBoost, aware female 18112 2133 2094 1630 12255       0.7666 0.1459 0.5668     0.5046                0.1174
       Logistic, unaware   male 11888 1639 1610 1234  7405       0.7267 0.1786 0.5705     0.5045                0.1428
       Logistic, unaware female 18112 2004 2237 1759 12112       0.7658 0.1559 0.5326     0.4725                0.1268
    Random forest, unaware   male 11888 1706 1577 1167  7438       0.7238 0.1749 0.5938     0.5196                0.1356
    Random forest, unaware female 18112 2160 2134 1603 12215       0.7629 0.1487 0.5740     0.5030                0.1160

real    0m1.252s
user    0m1.717s
sys     0m0.052s
```

Note. Fairness summary and per-sex confusion matrices for the four configurations in Table 7.

Figure E7

RQ4 Mitigation Script Output



```
Terminal: RQ4 mitigation script (Mac Studio container)


mj@mjs-mac-studio-local walsh-qm640-capstone % time python3 analysis/05_rq4_mitigation.py
lower_bound_one_sided_95  -0.000656
margin                       -0.01
z_noninferiority          57.508265
p_noninferiority                0.0
non_inferior                   True
paired_auc_correlation     0.998711
AUC_reweighed_ci95_low     0.776746
AUC_reweighed_ci95_high    0.789665
 retention_target                          configuration  overall_retain_rate  default_rate_retained    AUC  DI_ratio  FDR_gap  FDR_gap_ci95_low
    FDR_gap_ci95_high  TPR_gap  meets_DI_0.80  meets_FDR_gap_0.05
           0.65           Unmitigated (single threshold)               0.6467                0.1106 0.7836    0.9469   0.0232            0.0121
    0.0347   0.0139          True               True
           0.65            Reweighing (single threshold)               0.6482                0.1108 0.7832    0.9529   0.0193            0.0081
    0.0308   0.0092          True               True
           0.65 Threshold adjustment (per-sex thresholds)               0.6478                0.1109 0.7836    0.9722   0.0057           -0.0052
    0.0170  -0.0010          True               True
           0.70           Unmitigated (single threshold)               0.6967                0.1157 0.7836    0.9488   0.0262            0.0158
    0.0372   0.0075          True               True
           0.70            Reweighing (single threshold)               0.6983                0.1158 0.7832    0.9514   0.0237            0.0136
    0.0342   0.0082          True               True
           0.70 Threshold adjustment (per-sex thresholds)               0.6983                0.1165 0.7836    0.9727   0.0082           -0.0018
    0.0191  -0.0063          True               True
           0.75           Unmitigated (single threshold)               0.7459                0.1234 0.7836    0.9470   0.0268            0.0174
    0.0373   0.0235          True               True
           0.75            Reweighing (single threshold)               0.7455                0.1237 0.7832    0.9492   0.0245            0.0150
    0.0338   0.0236          True               True
           0.75 Threshold adjustment (per-sex thresholds)               0.7478                0.1241 0.7836    0.9738   0.0069           -0.0025
    0.0163   0.0008          True               True
           0.80           Unmitigated (single threshold)               0.7968                0.1350 0.7836    0.9510   0.0265            0.0187
    0.0351   0.0256          True               True
           0.80            Reweighing (single threshold)               0.7973                0.1351 0.7832    0.9529   0.0247            0.0166
    0.0329   0.0251          True               True
           0.80 Threshold adjustment (per-sex thresholds)               0.7972                0.1361 0.7836    0.9800   0.0060           -0.0020
    0.0145  -0.0087          True               True
           0.85           Unmitigated (single threshold)               0.8463                0.1478 0.7836    0.9595   0.0212            0.0142
    0.0285   0.0273          True               True
           0.85            Reweighing (single threshold)               0.8465                0.1479 0.7832    0.9614   0.0193            0.0124
    0.0263   0.0267          True               True
           0.85 Threshold adjustment (per-sex thresholds)               0.8471                0.1478 0.7836    0.9838   0.0040           -0.0025
    0.0104  -0.0067          True               True

real    0m2.652s
user    0m3.884s
sys     0m0.069s
```

Note. Non-inferiority result for reweighing and the trade-off table across retention rates, as in Table 10.

Figure E8

Hypothesis-Test Register Script Output



```
Terminal: hypothesis-test register script (Mac Studio container)


mj@mjs-mac-studio-local walsh-qm640-capstone % time python3 analysis/08_statistical_depth.py
RQ1             Secondary: AUC equal for Random forest vs logistic (two-sided, Holm-adjusted)                 z 14.44000  5.82e-47   0.02910
    0.02510    0.03300                                  Reject
RQ1               Secondary: AUC equal for XGBoost vs random forest (two-sided, Holm-adjusted)                 z -0.23700     0.813  -0.00020
    -0.00190    0.00150                                  Retain
RQ1                        Robustness: mean fold-level AUC difference GB - LR = 0 (one-sided)                 t 10.14500  0.000266   0.02920
    0.02120    0.03710                                  Reject
RQ1 Calibration: observed = expected default rate across deciles (isotonic-calibrated XGBoost)              chi2 21.09000   0.00691   0.13460
    NaN        NaN         Reject (miscalibration detected)
RQ2                                  H2_0: p_male = p_female vs H2_1: p_male != p_female                 z  6.92100  4.47e-12   0.03390
    0.02420    0.04360                                Reject H2_0
RQ2                           Equivalence: |p_male - p_female| < 0.03 (TOST, margin 0.03)          z (upper)  0.79000     0.785   0.03390
    0.02420    0.04360      Retain (not equivalent within 0.03)
RQ2                                              H2b_0: DEFAULT independent of AGE_BAND               chi2 44.11000  1.43e-09   0.03830
    0.02740    0.05010                              Reject H2b_0
RQ2                            Adjusted: male coefficient = 0 given AGE and log LIMIT_BAL                 z  3.88300  0.000103   1.11870
    1.05710    1.18390                                  Reject
RQ2        Adjusted (full): male coefficient = 0 given AGE, log LIMIT_BAL, EDUCATION, MARRIAGE                z  4.39400  1.11e-05   1.13640
    1.07340    1.20320                                  Reject
RQ3                               H3_0: FDR_male = FDR_female at 75% retention (unaware XGBoost)              z  5.42800  5.68e-08   0.02680
    0.01700    0.03660                             Reject H3_0
RQ3                                Benchmark: |FDR_male - FDR_female| < 0.05 (TOST, margin 0.05)          z (upper) -4.64300  1.72e-06   0.02680
    0.01700    0.03660 Reject non-equivalence (gap within 0.05)
RQ3                                      Stricter benchmark: |gap| < 0.02 (TOST, margin 0.02)          z (upper)  1.35300     0.912   0.02680
    0.01700    0.03660                Retain (not within 0.02)
RQ3                                                 Benchmark: DI ratio >= 0.80 on RETAIN                DI  0.94700             0.94700
    0.93450    0.95800       Benchmark met (lower bound > 0.80)
RQ3                           H3_0 (chi-square form): FLAG independent of SEX among non-defaulters           chi2 29.47000  5.68e-08   0.03550
    NaN        NaN                                  Reject
RQ3                                    Secondary: TPR_male = TPR_female among defaulters                 z  1.92800    0.0539   0.02350
    -0.00040    0.04740                                  Retain
RQ3                               Unawareness effect: FDR gap (aware) - FDR gap (unaware) = 0 difference of gaps  0.00990         0   0.00990
    0.00590    0.01420                                  Reject
RQ3                                             Consistency: FDR gap across the five folds           mean gap  0.02680             0.00880
    0.02050    0.04190                  All five folds positive
RQ3  Robustness (age band): FDR equal for 30-39 vs >=50 (largest of six pairs, Holm-adjusted)                 z -7.16200  4.76e-12  -0.06390
    -0.08350   -0.04520                                 Reject
RQ4         H4_0: AUC_RW <= AUC_base - 0.01 vs H4_1: AUC_RW > AUC_base - 0.01 (unaware model)                z 57.51000         0  -0.00038
    -0.00066        NaN              Reject H4_0 (non-inferior)
RQ4                                       Extension: AUC_RW <= AUC_base - 0.01 (aware model)                z 35.04000 2.83e-269  -0.00039
    -0.00084        NaN                   Reject (non-inferior)
RQ4                               Reweighing (unaware) vs unmitigated: change in FDR gap = 0        difference -0.00220     0.046  -0.00220
    -0.00450   -0.00000                                 Reject
RQ4            Reweighing (unaware) vs unmitigated: change in default rate among retained = 0        difference  0.00030     0.342   0.00030
    -0.00030    0.00088                                  Retain
RQ4                               Threshold adjustment vs unmitigated: change in FDR gap = 0        difference -0.01990         0  -0.01990
    -0.02250   -0.01730                                 Reject
RQ4            Threshold adjustment vs unmitigated: change in default rate among retained = 0        difference  0.00072      0.03   0.00072
    0.00006    0.00143                                  Reject
RQ4                                 Reweighing (aware) vs aware unmitigated: change in FDR gap = 0        difference -0.02060         0  -0.02060
    -0.02350   -0.01760                                 Reject
RQ4         Reweighing (aware) vs aware unmitigated: change in default rate among retained = 0        difference -0.00008      0.78  -0.00008
    -0.00079    0.00063                                  Retain
RQ4                           Threshold adjustment: residual |FDR gap| < 0.02 (TOST, margin 0.02)          z (upper) -2.66500   0.00385   0.00690
    -0.00280    0.01660 Reject non-equivalence (gap within 0.02)
RQ4                  Threshold adjustment changes the overall flag rate (marginal homogeneity)              chi2 10.65000    0.0011 284.00000
    114.00000  170.00000                                   Reject
                        comparison  change_in_FDR_gap  gap_ci95_low  gap_ci95_high  change_in_default_rate_retained  bad_ci95_low  bad_ci95_high
    decisions_changed
    Reweighing (unaware) vs unmitigated           -0.00223      -0.00446       -0.00005                          0.00030      -0.00030        0.00088
    206
    Threshold adjustment vs unmitigated           -0.01992      -0.02247       -0.01733                          0.00072       0.00006        0.00143
    284
Reweighing (aware) vs aware unmitigated           -0.02063      -0.02351       -0.01761                         -0.00008      -0.00079        0.00063
    371

real    0m4.046s
user    0m5.133s
sys     0m0.052s
```

Note. The register of Appendix D and the paired bootstrap changes, as computed in the Mac Studio container with the older libraries, before the equivalence rows were added.

Figure E9


Pinned-Version Replication: Environment, Data Stage, and Training



Note. Python 3.12.14 with xgboost 3.4.1 and scikit-learn 1.9.1 installed from requirements.txt. The fold file has the same MD5 checksum as the primary run.

Figure E10

Pinned-Version Replication: RQ1 Output and the Register Rerun



Note. AUC, KS, Brier, and F1 agree with Table 4 to every reported decimal. The register rerun under the pinned environment reproduced all 34 rows of the primary run.