



Naive Bayes Classifiers

Last Updated : 10 Jul, 2024

A Naive Bayes classifiers, a family of algorithms based on Bayes' Theorem. Despite the “naive” assumption of feature independence, these classifiers are widely utilized for their simplicity and efficiency in machine learning. The article delves into theory, implementation, and applications, shedding light on their practical utility despite oversimplified assumptions.

What is Naive Bayes Classifiers?

Naive Bayes classifiers are a collection of classification algorithms based on [Bayes' Theorem](#). It is not a single algorithm but a family of algorithms where all of them share a common principle, i.e. every pair of features being classified is independent of each other. To start with, let us consider a dataset.

One of the most simple and effective classification algorithms, the Naïve Bayes classifier aids in the rapid development of machine learning models with rapid prediction capabilities.

Naïve Bayes algorithm is used for classification problems. It is highly used in text classification. In text classification tasks, data contains high dimension (as each word represent one feature in the data). It is used in spam filtering, sentiment detection, rating classification etc. The advantage of using naïve Bayes is its speed. It is fast and making prediction is easy with high dimension of data.

This model predicts the probability of an instance belongs to a class with a given set of feature value. It is a probabilistic classifier. It is because it

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

with no relation between each other. In real world, this condition satisfies rarely. It uses Bayes theorem in the algorithm for training and prediction

Why it is Called Naive Bayes?

The “Naive” part of the name indicates the simplifying assumption made by the Naïve Bayes classifier. The classifier assumes that the features used to describe an observation are conditionally independent, given the class label. The “Bayes” part of the name refers to Reverend Thomas Bayes, an 18th-century statistician and theologian who formulated Bayes’ theorem.

Consider a fictional dataset that describes the weather conditions for playing a game of golf. Given the weather conditions, each tuple classifies the conditions as fit(“Yes”) or unfit(“No”) for playing golf. Here is a tabular representation of our dataset.

	Outlook	Temperature	Humidity	Windy	Play Golf
0	Rainy	Hot	High	False	No
1	Rainy	Hot	High	True	No
2	Overcast	Hot	High	False	Yes
3	Sunny	Mild	High	False	Yes
4	Sunny	Cool	Normal	False	Yes
5	Sunny	Cool	Normal	True	No
6	Overcast	Cool	Normal	True	Yes

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

	Outlook	Temperature	Humidity	Windy	Play Golf
8	Rainy	Cool	Normal	False	Yes
9	Sunny	Mild	Normal	False	Yes
10	Rainy	Mild	Normal	True	Yes
11	Overcast	Mild	High	True	Yes
12	Overcast	Hot	Normal	False	Yes
13	Sunny	Mild	High	True	No

The dataset is divided into two parts, namely, **feature matrix** and the **response vector**.

- Feature matrix contains all the vectors(rows) of dataset in which each vector consists of the value of **dependent features**. In above dataset, features are 'Outlook', 'Temperature', 'Humidity' and 'Windy'.
- Response vector contains the value of **class variable**(prediction or output) for each row of feature matrix. In above dataset, the class variable name is 'Play golf'.

Assumption of Naive Bayes

The fundamental Naive Bayes assumption is that each feature makes an:

- **Feature independence:** The features of the data are conditionally independent of each other, given the class label.
- **Continuous features are normally distributed:** If a feature is continuous, then it is assumed to be normally distributed within each

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

each class.

- **Features are equally important:** All features are assumed to contribute equally to the prediction of the class label.
- **No missing data:** The data should not contain any missing values.

With relation to our dataset, this concept can be understood as:

- We assume that no pair of features are dependent. For example, the temperature being 'Hot' has nothing to do with the humidity or the outlook being 'Rainy' has no effect on the winds. Hence, the features are assumed to be **independent**.
- Secondly, each feature is given the same weight(or importance). For example, knowing only temperature and humidity alone can't predict the outcome accurately. None of the attributes is irrelevant and assumed to be contributing **equally** to the outcome.

The assumptions made by Naive Bayes are not generally correct in real-world situations. In-fact, the independence assumption is never correct but often works well in practice. Now, before moving to the formula for Naive Bayes, it is important to know about Bayes' theorem.

Bayes' Theorem

[Bayes' Theorem](#) finds the probability of an event occurring given the probability of another event that has already occurred. Bayes' theorem is stated mathematically as the following equation:

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

where A and B are events and $P(B) \neq 0$

- Basically, we are trying to find probability of event A, given the event B is true. Event B is also termed as **evidence**.
- $P(A)$ is the **priori** of A (the prior probability i.e. Probability of event

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

- $P(B)$ is Marginal Probability: Probability of Evidence.
- $P(A|B)$ is a posteriori probability of B, i.e. probability of event after evidence is seen.
- $P(B|A)$ is Likelihood probability i.e the likelihood that a hypothesis will come true based on the evidence.

Now, with regards to our dataset, we can apply Bayes' theorem in following way:

$$P(y|X) = \frac{P(X|y)P(y)}{P(X)}$$

where, y is class variable and X is a dependent feature vector (of size n) where:

$$X = (x_1, x_2, x_3, \dots, x_n)$$

Just to clear, an example of a feature vector and corresponding class variable can be: (refer 1st row of dataset)

$X = (\text{Rainy}, \text{Hot}, \text{High}, \text{False})$

$y = \text{No}$

So basically, $P(y|X)$ here means, the probability of “Not playing golf” given that the weather conditions are “Rainy outlook”, “Temperature is hot”, “high humidity” and “no wind”.

With relation to our dataset, this concept can be understood as:

- We assume that no pair of features are dependent. For example, the temperature being ‘Hot’ has nothing to do with the humidity or the outlook being ‘Rainy’ has no effect on the winds. Hence, the features are assumed to be **independent**.
- Secondly, each feature is given the same weight(or importance). For example, knowing only temperature and humidity alone can't predict the outcome accurately. None of the attributes is irrelevant and assumed to be contributing **equally** to the outcome.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

independent parts.

Now, if any two events A and B are independent, then,

$$P(A, B) = P(A)P(B)$$

Hence, we reach to the result:

$$P(y|x_1, \dots, x_n) = \frac{P(x_1|y)P(x_2|y)\dots P(x_n|y)P(y)}{P(x_1)P(x_2)\dots P(x_n)}$$

which can be expressed as:

$$P(y|x_1, \dots, x_n) = \frac{P(y) \prod_{i=1}^n P(x_i|y)}{P(x_1)P(x_2)\dots P(x_n)}$$

Now, as the denominator remains constant for a given input, we can remove that term:

$$P(y|x_1, \dots, x_n) \propto P(y) \prod_{i=1}^n P(x_i|y)$$

Now, we need to create a classifier model. For this, we find the probability of given set of inputs for all possible values of the class variable y and pick up the output with maximum probability. This can be expressed mathematically as:

$$y = \operatorname{argmax}_y P(y) \prod_{i=1}^n P(x_i|y)$$

So, finally, we are left with the task of calculating $P(y)$ and $P(x_i|y)$.

Please note that $P(y)$ is also called class probability and $P(x_i|y)$ is called conditional probability.

The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i|y)$.

Let us try to apply the above formula manually on our weather dataset. For this, we need to do some precomputations on our dataset.

We need to find $P(x_i|y_j)$ for each x_i in X and y_j in y . All these calculations have been demonstrated in the tables below:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Outlook					Temperature				
	Yes	No	P(Yes)	P(no)		Yes	No	P(Yes)	P(no)
Sunny	2	3	2/9	3/5	Hot	2	2	2/9	2/5
Overcast	4	0	4/9	0/5	Mild	4	2	4/9	2/5
Rainy	3	2	3/9	2/5	Cool	3	1	3/9	1/5
Total	9	5	100%	100%	Total	9	5	100%	100%

Humidity					Wind				
	Yes	No	P(Yes)	P(no)		Yes	No	P(Yes)	P(no)
High	3	4	3/9	4/5	False	6	2	6/9	2/5
Normal	6	1	6/9	1/5	True	3	3	3/9	3/5
Total	9	5	100%	100%	Total	9	5	100%	100%

Play	P(Yes)/P(No)	
Yes	9	9/14
No	5	5/14
Total	14	100%

Naive Bayes Classifiers

So, in the figure above, we have calculated $P(x_i | y_j)$ for each x_i in X and y_j in y manually in the tables 1-4. For example, probability of playing golf given that the temperature is cool, i.e $P(\text{temp.} = \text{cool} | \text{play golf} = \text{Yes}) = 3/9$.

Also, we need to find class probabilities $P(y)$ which has been calculated in the table 5. For example, $P(\text{play golf} = \text{Yes}) = 9/14$.

So now, we are done with our pre-computations and the classifier is ready!

Let us test it on a new set of features (let us call it today):

today = (Sunny, Hot, Normal, False)

$$P(\text{Yes} | \text{today}) =$$

$$\frac{P(\text{Sunny} | \text{Outlook} | \text{Yes}) P(\text{Hot} | \text{Temperature} | \text{Yes}) P(\text{Normal} | \text{Humidity} | \text{Yes}) P(\text{No} | \text{Wind} | \text{Yes}) P(\text{Yes})}{P(\text{today})}$$

and probability to not play golf is given by:

$$P(\text{No} | \text{today}) = \frac{P(\text{Sunny} | \text{Outlook} | \text{No}) P(\text{Hot} | \text{Temperature} | \text{No}) P(\text{Normal} | \text{Humidity} | \text{No}) P(\text{No} | \text{Wind} | \text{No}) P(\text{No})}{P(\text{today})}$$

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

$$P(Yes|today) \propto \frac{3}{9} \cdot \frac{2}{9} \cdot \frac{6}{9} \cdot \frac{6}{9} \cdot \frac{9}{14} \approx 0.02116$$

and

$$P(No|today) \propto \frac{3}{5} \cdot \frac{2}{5} \cdot \frac{1}{5} \cdot \frac{2}{5} \cdot \frac{5}{14} \approx 0.0068$$

Now, since

$$P(Yes|today) + P(No|today) = 1$$

These numbers can be converted into a probability by making the sum equal to 1 (normalization):

$$P(Yes|today) = \frac{0.02116}{0.02116+0.0068} \approx 0.0237$$

and

$$P(No|today) = \frac{0.0068}{0.02116+0.0068} \approx 0.33$$

Since

$$P(Yes|today) > P(No|today)$$

So, prediction that golf would be played is 'Yes'.

The method that we discussed above is applicable for discrete data. In case of continuous data, we need to make some assumptions regarding the distribution of values of each feature. The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i|y)$.


Types of Naive Bayes Model

There are three types of Naive Bayes Model:

Gaussian Naive Bayes classifier

In Gaussian Naive Bayes, continuous values associated with each feature are assumed to be distributed according to a Gaussian distribution. A Gaussian distribution is also called [Normal distribution](#). When plotted, it gives a bell shaped curve which is symmetric about the mean of the feature values as shown below:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).



Updated table of prior probabilities for outlook feature is as following:

The likelihood of the features is assumed to be Gaussian, hence, conditional probability is given by:

$$P(x_i|y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Now, we look at an implementation of Gaussian Naive Bayes classifier using scikit-learn.

	Yes	No	P(Yes)	P(No)
Sunny	3	2	3/9	2/5
Rainy	4	0	4/9	0/5
Overcast	2	3	2/9	3/5
Total	9	5	100%	100%

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).



```
1 # load the iris dataset
2 from sklearn.datasets import load_iris
3 iris = load_iris()
4
5 # store the feature matrix (X) and response vector (y)
6 X = iris.data
7 y = iris.target
8
9 # splitting X and y into training and testing sets
10 from sklearn.model_selection import train_test_split
11 X_train, X_test, y_train, y_test = train_test_split(X, y,
12
13 # training the model on training set
14 from sklearn.naive_bayes import GaussianNB
15 gnb = GaussianNB()
16 gnb.fit(X_train, y_train)
17
18 # making predictions on the testing set
19 y_pred = gnb.predict(X_test)
20
21 # comparing actual response values (y_test) with predicted
22 from sklearn import metrics
23 print("Gaussian Naive Bayes model accuracy(in %):", metrics
    y_pred)*100)
```

Output:

```
Gaussian Naive Bayes model accuracy(in %): 95.0
```

Multinomial Naive Bayes

Feature vectors represent the frequencies with which certain events have been generated by a multinomial distribution. This is the event model typically used for document classification.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

In the multivariate Bernoulli event model, features are independent booleans (binary variables) describing inputs. Like the multinomial model, this model is popular for document classification tasks, where binary term occurrence(i.e. a word occurs in a document or not) features are used rather than term frequencies(i.e. frequency of a word in the document).

Advantages of Naive Bayes Classifier

- Easy to implement and computationally efficient.
- Effective in cases with a large number of features.
- Performs well even with limited training data.
- It performs well in the presence of categorical features.
- For numerical features data is assumed to come from normal distributions

Disadvantages of Naive Bayes Classifier

- Assumes that features are independent, which may not always hold in real-world data.
- Can be influenced by irrelevant attributes.
- May assign zero probability to unseen events, leading to poor generalization.

Applications of Naive Bayes Classifier

- **Spam Email Filtering:** Classifies emails as spam or non-spam based on features.
- **Text Classification:** Used in sentiment analysis, document categorization, and topic classification.
- **Medical Diagnosis:** Helps in predicting the likelihood of a disease based on symptoms.
- **Credit Scoring:** Evaluates creditworthiness of individuals for loan approval.
- **Weather Prediction:** Classifies weather conditions based on various

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

As we reach to the end of this article, here are some important points to ponder upon:

- In spite of their apparently over-simplified assumptions, naive Bayes classifiers have worked quite well in many real-world situations, famously document classification and spam filtering. They require a small amount of training data to estimate the necessary parameters.
- Naive Bayes learners and classifiers can be extremely fast compared to more sophisticated methods. The decoupling of the class conditional feature distributions means that each distribution can be independently estimated as a one dimensional distribution. This in turn helps to alleviate problems stemming from the curse of dimensionality.

Conclusion

In conclusion, Naive Bayes classifiers, despite their simplified assumptions, prove effective in various applications, showcasing notable performance in document classification and spam filtering. Their efficiency, speed, and ability to work with limited data make them valuable in real-world scenarios, compensating for their naive independence assumption.

Frequently Asked Questions on Naive Bayes Classifiers

What is Naive Bayes real example?

Naive Bayes is a simple probabilistic classifier based on Bayes' theorem. It assumes that the features of a given data point are independent of each other, which is often not the case in reality. However, despite this simplifying assumption, Naive Bayes has been shown to be surprisingly effective in a wide range of applications.

Why is it called Naive Bayes?

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

not true in reality, but it does make the algorithm much simpler to compute.

What is an example of a Bayes classifier?

A Bayes classifier is a type of classifier that uses Bayes' theorem to compute the probability of a given class for a given data point. Naive Bayes is one of the most common types of Bayes classifiers.

What is better than Naive Bayes?

There are several classifiers that are better than Naive Bayes in some situations. For example, logistic regression is often more accurate than Naive Bayes, especially when the features of a data point are correlated with each other.

Can Naive Bayes probability be greater than 1?

No, the probability of an event cannot be greater than 1. The probability of an event is a number between 0 and 1, where 0 indicates that the event is impossible and 1 indicates that the event is certain.

Are you passionate about data and looking to make one giant leap into your career? Our [Data Science Course](#) will help you change your game and, most importantly, allow students, professionals, and working adults to tide over into the data science immersion. Master state-of-the-art methodologies, powerful tools, and industry best practices, hands-on

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).


Visualization with these growing skills. Ready to Transform Your Future?
Enroll Now to Be a Data Science Expert!



184

Next Article

Passive Aggressive Classifiers



Naive Bayes Classifiers

Similar Reads

Variable importance for support vector machine and naive Bayes...

Understanding the importance of variables in a model is crucial for interpreting and improving the model's performance. Variable importance

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Complement Naive Bayes (CNB) Algorithm

Naive Bayes algorithms are a group of very popular and commonly used Machine Learning algorithms used for classification. There are many differe...

7 min read

Bernoulli Naive Bayes

Supervised learning is a subcategory of machine learning algorithms. In this way, the models are trained on labeled datasets. Under supervised learning...

5 min read

Gaussian Naive Bayes

In the vast field of machine learning, classification algorithms play a pivotal role in making sense of data. One such algorithm, Gaussian Naive Bayes,...

6 min read

Gaussian Naive Bayes using Sklearn

In the world of machine learning, Gaussian Naive Bayes is a simple yet powerful algorithm used for classification tasks. It belongs to the Naive...

8 min read

Classification of Text Documents using the approach of Naive Bayes

In natural language processing and machine learning, the Naïve Bayes approach is a potent and popular method for classifying text documents....

10 min read

Multinomial Naive Bayes

Multinomial Naive Bayes (MNB) is a very popular and efficient machine learning algorithm that is based on Bayes' theorem. It is commonly used for...

9 min read

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

9 min read

Applying Multinomial Naive Bayes to NLP Problems

Multinomial Naive Bayes (MNB) is a popular machine learning algorithm for text classification problems in Natural Language Processing (NLP). It is...

7 min read

ML | Naive Bayes Scratch Implementation using Python

A key concept in probability theory, the Bayes theorem, provides the foundation for the probabilistic classifier known as Naive Bayes. It is a simp...

8 min read

Article Tags :

[AI-ML-DS](#)[Machine Learning](#)[Machine Learning](#)

Practice Tags :

[Machine Learning](#)[Machine Learning](#)

Corporate & Communications Address:-
A-143, 9th Floor, Sovereign Corporate
Tower, Sector- 136, Noida, Uttar Pradesh
(201305) | Registered Address:- K 061,
Tower K, Gulshan Vivante Apartment,
Sector 137, Noida, Gautam Buddh
Nagar, Uttar Pradesh, 201305



We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

In Media
Contact Us
Advertise with us
GFG Corporate Solution
Placement Training Program

Offline Classes (Delhi/NCR)
DSA in JAVA/C++
Master System Design
Master CP
GeeksforGeeks Videos
Geeks Community

Languages

Python
Java
C++
PHP
GoLang
SQL
R Language
Android Tutorial

Data Science & ML

Data Science With Python
Data Science For Beginner
Machine Learning
ML Maths
Data Visualisation
Pandas
NumPy
NLP
Deep Learning

DSA

Data Structures
Algorithms
DSA for Beginners
Basic DSA Problems
DSA Roadmap
DSA Interview Questions
Competitive Programming

Web Technologies

HTML
CSS
JavaScript
TypeScript
ReactJS
NextJS
NodeJs
Bootstrap
Tailwind CSS

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Python Tutorial

Python Programming Examples
Django Tutorial
Python Projects
Python Tkinter
Web Scraping
OpenCV Tutorial
Python Interview Question

DevOps

Git
AWS
Docker
Kubernetes
Azure
GCP
DevOps Roadmap

School Subjects

Mathematics
Physics
Chemistry
Biology
Social Science
English Grammar

Computer Science

GATE CS Notes
Operating Systems
Computer Network
Database Management System
Software Engineering
Digital Logic Design
Engineering Maths

System Design

High Level Design
Low Level Design
UML Diagrams
Interview Guide
Design Patterns
OOAD
System Design Bootcamp
Interview Questions

Commerce

Accountancy
Business Studies
Economics
Management
HR Management
Finance
Income Tax

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Databases

SQL
MYSQL
PostgreSQL
PL/SQL
MongoDB

Competitive Exams

JEE Advanced
UGC NET
UPSC
SSC CGL
SBI PO
SBI Clerk
IBPS PO
IBPS Clerk

Free Online Tools

Typing Test
Image Editor
Code Formatters
Code Converters
Currency Converter
Random Number Generator
Random Password Generator

DSA/Placements

DSA - Self Paced Course
DSA in JavaScript - Self Paced Course
DSA in Python - Self Paced
C Programming Course Online - Learn C with Data Structures
Complete Interview Preparation
Master Competitive Programming
Core CS Subject for Interview Preparation
Mastering System Design: LLD to HLD
Tech Interview 101 - From DSA to System Design [LIVE]
DSA to Development [HYBRID]
Placement Preparation Crash Course [LIVE]

Machine Learning/Data Science

Preparation Corner

Company-Wise Recruitment Process
Resume Templates
Aptitude Preparation
Puzzles
Company-Wise Preparation
Companies
Colleges

More Tutorials

Software Development
Software Testing
Product Management
Project Management
Linux
Excel
All Cheat Sheets
Recent Articles

Write & Earn

Write an Article
Improve an Article
Pick Topics to Write
Share your Experiences
Internships

Development/Testing

JavaScript Full Course
React JS Course
React Native Course
Django Web Development Course
Complete Bootstrap Course
Full Stack Development - [LIVE]
JAVA Backend Development - [LIVE]
Complete Software Testing Course [LIVE]
Android Mastery with Kotlin [LIVE]

Programming Languages

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Mastering Generative AI and ChatGPT

Clouds/Devops

DevOps Engineering

AWS Solutions Architect Certification

Salesforce Certified Administrator Course

GATE

GATE CS & IT Test Series - 2025

GATE DA Test Series 2025

GATE CS & IT Course - 2025

GATE DA Course 2025

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).