

## W1D4 solutions

### Question 1:

```
package work.D3.probl1a;

import java.util.*;

public class Subsetsum {
    public static boolean[][] subsetSumDP(int[] set, int sum) {
        int n = set.length;
        boolean[][] dp = new boolean[n + 1][sum + 1];

        for (int i = 0; i <= n; i++)
            dp[i][0] = true;

        for (int i = 1; i <= n; i++) {
            for (int j = 1; j <= sum; j++) {
                if (set[i - 1] <= j)
                    dp[i][j] = dp[i - 1][j] || dp[i - 1][j - set[i - 1]];
                else
                    dp[i][j] = dp[i - 1][j];
            }
        }

        return dp;
    }

    public static void findSubsets(int[] set, int n, int sum,
                                   List<Integer> current, boolean[][] dp,
                                   List<List<Integer>> allSolutions) {

        if (sum == 0) {
            allSolutions.add(new ArrayList<>(current));
            return;
        }
        if (n == 0)
            return;

        if (dp[n - 1][sum])
            findSubsets(set, n - 1, sum, current, dp, allSolutions);

        if (sum >= set[n - 1] && dp[n - 1][sum - set[n - 1]]) {
            current.add(set[n - 1]);
            findSubsets(set, n - 1, sum - set[n - 1], current, dp, allSolutions);
            current.remove(current.size() - 1);
        }
    }

    public static void main(String[] args) {
        int[] S = {3, 4, 7, 8};
        int K = 15;

        boolean[][] dp = subsetSumDP(S, K);
        int n = S.length;

        System.out.println("(a) Subset with sum " + K + " exists: " + (dp[n][K] ?
"True" : "False"));

        if (!dp[n][K]) {
            System.out.println("No subsets found.");
            return;
        }
    }
}
```

```

List<List<Integer>> allSolutions = new ArrayList<>();
findSubsets(S, n, K, new ArrayList<>(), dp, allSolutions);

System.out.println("(b) One solution: " + allSolutions.get(0));

System.out.print("(c) All solutions: ");
for (List<Integer> subset : allSolutions)
    System.out.print(subset+", ");
}
}

```

Output:

(a) Subset with sum 15 exists: True

(b) One solution: [8, 4, 3]

(c) All solutions: [8, 4, 3], [8, 7],

Question 2:

a

Element	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
-	T	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F
3	T	F	F	T	F	F	F	F	F	F	F	F	F	F	F	F
4	T	F	F	T	T	F	F	T	F	F	F	F	F	F	F	F
7	T	F	F	T	T	F	F	T	T	F	F	T	T	F	F	F
8	T	F	F	T	T	F	F	T	T	F	F	T	T	F	T	T

$S = \{3, 4, 7, 8\}$   $K = 15$

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
3	{}			{3}												
4	{}			{3}	{4}			{3,4}								
7	{}			{3}	{4}			{7}				{4,7}				
8	{}			{3}	{4}			{7}	{8}			{4,8}				
								{7,8}				{3,8}	{4,8}			
															{3,4,8}	{7,8}

b. One solution : {3,4,8}

c. All solutions : {3,4,8} and {7,8}

Question 3. 0/1 knapsack

<b>Weight:</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>	<b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>	<b>13</b>	<b>14</b>	<b>15</b>	<b>16</b>	<b>17</b>	<b>18</b>	<b>19</b>	<b>20</b>
<b>d,2,16</b>	0	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
<b>a,5,25</b>	0	16	16	16	25	25	41	41	41	41	41	41	41	41	41	41	41	41	41	41
<b>b,6,12</b>	0	16	16	16	25	25	41	41	41	41	41	41	53	53	53	53	53	53	53	53
<b>e,7,28</b>	0	16	16	16	25	25	41	41	44	44	44	53	53	69	69	69	69	69	69	81
<b>c,8,24</b>	0	16	16	16	25	25	41	41	44	44	44	53	53	69	69	69	69	69	69	81

Maximum value = 81, Items included = {d,a,b,e}

#### Question 4 : Fractional knapsack

*The maximum allowable total weight in the knapsack is  $W_{max} = 20$ .*

Item	a	b	c	d	e
value	25	12	24	16	28
Weight	5	6	8	2	7

Now value:weight :- a:5, b:2, c:3, d:8, e:4

items	d	a	e	$\frac{3}{4}$ of c
$W_{max} - \text{weight}$	$20 - 2 = 18$	$18 - 5 = 13$	$13 - 7 = 6$	$6 - 6 (\frac{3}{4} * 8)$
value	16	25	28	18

Items selected : d,a,e, and  $\frac{3}{4}$  c

Total weight used :  $2+5+7+6 = 20$

Maximum value :  $16+25+28+18(\frac{3}{4} \text{ of } 24) = 87$

#### Question 5:

```

class Solution {
    public int climbStairs(int n) {
        if (n<=0) return 0;
        if(n==1) return 1;
        if(n==2) return 2;
        int[] arr = new int[n+1];
        arr[1] =1;
        arr[2] = 2;
        for(int i=3;i<=n;i++){
            arr[i]=arr[i-1]+arr[i-2];
        }
        return arr[n];
    }
}

```

Question 6: `class Solution {`

```
    public int rob(int[] nums) {  
        int len = nums.length;  
        if(len==1) return nums[0];  
        int[] loot= new int[len];  
        loot[0] = nums[0];  
        loot[1]=Math.max(nums[0],nums[1]);  
        for(int i=2;i<len;i++){  
            loot[i]=Math.max(loot[i-1],loot[i-2]+nums[i]);  
        }  
        return loot[len-1];  
    }  
}
```