

Big Data Technologies

Agenda

- Hadoop Multi-node cluster
- Replication

Q & A

- Does NameNode needs higher configuration?
 - Hadoop can be installed on commodity hardware.
 - If any data node fails, its replica can be accessed from other data nodes.
 - However if name node fails, we cannot start secondary namenode immediately. This makes NameNode as SPOF.
 - Here NameNode is expected to be machine with good configuration.
 - NameNode should not fail (ideally).
 - All metadata is loaded in NameNode memory and served from there to workers/clients. It needs higher memory configuration.
- Hadoop ports
 - NameNode -- 9000 -- IPC port (worker/client communication)
 - ResourceManager -- 8032 -- Submit MR job
 - NameNode -- 9870 -- HDFS Web UI
- Can we modify files uploaded in HDFS?
 - NO. HDFS is "Write once, Read multiple times" file system.
 - In Hadoop 2.x, appending to existing file is allowed (-appendToFile).

Access Hadoop cluster from Client machine

- step 1: Install java, hadoop (.bashrc) on client.
- step 2: Use generic option -fs to deal with master node (e.g. 172.18.4.102) of Hadoop cluster.

```
hadoop fs -fs hdfs://172.18.4.102:9000 -ls /user/hduser  
hadoop fs -fs hdfs://172.18.4.102:9000 -put file.txt /user/hduser
```

Generic options

- terminal> `hadoop fs -help`
 - `-fs` --> specify namenode to communicate with (hdfs).
 - `-jt` --> specify resource manager to communicate with (map reduce).
 - `-D` --> specify configuration e.g. `dfs.replication`, `dfs.blocksize`, ...
- Syntax: `hadoop fs 'generic options' -command args`

getmerge command

- Merge output of the files given by a pattern and download them on client machine.
- terminal> `hadoop fs -usage getmerge`
- terminal> `hadoop fs -getmerge /user/osboxes/file*.txt myfile.txt`
- terminal> `cat myfile.txt`

Hadoop Java API documentation

- `$HADOOP_HOME/share/doc/hadoop/api/index.html`