



CS 228 : Logic in Computer Science

Krishna. S

LTL ModelChecking

- ▶ Given transition system TS , and LTL formula φ , does $TS \models \varphi$?

LTL ModelChecking

- ▶ Given transition system TS , and LTL formula φ , does $TS \models \varphi$?
- ▶ $Tr(TS) \subseteq L(\varphi)$ iff $Tr(TS) \cap \overline{L(\varphi)} = \emptyset$

LTL ModelChecking

- ▶ Given transition system TS , and LTL formula φ , does $TS \models \varphi$?
- ▶ $Tr(TS) \subseteq L(\varphi)$ iff $Tr(TS) \cap \overline{L(\varphi)} = \emptyset$
- ▶ First construct NBA $A_{\neg\varphi}$ for $\neg\varphi$ (this is a blackbox now)

LTL ModelChecking


- ▶ Given transition system TS , and LTL formula φ , does $TS \models \varphi$?
- ▶ $Tr(TS) \subseteq L(\varphi)$ iff $Tr(TS) \cap \overline{L(\varphi)} = \emptyset$
- ▶ First construct NBA $A_{\neg\varphi}$ for $\neg\varphi$ (this is a blackbox now)
- ▶ Construct product of TS and $A_{\neg\varphi}$, obtaining a new TS, say TS'

LTL ModelChecking

- ▶ Given transition system TS , and LTL formula φ , does $TS \models \varphi$?
- ▶ $Tr(TS) \subseteq L(\varphi)$ iff $Tr(TS) \cap \overline{L(\varphi)} = \emptyset$
- ▶ First construct NBA $A_{\neg\varphi}$ for $\neg\varphi$ (this is a blackbox now)
- ▶ Construct product of TS and $A_{\neg\varphi}$, obtaining a new TS, say TS'
- ▶ Check some **very simple** property on TS' , to check $TS \models \varphi$.


An Example $TS \models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.




An Example $TS \models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.




An Example $TS \models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.




An Example : $TS \not\models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.




An Example : $TS \not\models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.



An Example : $TS \not\models \varphi$

- ▶ Let $\varphi = \Box(a \vee b)$, $\neg\varphi = \Diamond(\neg a \wedge \neg b)$
- ▶ Take TS and $A_{\neg\varphi}$, and check the intersection.




Product of TS and NBA

Given $TS = (S, Act, I, AP, L)$ and $\mathcal{A} = (Q, 2^{AP}, \delta, Q_0, G)$ NBA.
Define $TS \otimes \mathcal{A} = (S \times Q, Act, I', AP', L')$ such that

- ▶ $I' = \{(s_0, q) \mid s_0 \in I \text{ and } \exists q_0 \in Q_0, q_0 \xrightarrow{L(s_0)} q\}$
- ▶ $AP' = Q, L' : S \times Q \rightarrow 2^Q$ such that $L'((s, q)) = \{q\}$
- ▶ If $s \xrightarrow{\alpha} t$ and $q \xrightarrow{L(t)} p$, then $(s, q) \xrightarrow{\alpha} (t, p)$

Persistence Properties


Let η be a propositional logic formula over AP . A persistence property P_{pers} has the form $\Diamond\Box\eta$. How will you check a persistence property on a TS?



- ▶ For example, $TS \not\models \Diamond\Box(a \vee b)$
- ▶ For example, $TS \models \Diamond\Box(a \vee (a \rightarrow b))$

Persistence Properties

Let η be a propositional logic formula over AP . A persistence property P_{pers} has the form $\Diamond\Box\eta$. How will you check a persistence property on a TS?



- ▶ For example, $TS \not\models \Diamond\Box(a \vee b)$
- ▶ For example, $TS \models \Diamond\Box(a \vee (a \rightarrow b))$
- ▶ $TS \not\models P_{pers}$ iff there is a reachable cycle in the TS containing a state with a label which satisfies $\neg\eta$.

LTL ModelChecking

- ▶ Given TS and LTL formula φ . Does $TS \models \varphi$?
- ▶ Construct $A_{\neg\varphi}$, and let g_1, \dots, g_n be the good states in $A_{\neg\varphi}$.
- ▶ Build $TS' = TS \otimes A_{\neg\varphi}$.
- ▶ The labels of TS' are the state names of $A_{\neg\varphi}$.
- ▶ Check if $TS' \models \Diamond\Box(\neg g_1 \wedge \dots \neg g_n)$.

LTL ModelChecking

- ▶ Given TS and LTL formula φ . Does $TS \models \varphi$?
- ▶ Construct $A_{\neg\varphi}$, and let g_1, \dots, g_n be the good states in $A_{\neg\varphi}$.
- ▶ Build $TS' = TS \otimes A_{\neg\varphi}$.
- ▶ The labels of TS' are the state names of $A_{\neg\varphi}$.
- ▶ Check if $TS' \models \Diamond\Box(\neg g_1 \wedge \dots \neg g_n)$.

ModelChecking LTL in TS = Check Persistence in TS'

The following are equivalent.

- ▶ $TS \models \varphi$
- ▶ $Tr(TS) \cap L(A_{\neg\varphi}) = \emptyset$
- ▶ $TS' \models \Diamond\Box(\neg g_1 \wedge \dots \neg g_n)$.