



# **CS 228 : Logic in Computer Science**

Krishna. S

# First-Order Logic : Syntax

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges
- ▶ Atleast 5 students scored more than 90 marks in a class of 50

# First Order Logic

---

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges
- ▶ Atleast 5 students scored more than 90 marks in a class of 50
- ▶ All words starting with the letter  $a$ , ending with the letter  $b$ , have even length



# Signatures

---

- ▶ A **vocabulary** or **signature**  $\tau$  is a set consisting of
  - ▶ constants  $c_1, c_2, \dots$
  - ▶ Relation symbols  $R_1, R_2, \dots$ , each with some arity  $k$ , denoted  $R_i^k$
- ▶ We look at finite signatures
- ▶  $\tau = (E^2, F^3)$  is a finite signature with two relations,  $E$  with arity 2 and  $F$  with arity 3

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**
- ▶ An element of the infinite set  $\mathcal{V} = \{x_1, x_2, \dots\}$  of **variables**

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**
- ▶ An element of the infinite set  $\mathcal{V} = \{x_1, x_2, \dots\}$  of **variables**
- ▶ Constants and relations from  $\tau$

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**
- ▶ An element of the infinite set  $\mathcal{V} = \{x_1, x_2, \dots\}$  of **variables**
- ▶ Constants and relations from  $\tau$
- ▶ The symbol  $\rightarrow$  called **implication**

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**
- ▶ An element of the infinite set  $\mathcal{V} = \{x_1, x_2, \dots\}$  of **variables**
- ▶ Constants and relations from  $\tau$
- ▶ The symbol  $\rightarrow$  called **implication**
- ▶ The symbol  $\forall$  called the **universal quantifier**

# Symbols in First Order Logic

---

Formulae of FO, over signature  $\tau$ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol  $\perp$  called **false**
- ▶ An element of the infinite set  $\mathcal{V} = \{x_1, x_2, \dots\}$  of **variables**
- ▶ Constants and relations from  $\tau$
- ▶ The symbol  $\rightarrow$  called **implication**
- ▶ The symbol  $\forall$  called the **universal quantifier**
- ▶ The symbols ( and ) called **paranthesis**



# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

- ▶  $\perp$  is a wff

# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

- ▶  $\perp$  is a wff
- ▶ If  $t_1, t_2$  are either variables or constants in  $\tau$ , then  $t_1 = t_2$  is a wff

# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

- ▶  $\perp$  is a wff
- ▶ If  $t_1, t_2$  are either variables or constants in  $\tau$ , then  $t_1 = t_2$  is a wff
- ▶ If  $t_i$  is either a variable or a constant, for  $1 \leq i \leq k$  and  $R$  is a  $k$ -ary relation symbol in  $\tau$ , then  $R(t_1, \dots, t_k)$  is a wff

# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

- ▶  $\perp$  is a wff
- ▶ If  $t_1, t_2$  are either variables or constants in  $\tau$ , then  $t_1 = t_2$  is a wff
- ▶ If  $t_i$  is either a variable or a constant, for  $1 \leq i \leq k$  and  $R$  is a  $k$ -ary relation symbol in  $\tau$ , then  $R(t_1, \dots, t_k)$  is a wff
- ▶ If  $\varphi$  and  $\psi$  are wff, then  $\varphi \rightarrow \psi$  is a wff

# Well formed Formulae

---

A well-formed formula (wff) over a signature  $\tau$  is inductively defined as follows:

- ▶  $\perp$  is a wff
- ▶ If  $t_1, t_2$  are either variables or constants in  $\tau$ , then  $t_1 = t_2$  is a wff
- ▶ If  $t_i$  is either a variable or a constant, for  $1 \leq i \leq k$  and  $R$  is a  $k$ -ary relation symbol in  $\tau$ , then  $R(t_1, \dots, t_k)$  is a wff
- ▶ If  $\varphi$  and  $\psi$  are wff, then  $\varphi \rightarrow \psi$  is a wff
- ▶ If  $\varphi$  is a wff and  $x$  is a variable, then  $(\forall x)\varphi$  is a wff

The universal quantifier is a symbol of symbolic logic which expresses that the statements within its scope are true for everything

# Logical Abbreviations : Boolean Connectives

---

►  $\neg\varphi = \varphi \rightarrow \perp$

# Logical Abbreviations : Boolean Connectives

---

- ▶  $\neg\varphi = \varphi \rightarrow \perp$
- ▶  $\top = \neg\perp$



# Logical Abbreviations : Boolean Connectives

---

- ▶  $\neg\varphi = \varphi \rightarrow \perp$
- ▶  $\top = \neg\perp$
- ▶  $\varphi \vee \psi = \neg\varphi \rightarrow \psi$

# Logical Abbreviations : Boolean Connectives

---

- ▶  $\neg\varphi = \varphi \rightarrow \perp$
- ▶  $\top = \neg\perp$
- ▶  $\varphi \vee \psi = \neg\varphi \rightarrow \psi$
- ▶  $\varphi \wedge \psi = \neg(\neg\varphi \vee \neg\psi)$

# Logical Abbreviations : Boolean Connectives

---

- ▶  $\neg\varphi = \varphi \rightarrow \perp$
- ▶  $\top = \neg\perp$
- ▶  $\varphi \vee \psi = \neg\varphi \rightarrow \psi$
- ▶  $\varphi \wedge \psi = \neg(\neg\varphi \vee \neg\psi)$
- ▶  $\exists x.\varphi = \neg(\forall x.\neg\varphi)$

# Logical Abbreviations : Boolean Connectives

---

- ▶  $\neg\varphi = \varphi \rightarrow \perp$
- ▶  $\top = \neg\perp$
- ▶  $\varphi \vee \psi = \neg\varphi \rightarrow \psi$
- ▶  $\varphi \wedge \psi = \neg(\neg\varphi \vee \neg\psi)$
- ▶  $\exists x.\varphi = \neg(\forall x.\neg\varphi)$
- ▶ Precedence of operators :  $\neg > \wedge > \vee > \rightarrow > \forall$

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$



# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$  Symmetry

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$  Symmetry
- ▶  $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$  Symmetry
- ▶  $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$  Anti-symmetry

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$  Symmetry
- ▶  $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$  Anti-symmetry
- ▶  $\forall x \forall y \forall z (R(x, y) \rightarrow (R(y, z) \rightarrow R(x, z)))$

# An Example

---

Consider the signature  $\tau = \{R\}$  where  $R$  is a binary relation. The following are FO formulae over this signature.

- ▶  $\forall x R(x, x)$  Reflexivity
- ▶  $\forall x (R(x, x) \rightarrow \perp)$  Irreflexivity
- ▶  $\forall x \forall y (R(x, y) \rightarrow R(y, x))$  Symmetry
- ▶  $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$  Anti-symmetry
- ▶  $\forall x \forall y \forall z (R(x, y) \rightarrow (R(y, z) \rightarrow R(x, z)))$  Transitivity

# First-Order Logic : Semantics



# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a fixed element  $c_{\mathcal{A}}$  is assigned from the universe  $A$

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a fixed element  $c_{\mathcal{A}}$  is assigned from the universe  $A$
  - ▶ For each  $k$ -ary relation  $R^k$  in the signature  $\tau$ , a set of  $k$ -tuples from  $A^k$  is assigned to  $R^{\mathcal{A}}$

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a fixed element  $c_{\mathcal{A}}$  is assigned from the universe  $A$
  - ▶ For each  $k$ -ary relation  $R^k$  in the signature  $\tau$ , a set of  $k$ -tuples from  $A^k$  is assigned to  $R^{\mathcal{A}}$
  - ▶ The structure  $\mathcal{A}$  is finite if  $A$  (or  $u(\mathcal{A})$ ) is finite

## Examples of Structures

# A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.

# A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.
  - ▶ A graph structure over  $\tau$  is  $\mathcal{G} = (V, E^{\mathcal{G}})$ ,
  - ▶ The **universe**  $u(\mathcal{G})$  is the set of vertices  $V$
  - ▶ The relation  $E$  is the edge relation



# A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.
  - ▶ A graph structure over  $\tau$  is  $\mathcal{G} = (V, E^{\mathcal{G}})$ ,
  - ▶ The **universe**  $u(\mathcal{G})$  is the set of vertices  $V$
  - ▶ The relation  $E$  is the edge relation
  - ▶  $\mathcal{G} = (V = \{1, 2, 3, 4\}, E^{\mathcal{G}} = \{(1, 2), (2, 3), (3, 4), (1, 1)\})$ . We could just as well draw the graph for convenience.

# A Total Order

---

- ▶  $\tau = \{<, S\}$  with  $<$ ,  $S$  binary.

# A Total Order

---

- ▶  $\tau = \{<, S\}$  with  $<$ ,  $S$  binary.
  - ▶ A finite order structure over  $\tau$  is  $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
  - ▶ The universe  $u(\mathcal{O})$  is the finite ordered set  $O$
  - ▶  $<^{\mathcal{O}}$  is the ordering on  $O$  and  $S^{\mathcal{O}}$  is the successor on  $O$

# A Total Order

---

- ▶  $\tau = \{<, S\}$  with  $<$ ,  $S$  binary.
  - ▶ A finite order structure over  $\tau$  is  $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
  - ▶ The universe  $u(\mathcal{O})$  is the finite ordered set  $O$
  - ▶  $<^{\mathcal{O}}$  is the ordering on  $O$  and  $S^{\mathcal{O}}$  is the successor on  $O$
  - ▶  $\mathcal{O} = (O = \{1, 2, 4\}, <^{\mathcal{O}} = \{(1, 2), (1, 4), (2, 4)\}, S^{\mathcal{O}} = \{(1, 2)\})$
- ▶ Can you write a **Partial Order** as a structure, where the universe consists of all subsets of a given finite set?

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$



# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$
  - ▶  $Q_b^{\mathcal{W}}$  is the set of positions labeled  $b$  in  $W$

# A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$
  - ▶  $Q_b^{\mathcal{W}}$  is the set of positions labeled  $b$  in  $W$
  - ▶ The structure with  $u(\mathcal{W}) = \{0, 1, 2, \dots, 8\}$ ,  
 $Q_a^{\mathcal{W}} = \{0, 1, 4, 6, 8\}$ ,  $Q_b^{\mathcal{W}} = \{2, 3, 5, 7\}$ ,
  - ▶  $<^{\mathcal{W}} = \{(0, 1), (0, 2), \dots, (7, 8)\}$ ,  $S^{\mathcal{W}} = \{(0, 1), (1, 2), \dots, (7, 8)\}$   
uniquely defines the word  $W = aabbababa$ .
  - ▶ For convenience, we can just write the word instead of the structure.