

**Q1 to Q11 have only one correct answer. Choose the correct option to answer your question.**

1. Movie Recommendation systems are an example of:

i) Classification

ii) Clustering iii)

Regression

Options:

a) 2 Only

b) 1 and 2

c) 1 and 3

d) 2 and 3

**a)2 only**

2. Sentiment Analysis is an example of:

i) Regression

ii) Classification iii) Clustering iv) Reinforcement Options:

a) 1 Only

b) 1 and 2

c) 1 and 3

d) 1, 2 and 4

**d)1,2 and 4**

3. Can decision trees be used for performing clustering?

a) True

b) False

**a)True**

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points: i) Capping and flooring of variables

ii) Removal of outliers Options:

a) 1 only

b) 2 only

c) 1 and 2

d) None of the above

**a)1 only**

5. What is the minimum no. of variables/ features required to perform clustering? a) 0

**b) 1**

c) 2

d) 3

**b)1**

6. For two runs of K-Mean clustering is it expected to get same clustering results? a) Yes

b) No

**b)No**

7. Is it possible that Assignment of observations to clusters does not change between successive iterations in K-Means?

a) Yes

b) No

c) Can't say

d) None of these

a) Yes

### MACHINE LEARNING

8. Which of the following can act as possible termination conditions in K-Means?
- i) For a fixed number of iterations.
  - ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
  - iii) Centroids do not change between successive iterations.
  - iv) Terminate when RSS falls below a threshold. Options:
    - a) 1, 3 and 4
    - b) 1, 2 and 3
    - c) 1, 2 and 4
    - d) All of the above

**d) All of the above**

9. Which of the following algorithms is most sensitive to outliers?
- b) K-means clustering algorithm
  - c) K-medians clustering algorithm
  - d) K-modes clustering algorithm
  - e) K-medoids clustering algorithm

**b) K-means clustering algorithm**

10. How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):
- i) Creating different models for different cluster groups.
  - ii) Creating an input feature for cluster ids as an ordinal variable.
  - iii) Creating an input feature for cluster centroids as a continuous variable.
  - iv) Creating an input feature for cluster size as a continuous variable. Options:
    - b) 1 only
    - c) 2 only
    - d) 3 and 4
    - e) All of the above

**e) All of the above**

11. What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?
- b) Proximity function used
  - c) of data points used
  - d) of variables used
  - e) All of the above

**e) All of the above**

Q12 to Q14 are subjective answers type questions, Answers them in their own words briefly

12. Is K sensitive to outliers?

K-Means clustering algorithm is most sensitive to outliers as it uses the mean of cluster data points to find the cluster center.

13. Why is K means better?

- Relatively simple to implement
- Scales to large data sets
- Guarantees convergence
- Can warm-start the positions of centroids
- Easily adapts to new examples
- Generalize clusters of different shapes and sizes, such as elliptical clusters

#### 14. Is K means a deterministic algorithm?

The non-deterministic nature of K-Means is due to its random selection of data points as initial centroids. ... The key idea of the algorithm is to select data points which belong to dense regions and which are adequately separated in feature space as the initial centroids.

