RAJALAKSHMI ENGINEERING COLLEGE

Deveswaran S 250701146-2025-CSE D2

Started on	Tuesday, 25 August 2026, 11:59 AM
State	Finished
Completed on	Monday, 31 August 2026, 11:57 AM
Time taken	5 days 23 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    int x = *(const int *)a;
    int y = *(const int *)b;

    if (x < y)
        return -1;
    if (x > y)
        return 1;
    return 0;
}

int compareDesc(const void *a, const void *b)
{
    int x = *(const int *)a;
    int y = *(const int *)b;

    if (x < y)
        return 1;
    if (x > y)
        return -1;
    return 0;
}

int main()
{
    int n;
    scanf("%d", &n);

    long long a[n], b[n];

    for (int i = 0; i < n; i++)
        scanf("%lld", &a[i]);

    for (int i = 0; i < n; i++)
        scanf("%lld", &b[i]);

    qsort(a, n, sizeof(long long), compare);
    qsort(b, n, sizeof(long long), compareDesc);

    long long sum = 0;

    for (int i = 0; i < n; i++)
    {
        sum += a[i] * b[i];
    }

    printf("%lld", sum);

```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course