

Nano cryptocurrency C library with P2PoW/DPoW support for Embedded
1.0.0

Generated by Doxygen 1.8.13

Contents

1	Overview	1
2	Data Structure Index	3
2.1	Data Structures	3
3	File Index	5
3.1	Files	5
4	Data Structure Documentation	7
4.1	f_bitcoin_serialize_t Struct Reference	7
4.1.1	Detailed Description	7
4.1.2	Field Documentation	7
4.1.2.1	chain_code	7
4.1.2.2	child_number	8
4.1.2.3	checksum	8
4.1.2.4	finger_print	8
4.1.2.5	master_node	8
4.1.2.6	sk_or_pk_data	8
4.1.2.7	version_bytes	8
4.2	f_block_transfer_t Struct Reference	9
4.2.1	Detailed Description	9
4.2.2	Field Documentation	9
4.2.2.1	account	9
4.2.2.2	balance	9
4.2.2.3	link	10

4.2.2.4	preamble	10
4.2.2.5	prefixes	10
4.2.2.6	previous	10
4.2.2.7	representative	10
4.2.2.8	signature	11
4.2.2.9	work	11
4.3	f_file_info_err_t Struct Reference	11
4.3.1	Detailed Description	11
4.4	f_nano_crypto_wallet_t Struct Reference	11
4.4.1	Detailed Description	12
4.4.2	Field Documentation	12
4.4.2.1	description	12
4.4.2.2	iv	12
4.4.2.3	nano_hdr	12
4.4.2.4	salt	12
4.4.2.5	seed_block	13
4.4.2.6	ver	13
4.5	f_nano_encrypted_wallet_t Struct Reference	13
4.5.1	Detailed Description	13
4.5.2	Field Documentation	13
4.5.2.1	hash_sk_unencrypted	14
4.5.2.2	iv	14
4.5.2.3	reserved	14
4.5.2.4	sk_encrypted	14
4.5.2.5	sub_salt	14
4.6	f_nano_wallet_info_bdy_t Struct Reference	15
4.6.1	Detailed Description	15
4.6.2	Field Documentation	15
4.6.2.1	last_used_wallet_number	15
4.6.2.2	max_fee	15
4.6.2.3	reserved	15
4.6.2.4	wallet_prefix	16
4.6.2.5	wallet_representative	16
4.7	f_nano_wallet_info_t Struct Reference	16
4.7.1	Detailed Description	16
4.7.2	Field Documentation	16
4.7.2.1	body	17
4.7.2.2	desc	17
4.7.2.3	file_info_integrity	17
4.7.2.4	header	17
4.7.2.5	nanoseed_hash	17
4.7.2.6	version	17

5	File Documentation	19
5.1	errors.h File Reference	19
5.1.1	Macro Definition Documentation	19
5.1.1.1	CANT_OPEN_DICTIONARY_FILE	19
5.1.1.2	ERROR_GEN_TOKEN_NO RAND_NUM_GEN	20
5.1.1.3	ERROR_INVALID_NANO_ADDRESS_VERIFY_CHKSUM	20
5.1.1.4	ERROR_SUCCESS	20
5.1.1.5	INVALID_RAW_BALANCE	20
5.1.2	Enumeration Type Documentation	20
5.1.2.1	f_nano_account_or_pk_string_to_pk_util_err_t	20
5.2	errors.h	21
5.3	f_add_bn_288_le.h File Reference	21
5.3.1	Detailed Description	21
5.3.2	Typedef Documentation	21
5.3.2.1	F_ADD_288	21
5.4	f_add_bn_288_le.h	22
5.5	f_bitcoin.h File Reference	22
5.5.1	Macro Definition Documentation	23
5.5.1.1	DERIVE_XPRIV_XPUB_DYN_OUT_BASE58	23
5.5.1.2	DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV	23
5.5.1.3	DERIVE_XPRIV_XPUB_DYN_OUT_XPUB	24
5.5.1.4	F_BITCOIN_BUF_SZ	24
5.5.1.5	F_BITCOIN_P2PKH	24
5.5.1.6	F_BITCOIN_SEED_GENERATOR	24
5.5.1.7	F_BITCOIN_T2PKH	24
5.5.1.8	F_BITCOIN_WIF_MAINNET	24
5.5.1.9	F_BITCOIN_WIF_TESTNET	25
5.5.1.10	F_GET_XKEY_IS_BASE58	25
5.5.1.11	F_MAX_BASE58_LENGTH	25
5.5.1.12	F_VERSION_BYTES_IDX_LEN	25

5.5.1.13	F_XPRIV_BASE58	25
5.5.1.14	F_XPUB_BASE58	25
5.5.1.15	MAINNET_PRIVATE	26
5.5.1.16	MAINNET_PUBLIC	26
5.5.1.17	TESTNET_PRIVATE	26
5.5.1.18	TESTNET_PUBLIC	26
5.5.2	Function Documentation	26
5.5.2.1	__attribute__()	26
5.5.2.2	f_bip32_to_public_key_or_private_key()	27
5.5.2.3	f_bitcoin_valid_bip32()	27
5.5.2.4	f_check_if_invalid_btc_public_key()	27
5.5.2.5	f_decode_b58_util()	27
5.5.2.6	f_derive_xkey_dynamic()	27
5.5.2.7	f_derive_xpriv_or_xpub_dynamic()	28
5.5.2.8	f_encode_b58()	28
5.5.2.9	f_fingerprint()	28
5.5.2.10	f_generate_master_key()	28
5.5.2.11	f_get_xkey_type()	28
5.5.2.12	f_private_key_to_wif()	29
5.5.2.13	f_public_key_to_address()	29
5.5.2.14	f_uncompress_elliptic_curve()	29
5.5.2.15	f_wif_to_private_key()	29
5.5.2.16	f_xpriv2xpub()	29
5.5.2.17	load_master_private_key()	30
5.5.3	Variable Documentation	30
5.5.3.1	chain_code	30
5.5.3.2	child_number	30
5.5.3.3	chksum	30
5.5.3.4	F_VERSION_BYTES	30
5.5.3.5	finger_print	31

5.5.3.6	master_node	31
5.5.3.7	sk_or_pk_data	31
5.5.3.8	version_bytes	31
5.6	f_bitcoin.h	31
5.7	f_nano_crypto_util.h File Reference	32
5.7.1	Detailed Description	36
5.7.2	Macro Definition Documentation	36
5.7.2.1	DEST_XRB	36
5.7.2.2	F_BALANCE_RAW_128	37
5.7.2.3	F_BALANCE_RAW_STRING	37
5.7.2.4	F_BALANCE_REAL_STRING	37
5.7.2.5	F_BLOCK_TRANSFER_SIZE	37
5.7.2.6	F_BRAIN_WALLET_BAD	37
5.7.2.7	F_BRAIN_WALLET_GOOD	38
5.7.2.8	F_BRAIN_WALLET_MAYBE_GOOD	38
5.7.2.9	F_BRAIN_WALLET_NICE	38
5.7.2.10	F_BRAIN_WALLET_PERFECT	38
5.7.2.11	F_BRAIN_WALLET_POOR	39
5.7.2.12	F_BRAIN_WALLET_STILL_WEAK	39
5.7.2.13	F_BRAIN_WALLET_VERY_BAD	39
5.7.2.14	F_BRAIN_WALLET_VERY_GOOD	39
5.7.2.15	F_BRAIN_WALLET_VERY_POOR	40
5.7.2.16	F_BRAIN_WALLET_VERY_WEAK	40
5.7.2.17	F_BRAIN_WALLET_WEAK	40
5.7.2.18	F_DEFAULT_THRESHOLD	40
5.7.2.19	F_IS_SIGNATURE_RAW_HEX_STRING	41
5.7.2.20	F_MESSAGE_IS_HASH_STRING	41
5.7.2.21	F_NANO_POW_MAX_THREAD	41
5.7.2.22	F_P2POW_BLOCK_TRANSFER_SIZE	41
5.7.2.23	F_SIGNATURE_OUTPUT_NANO_PK	42

5.7.2.24	F_SIGNATURE_OUTPUT_RAW_PK	42
5.7.2.25	F_SIGNATURE_OUTPUT_STRING_PK	42
5.7.2.26	F_SIGNATURE_OUTPUT_XRB_PK	42
5.7.2.27	F_SIGNATURE_RAW	43
5.7.2.28	F_SIGNATURE_STRING	43
5.7.2.29	F_VALUE_SEND_RECEIVE_RAW_128	43
5.7.2.30	F_VALUE_SEND_RECEIVE_RAW_STRING	43
5.7.2.31	F_VALUE_SEND_RECEIVE_REAL_STRING	43
5.7.2.32	F_VALUE_TO_RECEIVE	44
5.7.2.33	F_VALUE_TO_SEND	44
5.7.2.34	F_VERIFY_SIG_ASCII_HEX	44
5.7.2.35	F_VERIFY_SIG_NANO_WALLET	44
5.7.2.36	F_VERIFY_SIG_RAW_HEX	45
5.7.2.37	MAX_STR_NANO_CHAR	45
5.7.2.38	NANO_ENCRYPTED_SEED_FILE	45
5.7.2.39	NANO_FILE_WALLETS_INFO	45
5.7.2.40	NANO_PASSWD_MAX_LEN	46
5.7.2.41	NANO_PREFIX	46
5.7.2.42	PUB_KEY_EXTENDED_MAX_LEN	46
5.7.2.43	REP_XRB	46
5.7.2.44	SENDER_XRB	46
5.7.2.45	STR_NANO_SZ	47
5.7.2.46	XRB_PREFIX	47
5.7.3	Typedef Documentation	47
5.7.3.1	F_FILE_INFO_ERR	47
5.7.3.2	F_NANO_CREATE_BLOCK_DYN_ERR	47
5.7.3.3	f_nano_err	47
5.7.3.4	F_NANO_P2POW_BLOCK_DYN_ERR	48
5.7.3.5	F_TOKEN	48
5.7.3.6	f_uint128_t	48

5.7.3.7	f_write_seed_err	48
5.7.3.8	NANO_PRIVATE_KEY	48
5.7.3.9	NANO_PRIVATE_KEY_EXTENDED	48
5.7.3.10	NANO_PUBLIC_KEY	49
5.7.3.11	NANO_PUBLIC_KEY_EXTENDED	49
5.7.3.12	NANO_SEED	49
5.7.4	Enumeration Type Documentation	49
5.7.4.1	f_file_info_err_t	49
5.7.4.2	f_nano_create_block_dyn_err_t	50
5.7.4.3	f_nano_err_t	50
5.7.4.4	f_nano_p2pow_block_dyn_err_t	51
5.7.4.5	f_write_seed_err_t	51
5.7.5	Function Documentation	52
5.7.5.1	__attribute__()	52
5.7.5.2	f_bip39_to_nano_seed()	52
5.7.5.3	f_cloud_crypto_wallet_nano_create_seed()	53
5.7.5.4	f_extract_seed_from_brainwallet()	53
5.7.5.5	f_generate_nano_seed()	54
5.7.5.6	f_generate_token()	55
5.7.5.7	f_get_dictionary_path()	55
5.7.5.8	f_get_nano_file_info()	56
5.7.5.9	f_is_valid_nano_seed_encrypted()	56
5.7.5.10	f_nano_add_sub()	57
5.7.5.11	f_nano_balance_to_str()	58
5.7.5.12	f_nano_block_to_json()	58
5.7.5.13	f_nano_get_block_hash()	59
5.7.5.14	f_nano_get_p2pow_block_hash()	59
5.7.5.15	f_nano_is_valid_block()	59
5.7.5.16	f_nano_key_to_str()	60
5.7.5.17	f_nano_p2pow_to_JSON()	60

5.7.5.18	f_nano_parse_raw_str_to_raw128_t()	61
5.7.5.19	f_nano_parse_real_str_to_raw128_t()	61
5.7.5.20	f_nano_pow()	62
5.7.5.21	f_nano_raw_to_string()	62
5.7.5.22	f_nano_seed_to_bip39()	63
5.7.5.23	f_nano_sign_block()	63
5.7.5.24	f_nano_transaction_to_JSON()	64
5.7.5.25	f_nano_valid_nano_str_value()	64
5.7.5.26	f_nano_value_compare_value()	65
5.7.5.27	f_nano_verify_nano_funds()	66
5.7.5.28	f_parse_nano_seed_and_bip39_to_JSON()	67
5.7.5.29	f_read_seed()	68
5.7.5.30	f_seed_to_nano_wallet()	68
5.7.5.31	f_set_dictionary_path()	69
5.7.5.32	f_set_nano_file_info()	69
5.7.5.33	f_sign_data()	70
5.7.5.34	f_verify_signed_block()	71
5.7.5.35	f_verify_signed_data()	71
5.7.5.36	f_verify_token()	72
5.7.5.37	f_verify_work()	72
5.7.5.38	f_write_seed()	73
5.7.5.39	from_multiplier()	73
5.7.5.40	is_nano_prefix()	74
5.7.5.41	is_null_hash()	74
5.7.5.42	nano_base_32_2_hex()	75
5.7.5.43	nano_create_block_dynamic()	75
5.7.5.44	nano_create_p2pow_block_dynamic()	75
5.7.5.45	pk_to_wallet()	76
5.7.5.46	to_multiplier()	76
5.7.5.47	valid_nano_wallet()	77

5.7.5.48	valid_raw_balance()	77
5.7.6	Variable Documentation	77
5.7.6.1	account	78
5.7.6.2	balance	78
5.7.6.3	body	78
5.7.6.4	desc	78
5.7.6.5	description	78
5.7.6.6	file_info_integrity	79
5.7.6.7	hash_sk_unencrypted	79
5.7.6.8	header	79
5.7.6.9	iv	79
5.7.6.10	last_used_wallet_number	79
5.7.6.11	link	80
5.7.6.12	max_fee	80
5.7.6.13	nano_hdr	80
5.7.6.14	nanoseed_hash	80
5.7.6.15	preamble	80
5.7.6.16	prefixes	81
5.7.6.17	previous	81
5.7.6.18	representative	81
5.7.6.19	reserved	81
5.7.6.20	salt	81
5.7.6.21	seed_block	82
5.7.6.22	signature	82
5.7.6.23	sk_encrypted	82
5.7.6.24	sub_salt	82
5.7.6.25	ver	82
5.7.6.26	version	83
5.7.6.27	wallet_prefix	83
5.7.6.28	wallet_representative	83

5.7.6.29	work	83
5.8	f_nano_crypto_util.h	84
5.9	f_util.h File Reference	90
5.9.1	Detailed Description	91
5.9.2	Macro Definition Documentation	91
5.9.2.1	ENTROPY_BEGIN	92
5.9.2.2	ENTROPY_END	92
5.9.2.3	F_ENTROPY_TYPE_EXCELENT	92
5.9.2.4	F_ENTROPY_TYPE_GOOD	92
5.9.2.5	F_ENTROPY_TYPE_NOT_ENOUGH	93
5.9.2.6	F_ENTROPY_TYPE_NOT_RECOMENDED	93
5.9.2.7	F_ENTROPY_TYPE_PARANOIC	93
5.9.2.8	F_GET_CH_MODE_ANY_KEY	93
5.9.2.9	F_GET_CH_MODE_NO_ECHO	94
5.9.2.10	F_PASS_IS_OUT_OVF	94
5.9.2.11	F_PASS_IS_TOO_LONG	94
5.9.2.12	F_PASS_IS_TOO_SHORT	94
5.9.2.13	F_PASS_MUST_HAVE_AT_LEAST_NONE	94
5.9.2.14	F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE	95
5.9.2.15	F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER	95
5.9.2.16	F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL	95
5.9.2.17	F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE	95
5.9.3	Typedef Documentation	95
5.9.3.1	fn_det	95
5.9.3.2	rnd_fn	96
5.9.4	Function Documentation	96
5.9.4.1	crc32_init()	96
5.9.4.2	f_base64_decode_dynamic()	96
5.9.4.3	f_base64url_decode()	96
5.9.4.4	f_base64url_encode()	97

5.9.4.5	<code>f_base64url_encode_dynamic()</code>	97
5.9.4.6	<code>f_convert_to_double()</code>	97
5.9.4.7	<code>f_convert_to_long_int()</code>	97
5.9.4.8	<code>f_convert_to_long_int0()</code>	98
5.9.4.9	<code>f_convert_to_long_int0x()</code>	99
5.9.4.10	<code>f_convert_to_long_int_std()</code>	99
5.9.4.11	<code>f_convert_to_unsigned_int()</code>	100
5.9.4.12	<code>f_convert_to_unsigned_int0()</code>	100
5.9.4.13	<code>f_convert_to_unsigned_int0x()</code>	101
5.9.4.14	<code>f_convert_to_unsigned_int_std()</code>	101
5.9.4.15	<code>f_ecdsa_public_key_valid()</code>	102
5.9.4.16	<code>f_ecdsa_secret_key_valid()</code>	102
5.9.4.17	<code>f_encode_to_base64()</code>	102
5.9.4.18	<code>f_encode_to_base64_dynamic()</code>	102
5.9.4.19	<code>f_gen_ecdsa_key_pair()</code>	103
5.9.4.20	<code>f_get_char_no_block()</code>	103
5.9.4.21	<code>f_get_entropy_name()</code>	103
5.9.4.22	<code>f_hmac_sha512()</code>	104
5.9.4.23	<code>f_is_random_attached()</code>	104
5.9.4.24	<code>f_pass_must_have_at_least()</code>	104
5.9.4.25	<code>f_passwd_comp_safe()</code>	105
5.9.4.26	<code>f_random()</code>	106
5.9.4.27	<code>f_random_attach()</code>	106
5.9.4.28	<code>f_random_detach()</code>	107
5.9.4.29	<code>f_reverse()</code>	107
5.9.4.30	<code>f_ripemd160()</code>	107
5.9.4.31	<code>f_sel_to_entropy_level()</code>	107
5.9.4.32	<code>f_str_to_hex()</code>	108
5.9.4.33	<code>f_uncompress_elliptic_curve()</code>	108
5.9.4.34	<code>f_url_base64_to_base64_dynamic()</code>	108
5.9.4.35	<code>f_url_encode()</code>	109
5.9.4.36	<code>f_verify_system_entropy()</code>	109
5.9.4.37	<code>get_console_passwd()</code>	110
5.10	<code>f_util.h</code>	110
5.11	<code>sodium.h</code> File Reference	113
5.12	<code>sodium.h</code>	114

Chapter 1

Overview

myNanoEmbedded is a lightweight C library of source files that integrates Nano Cryptocurrency to low complexity computational devices to send/receive digital money to anywhere in the world with fast transaction and with a small fee by delegating a Proof of Work with your choice:

- DPoW (Distributed Proof of Work)
- P2PoW (a Decentralized P2P Proof of Work)

API features

- Attaches a random function to TRNG hardware (if available)
- Self entropy verifier to ensure excellent TRNG or PRNG entropy
- Creates an encrypted by password your stream or file to store your Nano SEED
- Bip39 and Brainwallet support
- Convert raw data to Base32
- Parse SEED and Bip39 to JSON
- Sign a block using Blake2b hash with Ed25519 algorithm
- ARM-A, ARM-M, Thumb, Xtensa-LX6 and IA64 compatible
- Linux desktop, Raspberry PI, ESP32 and Olimex A20 tested platforms
- Communication over Fenix protocol bridge over TLS
- Libsodium and mbedTLS libraries with smaller resources and best performance
- Optimized for size and speed
- Non static functions (all data is cleared before processed for security)
- Fully written in C for maximum performance and portability

To add this API in your project you must first:

1. Download the latest version.

```
git clone https://github.com/devfabiosilva/myNanoEmbedded.git --recurse-submodules
```

2. Include the main library files in the client application.

```
#include "f_nano_crypto_util.h"
```

Initialize API

Function	Description
<code>f_random_attach()</code> (p. ??)	Initializes the PRNG or TRNG to be used in this API

Transmit/Receive transactions

To transmit/receive your transaction you must use `Fenix` protocol to stabilish a DPoW/P2PoW support

Examples using platforms

The repository has some examples with most common embedded and Linux systems

- Native Linux
- Raspberry Pi
- ESP32
- Olimex A20
- STM

Credits

Author

Fábio Pereira da Silva

Date

Feb 2020

Version

1.0

Copyright

License MIT [see here](#)

References:

[1] - Colin LeMahieu - *Nano: A Feeless Distributed Cryptocurrency Network* - (2015)

[2] - Z. S. Spakovszky - *7.3 A Statistical Definition of Entropy* - (2005) - NOTE: Entropy function for cryptography is implemented based on `Definition (7.12)` of this amazing topic

[3] - Kaique Anarkrypto - *Delegated Proof of Work* - (2019)

[4] - `docs.nano.org` - *Node RPCs documentation*

Chapter 2

Data Structure Index

2.1 Data Structures

Here are the data structures with brief descriptions:

f_bitcoin_serialize_t	7
f_block_transfer_t	
Nano signed block raw data defined in this reference	9
f_file_info_err_t	
Error enumerator for info file functions	11
f_nano_crypto_wallet_t	
struct of the block of encrypted file to store Nano SEED	11
f_nano_encrypted_wallet_t	
struct of the block of encrypted file to store Nano SEED	13
f_nano_wallet_info_bdy_t	
struct of the body block of the info file	15
f_nano_wallet_info_t	
struct of the body block of the info file	16

Chapter 3

File Index

3.1 Files

Here is a list of all files with brief descriptions:

errors.h	19
f_add_bn_288_le.h	
Low level implementation of Nano Cryptocurrency C library	21
f_bitcoin.h	22
f_nano_crypto_util.h	
This API Integrates Nano Cryptocurrency to low computational devices	32
f_util.h	
This ABI is a utility for myNanoEmbedded library and sub routines are implemented here	90
sodium.h	113

Chapter 4

Data Structure Documentation

4.1 `f_bitcoin_serialize_t` Struct Reference

```
#include <f_bitcoin.h>
```

Data Fields

- `uint8_t version_bytes` [4]
- `uint8_t master_node`
- `uint8_t finger_print` [4]
- `uint8_t child_number` [4]
- `uint8_t chain_code` [32]
- `uint8_t sk_or_pk_data` [33]
- `uint8_t chksum` [4]

4.1.1 Detailed Description

Definition at line **24** of file **f_bitcoin.h**.

4.1.2 Field Documentation

4.1.2.1 `chain_code`

```
uint8_t chain_code[32]
```

Definition at line **29** of file **f_bitcoin.h**.

4.1.2.2 child_number

```
uint8_t child_number[4]
```

Definition at line **28** of file **f_bitcoin.h**.

4.1.2.3 chksum

```
uint8_t chksum[4]
```

Definition at line **31** of file **f_bitcoin.h**.

4.1.2.4 finger_print

```
uint8_t finger_print[4]
```

Definition at line **27** of file **f_bitcoin.h**.

4.1.2.5 master_node

```
uint8_t master_node
```

Definition at line **26** of file **f_bitcoin.h**.

4.1.2.6 sk_or_pk_data

```
uint8_t sk_or_pk_data[33]
```

Definition at line **30** of file **f_bitcoin.h**.

4.1.2.7 version_bytes

```
uint8_t version_bytes[4]
```

Definition at line **25** of file **f_bitcoin.h**.

The documentation for this struct was generated from the following file:

- **f_bitcoin.h**

4.2 `f_block_transfer_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t` **preamble** [32]
- `uint8_t` **account** [32]
- `uint8_t` **previous** [32]
- `uint8_t` **representative** [32]
- `f_uint128_t` **balance**
- `uint8_t` **link** [32]
- `uint8_t` **signature** [64]
- `uint8_t` **prefixes**
- `uint64_t` **work**

4.2.1 Detailed Description

Nano signed block raw data defined in this [reference](#)

Definition at line **266** of file **f_nano_crypto_util.h**.

4.2.2 Field Documentation

4.2.2.1 `account`

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **270** of file **f_nano_crypto_util.h**.

4.2.2.2 `balance`

```
f_uint128_t balance
```

Big number 128 bit raw balance.

See also

f_uint128_t (p. ??)

Definition at line **278** of file **f_nano_crypto_util.h**.

4.2.2.3 link

```
uint8_t link[32]
```

link or destination account

Definition at line **280** of file **f_nano_crypto_util.h**.

4.2.2.4 preamble

```
uint8_t preamble[32]
```

Block preamble.

Definition at line **268** of file **f_nano_crypto_util.h**.

4.2.2.5 prefixes

```
uint8_t prefixes
```

Internal use for this API.

Definition at line **284** of file **f_nano_crypto_util.h**.

4.2.2.6 previous

```
uint8_t previous[32]
```

Previous block.

Definition at line **272** of file **f_nano_crypto_util.h**.

4.2.2.7 representative

```
uint8_t representative[32]
```

Representative for current account.

Definition at line **274** of file **f_nano_crypto_util.h**.

4.2.2.8 signature

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **282** of file **f_nano_crypto_util.h**.

4.2.2.9 work

```
uint64_t work
```

Internal use for this API.

Definition at line **286** of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.3 f_file_info_err_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

4.3.1 Detailed Description

Error enumerator for info file functions.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.4 f_nano_crypto_wallet_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- uint8_t **nano_hdr** [sizeof(NANO_WALLET_MAGIC)]
- uint32_t **ver**
- uint8_t **description** [F_DESC_SZ]
- uint8_t **salt** [32]
- uint8_t **iv** [16]
- F_ENCRYPTED_BLOCK **seed_block**

4.4.1 Detailed Description

struct of the block of encrypted file to store Nano SEED

Definition at line **400** of file **f_nano_crypto_util.h**.

4.4.2 Field Documentation

4.4.2.1 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **406** of file **f_nano_crypto_util.h**.

4.4.2.2 iv

```
uint8_t iv[16]
```

Initial vector of first encryption layer.

Definition at line **410** of file **f_nano_crypto_util.h**.

4.4.2.3 nano_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **402** of file **f_nano_crypto_util.h**.

4.4.2.4 salt

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line **408** of file **f_nano_crypto_util.h**.

4.4.2.5 `seed_block`

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line **412** of file **`f_nano_crypto_util.h`**.

4.4.2.6 `ver`

```
uint32_t ver
```

Version of the file.

Definition at line **404** of file **`f_nano_crypto_util.h`**.

The documentation for this struct was generated from the following file:

- **`f_nano_crypto_util.h`**

4.5 `f_nano_encrypted_wallet_t` Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t` **`sub_salt`** [32]
- `uint8_t` **`iv`** [16]
- `uint8_t` **`reserved`** [16]
- `uint8_t` **`hash_sk_unencrypted`** [32]
- `uint8_t` **`sk_encrypted`** [32]

4.5.1 Detailed Description

struct of the block of encrypted file to store Nano SEED

Definition at line **372** of file **`f_nano_crypto_util.h`**.

4.5.2 Field Documentation

4.5.2.1 hash_sk_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **380** of file **f_nano_crypto_util.h**.

4.5.2.2 iv

```
uint8_t iv[16]
```

Initial sub vector.

Definition at line **376** of file **f_nano_crypto_util.h**.

4.5.2.3 reserved

```
uint8_t reserved[16]
```

Reserved (not used)

Definition at line **378** of file **f_nano_crypto_util.h**.

4.5.2.4 sk_encrypted

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **382** of file **f_nano_crypto_util.h**.

4.5.2.5 sub_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line **374** of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.6 f_nano_wallet_info_bdy_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- `uint8_t` **wallet_prefix**
- `uint32_t` **last_used_wallet_number**
- `char` **wallet_representative** [MAX_STR_NANO_CHAR]
- `char` **max_fee** [F_RAW_STR_MAX_SZ]
- `uint8_t` **reserved** [44]

4.6.1 Detailed Description

struct of the body block of the info file

Definition at line 484 of file `f_nano_crypto_util.h`.

4.6.2 Field Documentation

4.6.2.1 last_used_wallet_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line 488 of file `f_nano_crypto_util.h`.

4.6.2.2 max_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line 492 of file `f_nano_crypto_util.h`.

4.6.2.3 reserved

```
uint8_t reserved[44]
```

Reserved.

Definition at line 494 of file `f_nano_crypto_util.h`.

4.6.2.4 wallet_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line **486** of file **f_nano_crypto_util.h**.

4.6.2.5 wallet_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line **490** of file **f_nano_crypto_util.h**.

The documentation for this struct was generated from the following file:

- **f_nano_crypto_util.h**

4.7 f_nano_wallet_info_t Struct Reference

```
#include <f_nano_crypto_util.h>
```

Data Fields

- uint8_t **header** [sizeof(F_NANO_WALLET_INFO_MAGIC)]
- uint16_t **version**
- char **desc** [F_NANO_DESC_SZ]
- uint8_t **nanoseed_hash** [32]
- uint8_t **file_info_integrity** [32]
- F_NANO_WALLET_INFO_BODY **body**

4.7.1 Detailed Description

struct of the body block of the info file

Definition at line **516** of file **f_nano_crypto_util.h**.

4.7.2 Field Documentation

4.7.2.1 `body`

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **528** of file `f_nano_crypto_util.h`.

4.7.2.2 `desc`

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **522** of file `f_nano_crypto_util.h`.

4.7.2.3 `file_info_integrity`

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **526** of file `f_nano_crypto_util.h`.

4.7.2.4 `header`

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **518** of file `f_nano_crypto_util.h`.

4.7.2.5 `nanoseed_hash`

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **524** of file `f_nano_crypto_util.h`.

4.7.2.6 `version`

```
uint16_t version
```

Version.

Definition at line **520** of file `f_nano_crypto_util.h`.

The documentation for this struct was generated from the following file:

- `f_nano_crypto_util.h`

Chapter 5

File Documentation

5.1 errors.h File Reference

Macros

- `#define ERROR_SUCCESS 0`
- `#define ERROR_GEN_TOKEN_NO_RAND_NUM_GEN 3858`
- `#define ERROR_INVALID_NANO_ADDRESS_VERIFY_CHKSUM 23`
- `#define INVALID_RAW_BALANCE 8893`
- `#define CANT_OPEN_DICTIONARY_FILE 2580`

Enumerations

- `enum f_nano_account_or_pk_string_to_pk_util_err_t {
 NANO_ACCOUNT_TO_PK_OK = 0, NANO_ACCOUNT_TO_PK_OVFL = 8100, NANO_ACCOUNT_TO_↵
 _PK_NULL_STRING, NANO_ACCOUNT_WRONG_PK_STR_SZ,
 NANO_ACCOUNT_WRONG_HEX_STRING, NANO_ACCOUNT_BASE32_CONVERT_ERROR, NAN↵
 O_ACCOUNT_TO_PK_WRONG_ACCOUNT_LEN }`

5.1.1 Macro Definition Documentation

5.1.1.1 CANT_OPEN_DICTIONARY_FILE

```
#define CANT_OPEN_DICTIONARY_FILE 2580
```

Definition at line **23** of file **errors.h**.

5.1.1.2 ERROR_GEN_TOKEN_NO_RAND_NUM_GEN

```
#define ERROR_GEN_TOKEN_NO_RAND_NUM_GEN 3858
```

Definition at line 4 of file **errors.h**.

5.1.1.3 ERROR_INVALID_NANO_ADDRESS_VERIFY_CHKSUM

```
#define ERROR_INVALID_NANO_ADDRESS_VERIFY_CHKSUM 23
```

Definition at line 7 of file **errors.h**.

5.1.1.4 ERROR_SUCCESS

```
#define ERROR_SUCCESS 0
```

Definition at line 3 of file **errors.h**.

5.1.1.5 INVALID_RAW_BALANCE

```
#define INVALID_RAW_BALANCE 8893
```

Definition at line 20 of file **errors.h**.

5.1.2 Enumeration Type Documentation

5.1.2.1 f_nano_account_or_pk_string_to_pk_util_err_t

```
enum f_nano_account_or_pk_string_to_pk_util_err_t
```

Enumerator

NANO_ACCOUNT_TO_PK_OK	
NANO_ACCOUNT_TO_PK_OVFL	
NANO_ACCOUNT_TO_PK_NULL_STRING	
NANO_ACCOUNT_WRONG_PK_STR_SZ	
NANO_ACCOUNT_WRONG_HEX_STRING	
NANO_ACCOUNT_BASE32_CONVERT_ERROR	
NANO_ACCOUNT_TO_PK_WRONG_ACCOUNT_LEN	

Definition at line 9 of file **errors.h**.

5.2 errors.h

```

00001 //seg abr 26 20:56:00 -03 2021
00002
00003 #define ERROR_SUCCESS 0
00004 #define ERROR_GEN_TOKEN_NO RAND_NUM_GEN 3858
00005
00006 //nano_base_32_2_hex
00007 #define ERROR_INVALID_NANO_ADDRESS_VERIFY_CHKSUM 23
00008
00009 enum f_nano_account_or_pk_string_to_pk_util_err_t {
00010     NANO_ACCOUNT_TO_PK_OK=0,
00011     NANO_ACCOUNT_TO_PK_OVFL=8100,
00012     NANO_ACCOUNT_TO_PK_NULL_STRING,
00013     NANO_ACCOUNT_WRONG_PK_STR_SZ,
00014     NANO_ACCOUNT_WRONG_HEX_STRING,
00015     NANO_ACCOUNT_BASE32_CONVERT_ERROR,
00016     NANO_ACCOUNT_TO_PK_WRONG_ACCOUNT_LEN
00017 };
00018
00019 //valid_raw_balance
00020 #define INVALID_RAW_BALANCE 8893
00021
00022 //f_nano_seed_to_bip39
00023 #define CANT_OPEN_DICTIONARY_FILE 2580
00024

```

5.3 f_add_bn_288_le.h File Reference

```
#include <stdint.h>
```

Typedefs

- typedef uint8_t **F_ADD_288**[36]

5.3.1 Detailed Description

Low level implementation of Nano Cryptocurrency C library.

Definition in file **f_add_bn_288_le.h**.

5.3.2 Typedef Documentation

5.3.2.1 F_ADD_288

F_ADD_288

288 bit big number

Definition at line 19 of file **f_add_bn_288_le.h**.

5.4 f_add_bn_288_le.h

```

00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00008 #include <stdint.h>
00009
00019 typedef uint8_t F_ADD_288[36];
00020
00021
00022 #ifndef F_DOC_SKIP
00023
00033 void f_add_bn_288_le(F_ADD_288, F_ADD_288, F_ADD_288, int *, int);
00034 void f_sl_elv_add_le(F_ADD_288, int);
00035
00036 #endif
00037

```

5.5 f_bitcoin.h File Reference

```
#include <mbedtls/bignum.h>
```

Data Structures

- struct **f_bitcoin_serialize_t**

Macros

- #define **F_BITCOIN_WIF_MAINNET** (uint8_t)0x80
- #define **F_BITCOIN_WIF_TESTNET** (uint8_t)0xEF
- #define **F_BITCOIN_P2PKH** (uint8_t)0x00
- #define **F_BITCOIN_T2PKH** (uint8_t)0x6F
- #define **F_BITCOIN_BUF_SZ** (size_t)512
- #define **F_MAX_BASE58_LENGTH** (size_t)112
- #define **F_BITCOIN_SEED_GENERATOR** "Bitcoin seed"
- #define **MAINNET_PUBLIC** (size_t)0
- #define **MAINNET_PRIVATE** (size_t)1
- #define **TESTNET_PUBLIC** (size_t)2
- #define **TESTNET_PRIVATE** (size_t)3
- #define **F_VERSION_BYTES_IDX_LEN** (size_t)(sizeof(**F_VERSION_BYTES**)/(4*sizeof(uint8_t)))
- #define **F_XPRIV_BASE58** (int)1
- #define **F_XPUB_BASE58** (int)2
- #define **DERIVE_XPRIV_XPUB_DYN_OUT_BASE58** (int)8
- #define **DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV** (int)16
- #define **DERIVE_XPRIV_XPUB_DYN_OUT_XPUB** (int)32
- #define **F_GET_XKEY_IS_BASE58** (int)0x00008000

Functions

- struct **f_bitcoin_serialize_t** **__attribute__((packed))** BITCOIN_SERIALIZE
- int **f_decode_b58_util** (uint8_t *, size_t, size_t *, const char *)
- int **f_encode_b58** (char *, size_t, size_t *, uint8_t *, size_t)
- int **f_private_key_to_wif** (char *, size_t, size_t *, uint8_t, uint8_t *)
- int **f_wif_to_private_key** (uint8_t *, unsigned char *, const char *)
- int **f_generate_master_key** (BITCOIN_SERIALIZE *, size_t, uint32_t)
- int **f_bitcoin_valid_bip32** (BITCOIN_SERIALIZE *, int *, void *, int)
- int **f_uncompress_elliptic_curve** (uint8_t *, size_t, size_t *, mbedtls_ecp_group_id, uint8_t *, size_t)
- int **f_bip32_to_public_key_or_private_key** (uint8_t *, int *, uint8_t *, uint8_t *, uint8_t *, uint32_t, const void *, int)
- int **f_public_key_to_address** (char *, size_t, size_t *, uint8_t *, uint8_t)
- int **f_xpriv2xpub** (void *, size_t, size_t *, void *, int)
- int **load_master_private_key** (void *, unsigned char *, size_t)
- int **f_fingerprint** (uint8_t *, uint8_t *, uint8_t *)
- int **f_get_xkey_type** (void *)
- int **f_derive_xpriv_or_xpub_dynamic** (void **, uint8_t *, uint32_t *, void *, uint32_t, int)
- int **f_derive_xkey_dynamic** (void **, void *, const char *, int)
- int **f_check_if_invalid_btc_public_key** (uint8_t *)

Variables

- static const uint8_t **F_VERSION_BYTES** [][4]
- uint8_t **version_bytes** [4]
- uint8_t **master_node**
- uint8_t **finger_print** [4]
- uint8_t **child_number** [4]
- uint8_t **chain_code** [32]
- uint8_t **sk_or_pk_data** [33]
- uint8_t **chksum** [4]

5.5.1 Macro Definition Documentation

5.5.1.1 DERIVE_XPRIV_XPUB_DYN_OUT_BASE58

```
#define DERIVE_XPRIV_XPUB_DYN_OUT_BASE58 (int)8
```

Definition at line **58** of file **f_bitcoin.h**.

5.5.1.2 DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV

```
#define DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV (int)16
```

Definition at line **59** of file **f_bitcoin.h**.

5.5.1.3 DERIVE_XPRIV_XPUB_DYN_OUT_XPUB

```
#define DERIVE_XPRIV_XPUB_DYN_OUT_XPUB (int) 32
```

Definition at line **60** of file **f_bitcoin.h**.

5.5.1.4 F_BITCOIN_BUF_SZ

```
#define F_BITCOIN_BUF_SZ (size_t) 512
```

Definition at line **7** of file **f_bitcoin.h**.

5.5.1.5 F_BITCOIN_P2PKH

```
#define F_BITCOIN_P2PKH (uint8_t) 0x00
```

Definition at line **5** of file **f_bitcoin.h**.

5.5.1.6 F_BITCOIN_SEED_GENERATOR

```
#define F_BITCOIN_SEED_GENERATOR "Bitcoin seed"
```

Definition at line **9** of file **f_bitcoin.h**.

5.5.1.7 F_BITCOIN_T2PKH

```
#define F_BITCOIN_T2PKH (uint8_t) 0x6F
```

Definition at line **6** of file **f_bitcoin.h**.

5.5.1.8 F_BITCOIN_WIF_MAINNET

```
#define F_BITCOIN_WIF_MAINNET (uint8_t) 0x80
```

Definition at line **3** of file **f_bitcoin.h**.

5.5.1.9 **F_BITCOIN_WIF_TESTNET**

```
#define F_BITCOIN_WIF_TESTNET (uint8_t)0xEF
```

Definition at line 4 of file **f_bitcoin.h**.

5.5.1.10 **F_GET_XKEY_IS_BASE58**

```
#define F_GET_XKEY_IS_BASE58 (int)0x00008000
```

Definition at line 62 of file **f_bitcoin.h**.

5.5.1.11 **F_MAX_BASE58_LENGTH**

```
#define F_MAX_BASE58_LENGTH (size_t)112
```

Definition at line 8 of file **f_bitcoin.h**.

5.5.1.12 **F_VERSION_BYTES_IDX_LEN**

```
#define F_VERSION_BYTES_IDX_LEN (size_t)(sizeof( F_VERSION_BYTES)/(4*sizeof(uint8_t)))
```

Definition at line 22 of file **f_bitcoin.h**.

5.5.1.13 **F_XPRIV_BASE58**

```
#define F_XPRIV_BASE58 (int)1
```

Definition at line 52 of file **f_bitcoin.h**.

5.5.1.14 **F_XPUB_BASE58**

```
#define F_XPUB_BASE58 (int)2
```

Definition at line 53 of file **f_bitcoin.h**.

5.5.1.15 MAINNET_PRIVATE

```
#define MAINNET_PRIVATE (size_t)1
```

Definition at line 12 of file **f_bitcoin.h**.

5.5.1.16 MAINNET_PUBLIC

```
#define MAINNET_PUBLIC (size_t)0
```

Definition at line 11 of file **f_bitcoin.h**.

5.5.1.17 TESTNET_PRIVATE

```
#define TESTNET_PRIVATE (size_t)3
```

Definition at line 14 of file **f_bitcoin.h**.

5.5.1.18 TESTNET_PUBLIC

```
#define TESTNET_PUBLIC (size_t)2
```

Definition at line 13 of file **f_bitcoin.h**.

5.5.2 Function Documentation

5.5.2.1 __attribute__()

```
struct f_nano_wallet_info_t __attribute__ (  
    (packed) )
```


5.5.2.2 f_bip32_to_public_key_or_private_key()

```
int f_bip32_to_public_key_or_private_key (
    uint8_t * ,
    int * ,
    uint8_t * ,
    uint8_t * ,
    uint8_t * ,
    uint32_t ,
    const void * ,
    int )
```

5.5.2.3 f_bitcoin_valid_bip32()

```
int f_bitcoin_valid_bip32 (
    BITCOIN_SERIALIZE * ,
    int * ,
    void * ,
    int )
```

5.5.2.4 f_check_if_invalid_btc_public_key()

```
int f_check_if_invalid_btc_public_key (
    uint8_t * )
```

5.5.2.5 f_decode_b58_util()

```
int f_decode_b58_util (
    uint8_t * ,
    size_t ,
    size_t * ,
    const char * )
```

5.5.2.6 f_derive_xkey_dynamic()

```
int f_derive_xkey_dynamic (
    void ** ,
    void * ,
    const char * ,
    int )
```

5.5.2.7 f_derive_xpriv_or_xpub_dynamic()

```
int f_derive_xpriv_or_xpub_dynamic (
    void ** ,
    uint8_t * ,
    uint32_t * ,
    void * ,
    uint32_t ,
    int )
```

5.5.2.8 f_encode_b58()

```
int f_encode_b58 (
    char * ,
    size_t ,
    size_t * ,
    uint8_t * ,
    size_t )
```

5.5.2.9 f_fingerprint()

```
int f_fingerprint (
    uint8_t * ,
    uint8_t * ,
    uint8_t * )
```

5.5.2.10 f_generate_master_key()

```
int f_generate_master_key (
    BITCOIN_SERIALIZE * ,
    size_t ,
    uint32_t )
```

5.5.2.11 f_get_xkey_type()

```
int f_get_xkey_type (
    void * )
```

5.5.2.12 f_private_key_to_wif()

```
int f_private_key_to_wif (
    char * ,
    size_t ,
    size_t * ,
    uint8_t ,
    uint8_t * )
```

5.5.2.13 f_public_key_to_address()

```
int f_public_key_to_address (
    char * ,
    size_t ,
    size_t * ,
    uint8_t * ,
    uint8_t )
```

5.5.2.14 f_uncompress_elliptic_curve()

```
int f_uncompress_elliptic_curve (
    uint8_t * ,
    size_t ,
    size_t * ,
    mbedtls_ecp_group_id ,
    uint8_t * ,
    size_t )
```

5.5.2.15 f_wif_to_private_key()

```
int f_wif_to_private_key (
    uint8_t * ,
    unsigned char * ,
    const char * )
```

5.5.2.16 f_xpriv2xpub()

```
int f_xpriv2xpub (
    void * ,
    size_t ,
    size_t * ,
    void * ,
    int )
```

5.5.2.17 load_master_private_key()

```
int load_master_private_key (
    void * ,
    unsigned char * ,
    size_t )
```

5.5.3 Variable Documentation

5.5.3.1 chain_code

```
uint8_t chain_code[32]
```

Definition at line 21 of file **f_bitcoin.h**.

5.5.3.2 child_number

```
uint8_t child_number[4]
```

Definition at line 20 of file **f_bitcoin.h**.

5.5.3.3 chksum

```
uint8_t chksum[4]
```

Definition at line 23 of file **f_bitcoin.h**.

5.5.3.4 F_VERSION_BYTES

```
const uint8_t F_VERSION_BYTES[][4] [static]
```

Initial value:

```
= {
    {0x04, 0x88, 0xB2, 0x1E},
    {0x04, 0x88, 0xAD, 0xE4},
    {0x04, 0x35, 0x87, 0xCF},
    {0x04, 0x35, 0x83, 0x94}
}
```

Definition at line 16 of file **f_bitcoin.h**.

5.5.3.5 finger_print

```
uint8_t finger_print[4]
```

Definition at line 19 of file **f_bitcoin.h**.

5.5.3.6 master_node

```
uint8_t master_node
```

Definition at line 18 of file **f_bitcoin.h**.

5.5.3.7 sk_or_pk_data

```
uint8_t sk_or_pk_data[33]
```

Definition at line 22 of file **f_bitcoin.h**.

5.5.3.8 version_bytes

```
uint8_t version_bytes[4]
```

Definition at line 17 of file **f_bitcoin.h**.

5.6 f_bitcoin.h

```
00001 #include <mbedtls/bignum.h>
00002
00003 #define F_BITCOIN_WIF_MAINNET (uint8_t)0x80
00004 #define F_BITCOIN_WIF_TESTNET (uint8_t)0xEF
00005 #define F_BITCOIN_P2PKH (uint8_t)0x00 // P2PKH address
00006 #define F_BITCOIN_T2PKH (uint8_t)0x6F // Testnet Address
00007 #define F_BITCOIN_BUF_SZ (size_t)512
00008 #define F_MAX_BASE58_LENGTH (size_t)112//52 // including null char
00009 #define F_BITCOIN_SEED_GENERATOR "Bitcoin seed"
00010
00011 #define MAINNET_PUBLIC (size_t)0
00012 #define MAINNET_PRIVATE (size_t)1
00013 #define TESTNET_PUBLIC (size_t)2
00014 #define TESTNET_PRIVATE (size_t)3
00015
00016 static const uint8_t F_VERSION_BYTES[][4] = {
00017     {0x04, 0x88, 0xB2, 0x1E}, //mainnet public
00018     {0x04, 0x88, 0xAD, 0xE4}, //mainnet private
00019     {0x04, 0x35, 0x87, 0xCF}, //testnet public
00020     {0x04, 0x35, 0x83, 0x94} // testnet private
00021 };
00022 #define F_VERSION_BYTES_IDX_LEN (size_t)(sizeof(F_VERSION_BYTES)/(4*sizeof(uint8_t)))
00023
00024 typedef struct f_bitcoin_serialize_t {
00025     uint8_t version_bytes[4];
00026     uint8_t master_node;
00027     uint8_t finger_print[4];
```

```

00028     uint8_t child_number[4];
00029     uint8_t chain_code[32];
00030     uint8_t sk_or_pk_data[33];
00031     uint8_t chksum[4];
00032 } __attribute__((packed)) BITCOIN_SERIALIZE;
00033
00034 int f_decode_b58_util(uint8_t *, size_t, size_t *, const char *);
00035 int f_encode_b58(char *, size_t, size_t *, uint8_t *, size_t);
00036 int f_private_key_to_wif(char *, size_t, size_t *, uint8_t *, uint8_t *);
00037 int f_wif_to_private_key(uint8_t *, unsigned char *, const char *);
00038 int f_generate_master_key(BITCOIN_SERIALIZE *, size_t, uint32_t);
00039 int f_bitcoin_valid_bip32(BITCOIN_SERIALIZE *, int *, void *, int);
00040 int f_uncompress_elliptic_curve(uint8_t *, size_t, size_t *, mbedtls_ecp_group_id, uint8_t *, size_t);
00041 int f_bip32_to_public_key_or_private_key(
00042     uint8_t *,
00043     int *,
00044     uint8_t *,
00045     uint8_t *,
00046     uint8_t *,
00047     uint32_t,
00048     const void *,
00049     int
00050 );
00051 int f_public_key_to_address(char *, size_t, size_t *, uint8_t *, uint8_t);
00052 #define F_XPRIV_BASE58 (int)1
00053 #define F_XPUB_BASE58 (int)2
00054 int f_xpriv2xpub(void *, size_t, size_t *, void *, int);
00055 int load_master_private_key(void *, unsigned char *, size_t);
00056 int f_fingerprint(uint8_t *, uint8_t *, uint8_t *);
00057
00058 #define DERIVE_XPRIV_XPUB_DYN_OUT_BASE58 (int)8
00059 #define DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV (int)16
00060 #define DERIVE_XPRIV_XPUB_DYN_OUT_XPUB (int)32
00061
00062 #define F_GET_XKEY_IS_BASE58 (int)0x00008000
00063 int f_get_xkey_type(void *);
00064 int f_derive_xpriv_or_xpub_dynamic(void **, uint8_t *, uint32_t *, void *, uint32_t, int);
00065 int f_derive_xkey_dynamic(void **, void *, const char *, int);
00066 int f_check_if_invalid_btc_public_key(uint8_t *);
00067
00068

```

5.7 f_nano_crypto_util.h File Reference

```

#include <errors.h>
#include <stdint.h>
#include <f_util.h>
#include <f_bitcoin.h>

```

Data Structures

- struct **f_block_transfer_t**
- struct **f_nano_encrypted_wallet_t**
- struct **f_nano_crypto_wallet_t**
- struct **f_nano_wallet_info_bdy_t**
- struct **f_nano_wallet_info_t**

Macros

- #define **F_NANO_POW_MAX_THREAD** (size_t)10
- #define **MAX_STR_NANO_CHAR** (size_t)70
- #define **PUB_KEY_EXTENDED_MAX_LEN** (size_t)40
- #define **NANO_PREFIX** "nano_"
- #define **XRB_PREFIX** "xrb_"
- #define **NANO_ENCRYPTED_SEED_FILE** "/spiffs/secure/nano.nse"

- #define **NANO_PASSWD_MAX_LEN** (size_t)80
- #define **STR_NANO_SZ** (size_t)66
- #define **NANO_FILE_WALLETS_INFO** "/spiffs/secure/walletsinfo.i"
- #define **F_BLOCK_TRANSFER_SIZE** (size_t)sizeof(F_BLOCK_TRANSFER)
- #define **F_P2POW_BLOCK_TRANSFER_SIZE** 2* F_BLOCK_TRANSFER_SIZE
- #define **REP_XRB** (uint8_t)0x4
- #define **SENDER_XRB** (uint8_t)0x02
- #define **DEST_XRB** (uint8_t)0x01
- #define **F_BRAIN_WALLET_VERY_POOR** (uint32_t)0
- #define **F_BRAIN_WALLET_POOR** (uint32_t)1
- #define **F_BRAIN_WALLET_VERY_BAD** (uint32_t)2
- #define **F_BRAIN_WALLET_BAD** (uint32_t)3
- #define **F_BRAIN_WALLET_VERY_WEAK** (uint32_t)4
- #define **F_BRAIN_WALLET_WEAK** (uint32_t)5
- #define **F_BRAIN_WALLET_STILL_WEAK** (uint32_t)6
- #define **F_BRAIN_WALLET_MAYBE_GOOD** (uint32_t)7
- #define **F_BRAIN_WALLET_GOOD** (uint32_t)8
- #define **F_BRAIN_WALLET_VERY_GOOD** (uint32_t)9
- #define **F_BRAIN_WALLET_NICE** (uint32_t)10
- #define **F_BRAIN_WALLET_PERFECT** (uint32_t)11
- #define **F_SIGNATURE_RAW** (uint32_t)1
- #define **F_SIGNATURE_STRING** (uint32_t)2
- #define **F_SIGNATURE_OUTPUT_RAW_PK** (uint32_t)4
- #define **F_SIGNATURE_OUTPUT_STRING_PK** (uint32_t)8
- #define **F_SIGNATURE_OUTPUT_XRB_PK** (uint32_t)16
- #define **F_SIGNATURE_OUTPUT_NANO_PK** (uint32_t)32
- #define **F_IS_SIGNATURE_RAW_HEX_STRING** (uint32_t)64
- #define **F_MESSAGE_IS_HASH_STRING** (uint32_t)128
- #define **F_DEFAULT_THRESHOLD** (uint64_t) 0xffffffff00000000
- #define **F_VERIFY_SIG_NANO_WALLET** (uint32_t)1
- #define **F_VERIFY_SIG_RAW_HEX** (uint32_t)2
- #define **F_VERIFY_SIG_ASCII_HEX** (uint32_t)4
- #define **F_BALANCE_RAW_128** F_NANO_A_RAW_128
- #define **F_BALANCE_REAL_STRING** F_NANO_A_REAL_STRING
- #define **F_BALANCE_RAW_STRING** F_NANO_A_RAW_STRING
- #define **F_VALUE_SEND_RECEIVE_RAW_128** F_NANO_B_RAW_128
- #define **F_VALUE_SEND_RECEIVE_REAL_STRING** F_NANO_B_REAL_STRING
- #define **F_VALUE_SEND_RECEIVE_RAW_STRING** F_NANO_B_RAW_STRING
- #define **F_VALUE_TO_SEND** (int)(1<<0)
- #define **F_VALUE_TO_RECEIVE** (int)(1<<1)

Typedefs

- typedef uint8_t **F_TOKEN**[16]
- typedef uint8_t **NANO_SEED**[crypto_sign_SEEDBYTES]
- typedef uint8_t **f_uint128_t**[16]
- typedef uint8_t **NANO_PRIVATE_KEY**[sizeof(NANO_SEED)]
- typedef uint8_t **NANO_PRIVATE_KEY_EXTENDED**[crypto_sign_ed25519_SECRETKEYBYTES]
- typedef uint8_t **NANO_PUBLIC_KEY**[crypto_sign_ed25519_PUBLICKEYBYTES]
- typedef uint8_t **NANO_PUBLIC_KEY_EXTENDED**[PUB_KEY_EXTENDED_MAX_LEN]
- typedef enum **f_nano_err_t** **f_nano_err**
- typedef enum **f_write_seed_err_t** **f_write_seed_err**
- typedef enum **f_file_info_err_t** **F_FILE_INFO_ERR**
- typedef enum **f_nano_create_block_dyn_err_t** **F_NANO_CREATE_BLOCK_DYN_ERR**
- typedef enum **f_nano_p2pow_block_dyn_err_t** **F_NANO_P2POW_BLOCK_DYN_ERR**

Enumerations

- enum `f_nano_err_t` {
`NANO_ERR_OK` = 0, `NANO_ERR_CANT_PARSE_BN_STR` = 5151, `NANO_ERR_MALLOC`, `NANO_ERR_CANT_PARSE_FACTOR`,
`NANO_ERR_MPI_MULT`, `NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER`, `NANO_ERR_EMPTY_STR`, `NANO_ERR_CANT_PARSE_VALUE`,
`NANO_ERR_PARSE_MPI_TO_STR`, `NANO_ERR_CANT_COMPLETE_NULL_CHAR`, `NANO_ERR_CANT_PARSE_TO_MPI`, `NANO_ERR_INSUFFICIENT_FUNDS`,
`NANO_ERR_SUB_MPI`, `NANO_ERR_ADD_MPI`, `NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE`, `NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO`,
`NANO_ERR_NO_SENSE_BALANCE_NEGATIVE`, `NANO_ERR_VAL_A_INVALID_MODE`, `NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T`, `NANO_ERR_VAL_B_INVALID_MODE`,
`NANO_ERR_CANT_PARSE_RAW_A_TO_MPI`, `NANO_ERR_CANT_PARSE_RAW_B_TO_MPI`, `NANO_ERR_UNKNOWN_ADD_SUB_MODE`, `NANO_ERR_INVALID_RES_OUTPUT` }
- enum `f_write_seed_err_t` {
`WRITE_ERR_OK` = 0, `WRITE_ERR_NULL_PASSWORD` = 7180, `WRITE_ERR_EMPTY_STRING`, `WRITE_ERR_MALLOC`,
`WRITE_ERR_ENCRYPT_PRIV_KEY`, `WRITE_ERR_GEN_SUB_PRIV_KEY`, `WRITE_ERR_GEN_MAIN_PRIV_KEY`, `WRITE_ERR_ENCRYPT_SUB_BLOCK`,
`WRITE_ERR_UNKNOWN_OPTION`, `WRITE_ERR_FILE_ALREADY_EXISTS`, `WRITE_ERR_CREATING_FILE`, `WRITE_ERR_WRITING_FILE` }
- enum `f_file_info_err_t` {
`F_FILE_INFO_ERR_OK` = 0, `F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE` = 7001, `F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND`, `F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE`,
`F_FILE_INFO_ERR_MALLOC`, `F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE`, `F_FILE_INFO_ERR_CANT_READ_INFO_FILE`, `F_FILE_INFO_INVALID_HEADER_FILE`,
`F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE`, `F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL`, `F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE`, `F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE`,
`F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO`, `F_FILE_INFO_ERR_EXISTING_FILE`, `F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO` }
- enum `f_nano_create_block_dyn_err_t` {
`NANO_CREATE_BLK_DYN_OK` = 0, `NANO_CREATE_BLK_DYN_BLOCK_NULL` = 8000, `NANO_CREATE_BLK_DYN_ACCOUNT_NULL`, `NANO_CREATE_BLK_DYN_COMPARE_BALANCE`,
`NANO_CREATE_BLK_DYN_GENESIS_WITH_NON_EMPTY_BALANCE`, `NANO_CREATE_BLK_DYN_CANT_SEND_IN_GENESIS_BLOCK`, `NANO_CREATE_BLK_DYN_REP_NULL`, `NANO_CREATE_BLK_DYN_BALANCE_NULL`,
`NANO_CREATE_BLK_DYN_SEND_RECEIVE_NULL`, `NANO_CREATE_BLK_DYN_LINK_NULL`, `NANO_CREATE_BLK_DYN_BUF_MALLOC`, `NANO_CREATE_BLK_DYN_MALLOC`,
`NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_SZ`, `NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_STR_SZ`, `NANO_CREATE_BLK_DYN_PARSE_STR_HEX_ERR`, `NANO_CREATE_BLK_DYN_FORBIDDEN_AMOUNT_TYPE`,
`NANO_CREATE_BLK_DYN_COMPARE`, `NANO_CREATE_BLK_DYN_EMPTY_VAL_TO_SEND_OR_REC`, `NANO_CREATE_BLK_DYN_INVALID_DIRECTION_OPTION` }
- enum `f_nano_p2pow_block_dyn_err_t` {
`NANO_P2POW_CREATE_BLOCK_OK` = 0, `NANO_P2POW_CREATE_BLOCK_INVALID_USER_BLOCK` = 8400, `NANO_P2POW_CREATE_BLOCK_MALLOC`, `NANO_P2POW_CREATE_BLOCK_NULL`,
`NANO_P2POW_CREATE_OUTPUT`, `NANO_P2POW_CREATE_OUTPUT_MALLOC` }

Functions

- struct `f_block_transfer_t` `__attribute__((packed))` `F_BLOCK_TRANSFER`
- double `to_multiplier` (uint64_t, uint64_t)
- uint64_t `from_multiplier` (double, uint64_t)

- void **f_set_dictionary_path** (const char *)
- char * **f_get_dictionary_path** (void)
- int **f_generate_token** (F_TOKEN, void *, size_t, const char *)
- int **f_verify_token** (F_TOKEN, void *, size_t, const char *)
- int **f_cloud_crypto_wallet_nano_create_seed** (size_t, char *, char *)
- int **f_generate_nano_seed** (NANO_SEED, uint32_t)
- int **pk_to_wallet** (char *, char *, NANO_PUBLIC_KEY_EXTENDED)
- int **f_seed_to_nano_wallet** (NANO_PRIVATE_KEY, NANO_PUBLIC_KEY, NANO_SEED, uint32_t)
- int **f_nano_is_valid_block** (F_BLOCK_TRANSFER *)
- int **f_nano_block_to_json** (char *, size_t *, size_t, F_BLOCK_TRANSFER *)
- int **f_nano_get_block_hash** (uint8_t *, F_BLOCK_TRANSFER *)
- int **f_nano_get_p2pow_block_hash** (uint8_t *, uint8_t *, F_BLOCK_TRANSFER *)
- int **f_nano_p2pow_to_JSON** (char *, size_t *, size_t, F_BLOCK_TRANSFER *)
- char * **f_nano_key_to_str** (char *, unsigned char *)
- int **f_nano_seed_to_bip39** (char *, size_t, size_t *, NANO_SEED, char *)
- int **f_bip39_to_nano_seed** (uint8_t *, char *, char *)
- int **f_parse_nano_seed_and_bip39_to_JSON** (char *, size_t, size_t *, void *, int, const char *)
- int **f_read_seed** (uint8_t *, const char *, void *, int, int)
- int **f_nano_raw_to_string** (char *, size_t *, size_t, void *, int)
- int **f_nano_valid_nano_str_value** (const char *)
- int **valid_nano_wallet** (const char *)
- int **nano_base_32_2_hex** (uint8_t *, char *)
- int **f_nano_transaction_to_JSON** (char *, size_t, size_t *, NANO_PRIVATE_KEY_EXTENDED, F_BLOCK_TRANSFER *)
- int **valid_raw_balance** (const char *)
- int **is_null_hash** (uint8_t *)
- int **is_nano_prefix** (const char *, const char *)
- F_FILE_INFO_ERR **f_get_nano_file_info** (F_NANO_WALLET_INFO *)
- F_FILE_INFO_ERR **f_set_nano_file_info** (F_NANO_WALLET_INFO *, int)
- f_nano_err **f_nano_value_compare_value** (void *, void *, uint32_t *)
- f_nano_err **f_nano_verify_nano_funds** (void *, void *, void *, uint32_t)
- f_nano_err **f_nano_parse_raw_str_to_raw128_t** (uint8_t *, const char *)
- f_nano_err **f_nano_parse_real_str_to_raw128_t** (uint8_t *, const char *)
- f_nano_err **f_nano_add_sub** (void *, void *, void *, uint32_t)
- int **f_nano_sign_block** (F_BLOCK_TRANSFER *, F_BLOCK_TRANSFER *, NANO_PRIVATE_KEY_EXTENDED)
- f_write_seed_err **f_write_seed** (void *, int, uint8_t *, char *)
- f_nano_err **f_nano_balance_to_str** (char *, size_t, size_t *, f_uint128_t)
- int **f_extract_seed_from_brainwallet** (uint8_t *, char **, uint32_t, const char *, const char *)
- int **f_verify_work** (uint64_t *, const unsigned char *, uint64_t *, uint64_t)
- int **f_sign_data** (unsigned char * **signature**, void *out_public_key, uint32_t output_type, const unsigned char *message, size_t msg_len, const unsigned char *private_key)
- int **f_verify_signed_data** (const unsigned char *, const unsigned char *, size_t, const void *, uint32_t)
- int **f_is_valid_nano_seed_encrypted** (void *, size_t, int)
- int **nano_create_block_dynamic** (F_BLOCK_TRANSFER **, const void *, size_t, const void *, size_t, const void *, size_t, const void *, const void *, uint32_t, const void *, size_t, int)
- int **nano_create_p2pow_block_dynamic** (F_BLOCK_TRANSFER **, F_BLOCK_TRANSFER *, const void *, size_t, const void *, uint32_t, const void *, size_t)
- int **f_verify_signed_block** (F_BLOCK_TRANSFER *)
- int **f_nano_pow** (uint64_t *, unsigned char *, const uint64_t, int)

Variables

- `uint8_t` **preamble** [32]
- `uint8_t` **account** [32]
- `uint8_t` **previous** [32]
- `uint8_t` **representative** [32]
- `f_uint128_t` **balance**
- `uint8_t` **link** [32]
- `uint8_t` **signature** [64]
- `uint8_t` **prefixes**
- `uint64_t` **work**
- `uint8_t` **sub_salt** [32]
- `uint8_t` **iv** [16]
- `uint8_t` **reserved** [16]
- `uint8_t` **hash_sk_unencrypted** [32]
- `uint8_t` **sk_encrypted** [32]
- `uint8_t` **nano_hdr** [sizeof(NANO_WALLET_MAGIC)]
- `uint32_t` **ver**
- `uint8_t` **description** [F_DESC_SZ]
- `uint8_t` **salt** [32]
- `F_ENCRYPTED_BLOCK` **seed_block**
- `uint8_t` **wallet_prefix**
- `uint32_t` **last_used_wallet_number**
- `char` **wallet_representative** [MAX_STR_NANO_CHAR]
- `char` **max_fee** [F_RAW_STR_MAX_SZ]
- `uint8_t` **header** [sizeof(F_NANO_WALLET_INFO_MAGIC)]
- `uint16_t` **version**
- `char` **desc** [F_NANO_DESC_SZ]
- `uint8_t` **nanoseed_hash** [32]
- `uint8_t` **file_info_integrity** [32]
- `F_NANO_WALLET_INFO_BODY` **body**

5.7.1 Detailed Description

This API Integrates Nano Cryptocurrency to low computational devices.

Definition in file `f_nano_crypto_util.h`.

5.7.2 Macro Definition Documentation

5.7.2.1 DEST_XRB

```
#define DEST_XRB (uint8_t)0x01
```

Definition at line 438 of file `f_nano_crypto_util.h`.

5.7.2.2 F_BALANCE_RAW_128

```
#define F_BALANCE_RAW_128 F_NANO_A_RAW_128
```

Definition at line **1448** of file **f_nano_crypto_util.h**.

5.7.2.3 F_BALANCE_RAW_STRING

```
#define F_BALANCE_RAW_STRING F_NANO_A_RAW_STRING
```

Definition at line **1450** of file **f_nano_crypto_util.h**.

5.7.2.4 F_BALANCE_REAL_STRING

```
#define F_BALANCE_REAL_STRING F_NANO_A_REAL_STRING
```

Definition at line **1449** of file **f_nano_crypto_util.h**.

5.7.2.5 F_BLOCK_TRANSFER_SIZE

```
#define F_BLOCK_TRANSFER_SIZE (size_t)sizeof(F_BLOCK_TRANSFER)
```

Definition at line **289** of file **f_nano_crypto_util.h**.

5.7.2.6 F_BRAIN_WALLET_BAD

```
#define F_BRAIN_WALLET_BAD (uint32_t)3
```

[bad].

Crack within one day

Definition at line **1207** of file **f_nano_crypto_util.h**.

5.7.2.7 F_BRAIN_WALLET_GOOD

```
#define F_BRAIN_WALLET_GOOD (uint32_t)8
```

[good].

Crack within one thousand year

Definition at line **1238** of file **f_nano_crypto_util.h**.

5.7.2.8 F_BRAIN_WALLET_MAYBE_GOOD

```
#define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
```

[maybe good for you].

Crack within one century

Definition at line **1231** of file **f_nano_crypto_util.h**.

5.7.2.9 F_BRAIN_WALLET_NICE

```
#define F_BRAIN_WALLET_NICE (uint32_t)10
```

[very nice].

Crack withing one hundred thousand year

Definition at line **1250** of file **f_nano_crypto_util.h**.

5.7.2.10 F_BRAIN_WALLET_PERFECT

```
#define F_BRAIN_WALLET_PERFECT (uint32_t)11
```

[Perfect!] 3.34×10^{53} Years to crack

Definition at line **1256** of file **f_nano_crypto_util.h**.

5.7.2.11 **F_BRAIN_WALLET_POOR**

```
#define F_BRAIN_WALLET_POOR (uint32_t)1
```

[poor].

Crack within minutes

Definition at line **1195** of file **f_nano_crypto_util.h**.

5.7.2.12 **F_BRAIN_WALLET_STILL_WEAK**

```
#define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
```

[still weak].

Crack within one year

Definition at line **1225** of file **f_nano_crypto_util.h**.

5.7.2.13 **F_BRAIN_WALLET_VERY_BAD**

```
#define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
```

[very bad].

Crack within one hour

Definition at line **1201** of file **f_nano_crypto_util.h**.

5.7.2.14 **F_BRAIN_WALLET_VERY_GOOD**

```
#define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
```

[very good].

Crack within ten thousand year

Definition at line **1244** of file **f_nano_crypto_util.h**.

5.7.2.15 F_BRAIN_WALLET_VERY_POOR

```
#define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
```

[very poor].

Crack within seconds or less

Definition at line **1189** of file **f_nano_crypto_util.h**.

5.7.2.16 F_BRAIN_WALLET_VERY_WEAK

```
#define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
```

[very weak].

Crack within one week

Definition at line **1213** of file **f_nano_crypto_util.h**.

5.7.2.17 F_BRAIN_WALLET_WEAK

```
#define F_BRAIN_WALLET_WEAK (uint32_t)5
```

[weak].

Crack within one month

Definition at line **1219** of file **f_nano_crypto_util.h**.

5.7.2.18 F_DEFAULT_THRESHOLD

```
#define F_DEFAULT_THRESHOLD (uint64_t) 0xffffffffc000000000
```

Default Nano Proof of Work Threshold.

Definition at line **1359** of file **f_nano_crypto_util.h**.

5.7.2.19 **F_IS_SIGNATURE_RAW_HEX_STRING**

```
#define F_IS_SIGNATURE_RAW_HEX_STRING (uint32_t)64
```

Signature is raw hex string flag.

See also

f_sign_data() (p. ??)

Definition at line **1346** of file **f_nano_crypto_util.h**.

5.7.2.20 **F_MESSAGE_IS_HASH_STRING**

```
#define F_MESSAGE_IS_HASH_STRING (uint32_t)128
```

Message is raw hex hash string.

See also

f_sign_data() (p. ??)

Definition at line **1353** of file **f_nano_crypto_util.h**.

5.7.2.21 **F_NANO_POW_MAX_THREAD**

```
#define F_NANO_POW_MAX_THREAD (size_t)10
```

(desktop only) Number of threads for Proof of Work routines.

Default 10

Definition at line **138** of file **f_nano_crypto_util.h**.

5.7.2.22 **F_P2POW_BLOCK_TRANSFER_SIZE**

```
#define F_P2POW_BLOCK_TRANSFER_SIZE 2* F_BLOCK_TRANSFER_SIZE
```

Definition at line **290** of file **f_nano_crypto_util.h**.

5.7.2.23 F_SIGNATURE_OUTPUT_NANO_PK

```
#define F_SIGNATURE_OUTPUT_NANO_PK (uint32_t)32
```

Public key is a NANO wallet encoded base32 string.

See also

f_sign_data() (p. ??)

Definition at line 1339 of file **f_nano_crypto_util.h**.

5.7.2.24 F_SIGNATURE_OUTPUT_RAW_PK

```
#define F_SIGNATURE_OUTPUT_RAW_PK (uint32_t)4
```

Public key is raw data.

See also

f_sign_data() (p. ??)

Definition at line 1318 of file **f_nano_crypto_util.h**.

5.7.2.25 F_SIGNATURE_OUTPUT_STRING_PK

```
#define F_SIGNATURE_OUTPUT_STRING_PK (uint32_t)8
```

Public key is hex ASCII encoded string.

See also

f_sign_data() (p. ??)

Definition at line 1325 of file **f_nano_crypto_util.h**.

5.7.2.26 F_SIGNATURE_OUTPUT_XRB_PK

```
#define F_SIGNATURE_OUTPUT_XRB_PK (uint32_t)16
```

Public key is a XRB wallet encoded base32 string.

See also

f_sign_data() (p. ??)

Definition at line 1332 of file **f_nano_crypto_util.h**.

5.7.2.27 **F_SIGNATURE_RAW**

```
#define F_SIGNATURE_RAW (uint32_t)1
```

Signature is raw data.

See also

f_sign_data() (p. ??)

Definition at line **1304** of file **f_nano_crypto_util.h**.

5.7.2.28 **F_SIGNATURE_STRING**

```
#define F_SIGNATURE_STRING (uint32_t)2
```

Signature is hex ASCII encoded string.

See also

f_sign_data() (p. ??)

Definition at line **1311** of file **f_nano_crypto_util.h**.

5.7.2.29 **F_VALUE_SEND_RECEIVE_RAW_128**

```
#define F_VALUE_SEND_RECEIVE_RAW_128 F_NANO_B_RAW_128
```

Definition at line **1451** of file **f_nano_crypto_util.h**.

5.7.2.30 **F_VALUE_SEND_RECEIVE_RAW_STRING**

```
#define F_VALUE_SEND_RECEIVE_RAW_STRING F_NANO_B_RAW_STRING
```

Definition at line **1453** of file **f_nano_crypto_util.h**.

5.7.2.31 **F_VALUE_SEND_RECEIVE_REAL_STRING**

```
#define F_VALUE_SEND_RECEIVE_REAL_STRING F_NANO_B_REAL_STRING
```

Definition at line **1452** of file **f_nano_crypto_util.h**.

5.7.2.32 F_VALUE_TO_RECEIVE

```
#define F_VALUE_TO_RECEIVE (int) (1<<1)
```

Definition at line 1455 of file **f_nano_crypto_util.h**.

5.7.2.33 F_VALUE_TO_SEND

```
#define F_VALUE_TO_SEND (int) (1<<0)
```

Definition at line 1454 of file **f_nano_crypto_util.h**.

5.7.2.34 F_VERIFY_SIG_ASCII_HEX

```
#define F_VERIFY_SIG_ASCII_HEX (uint32_t) 4
```

Public key is a hex ASCII encoded string.

See also

f_verify_signed_data() (p. ??)

Definition at line 1411 of file **f_nano_crypto_util.h**.

5.7.2.35 F_VERIFY_SIG_NANO_WALLET

```
#define F_VERIFY_SIG_NANO_WALLET (uint32_t) 1
```

Public key is a NANO wallet with *XRB* or *NANO* prefixes encoded base32 string.

See also

f_verify_signed_data() (p. ??)

Definition at line 1397 of file **f_nano_crypto_util.h**.

5.7.2.36 F_VERIFY_SIG_RAW_HEX

```
#define F_VERIFY_SIG_RAW_HEX (uint32_t)2
```

Public key raw 32 bytes data.

See also

f_verify_signed_data() (p. ??)

Definition at line **1404** of file **f_nano_crypto_util.h**.

5.7.2.37 MAX_STR_NANO_CHAR

```
#define MAX_STR_NANO_CHAR (size_t)70
```

Defines a max size of Nano char (70 bytes)

Definition at line **150** of file **f_nano_crypto_util.h**.

5.7.2.38 NANO_ENCRYPTED_SEED_FILE

```
#define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
```

Path to non deterministic encrypted file with password.

File containing the SEED of the Nano wallets generated by TRNG (if available in your Hardware) or PRNG.
Default name: "nano.nse"

Definition at line **192** of file **f_nano_crypto_util.h**.

5.7.2.39 NANO_FILE_WALLETS_INFO

```
#define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
```

Custom information file path about Nano SEED wallet stored in "walletsinfo.i".

Definition at line **210** of file **f_nano_crypto_util.h**.

5.7.2.40 NANO_PASSWD_MAX_LEN

```
#define NANO_PASSWD_MAX_LEN (size_t)80
```

Password max length.

Definition at line **198** of file **f_nano_crypto_util.h**.

5.7.2.41 NANO_PREFIX

```
#define NANO_PREFIX "nano_"
```

Nano prefix.

Definition at line **162** of file **f_nano_crypto_util.h**.

5.7.2.42 PUB_KEY_EXTENDED_MAX_LEN

```
#define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
```

Max size of public key (extended)

Definition at line **156** of file **f_nano_crypto_util.h**.

5.7.2.43 REP_XRB

```
#define REP_XRB (uint8_t)0x4
```

Representative XRB flag.

Destination XRB flag.

Sender XRB flag.

5.7.2.44 SENDER_XRB

```
#define SENDER_XRB (uint8_t)0x02
```

Definition at line **432** of file **f_nano_crypto_util.h**.

5.7.2.45 STR_NANO_SZ

```
#define STR_NANO_SZ (size_t)66
```

String size of Nano encoded Base32 including NULL char.

Definition at line **204** of file **f_nano_crypto_util.h**.

5.7.2.46 XRB_PREFIX

```
#define XRB_PREFIX "xrb_"
```

XRB (old Raiblocks) prefix.

Definition at line **168** of file **f_nano_crypto_util.h**.

5.7.3 Typedef Documentation

5.7.3.1 F_FILE_INFO_ERR

```
F_FILE_INFO_ERR
```

Typedef Error enumerator for info file functions.

5.7.3.2 F_NANO_CREATE_BLOCK_DYN_ERR

```
typedef enum f_nano_create_block_dyn_err_t F_NANO_CREATE_BLOCK_DYN_ERR
```

5.7.3.3 f_nano_err

```
f_nano_err
```

Error function enumerator.

See also

f_nano_err_t (p. ??)

5.7.3.4 F_NANO_P2POW_BLOCK_DYN_ERR

```
typedef enum f_nano_p2pow_block_dyn_err_t F_NANO_P2POW_BLOCK_DYN_ERR
```

5.7.3.5 F_TOKEN

```
typedef uint8_t F_TOKEN[16]
```

Definition at line **216** of file **f_nano_crypto_util.h**.

5.7.3.6 f_uint128_t

```
f_uint128_t
```

128 bit big number of Nano balance

Definition at line **228** of file **f_nano_crypto_util.h**.

5.7.3.7 f_write_seed_err

```
typedef enum f_write_seed_err_t f_write_seed_err
```

5.7.3.8 NANO_PRIVATE_KEY

```
NANO_PRIVATE_KEY
```

Size of Nano Private Key.

Definition at line **238** of file **f_nano_crypto_util.h**.

5.7.3.9 NANO_PRIVATE_KEY_EXTENDED

```
NANO_PRIVATE_KEY_EXTENDED
```

Size of Nano Private Key extended.

Definition at line **244** of file **f_nano_crypto_util.h**.

5.7.3.10 NANO_PUBLIC_KEY

NANO_PUBLIC_KEY

Size of Nano Public Key.

Definition at line 250 of file f_nano_crypto_util.h.

5.7.3.11 NANO_PUBLIC_KEY_EXTENDED

NANO_PUBLIC_KEY_EXTENDED

Size of Public Key Extended.

Definition at line 256 of file f_nano_crypto_util.h.

5.7.3.12 NANO_SEED

NANO_SEED

Size of Nano SEED.

Definition at line 222 of file f_nano_crypto_util.h.

5.7.4 Enumeration Type Documentation

5.7.4.1 f_file_info_err_t

enum f_file_info_err_t

Enumerator

F_FILE_INFO_ERR_OK	SUCCESS.
F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE	Can't open info file.
F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND	Encrypted file with Nano SEED not found.
F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE	Can not delete Nano info file.
F_FILE_INFO_ERR_MALLOC	Fatal Error MALLOC.
F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE	Can not read encrypted Nano SEED in file.
F_FILE_INFO_ERR_CANT_READ_INFO_FILE	Can not read info file.
F_FILE_INFO_INVALID_HEADER_FILE	Invalid info file header.
F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE	Invalid SHA256 info file.
F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL	Nano SEED hash failed.
F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE	Invalid representative.
F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE	Invalid max fee value.
F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO	Can not open info file for write.
F_FILE_INFO_ERR_EXISTING_FILE	Error File Exists.

Definition at line 544 of file `f_nano_crypto_util.h`.

5.7.4.2 `f_nano_create_block_dyn_err_t`

enum `f_nano_create_block_dyn_err_t`

Enumerator

NANO_CREATE_BLK_DYN_OK	
NANO_CREATE_BLK_DYN_BLOCK_NULL	
NANO_CREATE_BLK_DYN_ACCOUNT_NULL	
NANO_CREATE_BLK_DYN_COMPARE_BALANCE	
NANO_CREATE_BLK_DYN_GENESIS_WITH_NON_EMPTY_BALANCE	
NANO_CREATE_BLK_DYN_CANT_SEND_IN_GENESIS_BLOCK	
NANO_CREATE_BLK_DYN_REP_NULL	
NANO_CREATE_BLK_DYN_BALANCE_NULL	
NANO_CREATE_BLK_DYN_SEND_RECEIVE_NULL	
NANO_CREATE_BLK_DYN_LINK_NULL	
NANO_CREATE_BLK_DYN_BUF_MALLOC	
NANO_CREATE_BLK_DYN_MALLOC	
NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_SZ	
NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_STR_SZ	
NANO_CREATE_BLK_DYN_PARSE_STR_HEX_ERR	
NANO_CREATE_BLK_DYN_FORBIDDEN_AMOUNT_TYPE	
NANO_CREATE_BLK_DYN_COMPARE	
NANO_CREATE_BLK_DYN_EMPTY_VAL_TO_SEND_OR_REC	
NANO_CREATE_BLK_DYN_INVALID_DIRECTION_OPTION	

Definition at line 604 of file `f_nano_crypto_util.h`.

5.7.4.3 `f_nano_err_t`

enum `f_nano_err_t`

Enumerator

NANO_ERR_OK	SUCCESS.
NANO_ERR_CANT_PARSE_BN_STR	Can not parse string big number.
NANO_ERR_MALLOC	Fatal ERROR MALLOC.
NANO_ERR_CANT_PARSE_FACTOR	Can not parse big number factor.
NANO_ERR_MPI_MULT	Error multiplication MPI.
NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER	Can not parse to block transfer.
NANO_ERR_EMPTY_STR	Error empty string.
NANO_ERR_CANT_PARSE_VALUE	Can not parse value.
NANO_ERR_PARSE_MPI_TO_STR	Can not parse MPI to string.

Enumerator

NANO_ERR_CANT_COMPLETE_NULL_CHAR	Can not complete NULL char.
NANO_ERR_CANT_PARSE_TO_MPI	Can not parse to MPI.
NANO_ERR_INSUFICIENT_FUNDS	Insuficient funds.
NANO_ERR_SUB_MPI	Error subtract MPI.
NANO_ERR_ADD_MPI	Error add MPI.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE	Does not make sense send negativative balance.
NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO	Does not make sense send empty value.
NANO_ERR_NO_SENSE_BALANCE_NEGATIVE	Does not make sense negative balance.
NANO_ERR_VAL_A_INVALID_MODE	Invalid A mode value.
NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T	Can not parse temporary memory to uint_128_t.
NANO_ERR_VAL_B_INVALID_MODE	Invalid A mode value.
NANO_ERR_CANT_PARSE_RAW_A_TO_MPI	Can not parse raw A value to MPI.
NANO_ERR_CANT_PARSE_RAW_B_TO_MPI	Can not parse raw B value to MPI.
NANO_ERR_UNKNOWN_ADD_SUB_MODE	Unknown ADD/SUB mode.
NANO_ERR_INVALID_RES_OUTPUT	Invalid output result.

Definition at line 303 of file **f_nano_crypto_util.h**.

5.7.4.4 f_nano_p2pow_block_dyn_err_t

enum **f_nano_p2pow_block_dyn_err_t**

Enumerator

NANO_P2POW_CREATE_BLOCK_OK	
NANO_P2POW_CREATE_BLOCK_INVALID_USER_BLOCK	
NANO_P2POW_CREATE_BLOCK_MALLOC	
NANO_P2POW_CREATE_BLOCK_NULL	
NANO_P2POW_CREATE_OUTPUT	
NANO_P2POW_CREATE_OUTPUT_MALLOC	

Definition at line 627 of file **f_nano_crypto_util.h**.

5.7.4.5 f_write_seed_err_t

enum **f_write_seed_err_t**

Enumerator

WRITE_ERR_OK	Error SUCCESS.
WRITE_ERR_NULL_PASSWORD	Error NULL password.
WRITE_ERR_EMPTY_STRING	Empty string.

Enumerator

WRITE_ERR_MALLOC	Error MALLOC.
WRITE_ERR_ENCRYPT_PRIV_KEY	Error encrypt private key.
WRITE_ERR_GEN_SUB_PRIV_KEY	Can not generate sub private key.
WRITE_ERR_GEN_MAIN_PRIV_KEY	Can not generate main private key.
WRITE_ERR_ENCRYPT_SUB_BLOCK	Can not encrypt sub block.
WRITE_ERR_UNKNOWN_OPTION	Unknown option.
WRITE_ERR_FILE_ALREADY_EXISTS	File already exists.
WRITE_ERR_CREATING_FILE	Can not create file.
WRITE_ERR_WRITING_FILE	Can not write file.

Definition at line **440** of file **f_nano_crypto_util.h**.

5.7.5 Function Documentation

5.7.5.1 __attribute__()

```
struct f_block_transfer_t __attribute__ (
    (packed) )
```

5.7.5.2 f_bip39_to_nano_seed()

```
int f_bip39_to_nano_seed (
    uint8_t * seed,
    char * str,
    char * dictionary )
```

Parse Nano Bip39 encoded string to raw Nano SEED given a dictionary file.

Parameters

out	<i>seed</i>	Nano SEED
in	<i>str</i>	A encoded Bip39 string pointer
in	<i>dictionary</i>	A string pointer path to file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_nano_seed_to_bip39() (p. ??)

5.7.5.3 f_cloud_crypto_wallet_nano_create_seed()

```
int f_cloud_crypto_wallet_nano_create_seed (
    size_t entropy,
    char * file_name,
    char * password )
```

Generates a new SEED and saves it to an non deterministic encrypted file.

password is mandatory

Parameters

in	<i>entropy</i>	Entropy type. Entropy type are: F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED
in	<i>file_name</i>	The file and path to be stored in your file system directory. It can be <i>NULL</i> . If you parse a <i>NULL</i> value then file will be stored in <i>NANO_ENCRYPTED_SEED_FILE</i> variable file system pointer.
in	<i>password</i>	Password of the encrypted file. It can NOT be <i>NULL</i> or EMPTY

WARNING

f_cloud_crypto_wallet_nano_create_seed() (p. ??) does not verify your password. It is recommended to use a strong password like symbols, capital letters and numbers to keep your SEED safe and avoid brute force attacks.

You can use **f_pass_must_have_at_least()** (p. ??) function to check passwords strength

Return values

0	On Success, otherwise Error
---	-----------------------------

5.7.5.4 f_extract_seed_from_brainwallet()

```
int f_extract_seed_from_brainwallet (
    uint8_t * seed,
    char ** warning_msg,
    uint32_t allow_mode,
```

```
const char * brainwallet,
const char * salt )
```

Analyzes a text given a *mode* and if pass then the text in *brainwallet* is translated to a Nano SEED.

Parameters

out	<i>seed</i>	Output Nano SEED extracted from <i>brainwallet</i>
out	<i>warning_msg</i>	Warning message parsed to application. It can be NULL
in	<i>allow_mode</i>	<p>Allow <i>mode</i>. Funtion will return SUCCESS only if permitted mode set by user</p> <p>Allow mode are:</p> <ul style="list-style-type: none"> • <i>F_BRAIN_WALLET_VERY_POOR</i> Crack within seconds or less • <i>F_BRAIN_WALLET_POOR</i> Crack within minutes • <i>F_BRAIN_WALLET_VERY_BAD</i> Crack within one hour • <i>F_BRAIN_WALLET_BAD</i> Crack within one day • <i>F_BRAIN_WALLET_VERY_WEAK</i> Crack within one week • <i>F_BRAIN_WALLET_WEAK</i> Crack within one month • <i>F_BRAIN_WALLET_STILL_WEAK</i> Crack within one year • <i>F_BRAIN_WALLET_MAYBE_GOOD</i> Crack within one century • <i>F_BRAIN_WALLET_GOOD</i> Crack within one thousand year • <i>F_BRAIN_WALLET_VERY_GOOD</i> Crack within ten thousand year • <i>F_BRAIN_WALLET_NICE</i> Crack withing one hundred thousand year • <i>F_BRAIN_WALLET_PERFECT</i> 3.34x10⁵³ Years to crack
in	<i>brainwallet</i>	Brainwallet text to be parsed. It can be NOT NULL or null string
in	<i>salt</i>	Salt of the Braiwallet. It can be NOT NULL or null string

Return values

0	If success, otherwise error.
---	------------------------------

See also

f_bip39_to_nano_seed() (p. ??)

5.7.5.5 f_generate_nano_seed()

```
int f_generate_nano_seed (
    NANO_SEED seed,
    uint32_t entropy )
```

Generates a new SEED and stores it to *seed* pointer.

Parameters

out	<i>seed</i>	SEED generated in system PRNG or TRNG
in	<i>entropy</i>	Entropy type. Entropy type are: F_ENTROPY_TYPE_PARANOIC F_ENTROPY_TYPE_EXCELENT F_ENTROPY_TYPE_GOOD F_ENTROPY_TYPE_NOT_ENOUGH F_ENTROPY_TYPE_NOT_RECOMENDED

Return values

0	On Success, otherwise Error
---	-----------------------------

5.7.5.6 f_generate_token()

```
int f_generate_token (
    F_TOKEN signature,
    void * data,
    size_t data_sz,
    const char * password )
```

Generates a non deterministic token given a message data and a password.

Parameters

out	<i>signature</i>	128 bit non deterministic token
in	<i>data</i>	Data to be signed in token
in	<i>data_sz</i>	Size of data
in	<i>password</i>	Password

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_verify_token() (p. ??)

5.7.5.7 f_get_dictionary_path()

```
char * f_get_dictionary_path (
    void )
```

Get default dictionary path in **myNanoEmbedded** library.

Return values

<i>Path</i>	and name of the dictionary file
-------------	---------------------------------

See also

f_set_dictionary_path() (p. ??)

5.7.5.8 f_get_nano_file_info()

```
F_FILE_INFO_ERR f_get_nano_file_info (
    F_NANO_WALLET_INFO * info )
```

Opens default file *walletsinfo.i* (if exists) containing information *F_NANO_WALLET_INFO* structure and parsing to pointer *info* if success.

Parameters

out	<i>info</i>	Pointer to buffer to be parsed struct from <i>\$PATH/walletsinfo.i</i> file.
-----	-------------	--

Return values

<i>F_FILE_INFO_ERR_OK</i>	If Success, otherwise <i>F_FILE_INFO_ERR</i> enum type error
---------------------------	--

See also

F_FILE_INFO_ERR (p. ??) enum type error for detailed error and **f_nano_wallet_info_t** (p. ??) for info type details

5.7.5.9 f_is_valid_nano_seed_encrypted()

```
int f_is_valid_nano_seed_encrypted (
    void * stream,
    size_t stream_len,
    int read_from )
```

Verifies if encrypted Nano SEED is valid.

Parameters

in	<i>stream</i>	Encrypted binary data block coming from memory or file
in	<i>stream_len</i>	size of <i>stream</i> data
in	<i>read_from</i>	Source <i>READ_SEED_FROM_STREAM</i> if encrypted binary data is in memory or <i>READ_SEED_FROM_FILE</i> is in a file.

Return values

0	If invalid, greater than zero if is valid or error if less than zero.
---	---

5.7.5.10 f_nano_add_sub()

```
f_nano_err f_nano_add_sub (
    void * res,
    void * valA,
    void * valB,
    uint32_t mode )
```

Add/Subtract two Nano balance values and stores value in *res*

Parameters

out	<i>res</i>	Result value $res = valA + valB$ or $res = valA - valB$
in	<i>valA</i>	Input balance A value
in	<i>valB</i>	Input balance B value
in	<i>mode</i>	Mode type: <ul style="list-style-type: none"> • <i>F_NANO_ADD_A_B</i> $valA + valB$ • <i>F_NANO_SUB_A_B</i> $valA - valB$ • <i>F_NANO_RES_RAW_128</i> Output is a raw data 128 bit big number result • <i>F_NANO_RES_RAW_STRING</i> Output is a 128 bit Big Integer string • <i>F_NANO_RES_REAL_STRING</i> Output is a Real string value • <i>F_NANO_A_RAW_128</i> if <i>balance</i> is big number raw buffer type • <i>F_NANO_A_RAW_STRING</i> if <i>balance</i> is big number raw string type • <i>F_NANO_A_REAL_STRING</i> if <i>balance</i> is real number string type • <i>F_NANO_B_RAW_128</i> if <i>value_to_send</i> is big number raw buffer type • <i>F_NANO_B_RAW_STRING</i> if <i>value_to_send</i> is big number raw string type • <i>F_NANO_B_REAL_STRING</i> if <i>value_to_send</i> is real number string type

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.7.5.11 `f_nano_balance_to_str()`

```
f_nano_err f_nano_balance_to_str (
    char * str,
    size_t str_len,
    size_t * out_len,
    f_uint128_t value )
```

Converts a raw Nano balance to string raw balance.

Parameters

out	<i>str</i>	Output string pointer
in	<i>str_len</i>	Size of string pointer memory
out	<i>out_len</i>	Output length of converted value to string. If <i>out_len</i> is NULL then <i>str</i> returns converted value with NULL terminated string
in	<i>value</i>	Raw Nano balance value

Return values

0	If success, otherwise error.
---	------------------------------

See also

function `f_nano_parse_raw_str_to_raw128_t()` (p. ??) and return errors `f_nano_err` (p. ??)

5.7.5.12 `f_nano_block_to_json()`

```
int f_nano_block_to_json (
    char * dest,
    size_t * olen,
    size_t dest_size,
    F_BLOCK_TRANSFER * user_block )
```

Parse a Nano Block to JSON.

Parameters

out	<i>dest</i>	Destination of the converted JSON block
out	<i>olen</i>	Output length of the converted JSON block. <i>olen</i> can be NULL. If NULL, destination size contains a NULL char
in	<i>dest_size</i>	Size of <i>dest</i> memory buffer
in	<i>user_block</i>	User Nano block

Returns

0 if success, non zero if error

5.7.5.13 f_nano_get_block_hash()

```
int f_nano_get_block_hash (
    uint8_t * hash,
    F_BLOCK_TRANSFER * block )
```

Gets a hash from Nano block.

Parameters

out	<i>hash</i>	Output hash
in	<i>block</i>	Nano Block

Returns

0 if success, non zero if error

5.7.5.14 f_nano_get_p2pow_block_hash()

```
int f_nano_get_p2pow_block_hash (
    uint8_t * user_hash,
    uint8_t * fee_hash,
    F_BLOCK_TRANSFER * block )
```

Get Nano user block hash and Nano fee block hashes from P2PoW block.

Parameters

out	<i>user_hash</i>	Hash of the user block
out	<i>fee_hash</i>	Hash of the P2PoW block
in	<i>block</i>	Input Nano Block

Returns

0 if success, non zero if error

5.7.5.15 f_nano_is_valid_block()

```
int f_nano_is_valid_block (
    F_BLOCK_TRANSFER * block )
```

Checks if Binary Nano Block is valid.

Parameters

in	<i>block</i>	Nano Block
----	--------------	------------

Returns

0 if is invalid block or 1 if is valid block

5.7.5.16 f_nano_key_to_str()

```
char * f_nano_key_to_str (
    char * out,
    unsigned char * key )
```

Parse a raw binary public key to string.

Parameters

out	<i>out</i>	Pointer to outuput string
in	<i>in</i>	Pointer to raw public key

Returns

A pointer to output string

5.7.5.17 f_nano_p2pow_to_JSON()

```
int f_nano_p2pow_to_JSON (
    char * buffer,
    size_t * olen,
    size_t buffer_sz,
    F_BLOCK_TRANSFER * block )
```

Parse binary P2PoW block to JSON.

Parameters

out	<i>buffer</i>	Output JSON string
out	<i>olen</i>	Output JSON string size. <i>olen</i> can be NULL. If NULL, <i>buffer</i> will be terminated with a NULL char
in	<i>buffer_sz</i>	Size of memory buffer
in	<i>block</i>	P2PoW block

Returns

0 if success, non zero if error

5.7.5.18 f_nano_parse_raw_str_to_raw128_t()

```
f_nano_err f_nano_parse_raw_str_to_raw128_t (
    uint8_t * res,
    const char * raw_str_value )
```

Parse a raw string balance to raw big number 128 bit.

Parameters

out	<i>res</i>	Binary raw balance
in	<i>raw_str_value</i>	Raw balance string

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.7.5.19 f_nano_parse_real_str_to_raw128_t()

```
f_nano_err f_nano_parse_real_str_to_raw128_t (
    uint8_t * res,
    const char * real_str_value )
```

Parse a real string balance to raw big number 128 bit.

Parameters

out	<i>res</i>	Binary raw balance
in	<i>real_str_value</i>	Real balance string

Return values

<i>NANO_ERR_OK</i>	If Success, otherwise f_nano_err_t enum type error
--------------------	--

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.7.5.20 f_nano_pow()

```
int f_nano_pow (
    uint64_t * PoW_res,
    unsigned char * hash,
    const uint64_t threshold,
    int n_thr )
```

Calculates a Proof of Work given a *hash*, *threshold* and number of threads *n_thr*

Parameters

out	<i>PoW_res</i>	Output Proof of Work
in	<i>hash</i>	Input <i>hash</i>
in	<i>threshold</i>	Input <i>threshold</i>
in	<i>n_thr</i>	Number of threads. Default maximum value: 10. You can modify <i>F_NANO_POW_MAX_THREAD</i> in f_nano_crypto_util.h (p. ??)

Mandatory: You need to enable attach a random function to your project using **f_random_attach()** (p. ??)

Return values

0	If success, otherwise error.
---	------------------------------

See also

f_verify_work() (p. ??)

5.7.5.21 f_nano_raw_to_string()

```
int f_nano_raw_to_string (
    char * str,
    size_t * olen,
    size_t str_sz,
    void * raw,
    int raw_type )
```

Converts Nano raw balance [string | f_uint128_t] to real string value.

Parameters

out	<i>str</i>	Output real string value
out	<i>olen</i>	Size of output real string value. It can be NULL. If NULL output <i>str</i> will have a NULL char at the end.
in	<i>str_sz</i>	Size of <i>str</i> buffer
in	<i>raw</i>	Raw balance.
in	<i>raw_type</i>	Raw balance type: <ul style="list-style-type: none"> F_RAW_TO_STR_UINT128 for raw f_uint128_t balance F_RAW_TO_STR_STRING for raw char balance

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_nano_valid_nano_str_value() (p. ??)

5.7.5.22 f_nano_seed_to_bip39()

```
int f_nano_seed_to_bip39 (
    char * buf,
    size_t buf_sz,
    size_t * out_buf_len,
    NANO_SEED seed,
    char * dictionary_file )
```

Parse Nano SEED to Bip39 encoding given a dictionary file.

Parameters

out	<i>buf</i>	Output string containing encoded Bip39 SEED
in	<i>buf_sz</i>	Size of memory of buf pointer
out	<i>out_buf_len</i>	If <i>out_buf_len</i> is NOT NULL then <i>out_buf_len</i> returns the size of string encoded Bip39 and <i>out</i> with non NULL char. If <i>out_buf_len</i> is NULL then <i>out</i> has a string encoded Bip39 with a NULL char.
in	<i>seed</i>	Nano SEED
in	<i>dictionary_file</i>	Path to dictionary file

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_bip39_to_nano_seed() (p. ??)

5.7.5.23 f_nano_sign_block()

```
int f_nano_sign_block (
    F_BLOCK_TRANSFER * user_block,
    F_BLOCK_TRANSFER * fee_block,
    NANO_PRIVATE_KEY_EXTENDED private_key )
```

Signs *user_block* and worker *fee_block* given a private key *private_key*

Parameters

in, out	<i>user_block</i>	User block to be signed with a private key <i>private_key</i>
in, out	<i>fee_block</i>	Fee block to be signed with a private key <i>private_key</i> . Can be NULL if worker does not require fee
in	<i>private_key</i>	Private key to sign block(s)

Return values

0	If Success, otherwise error
---	-----------------------------

See also

f_nano_transaction_to_JSON() (p. ??)

5.7.5.24 f_nano_transaction_to_JSON()

```
int f_nano_transaction_to_JSON (
    char * str,
    size_t str_len,
    size_t * str_out,
    NANO_PRIVATE_KEY_EXTENDED private_key,
    F_BLOCK_TRANSFER * block_transfer )
```

Sign a block pointed in *block_transfer* with a given *private_key* and stores signed block to *block_transfer* and parse to JSON Nano RPC.

Parameters

out	<i>str</i>	A string pointer to store JSON Nano RPC
in	<i>str_len</i>	Size of buffer in <i>str</i> pointer
out	<i>str_out</i>	Size of JSON string. <i>str_out</i> can be NULL
in	<i>private_key</i>	Private key to sign the block <i>block_transfer</i>
in, out	<i>block_transfer</i>	Nano block containing raw data to be stored in Nano Blockchain

WARNING Sensitive data. Do not share any PRIVATE KEY

Return values

0	On Success, otherwise Error
---	-----------------------------

5.7.5.25 f_nano_valid_nano_str_value()

```
int f_nano_valid_nano_str_value (
    const char * str )
```

Check if a real string or raw string are valid Nano balance.

Parameters

in	str	Value to be checked
----	-----	---------------------

Return values

0	If valid, otherwise is invalid
---	--------------------------------

See also

f_nano_raw_to_string() (p. ??)

5.7.5.26 f_nano_value_compare_value()

```
f_nano_err f_nano_value_compare_value (
    void * valA,
    void * valB,
    uint32_t * mode_compare )
```

Comparare two Nano balance.

Parameters

in	valA	Nano balance value A
in	valB	Nano balance value B
in, out	mode_compare	<p>Input mode and output result</p> <p>Input mode:</p> <ul style="list-style-type: none"> • <i>F_NANO_A_RAW_128</i> if <i>valA</i> is big number raw buffer type • <i>F_NANO_A_RAW_STRING</i> if <i>valA</i> is big number raw string type • <i>F_NANO_A_REAL_STRING</i> if <i>valA</i> is real number string type • <i>F_NANO_B_RAW_128</i> if <i>valB</i> is big number raw buffer type • <i>F_NANO_B_RAW_STRING</i> if <i>valB</i> is big number raw string type • <i>F_NANO_B_REAL_STRING</i> if <i>valB</i> is real number string type <p>Output type:</p> <ul style="list-style-type: none"> • <i>F_NANO_COMPARE_EQ</i> If <i>valA</i> is equal <i>valB</i> • <i>F_NANO_COMPARE_LT</i> if <i>valA</i> is lesser than <i>valB</i> • <i>F_NANO_COMPARE_GT</i> if <i>valA</i> is greater than <i>valB</i>

Return values

<code>NANO_ERR_OK</code>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------------	---

See also

`f_nano_err_t` (p. ??) for `f_nano_err` (p. ??) enum error type

5.7.5.27 `f_nano_verify_nano_funds()`

```
f_nano_err f_nano_verify_nano_funds (
    void * balance,
    void * value_to_send,
    void * fee,
    uint32_t mode )
```

Check if Nano balance has sufficient funds.

Parameters

in	<i>balance</i>	Nano balance
in	<i>value_to_send</i>	Value to send
in	<i>fee</i>	Fee value (it can be NULL)
in	<i>mode</i>	Value type mode <ul style="list-style-type: none"> • <code>F_NANO_A_RAW_128</code> if <i>balance</i> is big number raw buffer type • <code>F_NANO_A_RAW_STRING</code> if <i>balance</i> is big number raw string type • <code>F_NANO_A_REAL_STRING</code> if <i>balance</i> is real number string type • <code>F_NANO_B_RAW_128</code> if <i>value_to_send</i> is big number raw buffer type • <code>F_NANO_B_RAW_STRING</code> if <i>value_to_send</i> is big number raw string type • <code>F_NANO_B_REAL_STRING</code> if <i>value_to_send</i> is real number string type • <code>F_NANO_C_RAW_128</code> if <i>fee</i> is big number raw buffer type (can be omitted if <i>fee</i> is NULL) • <code>F_NANO_C_RAW_STRING</code> if <i>fee</i> is big number raw string type (can be omitted if <i>fee</i> is NULL) • <code>F_NANO_C_REAL_STRING</code> if <i>fee</i> is real number string type (can be omitted if <i>fee</i> is NULL)

Return values

<code>NANO_ERR_OK</code>	If Success, otherwise <code>f_nano_err_t</code> enum type error
--------------------------	---

See also

f_nano_err_t (p. ??) for **f_nano_err** (p. ??) enum error type

5.7.5.28 f_parse_nano_seed_and_bip39_to_JSON()

```
int f_parse_nano_seed_and_bip39_to_JSON (
    char * dest,
    size_t dest_sz,
    size_t * olen,
    void * source_data,
    int source,
    const char * password )
```

Parse Nano SEED and Bip39 to JSON given a encrypted data in memory or encrypted data in file or unencrypted seed in memory.

Parameters

out	<i>dest</i>	Destination JSON string pointer
in	<i>dest_sz</i>	Buffer size of <i>dest</i> pointer
out	<i>olen</i>	Size of the output JSON string. If NULL string JSON returns a NULL char at the end of string otherwise it will return the size of the string is stored into <i>olen</i> variable without NULL string in <i>dest</i>
in	<i>source_data</i>	Input data source (encrypted file encrypted data in memory unencrypted seed in memory)
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> • PARSE_JSON_READ_SEED_GENERIC: If seed are in memory pointed in <i>source_data</i>. Password is ignored. Can be NULL. • READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required. • READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.
in	<i>password</i>	Required for READ_SEED_FROM_STREAM and READ_SEED_FROM_FILE sources

WARNING Sensitive data. Do not share any SEED or Bip39 encoded string !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_read_seed() (p. ??)

5.7.5.29 f_read_seed()

```
int f_read_seed (
    uint8_t * seed,
    const char * passwd,
    void * source_data,
    int force_read,
    int source )
```

Extracts a Nano SEED from encrypted stream in memory or in a file.

Parameters

out	<i>seed</i>	Output Nano SEED
in	<i>passwd</i>	Password (always required)
in	<i>source_data</i>	Encrypted source data from memory or path pointed in <i>source_data</i>
in	<i>force_read</i>	If non zero value then forces reading from a corrupted file. This param is ignored when reading <i>source_data</i> from memory
in	<i>source</i>	Source data type: <ul style="list-style-type: none"> • READ_SEED_FROM_STREAM: Read encrypted data from stream pointed in <i>source_data</i>. Password is required. • READ_SEED_FROM_FILE: Read encrypted data stored in a file where <i>source_data</i> is path to file. Password is required.

WARNING Sensitive data. Do not share any SEED !

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

f_parse_nano_seed_and_bip39_to_JSON() (p. ??) **f_write_seed()** (p. ??)

5.7.5.30 f_seed_to_nano_wallet()

```
int f_seed_to_nano_wallet (
    NANO_PRIVATE_KEY private_key,
    NANO_PUBLIC_KEY public_key,
    NANO_SEED seed,
    uint32_t wallet_number )
```

Extracts one key pair from Nano SEED given a wallet number.

Parameters

out	<i>private_key</i>	Private key of the <i>wallet_number</i> from given <i>seed</i>
out	<i>public_key</i>	Public key of the <i>wallet_number</i> from given <i>seed</i>
in, out	<i>seed</i>	Nano SEED
in	<i>wallet_number</i>	Wallet number of key pair to be extracted from Nano SEED

WARNING 1:

- Seed must be read from memory
- Seed is destroyed when extracting public and private keys

WARNING 2:

- Never expose SEED and private key. This function destroys seed and any data after execution and finally parse public and private keys to output.

Return values

0	On Success, otherwise Error
---	-----------------------------

5.7.5.31 f_set_dictionary_path()

```
void f_set_dictionary_path (
    const char * path )
```

Set default dictionary file and path to **myNanoEmbedded** library.

Parameters

in	<i>path</i>	Path to dictionary file
----	-------------	-------------------------

If **f_set_dictionary_path()** (p. ??) is not used in **myNanoEmbedded** library then default path stored in *BIP39_DICTIONARY* is used

See also

f_get_dictionary_path() (p. ??)

5.7.5.32 f_set_nano_file_info()

```
F_FILE_INFO_ERR f_set_nano_file_info (
    F_NANO_WALLET_INFO * info,
    int overwrite_existing_file )
```

Saves wallet information stored at buffer struct *info* to file *walletsinfo.i*

Parameters

in	<i>info</i>	Pointer to data to be saved at <i>\$PATH/walletsinfo.i</i> file.
in	<i>overwrite_existing_file</i>	If non zero then overwrites file <i>\$PATH/walletsinfo.i</i>

Return values

<code>F_FILE_INFO_ERR_OK</code>	If Success, otherwise <code>F_FILE_INFO_ERR</code> enum type error
---------------------------------	--

See also

F_FILE_INFO_ERR (p. ??) enum type error for detailed error and **f_nano_wallet_info_t** (p. ??) for info type details

5.7.5.33 f_sign_data()

```
int f_sign_data (
    unsigned char * signature,
    void * out_public_key,
    uint32_t output_type,
    const unsigned char * message,
    size_t msg_len,
    const unsigned char * private_key )
```

Signs a *message* with a deterministic signature given a *private key*

Parameters

out	<i>signature</i>	Output signature
out	<i>out_public_key</i>	Output public key. It can be NULL
in	<i>output_type</i>	Output type of public key. Public key types are: <ul style="list-style-type: none"> • <code>F_SIGNATURE_RAW</code> Signature is raw 64 bytes long • <code>F_SIGNATURE_STRING</code> Singnature is hex ASCII encoded string • <code>F_SIGNATURE_OUTPUT_RAW_PK</code> Public key is raw 32 bytes data • <code>F_SIGNATURE_OUTPUT_STRING_PK</code> Public key is hes ASCII encoded string • <code>F_SIGNATURE_OUTPUT_XRB_PK</code> Public key is a XRB wallet encoded base32 string • <code>F_SIGNATURE_OUTPUT_NANO_PK</code> Public key is a NANO wallet encoded base32 string
in	<i>message</i>	Message to be signed with Elliptic Curve Ed25519 with blake2b hash
in	<i>msg_len</i>	Size of message to be signed
in	<i>private_key</i>	Private key to sign message

Return values

<code>0</code>	If success, otherwise error.
----------------	------------------------------

See also

f_verify_signed_data() (p. ??)

5.7.5.34 f_verify_signed_block()

```
int f_verify_signed_block (
    F_BLOCK_TRANSFER * )
```

5.7.5.35 f_verify_signed_data()

```
int f_verify_signed_data (
    const unsigned char * signature,
    const unsigned char * message,
    size_t message_len,
    const void * public_key,
    uint32_t pk_type )
```

Verifies if a signed message is valid.

Parameters

in	<i>signature</i>	Signature of the <i>message</i>
in	<i>message</i>	Message to be verified
in	<i>message_len</i>	Length of the message
in	<i>public_key</i>	Public key to verify signed message
in	<i>pk_type</i>	Type of the public key. Types are: <ul style="list-style-type: none"> • <i>F_VERIFY_SIG_NANO_WALLET</i> Public key is a NANO wallet with <i>XRB</i> or <i>NANO</i> prefixes encoded base32 string • <i>F_VERIFY_SIG_RAW_HEX</i> Public key is raw 32 bytes data • <i>F_VERIFY_SIG_ASCII_HEX</i> Public key is a hex ASCII encoded string

Return value are

- Greater than zero if *signature* is VALID
- 0 (zero) if *signature* is INVALID
- Negative if ERROR occurred

See also

f_sign_data() (p. ??)

5.7.5.36 f_verify_token()

```
int f_verify_token (
    F_TOKEN signature,
    void * data,
    size_t data_sz,
    const char * password )
```

Verifies if a token is valid given data and password.

Parameters

in	<i>signature</i>	128 bit non deterministic token
in	<i>data</i>	Data to be signed in token
in	<i>data_sz</i>	Size of data
in	<i>password</i>	Password

Return values

0	On if invalid; 1 if valid ; less than zero if an error occurs
---	---

See also

f_generate_token() (p. ??)

5.7.5.37 f_verify_work()

```
int f_verify_work (
    uint64_t * result,
    const unsigned char * hash,
    uint64_t * work,
    uint64_t threshold )
```

Verifies if Proof of Work of a given *hash* is valid.

Parameters

out	<i>result</i>	Result of work. It can be NULL
in	<i>hash</i>	Input <i>hash</i> for verification
in	<i>work</i>	Work previously calculated to be checked
in	<i>threshold</i>	Input <i>threshold</i>

Return values

0	If is not valid or less than zero if error or greater than zero if is valid
---	---

See also

f_nano_pow() (p. ??)

5.7.5.38 f_write_seed()

```
f_write_seed_err f_write_seed (
    void * source_data,
    int source,
    uint8_t * seed,
    char * passwd )
```

Writes a SEED into a encrypted with password with non deterministic stream in memory or file.

Parameters

out	<i>source_data</i>	Memory pointer or file name
in	<i>source</i>	Source of output data: <ul style="list-style-type: none"> • <i>WRITE_SEED_TO_STREAM</i> Output data is a pointer to memory to store encrypted Nano SEED data • <i>WRITE_SEED_TO_FILE</i> Output is a string filename to store encrypted Nano SEED data
in	<i>seed</i>	Nano SEED to be stored in encrypted stream or file
in	<i>passwd</i>	(Mandatory) It can not be null string or NULL. See f_pass_must_have_at_least() (p. ??) function to check passwords strength

Return values

0	If Success, otherwise error
---	-----------------------------

See also

f_read_seed() (p. ??)

5.7.5.39 from_multiplier()

```
uint64_t from_multiplier (
    double multiplier,
    uint64_t base_difficulty )
```

Calculates a PoW given a multiplier and base difficulty.

Parameters

in	<i>multiplier</i>	Multiplier of the work
in	<i>base_difficulty</i>	Base difficulty Details here

See also

to_multiplier() (p. ??)

Return values

<i>Calculated</i>	value
-------------------	-------

5.7.5.40 is_nano_prefix()

```
int is_nano_prefix (
    const char * nano_wallet,
    const char * prefix )
```

Checks *prefix* in *nano_wallet*

Parameters

in	<i>nano_wallet</i>	Base32 Nano wallet encoded string
in	<i>prefix</i>	Prefix type <ul style="list-style-type: none"> • NANO_PREFIX for nano_ • XRB_PREFIX for xrb_

Return values

1	If <i>prefix</i> in <i>nano_wallet</i> , otherwise 0
---	--

5.7.5.41 is_null_hash()

```
int is_null_hash (
    uint8_t * hash )
```

Check if 32 bytes hash is filled with zeroes.

Parameters

in	<i>hash</i>	32 bytes binary <i>hash</i>
----	-------------	-----------------------------

Return values

1	If zero filled buffer, otherwise 0
---	------------------------------------

5.7.5.42 nano_base_32_2_hex()

```
int nano_base_32_2_hex (
    uint8_t * res,
    char * str_wallet )
```

Parse Nano Base32 wallet string to public key binary.

Parameters

out	<i>res</i>	Output raw binary public key
in	<i>str_wallet</i>	Valid Base32 encoded Nano string to be parsed

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

pk_to_wallet() (p. ??)

5.7.5.43 nano_create_block_dynamic()

```
int nano_create_block_dynamic (
    F_BLOCK_TRANSFER **,
    const void * ,
    size_t ,
    const void * ,
    size_t ,
    const void * ,
    size_t ,
    const void * ,
    const void * ,
    uint32_t ,
    const void * ,
    size_t ,
    int )
```

5.7.5.44 nano_create_p2pow_block_dynamic()

```
int nano_create_p2pow_block_dynamic (
    F_BLOCK_TRANSFER **,
    F_BLOCK_TRANSFER * ,
```

```

    const void * ,
    size_t ,
    const void * ,
    uint32_t ,
    const void * ,
    size_t )

```

5.7.5.45 pk_to_wallet()

```

int pk_to_wallet (
    char * out,
    char * prefix,
    NANO_PUBLIC_KEY_EXTENDED pubkey_extended )

```

Parse a Nano public key to Base32 Nano wallet string.

Parameters

out	<i>out</i>	Output string containing the wallet
in	<i>prefix</i>	Nano prefix. <i>NANO_PREFIX</i> for nano_ <i>XRB_PREFIX</i> for xrb_
in, out	<i>pubkey_extended</i>	Public key to be parsed to string

WARNING: *pubkey_extended* is destroyed when parsing to Nano base32 encoding

Return values

0	On Success, otherwise Error
---	-----------------------------

See also

nano_base_32_2_hex() (p. ??)

5.7.5.46 to_multiplier()

```

double to_multiplier (
    uint64_t difficulty,
    uint64_t base_difficulty )

```

Calculates a relative difficulty compared PoW with another.

Parameters

in	<i>difficulty</i>	Work difficulty
in	<i>base_difficulty</i>	Base difficulty Details here

See also

from_multiplier() (p. ??)

Return values

<i>Calculated</i>	value
-------------------	-------

5.7.5.47 valid_nano_wallet()

```
int valid_nano_wallet (
    const char * wallet )
```

Check if a string containing a Base32 Nano wallet is valid.

Parameters

in	<i>wallet</i>	Base32 Nano wallet encoded string
----	---------------	-----------------------------------

Return values

0	If valid wallet otherwise is invalid
---	--------------------------------------

5.7.5.48 valid_raw_balance()

```
int valid_raw_balance (
    const char * balance )
```

Checks if a string buffer pointed in *balance* is a valid raw balance.

Parameters

in	<i>balance</i>	Pointer containing a string buffer
----	----------------	------------------------------------

Return values

0	On Success, otherwise Error
---	-----------------------------

5.7.6 Variable Documentation

5.7.6.1 account

```
uint8_t account[32]
```

Account in raw binary data.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.7.6.2 balance

```
f_uint128_t balance
```

Big number 128 bit raw balance.

See also

f_uint128_t (p. ??)

Definition at line **268** of file **f_nano_crypto_util.h**.

5.7.6.3 body

```
F_NANO_WALLET_INFO_BODY body
```

Body of the file info.

Definition at line **268** of file **f_nano_crypto_util.h**.

5.7.6.4 desc

```
char desc[F_NANO_DESC_SZ]
```

Description.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.7.6.5 description

```
uint8_t description[F_DESC_SZ]
```

File description.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.7.6.6 file_info_integrity

```
uint8_t file_info_integrity[32]
```

File info integrity of the body block.

Definition at line **266** of file **f_nano_crypto_util.h**.

5.7.6.7 hash_sk_unencrypted

```
uint8_t hash_sk_unencrypted[32]
```

hash of Nano SEED when unencrypted

Definition at line **264** of file **f_nano_crypto_util.h**.

5.7.6.8 header

```
uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)]
```

Header magic.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.7.6.9 iv

```
uint8_t iv
```

Initial sub vector.

Initial vector of first encryption layer.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.7.6.10 last_used_wallet_number

```
uint32_t last_used_wallet_number
```

Last used wallet number.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.7.6.11 link

```
uint8_t link[32]
```

link or destination account

Definition at line **270** of file **f_nano_crypto_util.h**.

5.7.6.12 max_fee

```
char max_fee[F_RAW_STR_MAX_SZ]
```

Custom preferred max fee of Proof of Work.

Definition at line **264** of file **f_nano_crypto_util.h**.

5.7.6.13 nano_hdr

```
uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)]
```

Header of the file.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.7.6.14 nanoseed_hash

```
uint8_t nanoseed_hash[32]
```

Nano SEED hash file.

Definition at line **264** of file **f_nano_crypto_util.h**.

5.7.6.15 preamble

```
uint8_t preamble[32]
```

Block preamble.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.7.6.16 `prefixes`

```
uint8_t prefixes
```

Internal use for this API.

Definition at line **274** of file `f_nano_crypto_util.h`.

5.7.6.17 `previous`

```
uint8_t previous[32]
```

Previous block.

Definition at line **262** of file `f_nano_crypto_util.h`.

5.7.6.18 `representative`

```
uint8_t representative[32]
```

Representative for current account.

Definition at line **264** of file `f_nano_crypto_util.h`.

5.7.6.19 `reserved`

```
uint8_t reserved
```

Reserved (not used)

Reserved.

Definition at line **262** of file `f_nano_crypto_util.h`.

5.7.6.20 `salt`

```
uint8_t salt[32]
```

Salt of the first encryption layer.

Definition at line **264** of file `f_nano_crypto_util.h`.

5.7.6.21 seed_block

```
F_ENCRYPTED_BLOCK seed_block
```

Second encrypted block for Nano SEED.

Definition at line **268** of file **f_nano_crypto_util.h**.

5.7.6.22 signature

```
uint8_t signature[64]
```

Signature of the block.

Definition at line **272** of file **f_nano_crypto_util.h**.

5.7.6.23 sk_encrypted

```
uint8_t sk_encrypted[32]
```

Secret.

SEED encrypted (second layer)

Definition at line **266** of file **f_nano_crypto_util.h**.

5.7.6.24 sub_salt

```
uint8_t sub_salt[32]
```

Salt of the sub block to be stored.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.7.6.25 ver

```
uint32_t ver
```

Version of the file.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.7.6.26 version

```
uint16_t version
```

Version.

Definition at line **260** of file **f_nano_crypto_util.h**.

5.7.6.27 wallet_prefix

```
uint8_t wallet_prefix
```

Wallet prefix: 0 for NANO; 1 for XRB.

Definition at line **258** of file **f_nano_crypto_util.h**.

5.7.6.28 wallet_representative

```
char wallet_representative[ MAX_STR_NANO_CHAR]
```

Wallet representative.

Definition at line **262** of file **f_nano_crypto_util.h**.

5.7.6.29 work

```
uint64_t work
```

Internal use for this API.

Definition at line **276** of file **f_nano_crypto_util.h**.

5.8 f_nano_crypto_util.h

```

00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00008 #include <errors.h>
00009 #include <stdint.h>
00010 #include <f_util.h>
00011 #include <f_bitcoin.h>
00012
00013 #ifndef F_DOC_SKIP
00014     #ifdef F_XTENZA
00015     #ifdef F_ESP32
00016         #define F_ESP32
00017     #endif
00018     #include "esp_system.h"
00019 #endif
00020
00021 #include "sodium/crypto_generichash.h"
00022 #include "sodium/crypto_sign.h"
00023 #include "sodium.h"
00024
00025 #ifdef F_ESP32
00026     #include "sodium/private/curve25519_ref10.h"
00027 #else
00028     #include "sodium/private/ed25519_ref10.h"
00029
00030     #define ge_p3 ge25519_p3
00031     #define sc_reduce sc25519_reduce
00032     #define sc_muladd sc25519_muladd
00033     #define ge_scalarmult_base ge25519_scalarmult_base
00034     #define ge_p3_tobytes ge25519_p3_tobytes
00035 #endif
00036
00037 #endif
00038
00039 #ifdef __cplusplus
00040 extern "C" {
00041 #endif
00042
00043 #define F_NANO_POW_MAX_THREAD (size_t)10
00044
00045 #ifndef F_DOC_SKIP
00046     #ifdef F_ESP32
00047         #undef F_NANO_POW_MAX_THREAD
00048     #endif
00049 #endif
00050
00051 #define MAX_STR_NANO_CHAR (size_t)70 //5+56+8+1
00052
00053 #define PUB_KEY_EXTENDED_MAX_LEN (size_t)40
00054
00055 #define NANO_PREFIX "nano_"
00056
00057 #define XRB_PREFIX "xrb_"
00058
00059 #ifdef F_ESP32
00060     #define BIP39_DICTIONARY "/spiffs/dictionary.dic"
00061 #else
00062     #ifndef F_DOC_SKIP
00063         #define BIP39_DICTIONARY_SAMPLE ".././dictionary.dic"
00064         #define BIP39_DICTIONARY "dictionary.dic"
00065     #endif
00066 #endif
00067
00068 #define NANO_ENCRYPTED_SEED_FILE "/spiffs/secure/nano.nse"
00069
00070 #define NANO_PASSWD_MAX_LEN (size_t)80
00071
00072 #define STR_NANO_SZ (size_t)66// 65+1 Null included

```

```

00205
00210 #define NANO_FILE_WALLETS_INFO "/spiffs/secure/walletsinfo.i"
00211
00216 typedef uint8_t F_TOKEN[16];
00217
00222 typedef uint8_t NANO_SEED[crypto_sign_SEEDBYTES];
00223
00228 typedef uint8_t f_uint128_t[16];
00229
00230 #ifndef F_DOC_SKIP
00231 #define EXPORT_KEY_TO_CHAR_SZ (size_t)sizeof(NANO_SEED)+1
00232 #endif
00233
00238 typedef uint8_t NANO_PRIVATE_KEY[sizeof(NANO_SEED)];
00239
00244 typedef uint8_t NANO_PRIVATE_KEY_EXTENDED[crypto_sign_ed25519_SECRETKEYBYTES];
00245
00250 typedef uint8_t NANO_PUBLIC_KEY[crypto_sign_ed25519_PUBLICKEYBYTES];
00251
00256 typedef uint8_t NANO_PUBLIC_KEY_EXTENDED[PUB_KEY_EXTENDED_MAX_LEN];
00257
00266 typedef struct f_block_transfer_t {
00268     uint8_t preamble[32];
00270     uint8_t account[32];
00272     uint8_t previous[32];
00274     uint8_t representative[32];
00278     f_uint128_t balance;
00280     uint8_t link[32];
00282     uint8_t signature[64];
00284     uint8_t prefixes;
00286     uint64_t work;
00287 } __attribute__((packed)) F_BLOCK_TRANSFER;
00288
00289 #define F_BLOCK_TRANSFER_SIZE (size_t)sizeof(F_BLOCK_TRANSFER)
00290 #define F_P2POW_BLOCK_TRANSFER_SIZE 2*F_BLOCK_TRANSFER_SIZE
00291
00292 #ifndef F_DOC_SKIP
00293 #define F_BLOCK_TRANSFER_SIGNABLE_SZ
00294     (size_t)(sizeof(F_BLOCK_TRANSFER)-64-sizeof(uint64_t)-sizeof(uint8_t))
00295 #endif
00295
00303 typedef enum f_nano_err_t {
00305     NANO_ERR_OK=0,
00307     NANO_ERR_CANT_PARSE_BN_STR=5151,
00309     NANO_ERR_MALLOC,
00311     NANO_ERR_CANT_PARSE_FACTOR,
00313     NANO_ERR_MPI_MULT,
00315     NANO_ERR_CANT_PARSE_TO_BLK_TRANSFER,
00317     NANO_ERR_EMPTY_STR,
00319     NANO_ERR_CANT_PARSE_VALUE,
00321     NANO_ERR_PARSE_MPI_TO_STR,
00323     NANO_ERR_CANT_COMPLETE_NULL_CHAR,
00325     NANO_ERR_CANT_PARSE_TO_MPI,
00327     NANO_ERR_INSUFFICIENT_FUNDS,
00329     NANO_ERR_SUB_MPI,
00331     NANO_ERR_ADD_MPI,
00333     NANO_ERR_NO_SENSE_VALUE_TO_SEND_NEGATIVE,
00335     NANO_ERR_NO_SENSE_VALUE_TO_SEND_ZERO,
00337     NANO_ERR_NO_SENSE_BALANCE_NEGATIVE,
00339     NANO_ERR_VAL_A_INVALID_MODE,
00341     NANO_ERR_CANT_PARSE_TO_TEMP_UINT128_T,
00343     NANO_ERR_VAL_B_INVALID_MODE,
00345     NANO_ERR_CANT_PARSE_RAW_A_TO_MPI,
00347     NANO_ERR_CANT_PARSE_RAW_B_TO_MPI,
00349     NANO_ERR_UNKNOWN_ADD_SUB_MODE,
00351     NANO_ERR_INVALID_RES_OUTPUT
00352 } f_nano_err;
00353
00354 #ifndef F_DOC_SKIP
00355
00356 #define READ_SEED_FROM_STREAM (int)1
00357 #define READ_SEED_FROM_FILE (int)2
00358 #define WRITE_SEED_TO_STREAM (int)4
00359 #define WRITE_SEED_TO_FILE (int)8
00360 #define PARSE_JSON_READ_SEED_GENERIC (int)16
00361 #define F_STREAM_DATA_FILE_VERSION (uint32_t)((1<<16)|0)
00362
00363 #endif
00364
00372 typedef struct f_nano_encrypted_wallet_t {
00374     uint8_t sub_salt[32];
00376     uint8_t iv[16];
00378     uint8_t reserved[16];
00380     uint8_t hash_sk_unencrypted[32];
00382     uint8_t sk_encrypted[32];
00383 } __attribute__((packed)) F_ENCRYPTED_BLOCK;
00384

```

```

00385 #ifndef F_DOC_SKIP
00386
00387 static const uint8_t NANO_WALLET_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't', 'f',
'i', 'l', 'e', '_'};
00388 #define F_NANO_FILE_DESC "NANO Seed Encrypted file/stream. Keep it safe and backup it. This file is
protected by password. BUY BITCOIN and NANO !!!"
00389 #define F_DESC_SZ (size_t) (160-sizeof(uint32_t))
00390
00391 #endif
00392
00400 typedef struct f_nano_crypto_wallet_t {
00402     uint8_t nano_hdr[sizeof(NANO_WALLET_MAGIC)];
00404     uint32_t ver;
00406     uint8_t description[F_DESC_SZ];
00408     uint8_t salt[32];
00410     uint8_t iv[16];
00412     F_ENCRYPTED_BLOCK seed_block;
00413 } __attribute__((packed)) F_NANO_CRYPTOWALLET;
00414
00415 #ifndef F_DOC_SKIP
00416
00417 _Static_assert((sizeof(F_NANO_CRYPTOWALLET)&0x1F)==0, "Error 1");
00418 _Static_assert((sizeof(F_ENCRYPTED_BLOCK)&0x1F)==0, "Error 2");
00419
00420 #endif
00421
00426 #define REP_XRB (uint8_t)0x4
00427
00432 #define SENDER_XRB (uint8_t)0x02
00433
00438 #define DEST_XRB (uint8_t)0x01
00439
00440 typedef enum f_write_seed_err_t {
00442     WRITE_ERR_OK=0,
00444     WRITE_ERR_NULL_PASSWORD=7180,
00446     WRITE_ERR_EMPTY_STRING,
00448     WRITE_ERR_MALLOC,
00450     WRITE_ERR_ENCRYPT_PRIV_KEY,
00452     WRITE_ERR_GEN_SUB_PRIV_KEY,
00454     WRITE_ERR_GEN_MAIN_PRIV_KEY,
00456     WRITE_ERR_ENCRYPT_SUB_BLOCK,
00458     WRITE_ERR_UNKNOWN_OPTION,
00460     WRITE_ERR_FILE_ALREADY_EXISTS,
00462     WRITE_ERR_CREATING_FILE,
00464     WRITE_ERR_WRITING_FILE
00465 } f_write_seed_err;
00466
00467 #ifndef F_DOC_SKIP
00468
00469 #define F_RAW_TO_STR_UINT128 (int)1
00470 #define F_RAW_TO_STR_STRING (int)2
00471 #define F_RAW_STR_MAX_SZ (size_t)41 // 39 + '\0' + '.' -> 39 = log10(2^128)
00472 #define F_MAX_STR_RAW_BALANCE_MAX (size_t)40 //39+'\0'
00473 #define F_NANO_EMPTY_BALANCE "0.0"
00474
00475 #endif
00476
00484 typedef struct f_nano_wallet_info_bdy_t {
00486     uint8_t wallet_prefix; // 0 for NANO; 1 for XRB
00488     uint32_t last_used_wallet_number;
00490     char wallet_representative[MAX_STR_NANO_CHAR];
00492     char max_fee[F_RAW_STR_MAX_SZ];
00494     uint8_t reserved[44];
00495 } __attribute__((packed)) F_NANO_WALLET_INFO_BODY;
00496
00497 #ifndef F_DOC_SKIP
00498
00499 _Static_assert((sizeof(F_NANO_WALLET_INFO_BODY)&0x1F)==0, "Error F_NANO_WALLET_INFO_BODY is not byte
aligned");
00500
00501 #define F_NANO_WALLET_INFO_DESC "Nano file descriptor used for fast custom access. BUY BITCOIN AND NANO."
00502 #define F_NANO_WALLET_INFO_VERSION (uint16_t)((1<<8)|1)
00503 static const uint8_t F_NANO_WALLET_INFO_MAGIC[] = {'_', 'n', 'a', 'n', 'o', 'w', 'a', 'l', 'l', 'e', 't',
'i', 'l', 'e', '_'};
00504
00505 #define F_NANO_DESC_SZ (size_t)78
00506
00507 #endif
00508
00516 typedef struct f_nano_wallet_info_t {
00518     uint8_t header[sizeof(F_NANO_WALLET_INFO_MAGIC)];
00520     uint16_t version;
00522     char desc[F_NANO_DESC_SZ];
00524     uint8_t nanoseed_hash[32];
00526     uint8_t file_info_integrity[32];
00528     F_NANO_WALLET_INFO_BODY body;
00529 } __attribute__((packed)) F_NANO_WALLET_INFO;

```

```

00530
00531 #ifndef F_DOC_SKIP
00532
00533 _Static_assert((sizeof(F_NANO_WALLET_INFO)&0x1F)==0, "Error F_NANO_WALLET_INFO is not byte aligned");
00534
00535 #endif
00536
00544 typedef enum f_file_info_err_t {
00546     F_FILE_INFO_ERR_OK=0,
00548     F_FILE_INFO_ERR_CANT_OPEN_INFO_FILE=7001,
00550     F_FILE_INFO_ERR_NANO_SEED_ENCRYPTED_FILE_NOT_FOUND,
00552     F_FILE_INFO_ERR_CANT_DELETE_NANO_INFO_FILE,
00554     F_FILE_INFO_ERR_MALLOC,
00556     F_FILE_INFO_ERR_CANT_READ_NANO_SEED_ENCRYPTED_FILE,
00558     F_FILE_INFO_ERR_CANT_READ_INFO_FILE,
00560     F_FILE_INFO_INVALID_HEADER_FILE,
00562     F_FILE_INFO_ERR_INVALID_SHA256_INFO_FILE,
00564     F_FILE_INFO_ERR_NANO_SEED_HASH_FAIL,
00566     F_FILE_INFO_ERR_NANO_INVALID_REPRESENTATIVE,
00568     F_FILE_INFO_ERR_NANO_INVALID_MAX_FEE_VALUE,
00570     F_FILE_INFO_ERR_OPEN_FOR_WRITE_INFO,
00572     F_FILE_INFO_ERR_EXISTING_FILE,
00574     F_FILE_INFO_ERR_CANT_WRITE_FILE_INFO
00575 } F_FILE_INFO_ERR;
00576
00577 #ifndef F_DOC_SKIP
00578
00579 #define F_NANO_ADD_A_B (uint32_t)(1<<0)
00580 #define F_NANO_SUB_A_B (uint32_t)(1<<1)
00581 #define F_NANO_A_RAW_128 (uint32_t)(1<<2)
00582 #define F_NANO_A_RAW_STRING (uint32_t)(1<<3)
00583 #define F_NANO_A_REAL_STRING (uint32_t)(1<<4)
00584 #define F_NANO_B_RAW_128 (uint32_t)(1<<5)
00585 #define F_NANO_B_RAW_STRING (uint32_t)(1<<6)
00586 #define F_NANO_B_REAL_STRING (uint32_t)(1<<7)
00587 #define F_NANO_RES_RAW_128 (uint32_t)(1<<8)
00588 #define F_NANO_RES_RAW_STRING (uint32_t)(1<<9)
00589 #define F_NANO_RES_REAL_STRING (uint32_t)(1<<10)
00590 #define F_NANO_C_RAW_128 (uint32_t)(F_NANO_B_RAW_128<<16)
00591 #define F_NANO_C_RAW_STRING (uint32_t)(F_NANO_B_RAW_STRING<<16)
00592 #define F_NANO_C_REAL_STRING (uint32_t)(F_NANO_B_REAL_STRING<<16)
00593
00594 #define F_NANO_COMPARE_EQ (uint32_t)(1<<16) //Equal
00595 #define F_NANO_COMPARE_LT (uint32_t)(1<<17) // Lesser than
00596 #define F_NANO_COMPARE_LEQ (F_NANO_COMPARE_LT|F_NANO_COMPARE_EQ) // Less or equal
00597 #define F_NANO_COMPARE_GT (uint32_t)(1<<18) // Greater
00598 #define F_NANO_COMPARE_GEQ (F_NANO_COMPARE_GT|F_NANO_COMPARE_EQ) // Greater or equal
00599 #define DEFAULT_MAX_FEE "0.001"
00600
00601 #endif
00602
00603 #ifndef F_ESP32
00604 typedef enum f_nano_create_block_dyn_err_t {
00605     NANO_CREATE_BLK_DYN_OK = 0,
00606     NANO_CREATE_BLK_DYN_BLOCK_NULL = 8000,
00607     NANO_CREATE_BLK_DYN_ACCOUNT_NULL,
00608     // NANO_CREATE_BLK_DYN_PREV_NULL,
00609     NANO_CREATE_BLK_DYN_COMPARE_BALANCE,
00610     NANO_CREATE_BLK_DYN_GENESIS_WITH_NON_EMPTY_BALANCE,
00611     NANO_CREATE_BLK_DYN_CANT_SEND_IN_GENESIS_BLOCK,
00612     NANO_CREATE_BLK_DYN_REP_NULL,
00613     NANO_CREATE_BLK_DYN_BALANCE_NULL,
00614     NANO_CREATE_BLK_DYN_SEND_RECEIVE_NULL,
00615     NANO_CREATE_BLK_DYN_LINK_NULL,
00616     NANO_CREATE_BLK_DYN_BUF_MALLOC,
00617     NANO_CREATE_BLK_DYN_MALLOC,
00618     NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_SZ,
00619     NANO_CREATE_BLK_DYN_WRONG_PREVIOUS_STR_SZ,
00620     NANO_CREATE_BLK_DYN_PARSE_STR_HEX_ERR,
00621     NANO_CREATE_BLK_DYN_FORBIDDEN_AMOUNT_TYPE,
00622     NANO_CREATE_BLK_DYN_COMPARE,
00623     NANO_CREATE_BLK_DYN_EMPTY_VAL_TO_SEND_OR_REC,
00624     NANO_CREATE_BLK_DYN_INVALID_DIRECTION_OPTION
00625 } F_NANO_CREATE_BLOCK_DYN_ERR;
00626
00627 typedef enum f_nano_p2pow_block_dyn_err_t {
00628     NANO_P2POW_CREATE_BLOCK_OK = 0,
00629     NANO_P2POW_CREATE_BLOCK_INVALID_USER_BLOCK = 8400,
00630     NANO_P2POW_CREATE_BLOCK_MALLOC,
00631     NANO_P2POW_CREATE_BLOCK_NULL,
00632     NANO_P2POW_CREATE_OUTPUT,
00633     NANO_P2POW_CREATE_OUTPUT_MALLOC
00634 } F_NANO_P2POW_BLOCK_DYN_ERR;
00635
00636 #endif
00637
00649 double to_multiplier(uint64_t, uint64_t);

```

```
00650
00662 uint64_t from_multiplier(double, uint64_t);
00663
00673 void f_set_dictionary_path(const char *);
00674
00682 char *f_get_dictionary_path(void);
00683
00696 int f_generate_token(F_TOKEN, void *, size_t, const char *);
00697
00710 int f_verify_token(F_TOKEN, void *, size_t, const char *);
00711
00734 int f_cloud_crypto_wallet_nano_create_seed(size_t, char *, char *);
00735
00748 int f_generate_nano_seed(NANO_SEED, uint32_t);
00749
00764 int pk_to_wallet(char *, char *, NANO_PUBLIC_KEY_EXTENDED);
00765
00783 int f_seed_to_nano_wallet(NANO_PRIVATE_KEY, NANO_PUBLIC_KEY, NANO_SEED, uint32_t);
00784
00794 int f_nano_is_valid_block(F_BLOCK_TRANSFER *);
00795
00808 int f_nano_block_to_json(char *, size_t *, size_t, F_BLOCK_TRANSFER *);
00809
00820 int f_nano_get_block_hash(uint8_t *, F_BLOCK_TRANSFER *);
00821
00833 int f_nano_get_p2pow_block_hash(uint8_t *, uint8_t *, F_BLOCK_TRANSFER *);
00834
00847 int f_nano_p2pow_to_JSON(char *, size_t *, size_t, F_BLOCK_TRANSFER *);
00848
00858 char *f_nano_key_to_str(char *, unsigned char *);
00859
00878 int f_nano_seed_to_bip39(char *, size_t, size_t *, NANO_SEED, char *);
00879
00894 int f_bip39_to_nano_seed(uint8_t *, char *, char *);
00895
00917 int f_parse_nano_seed_and_bip39_to_JSON(char *, size_t, size_t *, void *, int, const char *);
00918
00936 int f_read_seed(uint8_t *, const char *, void *, int, int);
00937
00952 int f_nano_raw_to_string(char *, size_t *, size_t, void *, int);
00953
00962 int f_nano_valid_nano_str_value(const char *);
00963
00971 int valid_nano_wallet(const char *);
00972
00982 int nano_base_32_2_hex(uint8_t *, char *);
00983
00998 int f_nano_transaction_to_JSON(char *, size_t, size_t *, NANO_PRIVATE_KEY_EXTENDED, F_BLOCK_TRANSFER *);
00999
01007 int valid_raw_balance(const char *);
01008
01016 int is_null_hash(uint8_t *);
01017
01029 int is_nano_prefix(const char *, const char *);
01030
01039 F_FILE_INFO_ERR f_get_nano_file_info(F_NANO_WALLET_INFO *);
01040
01050 F_FILE_INFO_ERR f_set_nano_file_info(F_NANO_WALLET_INFO *, int);
01051
01073 f_nano_err f_nano_value_compare_value(void *, void *, uint32_t *);
01074
01095 f_nano_err f_nano_verify_nano_funds(void *, void *, void *, uint32_t);
01096
01106 f_nano_err f_nano_parse_raw_str_to_raw128_t(uint8_t *, const char *);
01107
01117 f_nano_err f_nano_parse_real_str_to_raw128_t(uint8_t *, const char *);
01118
01141 f_nano_err f_nano_add_sub(void *, void *, void *, uint32_t);
01142
01153 int f_nano_sign_block(F_BLOCK_TRANSFER *, F_BLOCK_TRANSFER *, NANO_PRIVATE_KEY_EXTENDED);
01154
01168 f_write_seed_err f_write_seed(void *, int, uint8_t *, char *);
01169
01182 f_nano_err f_nano_balance_to_str(char *, size_t, size_t *, f_uint128_t);
01183
01184
01189 #define F_BRAIN_WALLET_VERY_POOR (uint32_t)0
01190
01195 #define F_BRAIN_WALLET_POOR (uint32_t)1
01196
01201 #define F_BRAIN_WALLET_VERY_BAD (uint32_t)2
01202
01207 #define F_BRAIN_WALLET_BAD (uint32_t)3
01208
01213 #define F_BRAIN_WALLET_VERY_WEAK (uint32_t)4
01214
01219 #define F_BRAIN_WALLET_WEAK (uint32_t)5
```

```

01220
01225 #define F_BRAIN_WALLET_STILL_WEAK (uint32_t)6
01226
01231 #define F_BRAIN_WALLET_MAYBE_GOOD (uint32_t)7
01232
01233
01238 #define F_BRAIN_WALLET_GOOD (uint32_t)8
01239
01244 #define F_BRAIN_WALLET_VERY_GOOD (uint32_t)9
01245
01250 #define F_BRAIN_WALLET_NICE (uint32_t)10
01251
01256 #define F_BRAIN_WALLET_PERFECT (uint32_t)11
01257
01284 int f_extract_seed_from_brainwallet(uint8_t *, char **, uint32_t, const char *, const char *);
01285
01297 int f_verify_work(uint64_t *, const unsigned char *, uint64_t *, uint64_t);
01298
01304 #define F_SIGNATURE_RAW (uint32_t)1
01305
01311 #define F_SIGNATURE_STRING (uint32_t)2
01312
01318 #define F_SIGNATURE_OUTPUT_RAW_PK (uint32_t)4
01319
01325 #define F_SIGNATURE_OUTPUT_STRING_PK (uint32_t)8
01326
01332 #define F_SIGNATURE_OUTPUT_XRB_PK (uint32_t)16
01333
01339 #define F_SIGNATURE_OUTPUT_NANO_PK (uint32_t)32
01340
01346 #define F_IS_SIGNATURE_RAW_HEX_STRING (uint32_t)64
01347
01353 #define F_MESSAGE_IS_HASH_STRING (uint32_t)128
01354
01359 #define F_DEFAULT_THRESHOLD (uint64_t) 0xffffffffc000000000
01360
01384 int f_sign_data(
01385     unsigned char *signature,
01386     void *out_public_key,
01387     uint32_t output_type,
01388     const unsigned char *message,
01389     size_t msg_len,
01390     const unsigned char *private_key);
01391
01397 #define F_VERIFY_SIG_NANO_WALLET (uint32_t)1
01398
01404 #define F_VERIFY_SIG_RAW_HEX (uint32_t)2
01405
01411 #define F_VERIFY_SIG_ASCII_HEX (uint32_t)4
01412
01433 int f_verify_signed_data(const unsigned char *, const unsigned char *, size_t, const void *, uint32_t);
01434
01444 int f_is_valid_nano_seed_encrypted(void *, size_t, int);
01445
01446 #ifndef F_ESP32
01447
01448 #define F_BALANCE_RAW_128 F_NANO_A_RAW_128
01449 #define F_BALANCE_REAL_STRING F_NANO_A_REAL_STRING
01450 #define F_BALANCE_RAW_STRING F_NANO_A_RAW_STRING
01451 #define F_VALUE_SEND_RECEIVE_RAW_128 F_NANO_B_RAW_128
01452 #define F_VALUE_SEND_RECEIVE_REAL_STRING F_NANO_B_REAL_STRING
01453 #define F_VALUE_SEND_RECEIVE_RAW_STRING F_NANO_B_RAW_STRING
01454 #define F_VALUE_TO_SEND (int) (1<<0)
01455 #define F_VALUE_TO_RECEIVE (int) (1<<1)
01456
01457 int nano_create_block_dynamic(
01458     F_BLOCK_TRANSFER **,
01459     const void *,
01460     size_t,
01461     const void *,
01462     size_t,
01463     const void *,
01464     size_t,
01465     const void *,
01466     const void *,
01467     uint32_t,
01468     const void *,
01469     size_t,
01470     int
01471 );
01472
01473 int nano_create_p2pow_block_dynamic(
01474     F_BLOCK_TRANSFER **,
01475     F_BLOCK_TRANSFER *,
01476     const void *,
01477     size_t,
01478     const void *,

```

```

01479     uint32_t,
01480     const void *,
01481     size_t
01482 );
01483
01484 int f_verify_signed_block(F_BLOCK_TRANSFER *);
01485
01486 int f_nano_pow(uint64_t *, unsigned char *, const uint64_t, int);
01499 #endif
01500
01501 #ifdef __cplusplus
01502 }
01503 #endif
01504

```

5.9 f_util.h File Reference

```

#include <stdint.h>
#include "mbedtls/sha256.h"
#include "mbedtls/aes.h"
#include "mbedtls/ecdsa.h"

```

Macros

- #define **F_ENTROPY_TYPE_PARANOIC** (uint32_t)1477682819
- #define **F_ENTROPY_TYPE_EXCELENT** (uint32_t)1476885281
- #define **F_ENTROPY_TYPE_GOOD** (uint32_t)1472531015
- #define **F_ENTROPY_TYPE_NOT_ENOUGH** (uint32_t)1471001808
- #define **F_ENTROPY_TYPE_NOT_RECOMENDED** (uint32_t)1470003345
- #define **ENTROPY_BEGIN** f_verify_system_entropy_begin();
- #define **ENTROPY_END** f_verify_system_entropy_finish();
- #define **F_PASS_MUST_HAVE_AT_LEAST_NONE** (int)0
- #define **F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER** (int)1
- #define **F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL** (int)2
- #define **F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE** (int)4
- #define **F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE** (int)8
- #define **F_PASS_IS_TOO_LONG** (int)256
- #define **F_PASS_IS_TOO_SHORT** (int)512
- #define **F_PASS_IS_OUT_OVF** (int)1024
- #define **F_GET_CH_MODE_NO_ECHO** (int)(1<<16)
- #define **F_GET_CH_MODE_ANY_KEY** (int)(1<<17)

Typedefs

- typedef void(* **rnd_fn**) (void *, size_t)
- typedef int(* **fn_det**) (void *, unsigned char *, size_t)

Functions

- int **f_verify_system_entropy** (uint32_t, void *, size_t, int)
- int **f_pass_must_have_at_least** (char *, size_t, size_t, size_t, int)
- int **f_passwd_comp_safe** (char *, char *, size_t, size_t, size_t)
- char * **f_get_entropy_name** (uint32_t)
- uint32_t **f_sel_to_entropy_level** (int)
- int **f_str_to_hex** (uint8_t *, char *)
- void **f_random_attach** (rnd_fn)
- void **f_random** (void *, size_t)
- int **get_console_passwd** (char *, size_t)
- int **f_get_char_no_block** (int)
- int **f_convert_to_long_int** (unsigned long int *, char *, size_t)
- int **f_convert_to_unsigned_int** (unsigned int *, char *, size_t)
- int **f_convert_to_long_int0x** (unsigned long int *, char *, size_t)
- int **f_convert_to_long_int0** (unsigned long int *, char *, size_t)
- int **f_convert_to_long_int_std** (unsigned long int *, char *, size_t)
- void * **f_is_random_attached** ()
- void **f_random_detach** ()
- int **f_convert_to_unsigned_int0x** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_unsigned_int0** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_unsigned_int_std** (unsigned int *val, char *value, size_t value_sz)
- int **f_convert_to_double** (double *, const char *)
- uint32_t **crc32_init** (unsigned char *, size_t, uint32_t)
- int **f_reverse** (unsigned char *, size_t)
- f_md_hmac_sha512 **f_hmac_sha512** (unsigned char *, const unsigned char *, size_t, const unsigned char *, size_t)
- int **f_ecdsa_secret_key_valid** (mbedtls_ecp_group_id, unsigned char *, size_t)
- int **f_ecdsa_public_key_valid** (mbedtls_ecp_group_id, unsigned char *, size_t)
- f_ecdsa_key_pair_err **f_gen_ecdsa_key_pair** (f_ecdsa_key_pair *, int, **fn_det**, void *)
- int **f_uncompress_elliptic_curve** (uint8_t *, size_t, size_t *, mbedtls_ecp_group_id, uint8_t *, size_t)
- uint8_t * **f_ripemd160** (const uint8_t *, size_t)
- int **f_url_encode** (char *, size_t, size_t *, uint8_t *, size_t)
- int **f_encode_to_base64_dynamic** (char **, size_t *, void *, size_t)
- int **f_base64_decode_dynamic** (void **, size_t *, const char *, size_t)
- int **f_base64url_encode_dynamic** (void **, size_t *, void *, size_t)
- int **f_encode_to_base64** (char *, size_t, size_t *, void *, size_t)
- int **f_base64url_encode** (char *, size_t, size_t *, void *, size_t)
- int **f_base64url_decode** (void *, size_t, size_t *, const char *, size_t)
- int **f_url_base64_to_base64_dynamic** (char **, size_t *, const char *, size_t)

5.9.1 Detailed Description

This ABI is a utility for myNanoEmbedded library and sub routines are implemented here.

Definition in file **f_util.h**.

5.9.2 Macro Definition Documentation

5.9.2.1 ENTROPY_BEGIN

```
#define ENTROPY_BEGIN f_verify_system_entropy_begin();
```

Begins and prepares a entropy function.

See also

f_verify_system_entropy() (p. ??)

Definition at line **153** of file **f_util.h**.

5.9.2.2 ENTROPY_END

```
#define ENTROPY_END f_verify_system_entropy_finish();
```

Ends a entropy function.

See also

f_verify_system_entropy() (p. ??)

Definition at line **160** of file **f_util.h**.

5.9.2.3 F_ENTROPY_TYPE_EXCELENT

```
#define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
```

Type of the excelent entropy used for verifier.

Slow

Definition at line **125** of file **f_util.h**.

5.9.2.4 F_ENTROPY_TYPE_GOOD

```
#define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
```

Type of the good entropy used for verifier.

Not so slow

Definition at line **132** of file **f_util.h**.

5.9.2.5 F_ENTROPY_TYPE_NOT_ENOUGH

```
#define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
```

Type of the moderate entropy used for verifier.

Fast

Definition at line **139** of file **f_util.h**.

5.9.2.6 F_ENTROPY_TYPE_NOT_RECOMENDED

```
#define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
```

Type of the not recommended entropy used for verifier.

Very fast

Definition at line **146** of file **f_util.h**.

5.9.2.7 F_ENTROPY_TYPE_PARANOIC

```
#define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
```

Type of the very excelent entropy used for verifier.

Very slow

Definition at line **118** of file **f_util.h**.

5.9.2.8 F_GET_CH_MODE_ANY_KEY

```
#define F_GET_CH_MODE_ANY_KEY (int) (1<<17)
```

See also

f_get_char_no_block() (p. ??)

Definition at line **375** of file **f_util.h**.

5.9.2.9 F_GET_CH_MODE_NO_ECHO

```
#define F_GET_CH_MODE_NO_ECHO (int) (1<<16)
```

See also

f_get_char_no_block() (p. ??)

Definition at line **369** of file **f_util.h**.

5.9.2.10 F_PASS_IS_OUT_OVF

```
#define F_PASS_IS_OUT_OVF (int) 1024
```

Password is overflow and cannot be stored.

Definition at line **208** of file **f_util.h**.

5.9.2.11 F_PASS_IS_TOO_LONG

```
#define F_PASS_IS_TOO_LONG (int) 256
```

Password is too long.

Definition at line **196** of file **f_util.h**.

5.9.2.12 F_PASS_IS_TOO_SHORT

```
#define F_PASS_IS_TOO_SHORT (int) 512
```

Password is too short.

Definition at line **202** of file **f_util.h**.

5.9.2.13 F_PASS_MUST_HAVE_AT_LEAST_NONE

```
#define F_PASS_MUST_HAVE_AT_LEAST_NONE (int) 0
```

Password does not need any criteria to pass.

Definition at line **166** of file **f_util.h**.

5.9.2.14 F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
```

Password must have at least one lower case.

Definition at line **190** of file **f_util.h**.

5.9.2.15 F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
```

Password must have at least one number.

Definition at line **172** of file **f_util.h**.

5.9.2.16 F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
```

Password must have at least one symbol.

Definition at line **178** of file **f_util.h**.

5.9.2.17 F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE

```
#define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
```

Password must have at least one upper case.

Definition at line **184** of file **f_util.h**.

5.9.3 Typedef Documentation

5.9.3.1 fn_det

```
typedef int(* fn_det) (void *, unsigned char *, size_t)
```

Definition at line **539** of file **f_util.h**.

5.9.3.2 rnd_fn

`rnd_fn`

Pointer caller for random function.

Definition at line **334** of file **f_util.h**.

5.9.4 Function Documentation

5.9.4.1 crc32_init()

```
uint32_t crc32_init (
    unsigned char * p,
    size_t len,
    uint32_t crcinit )
```

Performs a CRC32 of a given data.

Parameters

in	<i>p</i>	Pointer of the data
in	<i>len</i>	Size of data in pointer <i>p</i>
in	<i>crcinit</i>	Init vector of the CRC32

Return values

<i>CRC32</i>	hash
--------------	------

5.9.4.2 f_base64_decode_dynamic()

```
int f_base64_decode_dynamic (
    void ** ,
    size_t * ,
    const char * ,
    size_t )
```

5.9.4.3 f_base64url_decode()

```
int f_base64url_decode (
    void * ,
```

```
size_t ,  
size_t * ,  
const char * ,  
size_t )
```

5.9.4.4 f_base64url_encode()

```
int f_base64url_encode (  
    char * ,  
    size_t ,  
    size_t * ,  
    void * ,  
    size_t )
```

5.9.4.5 f_base64url_encode_dynamic()

```
int f_base64url_encode_dynamic (  
    void ** ,  
    size_t * ,  
    void * ,  
    size_t )
```

5.9.4.6 f_convert_to_double()

```
int f_convert_to_double (  
    double * val,  
    const char * value )
```

Convert any valid number in *value* and converts it to double *val*

Parameters

out	<i>val</i>	Value converted to double
in	<i>value</i>	Value in string to be converted

Return values

0	On Success, Otherwise error
---	-----------------------------

5.9.4.7 f_convert_to_long_int()

```
int f_convert_to_long_int (  

```

```
unsigned long int * val,  
char * value,  
size_t value_sz )
```

Converts a string value to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int() (p. ??)

5.9.4.8 f_convert_to_long_int0()

```
int f_convert_to_long_int0 (  
    unsigned long int * val,  
    char * value,  
    size_t value_sz )
```

Converts a octal value in ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int0x() (p. ??)

5.9.4.9 f_convert_to_long_int0x()

```
int f_convert_to_long_int0x (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a hex value in ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int0() (p. ??)

5.9.4.10 f_convert_to_long_int_std()

```
int f_convert_to_long_int_std (
    unsigned long int * val,
    char * value,
    size_t value_sz )
```

Converts a actal/decimal/hexadecimal into ASCII string to unsigned long int.

Parameters

out	<i>val</i>	Value stored in a unsigned long int variable
in	<i>value</i>	Input value to be parsed to unsigned long int <ul style="list-style-type: none">• If a string contains only numbers, it will be parsed to unsigned long int decimal• If a string begins with 0 it will be parsed to octal EX.: 010(octal) = 08(decimal)• If a string contains 0x or 0X it will be parsed to hexadecimal. EX.: 0x10(hexadecimal) = 16 (decimal)
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int() (p. ??)

5.9.4.11 f_convert_to_unsigned_int()

```
int f_convert_to_unsigned_int (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a string value to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_long_int() (p. ??)

5.9.4.12 f_convert_to_unsigned_int0()

```
int f_convert_to_unsigned_int0 (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a octal value in ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int0x() (p. ??)

5.9.4.13 f_convert_to_unsigned_int0x()

```
int f_convert_to_unsigned_int0x (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a hex value in ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int0() (p. ??)

5.9.4.14 f_convert_to_unsigned_int_std()

```
int f_convert_to_unsigned_int_std (
    unsigned int * val,
    char * value,
    size_t value_sz )
```

Converts a actal/decimal/hexadecimal into ASCII string to unsigned int.

Parameters

out	<i>val</i>	Value stored in a unsigned int variable
in	<i>value</i>	Input value to be parsed to unsigned int <ul style="list-style-type: none">• If a string contains only numbers, it will be parsed to unsigned int decimal• If a string begins with 0 it will be parsed to octal EX.: 010(octal) = 08(decimal)• If a string contains 0x or 0X it will be parsed to hexadecimal. EX.: 0x10(hexadecimal) = 16 (decimal)
in	<i>value_sz</i>	Max size allowed in <i>value</i> string.

Return values

0	On Success, Otherwise error
---	-----------------------------

See also

f_convert_to_unsigned_int() (p. ??)

5.9.4.15 f_ecdsa_public_key_valid()

```
int f_ecdsa_public_key_valid (
    mbedtls_ecp_group_id ,
    unsigned char * ,
    size_t )
```

5.9.4.16 f_ecdsa_secret_key_valid()

```
int f_ecdsa_secret_key_valid (
    mbedtls_ecp_group_id ,
    unsigned char * ,
    size_t )
```

5.9.4.17 f_encode_to_base64()

```
int f_encode_to_base64 (
    char * ,
    size_t ,
    size_t * ,
    void * ,
    size_t )
```

5.9.4.18 f_encode_to_base64_dynamic()

```
int f_encode_to_base64_dynamic (
    char ** ,
    size_t * ,
    void * ,
    size_t )
```

5.9.4.19 f_gen_ecdsa_key_pair()

```
f_ecdsa_key_pair_err f_gen_ecdsa_key_pair (
    f_ecdsa_key_pair * ,
    int ,
    fn_det ,
    void * )
```

5.9.4.20 f_get_char_no_block()

```
int f_get_char_no_block (
    int mode )
```

Reads a char from console.

Waits a char and returns its value

Parameters

in	mode	Mode and/or character to be returned
		<ul style="list-style-type: none">• <i>F_GET_CH_MODE_NO_ECHO</i> No echo is on the console string• <i>F_GET_CH_MODE_ANY_KEY</i> Returns any key pressed

Example:

```
key=f_get_char_no_block(F_GET_CH_MODE_NO_ECHO|'c'); // Waits 'c' char key and returns value 0x00000063
              without echo 'c' on the screen
```

Return values

key	code: On Success, Negative value on error
-----	---

5.9.4.21 f_get_entropy_name()

```
char * f_get_entropy_name (
    uint32_t val )
```

Returns a entropy name given a index/ASCII index or entropy value.

Parameters

in	val	Index/ASCII index or entropy value
----	-----	------------------------------------

Return values:

- *NULL* If no entropy index/ASCII/entropy found in *va*
- *F_ENTROPY_TYPE_** name if found in index/ASCII or entropy value

5.9.4.22 f_hmac_sha512()

```
f_md_hmac_sha512 f_hmac_sha512 (
    unsigned char * ,
    const unsigned char * ,
    size_t ,
    const unsigned char * ,
    size_t )
```

5.9.4.23 f_is_random_attached()

```
void * f_is_random_attached ( )
```

Verifies if system random function is attached in myNanoEmbedded API.

Return values

<i>NULL</i>	if not attached, Otherwise returns the pointer of random number generator function
-------------	--

See also

f_random_attach() (p. ??)

5.9.4.24 f_pass_must_have_at_least()

```
int f_pass_must_have_at_least (
    char * password,
    size_t n,
    size_t min,
    size_t max,
    int must_have )
```

Checks if a given password has enough requirements to be parsed to a function.

Parameters

in	<i>password</i>	Password string
in	<i>n</i>	Max buffer string permitted to store password including NULL char
in	<i>min</i>	Minimum size allowed in password string
in	<i>max</i>	Maximum size allowed in password
in	<i>must_have</i>	Must have a type: <ul style="list-style-type: none"> • <code>F_PASS_MUST_HAVE_AT_LEAST_NONE</code> Not need any special characters or number • <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER</code> Must have at least one number • <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL</code> Must have at least one symbol • <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE</code> Must have at least one upper case • <code>F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE</code> Must have at least one lower case

Return values:

- `0 (zero)`: If password is passed in the test
- `F_PASS_IS_OUT_OVF`: If password length exceeds *n* value
- `F_PASS_IS_TOO_SHORT`: If password length is less than *min* value
- `F_PASS_IS_TOO_LONG`: If password length is greater than *m* value
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE`: If password is required in *must_have* type upper case characters
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE`: If password is required in *must_have* type lower case characters
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL`: If password is required in *must_have* type to have symbol(s)
- `F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER`: if password is required in *must_have* type to have number(s)

5.9.4.25 f_passwd_comp_safe()

```
int f_passwd_comp_safe (
    char * pass1,
    char * pass2,
    size_t n,
    size_t min,
    size_t max )
```

Compares two passwords values with safe buffer.

Parameters

in	<i>pass1</i>	First password to compare with <i>pass2</i>
in	<i>pass2</i>	Second password to compare with <i>pass1</i>
in	<i>n</i>	Size of Maximum buffer of both <i>pass1</i> and <i>pass2</i>
in	<i>min</i>	Minimun value of both <i>pass1</i> and <i>pass2</i>
in	<i>max</i>	Maximum value of both <i>pass1</i> and <i>pass2</i>

Return values

0	If <i>pass1</i> is equal to <i>pass2</i> , otherwise value is less than 0 (zero) if password does not match
---	---

5.9.4.26 f_random()

```
void f_random (
    void * random,
    size_t random_sz )
```

Random function to be called to generate a *random* data with *random_sz*

Parameters

out	<i>random</i>	Random data to be parsed
in	<i>random_sz</i>	Size of random data to be filled

See also

f_random_attach() (p. ??)

5.9.4.27 f_random_attach()

```
void f_random_attach (
    rnd_fn fn )
```

Attaches a function to be called by **f_random()** (p. ??)

Parameters

in	<i>fn</i>	A function to be called
----	-----------	-------------------------

See also

rnd_fn() (p. ??)

5.9.4.28 f_random_detach()

```
void f_random_detach ( )
```

Detaches system random number generator from myNanoEmbedded API.

See also

f_random_attach() (p. ??)

5.9.4.29 f_reverse()

```
int f_reverse (
    unsigned char * ,
    size_t )
```

5.9.4.30 f_ripemd160()

```
uint8_t* f_ripemd160 (
    const uint8_t * ,
    size_t )
```

5.9.4.31 f_sel_to_entropy_level()

```
uint32_t f_sel_to_entropy_level (
    int sel )
```

Return a given entropy number given a number encoded ASCII or index number.

Parameters

in	sel	ASCII or index value
----	-----	----------------------

Return values:

- 0 (zero): If no entropy number found in *sel*
- *F_ENTROPY_TYPE_PARANOIC*

- *F_ENTROPY_TYPE_EXCELENT*
- *F_ENTROPY_TYPE_GOOD*
- *F_ENTROPY_TYPE_NOT_ENOUGH*
- *F_ENTROPY_TYPE_NOT_RECOMENDED*

5.9.4.32 *f_str_to_hex()*

```
int f_str_to_hex (
    uint8_t * hex_stream,
    char * str )
```

Converts a *str* string buffer to raw *hex_stream* value stream.

Parameters

out	<i>hex</i>	Raw hex value
in	<i>str</i>	String buffer terminated with NULL char

Return values

0	On Success, otherwise Error
---	-----------------------------

5.9.4.33 *f_uncompress_elliptic_curve()*

```
int f_uncompress_elliptic_curve (
    uint8_t * ,
    size_t ,
    size_t * ,
    mbedtls_ecp_group_id ,
    uint8_t * ,
    size_t )
```

5.9.4.34 *f_url_base64_to_base64_dynamic()*

```
int f_url_base64_to_base64_dynamic (
    char ** ,
    size_t * ,
    const char * ,
    size_t )
```

5.9.4.35 f_url_encode()

```
int f_url_encode (
    char * ,
    size_t ,
    size_t * ,
    uint8_t * ,
    size_t )
```

5.9.4.36 f_verify_system_entropy()

```
int f_verify_system_entropy (
    uint32_t type,
    void * rand,
    size_t rand_sz,
    int turn_on_wdt )
```

Take a random number generator function and returns random value only if randomized data have a desired entropy value.

Parameters

in	<i>type</i>	Entropy type. Entropy type values are: <ul style="list-style-type: none"> • F_ENTROPY_TYPE_PARANOIC Highest level entropy recommended for generate a Nano SEED with a paranoic entropy. Very slow • F_ENTROPY_TYPE_EXCELENT Gives a very excellent entropy for generating Nano SEED. Slow • F_ENTROPY_TYPE_GOOD Good entropy type for generating Nano SEED. Normal. • F_ENTROPY_TYPE_NOT_ENOUGH Moderate entropy for generating Nano SEED. Usually fast to create a temporary Nano SEED. Fast • F_ENTROPY_TYPE_NOT_RECOMENDED Fast but not recommended for generating Nano SEED.
out	<i>rand</i>	Random data with a satisfied type of entropy
in	<i>rand_sz</i>	Size of random data output
in	<i>turn_on_wdt</i>	For ESP32, Arduino platform and other microcontrollers only. Turns on/off WATCH DOG (0: OFF, NON ZERO: ON). For Raspberry PI and Linux native is ommited.

This implementation is based on topic in [Definition 7.12](#) in MIT opencourseware (7.3 A Statistical Definition of Entropy - 2005)

Many thanks to **Professor Z. S. Spakovszky** for this amazing topic

Return values

0	On Success, otherwise Error
---	-----------------------------

5.9.4.37 get_console_passwd()

```
int get_console_passwd (
    char * pass,
    size_t pass_sz )
```

Reads a password from console.

Parameters

out	<i>pass</i>	Password to be parsed to pointer
in	<i>pass_sz</i>	Size of buffer <i>pass</i>

Return values

0	On Success, otherwise Error
---	-----------------------------

5.10 f_util.h

```
00001 /*
00002     AUTHOR: Fábio Pereira da Silva
00003     YEAR: 2019-20
00004     LICENSE: MIT
00005     EMAIL: fabioegel@gmail.com or fabioegel@protonmail.com
00006 */
00007
00013 #include <stdint.h>
00014 #include "mbedtls/sha256.h"
00015 #include "mbedtls/aes.h"
00016 #include "mbedtls/ecdsa.h"
00017
00018 #ifdef __cplusplus
00019 extern "C" {
00020 #endif
00021
00022 #ifndef F_DOC_SKIP
00023
00024     #define F_LOG_MAX 8*256
00025     #define LICENSE \
00026     "MIT License\n\n\
00027     Copyright (c) 2019 Fábio Pereira da Silva\n\n\
00028     Permission is hereby granted, free of charge, to any person obtaining a copy\n\
00029     of this software and associated documentation files (the \"Software\"), to deal\n\
00030     in the Software without restriction, including without limitation the rights\n\
00031     to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n\
00032     copies of the Software, and to permit persons to whom the Software is\n\
00033     furnished to do so, subject to the following conditions:\n\n\
00034     The above copyright notice and this permission notice shall be included in all\n\
00035     copies or substantial portions of the Software.\n\n\
00036     THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n\
00037     IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n\
00038     FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n\
00039     AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n\
00040     LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n\
00041     OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE\n\
00042     SOFTWARE.\n\n\
00043
00044 #endif
00045
00046 #ifndef F_ESP32
00047
00048     #define F_WDT_MAX_ENTROPY_TIME 2*120
00049     #define F_WDT_PANIC true
00050     #define F_WDT_MIN_TIME 20//4
00051
00052 #endif
00053
00071 int f_verify_system_entropy(uint32_t, void *, size_t, int);
00072
```

```
00099 int f_pass_must_have_at_least(char *, size_t, size_t, size_t, int);
00100
00101 #ifndef F_DOC_SKIP
00102
00103 int f_verify_system_entropy_begin();
00104 void f_verify_system_entropy_finish();
00105 int f_file_exists(char *);
00106 int f_find_str(size_t *, char *, size_t, char *);
00107 int f_find_replace(char *, size_t *, size_t, char *, size_t, char *, char *);
00108 int f_is_integer(char *, size_t);
00109 int is_filled_with_value(uint8_t *, size_t, uint8_t);
00110
00111 #endif
00112
00113 // #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1476682819
00118 #define F_ENTROPY_TYPE_PARANOIC (uint32_t)1477682819
00119
00120 // #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1475885281
00125 #define F_ENTROPY_TYPE_EXCELENT (uint32_t)1476885281
00126
00127 // #define F_ENTROPY_TYPE_GOOD (uint32_t)1471531015
00132 #define F_ENTROPY_TYPE_GOOD (uint32_t)1472531015
00133
00134 // #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1470001808
00139 #define F_ENTROPY_TYPE_NOT_ENOUGH (uint32_t)1471001808
00140
00141 // #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1469703345
00146 #define F_ENTROPY_TYPE_NOT_RECOMENDED (uint32_t)1470003345
00147
00153 #define ENTROPY_BEGIN f_verify_system_entropy_begin();
00154
00160 #define ENTROPY_END f_verify_system_entropy_finish();
00161
00166 #define F_PASS_MUST_HAVE_AT_LEAST_NONE (int)0
00167
00172 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER (int)1
00173
00178 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL (int)2
00179
00184 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_CASE (int)4
00185
00190 #define F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_CASE (int)8
00191
00196 #define F_PASS_IS_TOO_LONG (int)256
00197
00202 #define F_PASS_IS_TOO_SHORT (int)512
00203
00208 #define F_PASS_IS_OUT_OVF (int)1024//768
00209
00210 #ifndef F_DOC_SKIP
00211
00212 #define F_PBKDF2_ITER_SZ 2*4096
00213
00214 typedef enum f_pbkdf2_err_t {
00215     F_PBKDF2_RESULT_OK=0,
00216     F_PBKDF2_ERR_CTX=95,
00217     F_PBKDF2_ERR_PKCS5,
00218     F_PBKDF2_ERR_INFO_SHA
00219 } f_pbkdf2_err;
00220
00221 typedef enum f_aes_err {
00222     F_AES_RESULT_OK=0,
00223     F_AES_ERR_ENCKEY=30,
00224     F_AES_ERR_DECKEY,
00225     F_AES_ERR_MALLOC,
00226     F_AES_UNKNOW_DIRECTION,
00227     F_ERR_ENC_DECRYPT_FAILED
00228 } f_aes_err;
00229
00230 typedef enum f_md_hmac_sha512_t {
00231     F_HMAC_SHA512_OK = 0,
00232     F_HMAC_SHA512_MALLOC = 304,
00233     F_HMAC_SHA512_ERR_INFO,
00234     F_HMAC_SHA512_ERR_SETUP,
00235     F_HMAC_SHA512_DIGEST_ERROR
00236 } f_md_hmac_sha512;
00238 typedef enum f_ecdsa_key_pair_err_t {
00239     F_ECDSA_KEY_PAIR_OK = 0,
00240     F_ECDSA_KEY_PAIR_NULL = 330,
00241     F_ECDSA_KEY_PAIR_MALLOC
00242 } f_ecdsa_key_pair_err;
00243
00244 typedef struct f_ecdsa_key_pair_t {
00245     size_t public_key_sz;
00246     size_t private_key_sz;
00247     mbedtls_ecdsa_context *ctx;
00248     mbedtls_ecp_group_id gid;
```

```

00249     unsigned char public_key[MBEDTLS_ECDSA_MAX_LEN];
00250     unsigned char private_key[MBEDTLS_ECDSA_MAX_LEN];
00251 } f_ecdsa_key_pair;
00252
00253 enum f_encode_decode_error_t {
00254     F_URL_ENCODE_OK = 0,
00255     F_ENCODE_BASE64_DEST_SMALL=11300,
00256     F_ENCODE_TO_BASE64_MALLOC,
00257     F_BASE64_DECODE_MALLOC,
00258     F_URL_ENCODE_EMPTY,
00259     F_URL_ENCODE_DEST_SMALL,
00260     F_BASE64_URL_DECODE_MALLOC,
00261     F_BASE64_URL_DECODE_MEMORY_SMALL,
00262     F_BASE64_URL_TO_BASE64_EMPTY_BASE64,
00263     F_BASE64_URL_TO_BASE64_MALLOC
00264 };
00265
00266 char *fhex2strv2(char *, const void *, size_t, int);
00267 int f_sha256_digest(void **, int, uint8_t *, size_t);
00268 f_pbkdf2_err f_pbkdf2_hmac(unsigned char *, size_t, unsigned char *, size_t, uint8_t *);
00269 f_aes_err f_aes256cipher(uint8_t *, uint8_t *, void *, size_t, void *, int);
00270
00271 #endif
00272
00273 int f_passwd_comp_safe(char *, char *, size_t, size_t, size_t);
00274
00275 char *f_get_entropy_name(uint32_t);
00276
00277 uint32_t f_sel_to_entropy_level(int);
00278
00279 int f_str_to_hex(uint8_t *, char *);
00280
00281 #ifndef F_ESP32
00282
00283 typedef void (*rnd_fn)(void *, size_t);
00284
00285 void f_random_attach(rnd_fn);
00286
00287 void f_random(void *, size_t);
00288
00289 int get_console_passwd(char *, size_t);
00290
00291 #define F_GET_CH_MODE_NO_ECHO (int) (1<<16)
00292
00293 #define F_GET_CH_MODE_ANY_KEY (int) (1<<17)
00294
00295 int f_get_char_no_block(int);
00296
00297 #endif
00298
00299 int f_convert_to_long_int(unsigned long int *, char *, size_t);
00300
00301 int f_convert_to_unsigned_int(unsigned int *, char *, size_t);
00302
00303 int f_convert_to_long_int0x(unsigned long int *, char *, size_t);
00304
00305 int f_convert_to_long_int0(unsigned long int *, char *, size_t);
00306
00307 int f_convert_to_long_int_std(unsigned long int *, char *, size_t);
00308
00309 void *f_is_random_attached();
00310
00311 void f_random_detach();
00312
00313 int f_convert_to_unsigned_int0x(unsigned int *val, char *value, size_t value_sz);
00314
00315 int f_convert_to_unsigned_int0(unsigned int *val, char *value, size_t value_sz);
00316
00317 int f_convert_to_unsigned_int_std(unsigned int *val, char *value, size_t value_sz);
00318
00319 int f_convert_to_double(double *, const char *);
00320
00321 uint32_t crc32_init(unsigned char *, size_t, uint32_t);
00322
00323 //
00324 typedef int (*fn_det)(void *, unsigned char *, size_t);
00325 int f_reverse(unsigned char *, size_t);
00326 f_md_hmac_sha512 f_hmac_sha512(unsigned char *, const unsigned char *, size_t, const unsigned char *,
00327     size_t);
00328 int f_ecdsa_secret_key_valid(mbedtls_ecp_group_id, unsigned char *, size_t);
00329 int f_ecdsa_public_key_valid(mbedtls_ecp_group_id, unsigned char *, size_t);
00330 f_ecdsa_key_pair_err f_gen_ecdsa_key_pair(f_ecdsa_key_pair *, int, fn_det, void *);
00331 int f_uncompress_elliptic_curve(uint8_t *, size_t, size_t *, mbedtls_ecp_group_id, uint8_t *, size_t);
00332 uint8_t *f_ripemd160(const uint8_t *, size_t);
00333 int f_url_encode(char *, size_t, size_t *, uint8_t *, size_t);
00334 int f_encode_to_base64_dynamic(char **, size_t *, void *, size_t);
00335 int f_base64_decode_dynamic(void **, size_t *, const char *, size_t);

```

```
00550 int f_base64url_encode_dynamic(void **, size_t *, void *, size_t);
00551 int f_encode_to_base64(char *, size_t, size_t *, void *, size_t);
00552 int f_base64url_encode(char *, size_t, size_t *, void *, size_t);
00553 int f_base64url_decode(void *, size_t, size_t *, const char *, size_t);
00554 int f_url_base64_to_base64_dynamic(char **, size_t *, const char *, size_t);
00555 #ifdef __cplusplus
00556 }
00557 #endif
```

5.11 sodium.h File Reference

```
#include "sodium/version.h"
#include "sodium/core.h"
#include "sodium/crypto_aead_aes256gcm.h"
#include "sodium/crypto_aead_chacha20poly1305.h"
#include "sodium/crypto_aead_xchacha20poly1305.h"
#include "sodium/crypto_auth.h"
#include "sodium/crypto_auth_hmacsha256.h"
#include "sodium/crypto_auth_hmacsha512.h"
#include "sodium/crypto_auth_hmacsha512256.h"
#include "sodium/crypto_box.h"
#include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
#include "sodium/crypto_core_hsalsa20.h"
#include "sodium/crypto_core_hchacha20.h"
#include "sodium/crypto_core_salsa20.h"
#include "sodium/crypto_core_salsa2012.h"
#include "sodium/crypto_core_salsa208.h"
#include "sodium/crypto_generichash.h"
#include "sodium/crypto_generichash_blake2b.h"
#include "sodium/crypto_hash.h"
#include "sodium/crypto_hash_sha256.h"
#include "sodium/crypto_hash_sha512.h"
#include "sodium/crypto_kdf.h"
#include "sodium/crypto_kdf_blake2b.h"
#include "sodium/crypto_kx.h"
#include "sodium/crypto_onetimeauth.h"
#include "sodium/crypto_onetimeauth_poly1305.h"
#include "sodium/crypto_pwhash.h"
#include "sodium/crypto_pwhash_argon2i.h"
#include "sodium/crypto_scalarmult.h"
#include "sodium/crypto_scalarmult_curve25519.h"
#include "sodium/crypto_secretbox.h"
#include "sodium/crypto_secretbox_xsalsa20poly1305.h"
#include "sodium/crypto_secretstream_xchacha20poly1305.h"
#include "sodium/crypto_shorthash.h"
#include "sodium/crypto_shorthash_siphhash24.h"
#include "sodium/crypto_sign.h"
#include "sodium/crypto_sign_ed25519.h"
#include "sodium/crypto_stream.h"
#include "sodium/crypto_stream_chacha20.h"
#include "sodium/crypto_stream_salsa20.h"
#include "sodium/crypto_stream_xsalsa20.h"
#include "sodium/crypto_verify_16.h"
#include "sodium/crypto_verify_32.h"
#include "sodium/crypto_verify_64.h"
#include "sodium/randombytes.h"
#include "sodium/randombytes_internal_random.h"
#include "sodium/randombytes_sysrandom.h"
```

```
#include "sodium/runtime.h"
#include "sodium/utils.h"
#include "sodium/crypto_box_curve25519xchacha20poly1305.h"
#include "sodium/crypto_core_ed25519.h"
#include "sodium/crypto_core_ristretto255.h"
#include "sodium/crypto_scalarmult_ed25519.h"
#include "sodium/crypto_scalarmult_ristretto255.h"
#include "sodium/crypto_secretbox_xchacha20poly1305.h"
#include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
#include "sodium/crypto_stream_salsa2012.h"
#include "sodium/crypto_stream_salsa208.h"
#include "sodium/crypto_stream_xchacha20.h"
```

5.12 sodium.h

```
00001
00002 #ifndef sodium_H
00003 #define sodium_H
00004
00005 #include "sodium/version.h"
00006
00007 #include "sodium/core.h"
00008 #include "sodium/crypto_aead_aes256gcm.h"
00009 #include "sodium/crypto_aead_chacha20poly1305.h"
00010 #include "sodium/crypto_aead_xchacha20poly1305.h"
00011 #include "sodium/crypto_auth.h"
00012 #include "sodium/crypto_auth_hmacsha256.h"
00013 #include "sodium/crypto_auth_hmacsha512.h"
00014 #include "sodium/crypto_auth_hmacsha512256.h"
00015 #include "sodium/crypto_box.h"
00016 #include "sodium/crypto_box_curve25519xsalsa20poly1305.h"
00017 #include "sodium/crypto_core_hsalsa20.h"
00018 #include "sodium/crypto_core_hchacha20.h"
00019 #include "sodium/crypto_core_salsa20.h"
00020 #include "sodium/crypto_core_salsa2012.h"
00021 #include "sodium/crypto_core_salsa208.h"
00022 #include "sodium/crypto_generichash.h"
00023 #include "sodium/crypto_generichash_blake2b.h"
00024 #include "sodium/crypto_hash.h"
00025 #include "sodium/crypto_hash_sha256.h"
00026 #include "sodium/crypto_hash_sha512.h"
00027 #include "sodium/crypto_kdf.h"
00028 #include "sodium/crypto_kdf_blake2b.h"
00029 #include "sodium/crypto_kx.h"
00030 #include "sodium/crypto_onetimeauth.h"
00031 #include "sodium/crypto_onetimeauth_poly1305.h"
00032 #include "sodium/crypto_pwhash.h"
00033 #include "sodium/crypto_pwhash_argon2i.h"
00034 #include "sodium/crypto_scalarmult.h"
00035 #include "sodium/crypto_scalarmult_curve25519.h"
00036 #include "sodium/crypto_secretbox.h"
00037 #include "sodium/crypto_secretbox_xsalsa20poly1305.h"
00038 #include "sodium/crypto_secretstream_xchacha20poly1305.h"
00039 #include "sodium/crypto_shorthash.h"
00040 #include "sodium/crypto_shorthash_siphhash24.h"
00041 #include "sodium/crypto_sign.h"
00042 #include "sodium/crypto_sign_ed25519.h"
00043 #include "sodium/crypto_stream.h"
00044 #include "sodium/crypto_stream_chacha20.h"
00045 #include "sodium/crypto_stream_salsa20.h"
00046 #include "sodium/crypto_stream_xsalsa20.h"
00047 #include "sodium/crypto_verify_16.h"
00048 #include "sodium/crypto_verify_32.h"
00049 #include "sodium/crypto_verify_64.h"
00050 #include "sodium/randombytes.h"
00051 #include "sodium/randombytes_internal_random.h"
00052 #include "sodium/randombytes_sysrandom.h"
00053 #include "sodium/runtime.h"
00054 #include "sodium/utils.h"
00055
00056 #ifndef SODIUM_LIBRARY_MINIMAL
00057 # include "sodium/crypto_box_curve25519xchacha20poly1305.h"
00058 # include "sodium/crypto_core_ed25519.h"
00059 # include "sodium/crypto_core_ristretto255.h"
00060 # include "sodium/crypto_scalarmult_ed25519.h"
```



```
00061 # include "sodium/crypto_scalarmult_ristretto255.h"
00062 # include "sodium/crypto_secretbox_xchacha20poly1305.h"
00063 # include "sodium/crypto_pwhash_scryptsalsa208sha256.h"
00064 # include "sodium/crypto_stream_salsa2012.h"
00065 # include "sodium/crypto_stream_salsa208.h"
00066 # include "sodium/crypto_stream_xchacha20.h"
00067 #endif
00068
00069 #endif
```


Index

- `__attribute__`
 - `f_bitcoin.h`, 26
 - `f_nano_crypto_util.h`, 52
- account
 - `f_block_transfer_t`, 9
 - `f_nano_crypto_util.h`, 77
- balance
 - `f_block_transfer_t`, 9
 - `f_nano_crypto_util.h`, 78
- body
 - `f_nano_crypto_util.h`, 78
 - `f_nano_wallet_info_t`, 16
- CANT_OPEN_DICTIONARY_FILE
 - `errors.h`, 19
- chain_code
 - `f_bitcoin.h`, 30
 - `f_bitcoin_serialize_t`, 7
- child_number
 - `f_bitcoin.h`, 30
 - `f_bitcoin_serialize_t`, 7
- chksum
 - `f_bitcoin.h`, 30
 - `f_bitcoin_serialize_t`, 8
- crc32_init
 - `f_util.h`, 96
- DERIVE_XPRIV_XPUB_DYN_OUT_BASE58
 - `f_bitcoin.h`, 23
- DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV
 - `f_bitcoin.h`, 23
- DERIVE_XPRIV_XPUB_DYN_OUT_XPUB
 - `f_bitcoin.h`, 23
- DEST_XRB
 - `f_nano_crypto_util.h`, 36
- desc
 - `f_nano_crypto_util.h`, 78
 - `f_nano_wallet_info_t`, 17
- description
 - `f_nano_crypto_util.h`, 78
 - `f_nano_crypto_wallet_t`, 12
- ENTROPY_BEGIN
 - `f_util.h`, 91
- ENTROPY_END
 - `f_util.h`, 92
- ERROR_GEN_TOKEN_NO_RAND_NUM_GEN
 - `errors.h`, 19
- ERROR_INVALID_NANO_ADDRESS_VERIFY_CHK←
SUM
 - `errors.h`, 20
- ERROR_SUCCESS
 - `errors.h`, 20
- errors.h, 19, 21
 - CANT_OPEN_DICTIONARY_FILE, 19
 - ERROR_GEN_TOKEN_NO_RAND_NUM_GEN, 19
 - ERROR_INVALID_NANO_ADDRESS_VERIFY←
_CHKSUM, 20
 - ERROR_SUCCESS, 20
 - `f_nano_account_or_pk_string_to_pk_util_err_t`, 20
 - INVALID_RAW_BALANCE, 20
- F_ADD_288
 - `f_add_bn_288_le.h`, 21
- F_BALANCE_RAW_128
 - `f_nano_crypto_util.h`, 36
- F_BALANCE_RAW_STRING
 - `f_nano_crypto_util.h`, 37
- F_BALANCE_REAL_STRING
 - `f_nano_crypto_util.h`, 37
- F_BITCOIN_BUF_SZ
 - `f_bitcoin.h`, 24
- F_BITCOIN_P2PKH
 - `f_bitcoin.h`, 24
- F_BITCOIN_SEED_GENERATOR
 - `f_bitcoin.h`, 24
- F_BITCOIN_T2PKH
 - `f_bitcoin.h`, 24
- F_BITCOIN_WIF_MAINNET
 - `f_bitcoin.h`, 24
- F_BITCOIN_WIF_TESTNET
 - `f_bitcoin.h`, 24
- F_BLOCK_TRANSFER_SIZE
 - `f_nano_crypto_util.h`, 37
- F_BRAIN_WALLET_BAD
 - `f_nano_crypto_util.h`, 37
- F_BRAIN_WALLET_GOOD
 - `f_nano_crypto_util.h`, 37
- F_BRAIN_WALLET_MAYBE_GOOD
 - `f_nano_crypto_util.h`, 38
- F_BRAIN_WALLET_NICE
 - `f_nano_crypto_util.h`, 38
- F_BRAIN_WALLET_PERFECT
 - `f_nano_crypto_util.h`, 38
- F_BRAIN_WALLET_POOR
 - `f_nano_crypto_util.h`, 38
- F_BRAIN_WALLET_STILL_WEAK

- f_nano_crypto_util.h, 39
- F_BRAIN_WALLET_VERY_BAD
 - f_nano_crypto_util.h, 39
- F_BRAIN_WALLET_VERY_GOOD
 - f_nano_crypto_util.h, 39
- F_BRAIN_WALLET_VERY_POOR
 - f_nano_crypto_util.h, 39
- F_BRAIN_WALLET_VERY_WEAK
 - f_nano_crypto_util.h, 40
- F_BRAIN_WALLET_WEAK
 - f_nano_crypto_util.h, 40
- F_DEFAULT_THRESHOLD
 - f_nano_crypto_util.h, 40
- F_ENTROPY_TYPE_EXCELENT
 - f_util.h, 92
- F_ENTROPY_TYPE_GOOD
 - f_util.h, 92
- F_ENTROPY_TYPE_NOT_ENOUGH
 - f_util.h, 92
- F_ENTROPY_TYPE_NOT_RECOMENDED
 - f_util.h, 93
- F_ENTROPY_TYPE_PARANOIC
 - f_util.h, 93
- F_FILE_INFO_ERR
 - f_nano_crypto_util.h, 47
- F_GET_CH_MODE_ANY_KEY
 - f_util.h, 93
- F_GET_CH_MODE_NO_ECHO
 - f_util.h, 93
- F_GET_XKEY_IS_BASE58
 - f_bitcoin.h, 25
- F_IS_SIGNATURE_RAW_HEX_STRING
 - f_nano_crypto_util.h, 40
- F_MAX_BASE58_LENGTH
 - f_bitcoin.h, 25
- F_MESSAGE_IS_HASH_STRING
 - f_nano_crypto_util.h, 41
- F_NANO_CREATE_BLOCK_DYN_ERR
 - f_nano_crypto_util.h, 47
- F_NANO_P2POW_BLOCK_DYN_ERR
 - f_nano_crypto_util.h, 47
- F_NANO_POW_MAX_THREAD
 - f_nano_crypto_util.h, 41
- F_P2POW_BLOCK_TRANSFER_SIZE
 - f_nano_crypto_util.h, 41
- F_PASS_IS_OUT_OVF
 - f_util.h, 94
- F_PASS_IS_TOO_LONG
 - f_util.h, 94
- F_PASS_IS_TOO_SHORT
 - f_util.h, 94
- F_PASS_MUST_HAVE_AT_LEAST_NONE
 - f_util.h, 94
- F_PASS_MUST_HAVE_AT_LEAST_ONE_LOWER_↔
 - CASE
 - f_util.h, 94
- F_PASS_MUST_HAVE_AT_LEAST_ONE_NUMBER
 - f_util.h, 95
- F_PASS_MUST_HAVE_AT_LEAST_ONE_SYMBOL
 - f_util.h, 95
- F_PASS_MUST_HAVE_AT_LEAST_ONE_UPPER_↔
 - CASE
 - f_util.h, 95
- F_SIGNATURE_OUTPUT_NANO_PK
 - f_nano_crypto_util.h, 41
- F_SIGNATURE_OUTPUT_RAW_PK
 - f_nano_crypto_util.h, 42
- F_SIGNATURE_OUTPUT_STRING_PK
 - f_nano_crypto_util.h, 42
- F_SIGNATURE_OUTPUT_XRB_PK
 - f_nano_crypto_util.h, 42
- F_SIGNATURE_RAW
 - f_nano_crypto_util.h, 42
- F_SIGNATURE_STRING
 - f_nano_crypto_util.h, 43
- F_TOKEN
 - f_nano_crypto_util.h, 48
- F_VALUE_SEND_RECEIVE_RAW_128
 - f_nano_crypto_util.h, 43
- F_VALUE_SEND_RECEIVE_RAW_STRING
 - f_nano_crypto_util.h, 43
- F_VALUE_SEND_RECEIVE_REAL_STRING
 - f_nano_crypto_util.h, 43
- F_VALUE_TO_RECEIVE
 - f_nano_crypto_util.h, 43
- F_VALUE_TO_SEND
 - f_nano_crypto_util.h, 44
- F_VERIFY_SIG_ASCII_HEX
 - f_nano_crypto_util.h, 44
- F_VERIFY_SIG_NANO_WALLET
 - f_nano_crypto_util.h, 44
- F_VERIFY_SIG_RAW_HEX
 - f_nano_crypto_util.h, 44
- F_VERSION_BYTES_IDX_LEN
 - f_bitcoin.h, 25
- F_VERSION_BYTES
 - f_bitcoin.h, 30
- F_XPRIV_BASE58
 - f_bitcoin.h, 25
- F_XPUB_BASE58
 - f_bitcoin.h, 25
- f_add_bn_288_le.h, 21, 22
 - F_ADD_288, 21
- f_base64_decode_dynamic
 - f_util.h, 96
- f_base64url_decode
 - f_util.h, 96
- f_base64url_encode
 - f_util.h, 97
- f_base64url_encode_dynamic
 - f_util.h, 97
- f_bip32_to_public_key_or_private_key
 - f_bitcoin.h, 26
- f_bip39_to_nano_seed
 - f_nano_crypto_util.h, 52
- f_bitcoin.h, 22, 31

- __attribute__, 26
- chain_code, 30
- child_number, 30
- chksum, 30
- DERIVE_XPRIV_XPUB_DYN_OUT_BASE58, 23
- DERIVE_XPRIV_XPUB_DYN_OUT_XPRIV, 23
- DERIVE_XPRIV_XPUB_DYN_OUT_XPUB, 23
- F_BITCOIN_BUF_SZ, 24
- F_BITCOIN_P2PKH, 24
- F_BITCOIN_SEED_GENERATOR, 24
- F_BITCOIN_T2PKH, 24
- F_BITCOIN_WIF_MAINNET, 24
- F_BITCOIN_WIF_TESTNET, 24
- F_GET_XKEY_IS_BASE58, 25
- F_MAX_BASE58_LENGTH, 25
- F_VERSION_BYTES_IDX_LEN, 25
- F_VERSION_BYTES, 30
- F_XPRIV_BASE58, 25
- F_XPUB_BASE58, 25
- f_bip32_to_public_key_or_private_key, 26
- f_bitcoin_valid_bip32, 27
- f_check_if_invalid_btc_public_key, 27
- f_decode_b58_util, 27
- f_derive_xkey_dynamic, 27
- f_derive_xpriv_or_xpub_dynamic, 27
- f_encode_b58, 28
- f_fingerprint, 28
- f_generate_master_key, 28
- f_get_xkey_type, 28
- f_private_key_to_wif, 28
- f_public_key_to_address, 29
- f_uncompress_elliptic_curve, 29
- f_wif_to_private_key, 29
- f_xpriv2xpub, 29
- finger_print, 30
- load_master_private_key, 29
- MAINNET_PRIVATE, 25
- MAINNET_PUBLIC, 26
- master_node, 31
- sk_or_pk_data, 31
- TESTNET_PRIVATE, 26
- TESTNET_PUBLIC, 26
- version_bytes, 31
- f_bitcoin_serialize_t, 7
 - chain_code, 7
 - child_number, 7
 - chksum, 8
 - finger_print, 8
 - master_node, 8
 - sk_or_pk_data, 8
 - version_bytes, 8
- f_bitcoin_valid_bip32
 - f_bitcoin.h, 27
- f_block_transfer_t, 9
 - account, 9
 - balance, 9
 - link, 9
 - preamble, 10
 - prefixes, 10
 - previous, 10
 - representative, 10
 - signature, 10
 - work, 11
- f_check_if_invalid_btc_public_key
 - f_bitcoin.h, 27
- f_cloud_crypto_wallet_nano_create_seed
 - f_nano_crypto_util.h, 53
- f_convert_to_double
 - f_util.h, 97
- f_convert_to_long_int
 - f_util.h, 97
- f_convert_to_long_int0
 - f_util.h, 98
- f_convert_to_long_int0x
 - f_util.h, 98
- f_convert_to_long_int_std
 - f_util.h, 99
- f_convert_to_unsigned_int
 - f_util.h, 100
- f_convert_to_unsigned_int0
 - f_util.h, 100
- f_convert_to_unsigned_int0x
 - f_util.h, 101
- f_convert_to_unsigned_int_std
 - f_util.h, 101
- f_decode_b58_util
 - f_bitcoin.h, 27
- f_derive_xkey_dynamic
 - f_bitcoin.h, 27
- f_derive_xpriv_or_xpub_dynamic
 - f_bitcoin.h, 27
- f_ecdsa_public_key_valid
 - f_util.h, 102
- f_ecdsa_secret_key_valid
 - f_util.h, 102
- f_encode_b58
 - f_bitcoin.h, 28
- f_encode_to_base64
 - f_util.h, 102
- f_encode_to_base64_dynamic
 - f_util.h, 102
- f_extract_seed_from_brainwallet
 - f_nano_crypto_util.h, 53
- f_file_info_err_t, 11
 - f_nano_crypto_util.h, 49
- f_fingerprint
 - f_bitcoin.h, 28
- f_gen_ecdsa_key_pair
 - f_util.h, 102
- f_generate_master_key
 - f_bitcoin.h, 28
- f_generate_nano_seed
 - f_nano_crypto_util.h, 54
- f_generate_token
 - f_nano_crypto_util.h, 55
- f_get_char_no_block

- f_util.h, 103
- f_get_dictionary_path
 - f_nano_crypto_util.h, 55
- f_get_entropy_name
 - f_util.h, 103
- f_get_nano_file_info
 - f_nano_crypto_util.h, 56
- f_get_xkey_type
 - f_bitcoin.h, 28
- f_hmac_sha512
 - f_util.h, 104
- f_is_random_attached
 - f_util.h, 104
- f_is_valid_nano_seed_encrypted
 - f_nano_crypto_util.h, 56
- f_nano_account_or_pk_string_to_pk_util_err_t
 - errors.h, 20
- f_nano_add_sub
 - f_nano_crypto_util.h, 57
- f_nano_balance_to_str
 - f_nano_crypto_util.h, 57
- f_nano_block_to_json
 - f_nano_crypto_util.h, 58
- f_nano_create_block_dyn_err_t
 - f_nano_crypto_util.h, 50
- f_nano_crypto_util.h, 32, 84
 - __attribute__, 52
 - account, 77
 - balance, 78
 - body, 78
 - DEST_XRB, 36
 - desc, 78
 - description, 78
 - F_BALANCE_RAW_128, 36
 - F_BALANCE_RAW_STRING, 37
 - F_BALANCE_REAL_STRING, 37
 - F_BLOCK_TRANSFER_SIZE, 37
 - F_BRAIN_WALLET_BAD, 37
 - F_BRAIN_WALLET_GOOD, 37
 - F_BRAIN_WALLET_MAYBE_GOOD, 38
 - F_BRAIN_WALLET_NICE, 38
 - F_BRAIN_WALLET_PERFECT, 38
 - F_BRAIN_WALLET_POOR, 38
 - F_BRAIN_WALLET_STILL_WEAK, 39
 - F_BRAIN_WALLET_VERY_BAD, 39
 - F_BRAIN_WALLET_VERY_GOOD, 39
 - F_BRAIN_WALLET_VERY_POOR, 39
 - F_BRAIN_WALLET_VERY_WEAK, 40
 - F_BRAIN_WALLET_WEAK, 40
 - F_DEFAULT_THRESHOLD, 40
 - F_FILE_INFO_ERR, 47
 - F_IS_SIGNATURE_RAW_HEX_STRING, 40
 - F_MESSAGE_IS_HASH_STRING, 41
 - F_NANO_CREATE_BLOCK_DYN_ERR, 47
 - F_NANO_P2POW_BLOCK_DYN_ERR, 47
 - F_NANO_POW_MAX_THREAD, 41
 - F_P2POW_BLOCK_TRANSFER_SIZE, 41
 - F_SIGNATURE_OUTPUT_NANO_PK, 41
 - F_SIGNATURE_OUTPUT_RAW_PK, 42
 - F_SIGNATURE_OUTPUT_STRING_PK, 42
 - F_SIGNATURE_OUTPUT_XRB_PK, 42
 - F_SIGNATURE_RAW, 42
 - F_SIGNATURE_STRING, 43
 - F_TOKEN, 48
 - F_VALUE_SEND_RECEIVE_RAW_128, 43
 - F_VALUE_SEND_RECEIVE_RAW_STRING, 43
 - F_VALUE_SEND_RECEIVE_REAL_STRING, 43
 - F_VALUE_TO_RECEIVE, 43
 - F_VALUE_TO_SEND, 44
 - F_VERIFY_SIG_ASCII_HEX, 44
 - F_VERIFY_SIG_NANO_WALLET, 44
 - F_VERIFY_SIG_RAW_HEX, 44
 - f_bip39_to_nano_seed, 52
 - f_cloud_crypto_wallet_nano_create_seed, 53
 - f_extract_seed_from_brainwallet, 53
 - f_file_info_err_t, 49
 - f_generate_nano_seed, 54
 - f_generate_token, 55
 - f_get_dictionary_path, 55
 - f_get_nano_file_info, 56
 - f_is_valid_nano_seed_encrypted, 56
 - f_nano_add_sub, 57
 - f_nano_balance_to_str, 57
 - f_nano_block_to_json, 58
 - f_nano_create_block_dyn_err_t, 50
 - f_nano_err, 47
 - f_nano_err_t, 50
 - f_nano_get_block_hash, 58
 - f_nano_get_p2pow_block_hash, 59
 - f_nano_is_valid_block, 59
 - f_nano_key_to_str, 60
 - f_nano_p2pow_block_dyn_err_t, 51
 - f_nano_p2pow_to_JSON, 60
 - f_nano_parse_raw_str_to_raw128_t, 60
 - f_nano_parse_real_str_to_raw128_t, 61
 - f_nano_pow, 61
 - f_nano_raw_to_string, 62
 - f_nano_seed_to_bip39, 63
 - f_nano_sign_block, 63
 - f_nano_transaction_to_JSON, 64
 - f_nano_valid_nano_str_value, 64
 - f_nano_value_compare_value, 65
 - f_nano_verify_nano_funds, 66
 - f_parse_nano_seed_and_bip39_to_JSON, 67
 - f_read_seed, 67
 - f_seed_to_nano_wallet, 68
 - f_set_dictionary_path, 69
 - f_set_nano_file_info, 69
 - f_sign_data, 70
 - f_uint128_t, 48
 - f_verify_signed_block, 71
 - f_verify_signed_data, 71
 - f_verify_token, 71
 - f_verify_work, 72
 - f_write_seed, 73
 - f_write_seed_err, 48

- f_write_seed_err_t, 51
- file_info_integrity, 78
- from_multiplier, 73
- hash_sk_unencrypted, 79
- header, 79
- is_nano_prefix, 74
- is_null_hash, 74
- iv, 79
- last_used_wallet_number, 79
- link, 79
- MAX_STR_NANO_CHAR, 45
- max_fee, 80
- NANO_ENCRYPTED_SEED_FILE, 45
- NANO_FILE_WALLETS_INFO, 45
- NANO_PASSWD_MAX_LEN, 45
- NANO_PREFIX, 46
- NANO_PRIVATE_KEY_EXTENDED, 48
- NANO_PRIVATE_KEY, 48
- NANO_PUBLIC_KEY_EXTENDED, 49
- NANO_PUBLIC_KEY, 48
- NANO_SEED, 49
- nano_base_32_2_hex, 75
- nano_create_block_dynamic, 75
- nano_create_p2pow_block_dynamic, 75
- nano_hdr, 80
- nanoseed_hash, 80
- PUB_KEY_EXTENDED_MAX_LEN, 46
- pk_to_wallet, 76
- preamble, 80
- prefixes, 80
- previous, 81
- REP_XRB, 46
- representative, 81
- reserved, 81
- SENDER_XRB, 46
- STR_NANO_SZ, 46
- salt, 81
- seed_block, 81
- signature, 82
- sk_encrypted, 82
- sub_salt, 82
- to_multiplier, 76
- valid_nano_wallet, 77
- valid_raw_balance, 77
- ver, 82
- version, 82
- wallet_prefix, 83
- wallet_representative, 83
- work, 83
- XRB_PREFIX, 47
- f_nano_crypto_wallet_t, 11
 - description, 12
 - iv, 12
 - nano_hdr, 12
 - salt, 12
 - seed_block, 12
 - ver, 13
- f_nano_encrypted_wallet_t, 13
 - hash_sk_unencrypted, 13
 - iv, 14
 - reserved, 14
 - sk_encrypted, 14
 - sub_salt, 14
- f_nano_err
 - f_nano_crypto_util.h, 47
- f_nano_err_t
 - f_nano_crypto_util.h, 50
- f_nano_get_block_hash
 - f_nano_crypto_util.h, 58
- f_nano_get_p2pow_block_hash
 - f_nano_crypto_util.h, 59
- f_nano_is_valid_block
 - f_nano_crypto_util.h, 59
- f_nano_key_to_str
 - f_nano_crypto_util.h, 60
- f_nano_p2pow_block_dyn_err_t
 - f_nano_crypto_util.h, 51
- f_nano_p2pow_to_JSON
 - f_nano_crypto_util.h, 60
- f_nano_parse_raw_str_to_raw128_t
 - f_nano_crypto_util.h, 60
- f_nano_parse_real_str_to_raw128_t
 - f_nano_crypto_util.h, 61
- f_nano_pow
 - f_nano_crypto_util.h, 61
- f_nano_raw_to_string
 - f_nano_crypto_util.h, 62
- f_nano_seed_to_bip39
 - f_nano_crypto_util.h, 63
- f_nano_sign_block
 - f_nano_crypto_util.h, 63
- f_nano_transaction_to_JSON
 - f_nano_crypto_util.h, 64
- f_nano_valid_nano_str_value
 - f_nano_crypto_util.h, 64
- f_nano_value_compare_value
 - f_nano_crypto_util.h, 65
- f_nano_verify_nano_funds
 - f_nano_crypto_util.h, 66
- f_nano_wallet_info_bdy_t, 15
 - last_used_wallet_number, 15
 - max_fee, 15
 - reserved, 15
 - wallet_prefix, 15
 - wallet_representative, 16
- f_nano_wallet_info_t, 16
 - body, 16
 - desc, 17
 - file_info_integrity, 17
 - header, 17
 - nanoseed_hash, 17
 - version, 17
- f_parse_nano_seed_and_bip39_to_JSON
 - f_nano_crypto_util.h, 67
- f_pass_must_have_at_least
 - f_util.h, 104

- f_passwd_comp_safe
 - f_util.h, 105
- f_private_key_to_wif
 - f_bitcoin.h, 28
- f_public_key_to_address
 - f_bitcoin.h, 29
- f_random
 - f_util.h, 106
- f_random_attach
 - f_util.h, 106
- f_random_detach
 - f_util.h, 107
- f_read_seed
 - f_nano_crypto_util.h, 67
- f_reverse
 - f_util.h, 107
- f_ripemd160
 - f_util.h, 107
- f_seed_to_nano_wallet
 - f_nano_crypto_util.h, 68
- f_sel_to_entropy_level
 - f_util.h, 107
- f_set_dictionary_path
 - f_nano_crypto_util.h, 69
- f_set_nano_file_info
 - f_nano_crypto_util.h, 69
- f_sign_data
 - f_nano_crypto_util.h, 70
- f_str_to_hex
 - f_util.h, 108
- f_uint128_t
 - f_nano_crypto_util.h, 48
- f_uncompress_elliptic_curve
 - f_bitcoin.h, 29
 - f_util.h, 108
- f_url_base64_to_base64_dynamic
 - f_util.h, 108
- f_url_encode
 - f_util.h, 108
- f_util.h, 90, 110
 - crc32_init, 96
 - ENTROPY_BEGIN, 91
 - ENTROPY_END, 92
 - F_ENTROPY_TYPE_EXCELENT, 92
 - F_ENTROPY_TYPE_GOOD, 92
 - F_ENTROPY_TYPE_NOT_ENOUGH, 92
 - F_ENTROPY_TYPE_NOT_RECOMENDED, 93
 - F_ENTROPY_TYPE_PARANOIC, 93
 - F_GET_CH_MODE_ANY_KEY, 93
 - F_GET_CH_MODE_NO_ECHO, 93
 - F_PASS_IS_OUT_OVF, 94
 - F_PASS_IS_TOO_LONG, 94
 - F_PASS_IS_TOO_SHORT, 94
 - F_PASS_MUST_HAVE_AT_LEAST_NONE, 94
 - F_PASS_MUST_HAVE_AT_LEAST_ONE_LO↵
 - WER_CASE, 94
 - F_PASS_MUST_HAVE_AT_LEAST_ONE_NU↵
 - MBER, 95
 - F_PASS_MUST_HAVE_AT_LEAST_ONE_SYM↵
 - BOL, 95
 - F_PASS_MUST_HAVE_AT_LEAST_ONE_UPP↵
 - ER_CASE, 95
 - f_base64_decode_dynamic, 96
 - f_base64url_decode, 96
 - f_base64url_encode, 97
 - f_base64url_encode_dynamic, 97
 - f_convert_to_double, 97
 - f_convert_to_long_int, 97
 - f_convert_to_long_int0, 98
 - f_convert_to_long_int0x, 98
 - f_convert_to_long_int_std, 99
 - f_convert_to_unsigned_int, 100
 - f_convert_to_unsigned_int0, 100
 - f_convert_to_unsigned_int0x, 101
 - f_convert_to_unsigned_int_std, 101
 - f_ecdsa_public_key_valid, 102
 - f_ecdsa_secret_key_valid, 102
 - f_encode_to_base64, 102
 - f_encode_to_base64_dynamic, 102
 - f_gen_ecdsa_key_pair, 102
 - f_get_char_no_block, 103
 - f_get_entropy_name, 103
 - f_hmac_sha512, 104
 - f_is_random_attached, 104
 - f_pass_must_have_at_least, 104
 - f_passwd_comp_safe, 105
 - f_random, 106
 - f_random_attach, 106
 - f_random_detach, 107
 - f_reverse, 107
 - f_ripemd160, 107
 - f_sel_to_entropy_level, 107
 - f_str_to_hex, 108
 - f_uncompress_elliptic_curve, 108
 - f_url_base64_to_base64_dynamic, 108
 - f_url_encode, 108
 - f_verify_system_entropy, 109
 - fn_det, 95
 - get_console_passwd, 109
 - rnd_fn, 95
 - f_verify_signed_block
 - f_nano_crypto_util.h, 71
 - f_verify_signed_data
 - f_nano_crypto_util.h, 71
 - f_verify_system_entropy
 - f_util.h, 109
 - f_verify_token
 - f_nano_crypto_util.h, 71
 - f_verify_work
 - f_nano_crypto_util.h, 72
 - f_wif_to_private_key
 - f_bitcoin.h, 29
 - f_write_seed
 - f_nano_crypto_util.h, 73
 - f_write_seed_err
 - f_nano_crypto_util.h, 48

- f_write_seed_err_t
 - f_nano_crypto_util.h, 51
- f_xpriv2xpub
 - f_bitcoin.h, 29
- file_info_integrity
 - f_nano_crypto_util.h, 78
 - f_nano_wallet_info_t, 17
- finger_print
 - f_bitcoin.h, 30
 - f_bitcoin_serialize_t, 8
- fn_det
 - f_util.h, 95
- from_multiplier
 - f_nano_crypto_util.h, 73
- get_console_passwd
 - f_util.h, 109
- hash_sk_unencrypted
 - f_nano_crypto_util.h, 79
 - f_nano_encrypted_wallet_t, 13
- header
 - f_nano_crypto_util.h, 79
 - f_nano_wallet_info_t, 17
- INVALID_RAW_BALANCE
 - errors.h, 20
- is_nano_prefix
 - f_nano_crypto_util.h, 74
- is_null_hash
 - f_nano_crypto_util.h, 74
- iv
 - f_nano_crypto_util.h, 79
 - f_nano_crypto_wallet_t, 12
 - f_nano_encrypted_wallet_t, 14
- last_used_wallet_number
 - f_nano_crypto_util.h, 79
 - f_nano_wallet_info_bdy_t, 15
- link
 - f_block_transfer_t, 9
 - f_nano_crypto_util.h, 79
- load_master_private_key
 - f_bitcoin.h, 29
- MAINNET_PRIVATE
 - f_bitcoin.h, 25
- MAINNET_PUBLIC
 - f_bitcoin.h, 26
- MAX_STR_NANO_CHAR
 - f_nano_crypto_util.h, 45
- master_node
 - f_bitcoin.h, 31
 - f_bitcoin_serialize_t, 8
- max_fee
 - f_nano_crypto_util.h, 80
 - f_nano_wallet_info_bdy_t, 15
- NANO_ENCRYPTED_SEED_FILE
 - f_nano_crypto_util.h, 45
- NANO_FILE_WALLETS_INFO
 - f_nano_crypto_util.h, 45
- NANO_PASSWD_MAX_LEN
 - f_nano_crypto_util.h, 45
- NANO_PREFIX
 - f_nano_crypto_util.h, 46
- NANO_PRIVATE_KEY_EXTENDED
 - f_nano_crypto_util.h, 48
- NANO_PRIVATE_KEY
 - f_nano_crypto_util.h, 48
- NANO_PUBLIC_KEY_EXTENDED
 - f_nano_crypto_util.h, 49
- NANO_PUBLIC_KEY
 - f_nano_crypto_util.h, 48
- NANO_SEED
 - f_nano_crypto_util.h, 49
- nano_base_32_2_hex
 - f_nano_crypto_util.h, 75
- nano_create_block_dynamic
 - f_nano_crypto_util.h, 75
- nano_create_p2pow_block_dynamic
 - f_nano_crypto_util.h, 75
- nano_hdr
 - f_nano_crypto_util.h, 80
 - f_nano_crypto_wallet_t, 12
- nanoseed_hash
 - f_nano_crypto_util.h, 80
 - f_nano_wallet_info_t, 17
- PUB_KEY_EXTENDED_MAX_LEN
 - f_nano_crypto_util.h, 46
- pk_to_wallet
 - f_nano_crypto_util.h, 76
- preamble
 - f_block_transfer_t, 10
 - f_nano_crypto_util.h, 80
- prefixes
 - f_block_transfer_t, 10
 - f_nano_crypto_util.h, 80
- previous
 - f_block_transfer_t, 10
 - f_nano_crypto_util.h, 81
- REP_XRB
 - f_nano_crypto_util.h, 46
- representative
 - f_block_transfer_t, 10
 - f_nano_crypto_util.h, 81
- reserved
 - f_nano_crypto_util.h, 81
 - f_nano_encrypted_wallet_t, 14
 - f_nano_wallet_info_bdy_t, 15
- rnd_fn
 - f_util.h, 95
- SENDER_XRB
 - f_nano_crypto_util.h, 46
- STR_NANO_SZ
 - f_nano_crypto_util.h, 46

- salt
 - f_nano_crypto_util.h, 81
 - f_nano_crypto_wallet_t, 12
- seed_block
 - f_nano_crypto_util.h, 81
 - f_nano_crypto_wallet_t, 12
- signature
 - f_block_transfer_t, 10
 - f_nano_crypto_util.h, 82
- sk_encrypted
 - f_nano_crypto_util.h, 82
 - f_nano_encrypted_wallet_t, 14
- sk_or_pk_data
 - f_bitcoin.h, 31
 - f_bitcoin_serialize_t, 8
- sodium.h, 113, 114
- sub_salt
 - f_nano_crypto_util.h, 82
 - f_nano_encrypted_wallet_t, 14
- TESTNET_PRIVATE
 - f_bitcoin.h, 26
- TESTNET_PUBLIC
 - f_bitcoin.h, 26
- to_multiplier
 - f_nano_crypto_util.h, 76
- valid_nano_wallet
 - f_nano_crypto_util.h, 77
- valid_raw_balance
 - f_nano_crypto_util.h, 77
- ver
 - f_nano_crypto_util.h, 82
 - f_nano_crypto_wallet_t, 13
- version
 - f_nano_crypto_util.h, 82
 - f_nano_wallet_info_t, 17
- version_bytes
 - f_bitcoin.h, 31
 - f_bitcoin_serialize_t, 8
- wallet_prefix
 - f_nano_crypto_util.h, 83
 - f_nano_wallet_info_bdy_t, 15
- wallet_representative
 - f_nano_crypto_util.h, 83
 - f_nano_wallet_info_bdy_t, 16
- work
 - f_block_transfer_t, 11
 - f_nano_crypto_util.h, 83
- XRB_PREFIX
 - f_nano_crypto_util.h, 47