ItalTherm

SISTEMA DI PRODUZIONE DI GRANIGLIA

GRAINS PRODUCTION SYSTEM

Mod IT.GMB



SISTEMA AUTOMATICO DI FUSIONE GRANULI

ITALTHERM: dotato di avanzata tecnologia di fusione a induzione a media frequenza. Progettato per leghe e metalli sensibili all'ossidazione, garantisce un riscaldamento rapido e uniforme con un controllo preciso della temperatura, necessario per mantenere l'integrità e la fluidità del metallo.

L'intero processo di granulazione, così come il raffreddamento dei granuli, lo scarico e il drenaggio, è completamente automatico, per garantire efficienza operativa e sicurezza.

Il processo di granulazione è protetto da gas inerte per ridurre al minimo l'ossidazione dei metalli.

ITALTHERM AUTOMATIC GRAINS MELTING SYSTEM

equipped with advanced medium-frequency induction melting technology. Designed for Alloys and Oxidation-Sensitive Metals. It ensures rapid and uniform heating with precise temperature control necessary for maintaining metal integrity and fluidity.

The whole granulation process and the grains cooling, offloading and draining are fully Automatic to grant operation efficiency and safety.

The granulation process is protected by inert gas to minimize the oxidation of metals.

TECHNICAL SPECIFICATIONS

MODEL NUMBER	IT.GMB30	IT.GMB50	IT.GMB100
VOLTAGGIO / VOLTAGE	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ
POTENZA / POWER	30KW (VARIABILE /ADJUSTABLE)	45KW (VARIABILE /ADJUSTABLE)	75KW (VARIABILE /ADJUSTABLE)
PESO / WEIGHT	330KG	350KG	380KG
CAPACITÀ MASSIMA / MAX CAPACITY	ORO / GOLD : 30 KG / ARGENTO / SILVER:15 KG	ORO / GOLD: 50 KG / ARGENTO / SILVER: 25 KG	ORO / GOLD: 100 KG / ARGENTO / SILVER: 50 KG
TEMPO DI FUSIONE / MELTING TIME	10-30 MIN	20-40 MIN	20-40 MIN
DIMENSIONI / DIMENSION (LWH)	2100*2360*2600MM	2100*2360*2600MM	2100*2360*2600MM
TEMPERATURA MASSIMA / MAX TEMPERATURE	1500°C	1500°C	1500°C
CONTROLLO TEMPERATURA TIPO K / TEMPERATURE CONTROL K-TYPE	FORNITO	FORNITO	FORNITO