ItalTherm

SISTEMA DI PRODUZIONE DI GRANULI

GRAINS PRODUCTION SYSTEM

Mod IT.GMS





SISTEMA AUTOMATICO ITALTHERM PER LA FUSIONE DI GRANULI, dotato di avanzata tecnologia di fusione a induzione a media frequenza.

Progettato per leghe e metalli sensibili all'ossidazione, assicura un riscaldamento rapido e uniforme con un controllo preciso della temperatura, necessario per mantenere l'integrità e la fluidità del metallo.

Il processo di granulazione è protetto da gas inerte per ridurre l'ossidazione dei metalli.

ITALTHERM AUTOMATIC GRAINS MELTING SYSTEM equipped with advanced medium-frequency induction melting technology.

Designed for Alloys and Oxidation-Sensitive Metals. It ensures rapid and uniform heating with precise temperature control necessary for maintaining metal integrity and fluidity.

The granulation process is protected by inert gas to minimize the oxidation of metals.

TECHNICAL SPECIFICATIONS

MODEL NUMBER	IT.GMS05	IT.GMS10	IT.GMS15
VOLTAGGIO / VOLTAGE	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ
POTENZA / POWER	10KW (VARIABILE /ADJUSTABLE)	20KW (VARIABILE /ADJUSTABLE)	25KW (VARIABILE /ADJUSTABLE)
PESO / WEIGHT	230KG	250KG	380KG
CAPACITÀ MASSIMA / MAX CAPACITY	ORO / GOLD : 5KG	ORO / GOLD: 10KG	ORO / GOLD: 15KG
TEMPO DI FUSIONE / MELTING TIME	10-20 MIN	10-20 MIN	10-20 MIN
DIMENSIONI / DIMENSION (LWH)	1100*1000*1100MM	1100*1000*1100MM	1100*1000*1100MM
TEMPERATURA MASSIMA / MAX TEMPERATURE	1500°C	1500°C	1500°C
CONTROLLO TEMPERATURA TIPO K / TEMPERATURE CONTROL K-TYPE	FORNITO	FORNITO	FORNITO